



# Using Conversion Functions and Conditional Expressions

# What You will learn at the end of this Session?



1. Describe the various types of conversion functions that are available in SQL
2. Use the TO\_CHAR, TO\_NUMBER, and TO\_DATE conversion functions
3. Apply conditional expressions in a SELECT statement





# Implicit Data Type Conversion

---

**In expressions, the Oracle server can automatically convert the following:**

| From             | To     |
|------------------|--------|
| VARCHAR2 or CHAR | NUMBER |
| VARCHAR2 or CHAR | DATE   |




# Implicit Data Type Conversion

---


**For expression evaluation, the Oracle server can automatically convert the following:**

| From   | To               |
|--------|------------------|
| NUMBER | VARCHAR2 or CHAR |
| DATE   | VARCHAR2 or CHAR |


# Explicit Data Type Conversion



# Explicit Data Type Conversion



# Explicit Data Type Conversion





# Using the TO\_CHAR Function with Dates

The format model:

```
TO_CHAR(date, 'format_model') 
```

**TO\_CHAR  
Function with  
Dates**

**Must be  
enclosed with  
single  
quotation  
marks**

**Is case-  
sensitive**

**Can include  
any valid  
date format  
element**

**Has an fm  
element to  
remove padded  
blanks or  
suppress leading  
zeros**

**Is separated  
from the date  
value by a  
comma**

**ORACLE**



# Elements of the Date Format Model

---

| Element | Result                                           |
|---------|--------------------------------------------------|
| YYYY    | Full year in numbers                             |
| YEAR    | Year spelled out (in English)                    |
| MM      | Two-digit value for the month                    |
| MONTH   | Full name of the month                           |
| MON     | Three-letter abbreviation of the month           |
| DY      | Three-letter abbreviation of the day of the week |
| DAY     | Full name of the day of the week                 |
| DD      | Numeric day of the month                         |





# Elements of the Date Format Model

---

- Time elements format the time portion of the date:

|               |             |
|---------------|-------------|
| HH24:MI:SS AM | 15:45:32 PM |
|---------------|-------------|

- Add character strings by enclosing them with double

|               |               |
|---------------|---------------|
| DD "of" MONTH | 12 of OCTOBER |
|---------------|---------------|

- Number suffixes spell out numbers:

|        |            |
|--------|------------|
| ddspth | fourteenth |
|--------|------------|



# Using the TO\_CHAR Function with Dates

```
SELECT order_id, to_char (order_date, ' fmDD Month YYYY ' )  
AS " Date of Order "  
FROM orders ;
```

|    | ORDER_ID | Date of Order    |
|----|----------|------------------|
| 1  | 2458     | 17 August 1999   |
| 2  | 2397     | 20 November 1999 |
| 3  | 2454     | 3 October 1999   |
| 4  | 2354     | 15 July 2000     |
| 5  | 2358     | 9 January 2000   |
| 6  | 2381     | 15 May 2000      |
| 7  | 2440     | 1 September 1999 |
| 8  | 2357     | 9 January 1998   |
| 9  | 2394     | 11 February 2000 |
| 10 | 2435     | 3 September 1999 |

...


# Using the TO\_CHAR Function with Numbers

```
TO_CHAR(number, 'format_model')  

```

These are some of the format elements that you can use with the TO\_CHAR function to display a number value as a character:

| Element | Result                                  |
|---------|-----------------------------------------|
| 9       | Represents a number                     |
| 0       | Forces a zero to be displayed           |
| \$      | Places a floating dollar sign           |
| £       | Uses the floating local currency symbol |
| .       | Prints a decimal point                  |
| ,       | Prints a comma as a thousands indicator |






## Using the TO\_CHAR Function with Numbers

```
SELECT TO_CHAR(salary, '$99,999.00') SALARY  
FROM   employees  
WHERE  last_name = 'Ernst';
```

|   | SALARY     |
|---|------------|
| 1 | \$6,000.00 |



# Using the TO\_NUMBER and TO\_DATE Functions

---


- Convert a character string to a number format using the TO\_NUMBER function:

```
TO_NUMBER(char[, 'format_model'])
```

- Convert a character string to a date format using the TO\_DATE function:

```
TO_DATE(char[, 'format_model'])
```

- These functions have an fx modifier. This modifier specifies the exact match for the character argument and date format model of a TO\_DATE function.



# Using the TO\_CHAR and TO\_DATE Function with the RR Date Format

To find employees hired before 1990, use the RR date format, which produces the same results whether the command is run in 1999 or now:

```
SELECT last_name, TO_CHAR(hire_date, 'DD-Mon-YYYY')
FROM employees
WHERE hire_date < TO_DATE('01-Jan-90', 'DD-Mon-RR');
```

|   | LAST_NAME | TO_CHAR(HIRE_DATE,'DD-MON-YYYY') |
|---|-----------|----------------------------------|
| 1 | Whalen    | 17-Sep-1987                      |
| 2 | King      | 17-Jun-1987                      |
| 3 | Kochhar   | 21-Sep-1989                      |