

Hydra Package Description

Source: <https://github.com>

Hydra is a parallelized login and password cracker tool which supports several protocols and databases. It is a very fast and flexible tool. This tool helps the researchers and security consultants to analyses how easy it would be to gain unauthorized remote access to any system

Tools included in the hydra package

hydra – Very fast network logon cracker

Syntax	
	<pre>hydra [[[-l LOGIN -L FILE] [-p PASS -P FILE]] [-C FILE]] [-e nsr] [-o FILE] [-t TASKS] [-M FILE [-T TASKS]] [-w TIME] [-W TIME] [-f] [-s PORT] [-x MIN:MAX:CHARSET] [-Suvv46] [server service [OPT]]][service://server[:PORT][[/OPT]]]</pre>
Arguments/ Options	
-R	Restores a previous aborted/crashed session
-S	Performs an SSL connect
-s PORT	If the service is on a different default port, define it here
-l LOGIN or -L FILE	Log in with a single username, or load several logins from FILE of username list
-p PASS or -P FILE	Try single password, or load several passwords from FILE of the password list
-x MIN:MAX:CHARSET	Password brute force generation, type "-x -h" to get help
-e nsr	Try "n" null password, "s" login as pass and/or "r" reversed login
-u	Loop around users, not passwords (effective! implied with -x)
-C FILE	Colon separated "login:pass" format, instead of -L/-P options
-M FILE	List of servers to be attacked in parallel, one entry per line
-o FILE	Write found login/password pairs to FILE instead of stdout
-f / -F	Exit when a login/pass pair is found (-M: -f per host, -F global)/ stop on the correct login
-t TASKS	Run TASKS number of connects in parallel (per host, default: 16)/ limit concurrent connections
-w / -W TIME	Wait time for responses (32s) / between connects per thread
-4 / -6	Prefer IPv4 (default) or IPv6 addresses
-v / -V / -d	Verbose output (mode) / show login+pass for each attempt / debug mode
-U	Service module usage details
server	The target server
service	The service to crack
OPT	Some service modules support additional input (-U for module help)

THC Hydra

Command	Description
hydra -V -l admin -P /root/Desktop/dictionary.txt	Attack the router along with its arguments
hydra -V -l admin -P /root/Desktop/dictionary.txt -e ns -f -s 21 <Target IP> ftp	Null password and to use login credentials as password
hydra -l <username> -P pass.txt <Target IP> ftp	Password Guessing for Specific Username
hydra -L user.txt -p <password> <Target IP> ftp	Username Guessing for Specific Password
hydra -L user.txt -P pass.txt <Target IP> ftp	Cracking Login Credential
hydra -L user.txt -P pass.txt <Target IP> ftp -V -e nsr	NULL/Same as Login/Reverse login Attempt
hydra -L user.txt -P pass.txt <Target IP> ftp -o result.txt	Save Output to Disk
hydra -L user.txt -P pass.txt <Target IP> ftp	Resuming the Brute Force Attack
hydra -l <username> -x MIN:MAX:CHARSET ftp://<Target IP> or hydra -l <username> -x MIN:MAX:CHARSET <Target IP> ftp	Password Generating Using Various Set of Character
hydra -l <username> -x MIN:MAX:CHARSET ftp://<Target IP> -V	Find the password for a username for FTP login
hydra -L user.txt -P pass.txt <Target IP> ftp -s <port>	Attacking on Specific Port Instead of Default
hydra -L user.txt -P pass.txt -M hosts.txt ftp	Brute force attack on multiple hosts by using the same dictionary
hydra -L user.txt -P pass.txt -M hosts.txt ftp -V -F	Enables to finish parameter when found valid credential for either host from inside the host list
hydra -t 4 -v -f -l <username> -P textname.txt rdp://<Target IP>	Using Remote Desktop Protocol to pull passwords from the text file
hydra -P passwordlist -t 1 -w 5 -f -s 5901 <Target IP> vnc -v	Turned off the blacklisting feature run this command in hydra
hydra -l root -p admin <Target IP> -t 4 ssh	Test the root user's SSH password
hydra -l root -P /usr/share/wordlists/rockyou.tx t <Target IP> -t 4 ssh	Using Word Lists
hydra -l root -P Documents/pass.txt <Target IP> -t 4 ssh	Words in that list
hydra -L /usr/share/wordlists.rockyou.tx t -P /usr/share/wordlists/rockyou.tx t -M Documents/ip.txt -t 4 ssh	Hydra accepts wordlists for users and targets. They can be specified with the -L flag for users, and the -M flag for IPs
hydra <Target IP> ssh -l <username> -P <password_file> -s 22 -vV	Brute-force ssh username input login and list of password

Command	Description
hydra <Target IP> ssh -l <username> -p <password> -s 22 -vV	Brute-force ssh username and password
hydra -L <username_file> -P <password_file> ftp://<Target_IP>	Brute-force FTP list of username and list of password
hydra -l <username> -p <password> ftp://<Target_IP>	Brute-force FTP input login and a single password
hydra -l <username> -p <password> telnet://<Target_IP>	Brute-force telnet username and password
hydra -L <USER> -P <Password> <IP Address> http-post-form "<Login Page>:<Request Body>:<Error Message>"	Brute force the user information from the website
hydra -t 1 -l admin -P /root/Desktop/password.lst -vV 192.168.1.1 ftp	Use this to brute force an FTP server to try to crack its password
hydra -l user1 -P wordlist.txt smb://<Target_IP>	Get the password for one of the users configured on the SMB service
hydra -l <smtp.gmail.com.server> -P /root/Desktop/wordlist.txt -S <port> smtp.gmail.com smtp	Crack the password of an email account
hydra -l John Doe -x Shortest length: longest length: combinations host	Brute force option is invoked in hydra
hydra <HOSTNAME> <PROTOCOL/METHOD> -m "<PATH/TO/AUTH/FILE>:<USERNAME_FIELD>=<USER^&<PASSWORD_FIELD>=<PASS^:<ERROR MESSAGE>" -L listofUsers.txt -P listofPasswords.txt -t 10 -w 30 -o <OUTPUT_FILENAME>	Brute-forcing with hydra (CLI)
hydra-wizard	For CLI-wizard
xhydra	For GUI
hydra	For CLI
hydra.restore	Restore Aborted Session
hydra -R	Resume parameter
\$ hydra -l plague -P passList.txt -vV -f -t 5 192.168.1.100 http-post-form "/wp/Forum/login.php:log=^USER^&pwd=^PASS^:login_error"	Password cracking through HTTP-POST-FORM
\$ hydra -s 21 -v -l plague -P wordlist.txt -e s -t 10 -w 5 192.168.1.100 ftp	Password cracking through FTP
\$ hydra -s 22 -v -l plague -P wordlist.txt -t 10 -f 192.168.1.100 ssh	Password cracking through SSH

reference Keyword	
<pre>\$ hydra -s 23 -V -l plague -P wordlist.txt -e ns -t 10 -w 5 -f -m 192.168.1.100 telnet</pre>	Password cracking through Telnet
<pre>\$ hydra 192.168.1.1 http-get -v -V -l telekom -P wordlist.txt -e ns -t 5 -w 30 -m / -f</pre>	Password cracking through HTTP Login. For HTTPS set "https-get"
<pre>\$ hydra -t 4 -V -l plague -P wordlist.txt rdp://192.168.1.100</pre>	Password cracking through RDP
<pre>\$ hydra -t 4 -V -f -l plague -e ns -P wordlist.txt 192.168.1.100 mysql</pre>	Password cracking through MySQL
<pre>HYDRA_PROXY_HTTP="http://<Target t IP>:<port>/"</pre>	Scan/Crack Over a Proxy, the environment variable HYDRA_PROXY_HTTP defines the web proxy
<pre>HYDRA_PROXY_HTTP="http://login: password@123. <Target IP>:<port>/"</pre>	HYDRA_PROXY_HTTP defines the Web Proxy
<pre>HYDRA_PROXY=[connect socks4 soc ks5]://[login:password@]proxy_ad dr:proxy_port</pre>	Use the HYDRA_PROXY variable to scan/crack for all other services

Pw-inspector- A tool to reduce the password list

Syntax	
<pre>pw-inspector [-i FILE] [-o FILE] [-m MINLEN] [-M MAXLEN] [-c MINSETS] -l -u -n -p -s</pre>	
Arguments/ Options	
-i FILE	File to read passwords from (default: stdin)
-o FILE	File to write valid passwords to (default: stdout)
-m MINLEN	Minimum length of a valid password
-M MAXLEN	Maximum length of a valid password
-c MINSETS	The minimum number of sets required (default: all given)
-h, --help	Show summary of options
-D	Turns Snort in daemon mode
-e	Displays or logs the link-layer packet headers
-F bpf-file	Reads Berkeley Packet Filters (BPF) from a bpf file
-g group	Changes the default group ID or GID under which Snort runs after initialization
-h home-net	Sets the "home network" to a specific address in CIDR format
Sets	
-l	Lowcase characters (a,b,c,d, etc.)s
-u	Upcase characters (A,B,C,D, etc.)
-n	Upcase characters (A,B,C,D, etc.)
-p	Printable characters (which are not -l/-n/-p, e.g. \$,!,/,*, etc.)
-s	Special characters - all others not within the sets above

Commands	Description
<pre>pw-inspector -i /usr/share/wordlists/nmap.lst -o /root/passes.txt -m 6 -M 10</pre>	Read in a list of passwords (-i /usr/share/wordlists/nmap.lst) and save to a file (-o /root/passes.txt), selecting passwords of a minimum length of 6 (-m 6) and a maximum length of 10 (-M 10)
<pre>pw-inspector -h</pre>	Access to pw-inspector parameters
<pre>cat attack_hydra.txt pw-inspector -m <passwordlength> -n > passwords.txt</pre>	Start the attack with Hydra command
<pre>cat first.txt pw-inspector -m 6 -M 128 > newfile.txt</pre>	Remove lines in a text file that are way too long and are less than a certain length
<pre>pw-inspector -i /path/to/input.list -O /path/to/output -m minchar -M maxchar</pre>	Use the rockyou.txt file available from Kali Linux
<pre>cat list.txt pw-inspector -m 5 > new_list.txt</pre>	Get some passwords with 4 characters
<pre>cat rockyou.txt sort uniq pw-inspector -m 8 -M 63 > newrockyou.txt</pre>	Read the passwords from the rockyou.txt file (cat rockyou.txt) into the standard output, sort them (sort), and delete the duplicate ones (uniq), from the remaining passwords we select those that are 8 or more characters, but less than 63 characters (-m 8 -M 63), the resulting list is saved in the file newrockyou.txt (> newrockyou.txt)
<pre>pw-inspector -i wordlists/rockyou.txt -s</pre>	Show passwords that have unprintable characters (-s) from a dictionary located on the path wordlists / rockyou.txt (-i wordlists / rockyou.txt)
<pre>pw-inspector -i wordlists/rockyou.txt -c 4 -l -u -n -p</pre>	Show passwords with at least one capital letter, one small letter, one number and one printed character (-c 4 -l -u -n -p) from the dictionary located on the path wordlists / rockyou.txt (-i wordlists / rockyou .txt)