



Chapter 7: Quantitative Process Analysis




Contents

1. Flow Analysis
2. Queuing Analysis
3. Simulation
4. Recap

Process Analysis in the BPM Lifecycle




Chapter 7: Quantitative Process Analysis



Contents


1. Flow Analysis
2. Queuing Analysis
3. Simulation
4. Recap

Flow analysis






Refresher: Process performance measures



Common time-related measures




Cycle time efficiency



$$\text{Processing Time} \div \text{Cycle Time} = \text{Cycle Time Efficiency}$$



Flow analysis of cycle time




Cycle time = X days



Sequence – Example

- What is the average cycle time?




$$\text{Cycle time} = 10 + 20 = 30$$



Example: Alternative Paths

- What is the average cycle time?




$$\text{Cycle time} = 10 + 0.5 * 20 + 0.5 * 10 = 25$$





Example: Parallel paths

- What is the average cycle time?




$$\text{Cycle time} = 10 + 20 = 30$$



Example: Rework loop

- What is the average cycle time?



$$\text{Cycle time} = 10 + 20 = 30$$



$$\text{Cycle time} = 10 + 20/0.01 = 2010$$

$$\text{Cycle time} = 10 + 20/0.8 = 35$$








Flow analysis equations for cycle time





$$CT = T_1 + T_2 + \dots + T_N$$



$$CT = p_1 * T_1 + p_2 * T_2 + \dots + p_n * T_N$$




$$CT = \max(T_1, T_2, \dots, T_N)$$



$$CT = T / (1-r)$$

Flow analysis of cycle time



1/0.8

$\max(1, 3)$

3


$0.6 \cdot 1 + 0.4 \cdot 2$



$$\text{Cycle time} = 1.25 + 3 + 3 + 1.4 = 8.65 \text{ days}$$



Flow analysis of processing time



Processing time = $2.5 + 3 + 2 + 1.4 = 8.9$ hours

Cycle time efficiency = $8.9 \text{ hours} / 8.65 \text{ days} = 12.9\%$




Flow analysis: scope and limitations



- We have seen how to use flow analysis for processing & cycle time calculation
- Flow analysis can also be applied to calculate:
 - The average cost of process instances (assuming we know the cost of each activity)
 - Cf. Section 7.1.6
 - The number of times on average each activity is executed
 - Can be used to calculate the “unit load” of each task, the resource utilization of each resource pool, and the theoretical capacity of an “as is” process
 - Cf. Section 7.1.5
- But flow analysis has some fundamental limitations...



Limitation 1: Not all Models are Structured





Limitation 2: Fixed arrival rate capacity

- Cycle time analysis does not consider:
 - The rate at which new process instances are created (arrival rate)
 - The number of available resources
- Higher arrival rate at fixed resource capacity
 - ➔ high resource contention
 - ➔ higher activity waiting times (longer queues)
 - ➔ higher activity cycle time
 - ➔ higher overall cycle time
- The slower you are, the more people have to queue up...
 - and vice-versa



Resource utilization



Resource utilization = 60%
→ on average resources are idle 40% of their allocated time



Resource utilization vs. waiting time



**Typically, when resource utilization $> 90\%$
→ Waiting time increases steeply**

Interlude: Cycle Time & Work-In-Progress



- WIP = (average) Work-In-Process
 - Number of cases that are running (started but not yet completed)
 - E.g. # of active and unfilled orders in an order-to-cash process
- WIP is a form of waste (cf. 7+1 sources of waste)
- Little's Formula: $WIP = \lambda \cdot CT$
 - λ = arrival rate (number of new cases per time unit)
 - CT = cycle time



Exercise



A fast-food restaurant receives on average 1200 customers per day (between 10:00 and 22:00). During peak times (12:00-15:00 and 18:00-21:00), the restaurant receives around 900 customers in total, and 90 customers can be found in the restaurant (on average) at a given point in time. At non-peak times, the restaurant receives 300 customers in total, and 30 customers can be found in the restaurant (on average) at a given point in time.

1. What is the average time that a customer spends in the restaurant during peak times?
2. What is the average time that a customer spends in the restaurant during non-peak times?




Exercise (cont.)



3. The restaurant plans to launch a marketing campaign to attract more customers. However, the restaurant's capacity is limited and becomes too full during peak times. What can the restaurant do to address this issue without investing in extending its building?



Chapter 7: Quantitative Process Analysis



Contents

1. Flow Analysis
2. Queuing Analysis
3. Simulation
4. Recap

Queuing Analysis



- Capacity problems are common and a key driver of process redesign
 - Need to balance the cost of increased capacity against the gains of increased productivity and service
- Queuing and waiting time analysis is particularly important in service systems
 - Large costs of waiting and/or lost sales due to waiting
- **Example – Emergency Room (ER) at a Hospital**
 - Patients arrive by ambulance or by their own accord
 - One doctor is always on duty
 - More patients seeks help $\Rightarrow$ longer waiting times
 - *Should we increase the capacity from one to two doctors?*


Inspired by an example by Laguna & Marklund (2004)



Delay is Caused by Job Interference


If arrivals are regular or sufficiently spaced apart, no queuing delay occurs

Arrival Times



Deterministic traffic

Arrival Times




Variable but spaced apart traffic



Burstiness Causes Interference

- * **Queuing results from variability in processing times and/or interarrival times**




Bursty Traffic



High Utilization Exacerbates Interference

- The queuing probability increases as the load increases
- Utilization close to 100% is unsustainable → too long queuing times



The Poisson Process




- Common arrival assumption in many queuing and simulation models
- The times between arrivals are independent, identically distributed and **exponential**
 - $P(\text{arrival} < t) = 1 - e^{-\lambda t}$
- This distribution is applicable when the next arrival (i.e. the next creation of a case) does not depend on how long ago the previous arrival occurred
 - In other words, the creation of a case is independent of the creation of other cases.

Inspired by slide by Laguna & Marklund (2004)




Negative Exponential Distribution





Queuing theory: basic concepts




Basic characteristics:

- λ (mean arrival rate) = average number of arrivals per time unit
- μ (mean service rate) = average number of jobs that can be handled by one server per time unit:
- c = number of servers




Queuing theory concepts (cont.)



Given λ , μ and c , we can calculate :

- occupation rate: ρ
- W_q = average time in queue
- W = average system in system (i.e. cycle time)
- L_q = average number in queue (i.e. length of queue)
- L = average number in system average (i.e. Work-in-Progress)

M/M/1 queue



Assumptions:

- time between arrivals and processing time follow a negative exponential distribution
- 1 server ($c = 1$)
- FIFO

$$\rho = \frac{\text{Capacity Demand}}{\text{Available Capacity}} = \frac{\lambda}{\mu}$$

$$L = \rho / (1 - \rho)$$

$$W = L / \lambda = 1 / (\mu - \lambda)$$

$$L_q = \rho^2 / (1 - \rho) = L \cdot \rho$$

$$W_q = L_q / \lambda = \lambda / (\mu(\mu - \lambda))$$



M/M/c queue

- Now there are c servers in parallel, so the expected capacity per time unit is then $c * \mu$

$$\rho = \frac{\text{Capacity Demand}}{\text{Available Capacity}} = \frac{\lambda}{c * \mu}$$

$$\text{Little's Formula} \Rightarrow W_q = L_q / \lambda$$

$$W = W_q + (1/\mu)$$

$$\text{Little's Formula} \Rightarrow L = \lambda W$$



Tool Support

- For M/M/c systems, the exact computation of L_q is rather complex...

$$L_q = \sum_{n=c}^{\infty} (n-c)P_n = \dots = \frac{(\lambda/\mu)^c \rho}{c!(1-\rho)^2} P_0$$

$$P_0 = \left(\sum_{n=0}^{c-1} \frac{(\lambda/\mu)^n}{n!} + \frac{(\lambda/\mu)^c}{c!} \cdot \frac{1}{1 - (\lambda/(c\mu))} \right)^{-1}$$

- Consider using a tool, e.g.
 - <http://www.supositorio.com/rcalc/rcalclite.htm>
 - <http://queueingtoolpak.org/> (for Excel)



Example – ER at County Hospital



➤ Situation

- Patients arrive according to a Poisson process with intensity λ ($\Leftrightarrow$ the time between arrivals is $\exp(\lambda)$ distributed).
 - The service time (the doctor's examination and treatment time of a patient) follows an exponential distribution with mean $1/\mu$ ($=\exp(\mu)$ distributed)
- $\Rightarrow$ *The ER can be modeled as an M/M/c system where c = the number of doctors*

➤ Data gathering

- $\Rightarrow \lambda = 2$ patients per hour
- $\Rightarrow \mu = 3$ patients per hour

❖ Question

- Should the capacity be increased from 1 to 2 doctors?





Queuing Analysis – Hospital Scenario

■ Interpretation

- To be in the queue = to be in the waiting room
- To be in the system = to be in the ER (waiting or under treatment)

Characteristic	One doctor (c=1)	Two Doctors (c=2)
ρ	2/3	1/3
L_q	4/3 patients	1/12 patients
L	2 patients	3/4 patients
W_q	2/3 h = 40 minutes	1/24 h = 2.5 minutes
W	1 h	3/8 h = 22.5 minutes

- Should we increase the capacity from one to two doctors?




Limitations of basic queuing models



- Can be used to analyze waiting times (and hence cycle times), but not cost or quality measures
- Suitable for analyzing one single activity at a time, performed by one single resource pool. Not suitable for analyzing end-to-end processes consisting of multiple activities performed by multiple resource pools.
- These limitations are addressed by process simulation

Chapter 7: Quantitative Process Analysis



Contents


1. Value-Added Analysis
2. Queuing analysis
- 3. Simulation**
4. Recap

Process Simulation




- Versatile quantitative analysis method for
 - As-is analysis
 - What-if analysis
- In a nutshell:
 - Run a large number of process instances
 - Gather performance data (cost, time, resource usage)
 - Calculate statistics from the collected data


Process Simulation



Example



Example




Elements of a simulation scenario

1. Processing times of activities
 - Fixed value
 - Probability distribution






Exponential Distribution





Normal Distribution






Choice of probability distribution

- Fixed
 - Rare, can be used to approximate case where the activity processing time varies very little
 - Example: a task performed by a software application
- Normal
 - Repetitive activities
 - Example: “Check completeness of an application”
- Exponential
 - Complex activities that may involve analysis or decisions
 - Example: “Assess an application”





Simulation Example



Elements of a simulation model





1. Processing times of activities
 - Fixed value
 - Probability distribution
2. Conditional branching probabilities
3. Arrival rate of process instances and probability distribution
 - Typically exponential distribution with a given mean inter-arrival time
 - Arrival calendar, e.g. Monday-Friday, 9am-5pm, or 24/7





Branching probability and arrival rate

Arrival rate = 2 applications per hour
 Inter-arrival time = 0.5 hour
 Negative exponential distribution
 From Monday-Friday, 9am-5pm



Elements of a simulation model



1. Processing times of activities
 - Fixed value
 - Probability distribution
2. Conditional branching probabilities
3. Arrival rate of process instances
 - Typically exponential distribution with a given mean inter-arrival time
 - Arrival calendar, e.g. Monday-Friday, 9am-5pm, or 24/7
4. Resource pools


Elements of a simulation model




1. Processing times of activities
 - Fixed value
 - Probability distribution
2. Conditional branching probabilities
3. Arrival rate of process instances and probability distribution
 - Typically exponential distribution with a given mean inter-arrival time
 - Arrival calendar, e.g. Monday-Friday, 9am-5pm, or 24/7
4. Resource pools
5. Assignment of tasks to resource pools



Resource pool assignment




Process Simulation






Output: Performance measures & histograms


Process durations



Process waiting times




Process costs (EUR)



Resource utilization %



Process Simulation



Tools for Process Simulation



- ARIS
- Bizagi Process Modeler
- ITP Commerce Process Modeler for Visio
- Logizian
- Oracle BPA
- Progress Savvion Process Modeler
- ProSim
- Signavio + BIMP



BIMP – bimp.cs.ut.ee




- Accepts standard BPMN 2.0 as input
- Simple form-based interface to enter simulation scenario
- Produces KPIs + simulation logs in MXML format
 - Simulation logs can be imported to the ProM process mining tool



BIMP Demo



<https://www.youtube.com/watch?v=TjXl6yASCSc>



Pitfalls of simulation



- Stochasticity
- Data quality pitfalls
- Simplifying assumptions





Stochasticity



- Simulation results may differ from one run to another
- Make the simulation tiemframe long enough to cover weekly and seasonal variability, where applicable
- Use multiple simulation runs
- Average results of multiple runs, compute confidence intervals

Data quality pitfalls



- Simulation results are only as trustworthy as the input data
- Rely as little as possible on “guesstimates”
- Use input analysis
 - Derive simulation scenario parameters from numbers in the scenario
 - Use statistical tools to check fit the probability distributions
- Simulate the “as is” scenario and cross-check results against actual observations




Simulation assumptions



- That the process model is always followed to the letter
 - No deviations
 - No workarounds
- That there is no multi-tasking (the same resource performs multiple tasks concurrently) nor batching (tasks being accumulated and performed in a single go)
- That resources work constantly and non-stop
 - Every day is the same!
 - No tiredness effects
 - No distractions beyond “stochastic” ones



Chapter 7: Quantitative Process Analysis



Contents

1. Value-Added Analysis
2. Queuing analysis
3. Simulation
4. Recap



Recap

- Assuming we have performance measures for each activity in a process, flow analysis allows us to calculate the following performance measures for an “as is” process:
 - Cycle time, processing times, cycle time efficiency of a process
 - Average cost per process instance
- It can also be used to calculate the theoretical capacity of an “as is” process and the resource utilization of resource pools
- But it is not suitable for “what if” analysis
- Queuing analysis is a suitable technique for “what if” analysis of waiting times and cycle times, suitable for analyzing individual activities performed by one resource pool
- Simulation is a versatile technique for “what if” analysis of entire processes, covering waiting times, cycle times, and costs.
 - Particularly useful for identifying bottlenecks

