

Technische Universität Dresden • Fakultät Informatik

Titel der Arbeit

Bachelorarbeit zur Erlangung des ersten
Hochschulgrades

Bachelor of Science (B.Sc.)

vorgelegt von

FRANZ MARTIN SCHMIDT

(geboren am 7. April 1999 in HALLE (SAALE))

Tag der Einreichung: May 3, 2023

Dipl. Inf Max Korn (Theoretische Informatik)

Contents

Abstract	1
1 Introduction	2
2 Preliminaries	3
2.1 Transition Systems	3
2.2 Markov Chain	3
2.3 Markov Decision Process	3
3 View	4
3.1 Grouping Function	4
3.2 Formal Definition	4
4 View Examples	6
4.1 Transition Systems	6
4.2 Markov Chain	6
4.3 Markov Decision Process	6
4.4 Comparison of the Examples	6
5 Outlook	6

Abstract

Lorem ipsum

1 Introduction

2 Preliminaries

2.1 Transition Systems

Motivation of transition systems

The following definition is directly taken from Principles of Modelchecking, Baier p. 20

Definition 2.1. A *transition system* TS is a tuple $(S, Act, \longrightarrow, I, AP, L)$ where

- S is a set of states,
- Act is a set of actions,
- $\longrightarrow \subseteq S \times Act \times S$ is transition relation,
- $I \subseteq S$ is a set of initial states,
- AP is a set of atomic propositions, and
- $L : S \rightarrow \mathcal{P}(AP)$

A transition system is called *finite* if S , AP and L are finite.

2.2 Markov Chain

2.3 Markov Decision Process

3 View

Views are the central objective of this thesis. The purpose of a view is to obtain a simplification of a given transition system (TS). It is an independent TS derived from a given TS and represents a (simplified) view on the given one - hence the name. Thereby the original TS is retained.

3.1 Grouping Function

The conceptual idea of a view is to group states by some criteria and structure the rest of the system accordingly. To formalize the grouping we define a dedicated function.

Definition 3.1. Let $TS = (S, Act, \longrightarrow, I, AP, L)$ be a transition system. We call any function $F : S \rightarrow \mathbb{N}$ a *grouping function*.

Two states are grouped to a new state if and only if the grouping function maps them to the same value. The definition offers an easy way of defining groups of states and labels them with a natural number. It is also very close to the actual implementation later on. The exact mapping depends on the desired grouping. In order to define a new set of states for the view, we define an equivalence relation R based on a given grouping function F .

Definition 3.2. Let F be a grouping function. We define the equivalence relation $R := \{(s_1, s_2) \in S \times S \mid F(s_1) = F(s_2)\}$

R is an equivalence relation because the equality relation is one. The property directly conveys to R . We observe that two states s_1, s_2 are grouped to a new state if and only if $(s_1, s_2) \in R$. This is if and only if the case when $s_1, s_2 \in [s_1]_R = [s_2]_R$ where $[s_i]_R$ denotes the equivalence class of R .

3.2 Formal Definition

The definition of a view depends on a given transition system and a grouping function F . We derive the equivalence relation R as in Definition 3.2 and use its equivalence classes $[s]_R$ as states for the view. The rest of the transition system is structured accordingly.

Definition 3.3. Let $TS = (S, Act, \longrightarrow, I, AP, L)$ be a transition system and F a grouping function. A *view* is a transition system $(S', Act', \longrightarrow', I', L')$ that is derived from TS where

- $S' = \{[s]_R \mid s \in S\}$ where R is an equivalence relation according to Definition 3.2,
- $Act' = Act$
- $\longrightarrow' = \{([s_1]_R, \alpha, [s_2]_R) \mid \exists s_1 \in [s_1]_R \exists s_2 \in [s_2]_R : ([s_1]_R, \alpha, [s_2]_R) \in \longrightarrow\}$
- $I' = \{[s']_R \in S' \mid \exists s \in [s']_R : s \in I\}$

- $L' : S' \rightarrow \mathcal{P}(AP), [s]_R \mapsto \bigcup_{s \in [s]_R} \{L(s)\}$

Note that the definition is in a most general form in the sense that if in a view a property accounts to one part of some entity the whole entity receives the property i.e.

- $(s_1, \alpha, s_2) \in \longrightarrow \Rightarrow ([s_1]_R, \alpha, [s_2]_R) \in \longrightarrow'$
- $s \in I \Rightarrow [s]_R \in I'$
- $\forall s \in S : L(s) \in L'([s]_R)$

4 View Examples

4.1 Transition Systems

4.2 Markov Chain

4.3 Markov Decision Process

4.4 Comparison of the Examples

5 Outlook

References