

Wenzhou Yi Xiang Electronic Technology Co., Ltd.

FCC REPORT

Applicant:	Wenzhou Yi Xiang Electronic Technology Co., Ltd.
Address:	B17-7 Mechanical Industrial Park, Wanquan Light Industry Production Base, Pingyang County, Wenzhou City, Zhejiang Province, China
Product Name:	FASCIAL GUN MASSAGE
Trade Name:	/
Model:	KK-26
Prepared By :	Ningbo Zhengou Testing Technology Co., Ltd. 1st Floor, Building 041, Building B, No. 188 Jinghua Road, Ningbo High tech Zone, Zhejiang Province, China.
Test Date:	Mar.19,2025-Mar.24,2025
Date of Report :	Mar.24,2025
Report No.:	ZOL250324Y8079-2RC

TABLE OF CONTENTS

TEST REPORT DECLARATION.....	3
1. GENERAL INFORMATION	4
1.1. Report information	4
1.2. Test Facility	4
1.3. Test Uncertainty	4
2. PRODUCT DESCRIPTION	5
2.1. EUT Description.....	5
2.2. Test Conditions.....	5
3. TEST RESULTS SUMMARY	6
4. TEST EQUIPMENT USED	7
4.1. For Conducted Emission Test	7
4.2. For Radiated Emission Measurement.....	7
5. CONDUCTED EMISSION TEST	8
5.1. Block Diagram of Test Setup	8
5.2. Test Standard.....	8
5.3. Conducted Emission Limit(Class B).....	8
5.4. EUT Configuration on Test.....	8
5.5. Operating Condition of EUT	8
5.6. Test Procedure.....	9
5.7. Test Result.....	9
6. RADIATED EMISSION MEASUREMENT.....	10
6.1. Block Diagram of EUT Configuration	10
6.2. Test Standard.....	10
6.3. Radiated Emission Limit(Class B)	10
6.4. EUT Configuration on Test.....	11
6.5. Operating Condition of EUT	11
6.6. Test Procedure.....	11
6.7. Test Result.....	11
APPENDIX I Test Curves	
APPENDIX II(Photos of the EUT)	

TEST REPORT DECLARATION

Applicant	:	Wenzhou Yi Xiang Electronic Technology Co., Ltd.
Address	:	B17-7 Mechanical Industrial Park, Wanquan Light Industry Production Base, Pingyang County, Wenzhou City, Zhejiang Province, China
EUT Description	:	FASCIAL GUN MASSAGE
Model Number	:	KK-26

Test Standards:

FCC Part 15:2016

The EUT described above is tested by US to determine the maximum emission levels emanating from the EUT, the maximum emission levels are compared to the FCC Part 15 limits. The measurement results are contained in this test report. and Ningbo Zhengou Testing Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT is to be technically compliant with the FCC requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of Ningbo Zhengou Testing Technology Co., Ltd.

Prepared by :

Jerry Qin

Assistant

Tested by :

Toby Zhong

Test Engineer

Reviewer :


Finerb bai

Supervisor

Approved & Authorized Signer :

Kubo Lee

Kubo Lee / Manager



1. GENERAL INFORMATION

1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that ZOL approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that ZOL in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, ZOL therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through ZOL, unless the applicant has authorized ZOL in writing to do so.

1.2. Test Facility

The test site used to collect the data is located on the
Ningbo Zhengou Testing Technology Co., Ltd.
The Test Site is constructed and calibrated to meet the FCC requirements.

1.3. Test Uncertainty

(95% confidence levels, $k=2$)

Test Item	Uncertainty
Uncertainty for Radiation emission test (30MHz to 1GHz)	4.0dB

2. PRODUCT DESCRIPTION

2.1.EUT Description

Description	:	FASCIAL GUN MASSAGE
Applicant	:	Wenzhou Yi Xiang Electronic Technology Co., Ltd. B17-7 Mechanical Industrial Park, Wanquan Light Industry Production Base, Pingyang County, Wenzhou City, Zhejiang Province, China
Manufacturer	:	Wenzhou Yi Xiang Electronic Technology Co., Ltd. B17-7 Mechanical Industrial Park, Wanquan Light Industry Production Base, Pingyang County, Wenzhou City, Zhejiang Province, China
Model Number	:	KK-26

2.2.Test Conditions

Temperature: 23~25 °C

Relative Humidity: 55~63 %

3. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	Test Results
Conducted disturbance	N.A
Radiated disturbance	Pass

Remark: "N/A" means "Not applicable."

4. TEST EQUIPMENT USED

4.1. For Conducted Emission Test


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESHS30	828985/018	Jun. 01, 24	1 Year
2.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	Jun. 01, 24	1 Year
3.	L.I.S.N.	Rohde & Schwarz	ESH2-Z5	834549/005	Jun. 01, 24	1 Year
4.	Conical	Emtek	N/A	N/A	N/A	N/A
5.	Voltage Probe	Schwarzbeck	TK9416	N/A	Jun. 01, 24	1 Year
6.	Coaxial Switch	Anritsu	MP59B	6100214550	Jun. 01, 24	1 Year

4.2. For Radiated Emission Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	ANRITSU	MS2661C	6200140915	Jun. 01, 24	1 Year
2.	Test Receiver	Rohde&Schwarz	ESC830	828982/018	Jun. 01, 24	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	142	Jun. 01, 24	1 Year
4.	50 Coaxial Switch	Anritsu Corp	MP59B	6100237248	Jun. 01, 24	1 Year
5.	Cable	Schwarzbeck	AK9513	ACRX1	Jun. 01, 24	1 Year
6.	Cable	Rosenberger	N/A	FR2RX2	Jun. 01, 24	1 Year
7.	Cable	Schwarzbeck	AK9513	CRRX2	Jun. 01, 24	1 Year
8.	Cable	Schwarzbeck	AK9513	CRRX2	Jun. 01, 24	1 Year
9.	Single Phase Power Line Filter	MPE	23332C	N/A	Jun. 01, 24	1 Year
10.	Single Phase Power Line Filter	MPE	23333C	N/A	Jun. 01, 24	1 Year
11.	Signal Generator	HP	864A	3625U00573	Jun. 01, 24	1 Year

5. CONDUCTED EMISSION TEST

5.1. Block Diagram of Test Setup



(EUT: FASCIAL GUN MASSAGE)

5.2. Test Standard

FCC Part 15: 2016

5.3. Conducted Emission Limit(Class B)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

5.4. EUT Configuration on Test

The following equipments are installed on conducted emission test to meet Part 15 requirement and operating in a manner, which tends to maximize its emission characteristics in a normal application.

5.4.1. EUT Information

Model Number : KK-26
Serial Number : N/A

5.5. Operating Condition of EUT

5.5.1. Setup the EUT and simulators as shown in Section 5.1.

5.5.2. Turn on the power of all equipments.

5.5.3. Let the EUT work in test modes (On) and test it.

5.6. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver is used to test the emissions form both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

The bandwidth of the test receiver is set at 9kHz.


5.7. Test Result

N.A

6. RADIATED EMISSION MEASUREMENT


6.1. Block Diagram of EUT Configuration

6.1.1. Block Diagram of connection between the EUT and the simulators



(EUT: FASCIAL GUN MASSAGE)

6.1.2. Semi-Anechoic Chamber Test Setup Diagram



6.2. Test Standard

FCC Part 15: 2016

6.3. Radiated Emission Limit(Class B)

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMITS (dB μ V/m)
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
960 ~ 1000	3	54.0

Note:(1) The smaller limit shall apply at the edge between two frequency bands.

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT or system.

6.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Measurement to meet the Commission requirements and operating regulations in a manner which tends to maximize Its emission characteristics in normal application.

6.5.Operating Condition of EUT

6.5.1.Setup the EUT as shown on Section 6.1.2

6.5.2.Turn on the power of all equipments.

6.5.3.Let the EUT work in test mode(On) and measure it.

6.6.Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.


The bandwidth setting on the test receiver is 120 KHz.


The EUT is tested in Semi-Anechoic Chamber. The frequency range from 30MHz to 1000 MHz is checked.All the test results are listed in Section 6.7. and all the scanning waveform are attached within **Appendix I**.

6.7.Test Result

PASS

APPENDIX I Test Curves





APPENDIX II

(Photos of the EUT)

Photo 1 General Appearance of the EUT



Photo 2 General Appearance of the EUT



Photo 3 General Appearance of the EUT



Photo 4 General Appearance of the EUT



Photo 5 General Appearance of the EUT

