FIRST ARTICLE INSPECTION REPORT FORM 3 Part LDW270M10003 page 1

Drawing Requirement	Nominal	Tol +	Tol -	Measured Value	Inspection Method	Item	Nonconformance Report No.	Comments
1.9950	1.9950	.0005	.0005	1.9950	CMM	1		
ELECTRO ETCH PART NUMBER AND ALL OTHER MARKINGS IN REGION MARKED USE BOTH SIDES IF NECESSARY.				C	Visual	2		
MANUFACTURING OPERATIONS UNLESS OTHERWISE SPECIFIED NOTES CHECKED APPLY TO THIS DWG.				C	Visual	3		
DEPTH SHOWN FOR TAPPED HOLES IS FULL THDS. 2-3 IMP THDS. BEYOND PERMISSIBLE.				C	Visual	4		
.016R TO .062R ± .010	.000	.010	.010	C	CMM	5.1		
.063R TO .250R ± .015	.000	.015	.015	C	CMM	5.2		
OVER .250R ± .030	.000	.030	.030	C	CMM	5.3		
EXTERNAL THREAD LENGTH SHOWN INCLUDES 2 IMPERFECT THREADS MAX.				C	Visual	6		
-33 1.1700				1.1693	Visual	7		
-35 1.1720				1.1727	Visual	8		
1.1600	1.1600	.0005	.0005	1.1601	CMM	9		
1.1620	1.1620	.0005	.0005	1.1620	CMM	10		
1.1660	1.1660	.0005	.0005	1.1662	CMM	11		
1.1680	1.1680	.0005	.0005	1.1679	CMM	12		
1.1640	1.1640	.0005	.0005	1.1641	CMM	13		
3.375				3.3748	Visual	14		
16				C	Visual	15		
16				C	Visual	16		
.037 .032	.037	.000	.005	.0341	CMM	17		
16				C	Visual	18		
DO NOT CADMIUM PLATE & PAINT HOLES OR SURFACES MARKED WITH DOUBLE ASTERISK.				C	Visual	19		
MISMATCH STEP OF ± .005 PERMISSIBLE DUE TO CHANGE OF CUTTERS AT INSIDE INTERSECTING SURFACES.				C	Visual	20		
DIAMETERS MARKED C MUST BE CONCENTRIC WITHIN .002 FULL INDICATOR READING				C	Visual	21		
-45 1.1820				1.1822	Visual	22		
-37 1.1740				1.1733	Visual	23		
-47 1.1840				1.1834	Visual	24		
-51 1.1880				1.1886	Visual	25		
-43 1.1800				1.1794	Visual	26		
-49 1.1860				1.1855	Visual	27		
-39 1.1760				1.1759	Visual	28		
-41 1.1780				1.1777	Visual	29		
4 HOLES EQUALLY SPACED WITHIN .001 OF TRUE LOCATION ▲ SEE NOTE 1				C	Visual	30		
CHAMFER 45° X .156 (3)	45.0000	.0312	.0312	44.9928	CMM	31.1		
CHAMFER 45° X .156 (3)	45.0000	.0312	.0312	44.9906	CMM	31.2		
CHAMFER 45° X .156 (3)	45.0000	.0312	.0312	44.9910	CMM	31.3		
.066-.067 HOLE	.0665	.0005	.0005	.0664	CMM	32		
2.506				2.5061	Visual	33		

Drawing Requirement	Nominal	Tol +	Tol -	Measured Value	Inspection Method	Item	Nonconformance Report No.	Comments
1.253				1.2535	Visual	34		
2.750 DIA € (BASIC)				2.7500	Visual	35		
.256-.263 HOLE(3)	.2595	.0035	.0035	.2591	CMM	36.1		
.256-.263 HOLE(3)	.2595	.0035	.0035	.2590	CMM	36.2		
.256-.263 HOLE(3)	.2595	.0035	.0035	.2585	CMM	36.3		
HOLES MUST BE KEPT FREE OF CHROME PLATING SOLUTION.				C	Visual	37		
ALL DIMENSIONS SHOWN TO BE MET AFTER CADMIUM PLATING. THICKNESS OF PLATE .0003 MIN. TO .0005 MAX. MIN. THICKNESS TO BE .0002 ON THREADED AREAS. NO ALLOWANCE FOR PLATING IN HOLES				C	Visual	38		
125 SURFACE ROUGHNESS PER MIL-STD-10				C	Visual	39		
-57 1.1940				1.1942	Visual	40		
-61 1.1980				1.1978	Visual	41		
-65 1.2760				1.2760	Visual	42		
-55 1.1920				1.1913	Visual	43		
-59 1.1960				1.1956	Visual	44		
-53 1.1900				1.1906	Visual	45		
-63 1.2730				1.2727	Visual	46		
2.101 2.100	2.101	.000	.001	2.1006	CMM	47		
.125 R				.1252	Visual	48		
.750				.7493	Visual	49		
1.253				1.2535	Visual	50		
2.506				2.5054	Visual	51		
A DIA REF				REF	Visual	52		
BREAK EDGE .002 MAX				C	Visual	53		
REMOVE ALL BURRS. BREAK ALL EDGES .015-.031				C	Visual	54		
200 FOR ALL HOLES				C	Visual	55		
INSPECTION INFORMATION MINIMUM PERMISSIBLE AVERAGE EDGE DISTANCE MARKED IS				C	Visual	56		
SYMBOL V DENOTES SURFACE TO BE MACHINED				C	Visual	57		
-69 1.2820				1.2815	Visual	58		
-73 1.2880				1.2884	Visual	59		
-75 1.2910				1.2917	Visual	60		
-79 1.2970				1.2969	Visual	61		
LDW270M10003-81 1.3000				1.2996	Visual	62		
-77 1.2940				1.2936	Visual	63		
-71 1.2850				1.2843	Visual	64		
-67 1.2790				1.2795	Visual	65		
ELECTRO ETCH PART NO. AND ACTUAL A DIA PER LSP-14-4706 ON TAB ONLY. USE BOTH SIDES IF NECESSARY				C	Visual	66		
.125 R (2)				.1250	Visual	67.1		
.125 R (2)				.1256	Visual	67.2		
45° (BASIC)				44.9°	Visual	68		

Drawing Requirement	Nominal	Tol +	Tol -	Measured Value	Inspection Method	Item	Nonconformance Report No.	Comments
1.671 1.670	1.671	.000	.001	1.6706	CMM	69		
.2522-.2532 HOLE	.2527	.0005	.0005	.2517	CMM	70	NCR-2026-0147	
UNLESS OTHERWISE SPECIFIED TOLERANCE ON FLANGES IS ± 1/32				C	Visual	71		
LENGTHS OF AN, NAS & MS AL ALY RIVETS SHORTER THAN 1 INCH ARE NOT SPECIFIED.				C	Visual	72		
TOLERANCE ON LOFTED DELINEATIONS IS				C	Visual	73		
GRAIN DIRECTION OPTIONAL				C	Visual	74		
3. TOOLING FOR THIS PART IS SIMILAR TO LDW270M10014.				C	Visual	75		
2. PARTS SHALL BE CLEANED PER LSP-14-7072.				C	Visual	76		
1. FOR HOLES MARKED ▲ SEE DWG LDW270M10004 AND LDW270M10005 FOR CORRESPONDING HOLE PATTERN.				C	Visual	77		