Bubble No.	Sheet / Zone	Characteristic Description	Key Char.	Min	Max	Actual Measurement	Gauge Used	Acc / Rej	NCR #	Remarks
2	1/D7	MATERIAL: ALUMINUM, PLATE, 6061-T651, IN ACCORDANCE WITH ASTM B205.				Conforms	Visual	ACC		
3	1/D7	IDENTIFICATION MARKING SHALL BE LOCATED APPROXIMATELY WHERE SHOWN IN ACCORDANCE WITH MIL-STD-130.				Conforms	Visual	ACC		
4	1/D8	⌓ 0.016 A B C		0.0000	0.0160	0.0033	CMM	ACC		
5	1/D7	UNLESS OTHERWISE SPECIFIED, ALL BASIC DIMENSION SURFACES SHALL COMPLY WITH:				Conforms	Visual	ACC		
6	1/D6	WHEN THE FLATNESS OF DATUM FEATURE A EXCEEDS THE STATED PROFILE TOLERANCE IN THE FREE STATE, THE FEATURE MAY BE RESTRAINED TO DATUM PLANE A WITHIN THE SPECIFIED PROFILE TOLERANCE VALUE. THE ITEM SHALL BE DEEMED ACCEPTABLE WHEN FEATURES RELATED TO DATUM A MEET TOLERANCE REQUIREMENTS IN THIS RESTRAINED STATE.				Conforms	Visual	ACC		
6	1/D6	UNLESS OTHERWISE SPECIFIED, DIMENSIONS AND TOLERANCES ARE EXPRESSED IN INCHES AND SHALL BE INTERPRETED IN ACCORDANCE WITH ASME Y14.5-2009.				Conforms	Visual	ACC		
8	1/D7	INFORMATION ENCLOSED IN IS FOR REFERENCE ONLY.				Conforms	Visual	ACC		
9	1/A4	MECHANICAL REFERENCE DATASET SEE PDM FOR DEFINING DATA				Conforms	Visual	ACC		
10A	2/D7	0.250				0.2499	Visual	ACC		
10B	2/D7	0.250				0.2498	Visual	ACC		
11A	2/D7	0.825				0.8255	Visual	ACC		
11B	2/D7	0.825				0.8247	Visual	ACC		
12	2/D7	2.500				2.5007	Visual	ACC		
13A	2/D6	0.050				0.0507	Visual	ACC		
13B	2/D6	0.050				0.0497	Visual	ACC		
13C	2/D6	0.050				0.0507	Visual	ACC		
13D	2/D6	0.050				0.0503	Visual	ACC		
14	2/D5	⌖ Ø0.005(L) A B C		0.0000	0.0050	0.0023	CMM	ACC		
15A	2/D5	Ø0.370 - 0.380		0.370	0.380	0.3757	CMM	ACC		
15B	2/D5	Ø0.370 - 0.380		0.370	0.380	0.3734	CMM	ACC		
16A	2/D5	0.050				0.0501	Visual	ACC		
16B	2/D5	0.050				0.0499	Visual	ACC		
16C	2/D5	0.050				0.0500	Visual	ACC		
16D	2/D5	0.050				0.0493	Visual	ACC		
17.1	2/D4	⌴ Ø0.245 - 0.255		0.245	0.255	0.2509	CMM	ACC		
17.2	2/D4	↧0.100 ± 0.010		0.090	0.110	0.1027	CMM	ACC		
18.1	2/D4	Ø0.182 - 0.192		0.182	0.192	0.1860	CMM	ACC		
18.2	2/D4	↧0.250 ± 0.010		0.240	0.260	0.2481	CMM	ACC		
19	2/D4	⌖ Ø0.005(M) A B C		0.0000	0.0050	0.0031	CMM	ACC		
20	2/D4	⌖ Ø0.005(M) A B C		0.0000	0.0050	0.0023	CMM	ACC		
21A	2/D4	0.050				0.0508	Visual	ACC		
21B	2/D4	0.050				0.0504	Visual	ACC		
21C	2/D4	0.050				0.0507	Visual	ACC		
21D	2/D4	0.050				0.0495	Visual	ACC		

Bubble No.	Sheet / Zone	Characteristic Description	Key Char.	Min	Max	Actual Measurement	Gauge Used	Acc / Rej	NCR #	Remarks
21E	2/D4	0.050				0.0505	Visual	ACC		
22	2/D8	2.738				2.7381	Visual	ACC		
23A	2/D8	1.750				1.7500	Visual	ACC		
23B	2/D8	1.750				1.7497	Visual	ACC		
24	2/D4	1.680				1.6804	Visual	ACC		
25	2/D4	2.016				2.0159	Visual	ACC		
26A	2/D2	SR0.094				0.0941	Visual	ACC		
26B	2/D2	SR0.094				0.0946	Visual	ACC		
26C	2/D2	SR0.094				0.0935	Visual	ACC		
26D	2/D2	SR0.094				0.0942	Visual	ACC		
27A	2/D1	0.768				0.7677	Visual	ACC		
27B	2/D1	0.768				0.7682	Visual	ACC		
27C	2/D1	0.768				0.7682	Visual	ACC		
27D	2/D1	0.768				0.7675	Visual	ACC		
28A	2/C8	Ø0.188				0.1879	Visual	ACC		
28B	2/C8	Ø0.188				0.1883	Visual	ACC		
28C	2/C8	Ø0.188				0.1880	Visual	ACC		
28D	2/C8	Ø0.188				0.1876	Visual	ACC		
29A	2/C7	1.000				1.0003	Visual	ACC		
29B	2/C7	1.000				0.9999	Visual	ACC		
30.1	2/C5	Ø0.145 - 0.155		0.145	0.155	0.1498	CMM	ACC		
30.2	2/C5	↧0.100 ± 0.010		0.090	0.110	0.0829	CMM	ACC		
31	2/C5	⌖ Ø0.005(M) A B C		0.0000	0.0050	0.0012	CMM	ACC		
31	2/C5	⌖ Ø0.005(M) A B C		0.0000	0.0050	0.0015	CMM	ACC		
32	2/C5	0.672					Visual	ACC		
34	2/C5	1.344				1.3447	Visual	ACC		
35A	2/C7	1.412				1.4114	Visual	ACC		
35B	2/C7	1.412				1.4127	Visual	ACC		
35C	2/C7	1.412				1.4128	Visual	ACC		
35D	2/C7	1.412				1.4117	Visual	ACC		
35E	2/C7	1.412				1.4114	Visual	ACC		
36	2/C7	2.375				2.3752	Visual	ACC		
37A	2/C6	3.912				3.9128	Visual	ACC		
37B	2/C6	3.912				3.9118	Visual	ACC		
37C	2/C6	3.912				3.9116	Visual	ACC		
37D	2/C6	3.912				3.9121	Visual	ACC		
37E	2/C6	3.912				3.9117	Visual	ACC		
38	2/C6	4.037				4.0367	Visual	ACC		
39.1	2/C5	⌴ Ø0.245 - 0.255		0.245	0.255	0.2482	CMM	ACC		
39.2	2/C5	↧0.125 ± 0.010		0.115	0.135	0.1234	CMM	ACC		
40A	2/C5	0.050				0.0502	Visual	ACC		

Bubble No.	Sheet / Zone	Characteristic Description	Key Char.	Min	Max	Actual Measurement	Gauge Used	Acc / Rej	NCR #	Remarks
40B	2/C5	0.050				0.0496	Visual	ACC		
40C	2/C5	0.050				0.0497	Visual	ACC		
40D	2/C5	0.050				0.0496	Visual	ACC		
40E	2/C5	0.050				0.0494	Visual	ACC		
41	2/C5	⌖ Ø 0.005(M) A B C		0.0000	0.0050	0.0013	CMM	ACC		
42	2/B8	0.268				0.2686	Visual	ACC		
43	2/B7	∠ 0.008 A		0.0000	0.0080	0.0028	CMM	ACC		
44A	2/B6	45°				45.0°	Visual	ACC		
44B	2/B6	45°				45.1°	Visual	ACC		
44C	2/B6	45°				44.9°	Visual	ACC		
44D	2/B6	45°				45.0°	Visual	ACC		
44E	2/B6	45°				44.9°	Visual	ACC		
45A	2/B5	0.518				0.5173	Visual	ACC		
45B	2/B5	0.518				0.5174	Visual	ACC		
45C	2/B5	0.518				0.5176	Visual	ACC		
45D	2/B5	0.518				0.5172	Visual	ACC		
45E	2/B5	0.518				0.5181	Visual	ACC		
45F	2/B5	0.518				0.5183	Visual	ACC		
45G	2/B5	0.518				0.5186	Visual	ACC		
46A	2/B5	0.050				0.0507	Visual	ACC		
46B	2/B5	0.050				0.0494	Visual	ACC		
46C	2/B5	0.050				0.0506	Visual	ACC		
46D	2/B5	0.050				0.0507	Visual	ACC		
46E	2/B5	0.050				0.0495	Visual	ACC		
47	2/B2	0.134				0.1333	Visual	ACC		
48	2/B8	⊥ 0.010 A B		0.0000	0.0100	0.0030	CMM	ACC		
49	2/B8	0.168				0.1685	Visual	ACC		
50	2/B4	⏥ 0.005		0.0000	0.0050	0.0026	CMM	ACC		
51	2/B4	⌓ 0.016		0.0000	0.0160	0.0096	CMM	ACC		
52	2/B3	0.138				0.1378	Visual	ACC		
53	2/B3	4 SURFACES				Conforms	Visual	ACC		
54A	2/A3	R0.032 ±0.010		0.022	0.042	0.0360	CMM	ACC		
54B	2/A3	R0.032 ±0.010		0.022	0.042	0.0335	CMM	ACC		
54C	2/A3	R0.032 ±0.010		0.022	0.042	0.0327	CMM	ACC		
54D	2/A3	R0.032 ±0.010		0.022	0.042	0.0335	CMM	ACC		
55	3/D5	3.869				3.8685	Visual	ACC		
56	3/D6	1.785				1.7854	Visual	ACC		
57	3/D5	2.257				2.2563	Visual	ACC		
58	3/D5	2.928				2.9278	Visual	ACC		
59	3/C6	0.785				0.7855	Visual	ACC		
60	3/C6	0.806					Visual	ACC		

Bubble No.	Sheet / Zone	Characteristic Description	Key Char.	Min	Max	Actual Measurement	Gauge Used	Acc / Rej	NCR #	Remarks
61	3/C6	0.168				0.1674	Visual	ACC		
62A	3/C3	0.168				0.1683	Visual	ACC		
62B	3/C3	0.168				0.1683	Visual	ACC		
63	3/C7	1.806				1.8060	Visual	ACC		
64	3/C3	1.209				1.2091	Visual	ACC		
65	3/C3	1.459				1.4594	Visual	ACC		
66	3/C2	1.713				1.7135	Visual	ACC		
67A	3/C2	2.570				2.5703	Visual	ACC		
67B	3/C2	2.570				2.5708	Visual	ACC		
68A	3/B7	⊕ 4X Ø0.005(M) A B C		0.0000	0.0050	0.0079	CMM	ACC		
68B	3/B7	⊕ 4X Ø0.005(M) A B C		0.0000	0.0050	0.0026	CMM	ACC		
68C	3/B7	⊕ 4X Ø0.005(M) A B C		0.0000	0.0050	0.0010	CMM	ACC		
68D	3/B7	⊕ 4X Ø0.005(M) A B C		0.0000	0.0050	0.0014	CMM	ACC		
69	3/B5	R0.135				0.1352	Visual	ACC		
70	3/B5	0.010				0.0104	Visual	ACC		
71A	3/B4	Ø0.215 - 0.220		0.215	0.220	0.2201	CMM	ACC		
71B	3/B4	Ø0.215 - 0.225		0.215	0.225	0.2217	CMM	ACC		
71C	3/B4	Ø0.215 - 0.225		0.215	0.225	0.2192	CMM	ACC		
71D	3/B4	Ø0.215 - 0.225		0.215	0.225	0.2185	CMM	ACC		
72	3/B6	0.542				0.5421	Visual	ACC		
73	3/B5	2.832				2.8312	Visual	ACC		
74	3/B5	2.632				2.6321	Visual	ACC		
75	3/B4	⊕ Ø0.005(L) A B C		0.0000	0.0050	0.0020	CMM	ACC		
76	3/A5	3.495				3.4952	Visual	ACC		
77		Ø0.3125 ±0.005		0.307	0.318	0.3137	CMM	ACC		
78		PASSIVATE PER AMS 2700, METHOD 1, TYPE 2				Conforms	Visual	ACC		