Drawing Requirement	Nominal	Tol +	Tol -	Measured Value	Inspection Method	Item	Nonconformance Report No.	Comments
1.9950	1.9950	.0005	.0005	1.9951	CMM	1		
ELECTRO ETCH PART NUMBER AND ALL OTHER MARKINGS IN REGION MARKED USE BOTH SIDES IF NECESSARY.				C	Visual	2		
MANUFACTURING OPERATIONS UNLESS OTHERWISE SPECIFIED NOTES CHECKED APPLY TO THIS DWG.				C	Visual	3		
DEPTH SHOWN FOR TAPPED HOLES IS FULL THDS. 2-3 IMP THDS. BEYOND PERMISSIBLE.				C	Visual	4		
.016R TO .062R ± .010	.000	.010	.010	C	CMM	5.1		
.063R TO .250R ± .015	.000	.015	.015	C	CMM	5.2		
OVER .250R ± .030	.000	.030	.030	C	CMM	5.3		
EXTERNAL THREAD LENGTH SHOWN INCLUDES 2 IMPERFECT THREADS MAX.				C	Visual	6		
-33 1.1700				1.1696	Visual	7		
-35 1.1720				1.1723	Visual	8		
1.1600	1.1600	.0005	.0005	1.1599	CMM	9		
1.1625	1.1620	.0005	.0005	1.1620	CMM	10		
1.1660	1.1660	.0005	.0005	1.1658	CMM	11		
1.1680	1.1680	.0005	.0005	1.1682	CMM	12		
1.1640	1.1640	.0005	.0005	1.1649	CMM	13		
3.375				3.3747	Visual	14		
16				C	Visual	15		
16				C	Visual	15		
16				C	Visual	15		
16				C	Visual	16		
.037 .032	.037	.000	.005	.0347	CMM	17		
16				C	Visual	18		
DO NOT CADMIUM PLATE & PAINT HOLES OR SURFACES MARKED WITH DOUBLE ASTERISK.				C	Visual	19		
MISMATCH STEP OF ± .005 PERMISSIBLE DUE TO CHANGE OF CUTTERS AT INSIDE INTERSECTING SURFACES.				C	Visual	20		
DIAMETERS MARKED C MUST BE CONCENTRIC WITHIN .002 FULL INDICATOR READING				C	Visual	21		
-45 1.1820					Visual	22		
-37 1.1740				1.1745	Visual	23		
-47 1.1840				1.1833	Visual	24		
-51 1.1880				1.1883	Visual	25		
-43 1.1800				1.1798	Visual	26		
-49 1.1860				1.1861	Visual	27		
-39 1.1760				1.1756	Visual	28		
-41 1.1780				1.1779	Visual	29		
4 HOLES EQUALLY SPACED WITHIN .001 OF TRUE LOCATION ▲ SEE NOTE 1				C	Visual	30		
CHAMFER 45° X .156 (3)	45.0000	.0312	.0312	44.9973	CMM	31.1		
CHAMFER 45° X .156 (3)	45.0000	.0312	.0312	45.0007	CMM	31.2		
CHAMFER 45° X .156 (3)	45.0000	.0312	.0312	44.9949	CMM	31.3		
.066-.067 HOLE	.0665	.0005	.0005	.0665	CMM	32		

Drawing Requirement	Nominal	Tol +	Tol -	Measured Value	Inspection Method	Item	Nonconformance Report No.	Comments
2.560				2.5064	Visual	33		
1.253				1.2526	Visual	32		
2.750 DIA € (BASIC)				2.7494	Visual	35		
.256-.263 HOLE(3)	.2595	.0035	.0035	.2600	CMM	36.1		
.256-.263 HOLE(3)	.2595	.0035	.0035	.2604	CMM	36.2		
.256-.263 HOLE(3)	.2595	.0035	.0035	.2581	CMM	36.3		
HOLES MUST BE KEPT FREE OF CHROME PLATING SOLUTION.				C	Visual	37		
ALL DIMENSIONS SHOWN TO BE MET AFTER CADMIUM PLATING. THICKNESS OF PLATE .0003 MIN. TO .0005 MAX. MIN. THICKNESS TO BE .0002 ON THREADED AREAS. NO ALLOWANCE FOR PLATING IN HOLES				C	Visual	38		
125 SURFACE ROUGHNESS PER MIL-STD-10				C	Visual	39		
-57 1.1940				1.1937	Visual	40		
-61 1.1980				1.1985	Visual	41		
-65 1.2760				1.2754	Visual	42		
-55 1.1920				1.1927	Visual	43		
-59 1.1960				1.1955	Visual	44		
-53 1.1900				1.1894	Visual	45		
-63 1.2730				1.2724	Visual	46		
2.101 2.100	2.101	.000	.001	2.1004	CMM	47		
.125 R				.1244	Visual	48		
.750				.7496	Visual	49		
1.253				1.2523	Visual	50		
2.506				2.5059	Visual	51		
A DIA REF				REF	Visual	52		
BREAK EDGE .002 MAX				C	Visual	53		
REMOVE ALL BURRS. BREAK ALL EDGES .015-.031				C	Visual	54		
200 FOR ALL HOLES				C	Visual	55		
INSPECTION INFORMATION MINIMUM PERMISSIBLE AVERAGE EDGE DISTANCE MARKED IS				C	Visual	56		
-69 1.2820				1.2820	Visual	58		
-73 1.2880				1.2879	Visual	59		
-75 1.2910				1.2912	Visual	60		
-79 1.2970				1.2963	Visual	61		
LDW270M10003-81 1.3000				1.2993	Visual	62		
-77 1.2940				1.2940	Visual	63		
-71 1.2850				1.2850	Visual	64		
-67 1.2790				1.2798	Visual	65		
ELECTRO ETCH PART NO. AND ACTUAL A DIA PER LSP-14-4706 ON TAB ONLY. USE BOTH SIDES IF NECESSARY				C	Visual	66		
.125 R (2)				.1243	Visual	67.1		
.125 R (2)				.1258	Visual	67.2		
45° (BASIC)				44.9°	Visual	68		

Drawing Requirement	Nominal	Tol +	Tol -	Measured Value	Inspection Method	Item	Nonconformance Report No.	Comments
1.671 1.670	1.671	.000	.001	1.6714	CMM	69		
.2522-.2532 HOLE	.2527	.0005	.0005		CMM	70		
UNLESS OTHERWISE SPECIFIED TOLERANCE ON FLANGES IS ± 1/32				C	Visual	71		
LENGTHS OF AN, NAS & MS AL ALY RIVETS SHORTER THAN 1 INCH ARE NOT SPECIFIED.				C	Visual	72		
TOLERANCE ON LOFTED DELINEATIONS IS				C	Visual	73		
GRAIN DIRECTION OPTIONAL				C	Visual	74		
3. TOOLING FOR THIS PART IS SIMILAR TO LDW270M10014.				C	Visual	75		
2. PARTS SHALL BE CLEANED PER LSP-14-7072.				C	Visual	76		
Ø.3125 ±.005	.3125	.0050	.0050	.3137	CMM	78		
PASSIVATE PER AMS 2700, METHOD 1, TYPE 2				C	Visual	79		