

```
first you set up the working space by:
    source ~/.bashrc && iflow --version
    mkdir ~/iflow-test && cd ~/iflow-test
```

and then the actual execution

```
[nnorian@nnorian iflow-test]$ iflow wizard
```

IncidentFlow Wizard

Answer the questions to generate a tailored playbook and report.

Select the attack technique:

- 1) T1566 – Phishing (Initial Access)
 - 2) T1059.001 – PowerShell Execution
 - 3) T1055 – Process Injection
- > 1

Output base name (files will be <name>.iflow and <name>_report.md) [incident]: test_phishing

T1566 – Phishing Response

Answer each question to configure the playbook.

What severity level triggered this alert?

- 4) LOW
 - 5) MEDIUM
 - 6) HIGH
 - 7) CRITICAL
- > 3

What type of phishing was detected?

- 8) Spearphishing attachment (T1566.001)
 - 9) Spearphishing link (T1566.002)
 - 10) Unknown / investigate both
- > 1

Was the attachment opened or payload executed on any endpoint?

- 11) Yes
 - 12) No
- > 1

Is manual escalation to an incident commander required?

- 13) Yes
 - 14) No
- > 1

```
✓ Playbook saved: test_phishing.iflow
✓ Report saved: test_phishing_report.md
[nnorian@nnorian iflow-test]$

[nnorian@nnorian iflow-test]$ ls
test_phishing.iflow test_phishing_report.md
[nnorian@nnorian iflow-test]$ cat test_phishing_report.md
```

IncidentFlow Incident Report

Generated: 2026-04-10 14:27:26

Configuration

team

- **lead:** "soc-lead"
- **members:** ["analyst_tier1", "analyst_tier2", "forensics"]
- **escalation_chain:** tier1 -> tier2 -> incident_commander

environment

- **name:** "production"
- **level:** HIGH

notification

- **channel:** "slack"
 - **fallback:** "email"
-

Playbook: PhishingResponse

Trigger: incident.severity >= HIGH

Phase: triage

- LOG: "T1566 Phishing triage initiated"
- ASSIGN: emailFlagged = checkEmailAlert(source: incident.alert_source)
- VERIFY: emailFlagged
 - ON_FAIL:
 - LOG: "Alert could not be confirmed – closing as false positive"
 - SEVERITY LOW

- GOTO: report_close
- SEVERITY HIGH
- LOG: "Spearphishing attachment detected (T1566.001)"
- GOTO: contain_attachment

Phase: contain_attachment

- LOG: "Containing spearphishing attachment – T1566.001"
- ASSIGN: affectedUsers = queryMailLogs(filter: "same_sender_hash")
- PARALLEL:
 - D0: quarantineEmail(scope: affectedUsers, reason: "malicious_attachment")
 - D0: blockSender(action: "blacklist")
 - D0: extractIOCs(type: "attachment", output: "ioc_list")
 - SEVERITY CRITICAL
 - LOG: "Payload executed on endpoint – promoting severity"
 - GOTO: endpoint_triage

Phase: endpoint_triage

- LOG: "Endpoint compromise suspected – running forensic checks"
- FOR EACH host IN affectedUsers.devices:
 - ASSIGN: result = runEDRScan(host: host, profile: "phishing_followup")
 - IF result.malware_found == TRUE:
 - THEN:
 - D0: isolateHost(target: host, reason: "phishing_payload_exec")
 - LOG: "Host isolated"
 - ELSE:
 - LOG: "Host clean"
 - WAIT ack FROM forensics TIMEOUT 30min
 - ON_TIMEOUT:
 - SEVERITY CRITICAL
 - GOTO: escalate
 - GOTO: notify_users

Phase: notify_users

- LOG: "Notifying affected users"
- D0: sendUserNotification(scope: affectedUsers, template: "phishing_awareness", channel: "email")

- DO: alertOnCall(service: "security_awareness", priority: MEDIUM)
- GOTO: resolve

Phase: escalate

- PARALLEL:
 - DO: notifyManager(level: CRITICAL)
 - DO: createTicket(priority: CRITICAL, type: "phishing_escalation")
 - SEVERITY CRITICAL
 - LOG: "Escalated to incident commander"

Phase: resolve

- ASSIGN: status = verifyEmailEnvironmentClean()
- VERIFY: status
 - ON_FAIL:
 - LOG: "Environment not clean – re-escalating"
 - GOTO: escalate
 - SEVERITY LOW
 - LOG: "Phishing campaign contained and remediated"

Phase: report_close

- LOG: "Incident closed as false positive after triage"

Report

- DO: closeTicket(id: incident.id, resolution: "phishing_remediated")
 - DO: generateReport(template: "T1566_postmortem", output: "pdf")
 - DO: updateIOCFeed(source: ioc_list)
 - SEVERITY LOW
 - LOG: "T1566 Phishing playbook completed"
-

Summary

Severity Trail

1. LOW
2. HIGH
3. CRITICAL

4. CRITICAL
5. CRITICAL
6. LOW
7. LOW

Actions Performed

- quarantineEmail(scope: affectedUsers, reason: "malicious_attachment")
- blockSender(action: "blacklist")
- extractIOCs(type: "attachment", output: "ioc_list")
- isolateHost(target: host, reason: "phishing_payload_exec")
- sendUserNotification(scope: affectedUsers, template: "phishing_awareness", channel: "email")
- alertOnCall(service: "security_awareness", priority: MEDIUM)
- notifyManager(level: CRITICAL)
- createTicket(priority: CRITICAL, type: "phishing_escalation")
- closeTicket(id: incident.id, resolution: "phishing_remediated")
- generateReport(template: "T1566_postmortem", output: "pdf")
- updateIOCFeed(source: ioc_list)

Log Entries

- "T1566 Phishing triage initiated"
- "Alert could not be confirmed – closing as false positive"
- "Spearphishing attachment detected (T1566.001)"
- "Containing spearphishing attachment – T1566.001"
- "Payload executed on endpoint – promoting severity"
- "Endpoint compromise suspected – running forensic checks"
- "Host isolated"
- "Host clean"
- "Notifying affected users"
- "Escalated to incident commander"
- "Environment not clean – re-escalating"
- "Phishing campaign contained and remediated"
- "Incident closed as false positive after triage"
- "T1566 Phishing playbook completed"