

# Introduction to Computer and Programming

## Chapter 3: Functions and recursion

Manuel

Fall 2018

# Outline

- ① Basics on functions
- ② Common MATLAB functions
- ③ Recursion

# From script to function

## Script:

- Sequence of MATLAB statements
- No input/output arguments
- Operates on data on the workspace

# From script to function

## Script:

- Sequence of MATLAB statements
- No input/output arguments
- Operates on data on the workspace

## Function:

- Sequence of MATLAB statements
- Accepts input/output arguments
- Variable are not created on the workspace

# Functions in MATLAB

Basics on MATLAB functions:

- Function saved in a .m file
- The .m file must be in the “path”
- The function name must be the same as the filename
- Prototype: `function [out1,out2,...] = Myfct(in1,inp2,...)`
- Functions can be called from an .m file or from the workspace

# Functions in MATLAB

## Basics on MATLAB functions:

- Function saved in a .m file
- The .m file must be in the “path”
- The function name must be the same as the filename
- Prototype: `function [out1,out2,...] = Myfct(in1,inp2,...)`
- Functions can be called from an .m file or from the workspace

## Script vs. function:

```
1 r=1.496*10^11; c=4.379*10^9;  
2 G=6.674*10^-11;  
3 T=365*24*3600;  
4 V=4*pi/3*(c/(2*pi))^3;  
5 M=4*pi^2*r^3/(G*T^2);  
6 M/V
```

### density.m

```
1 function d=density(r,c,T)  
2     G=6.674*10^-11;  
3     V=4*pi/3*(c/(2*pi))^3;  
4     M=4*pi^2*r^3/(G*T^2);  
5     d=M/V;
```

## Sub-functions

A .m file can contain:

- A main function: has the same name as the filename
- Sub-functions: only accessible by functions from the **same** file

Example.

Write a function returning the mean and the standard deviation.

Calculate the mean in a sub-function

## Sub-functions

A .m file can contain:

- A main function: has the same name as the filename
- Sub-functions: only accessible by functions from the **same** file

Example.

Write a function returning the mean and the standard deviation.  
Calculate the mean in a sub-function

stat.m

```
1 function [mean,stdev] = stat(x)
2     n = length(x);
3     mean = avg(x,n);
4     stdev = sqrt(sum((x-mean).^2)/n);
5
6 function mean = avg(x,n)
7     mean = sum(x)/n;
```



# Functions and sub-functions

In the previous example:

- How to save both the variable mean and stdev?
- How many Input have the avg and stat functions?
- Is the function avg accessible from the workspace, why?
- If mean is changed into m in the first function does it need to be changed in the second function, why?

# Outline

- 1 Basics on functions
- 2 Common MATLAB functions
- 3 Recursion

# Mathematical functions

Basic math calculations:

- Defining a function: `f=@(x) x^2-1`
- Integral: `syms z; int(z^2+1), int(z^2+1,0,1)`
- Differentiation: `syms t; diff(sin(t^2))`
- Limit: `limit(sin(t)/t,0)`
- Finding a root of a continuous function: `fzero(f,0.5)`
- Square root: `sqrt(9)`
- Nth root: `nthroot(4, 3)`

# Useful functions

The save and load functions:

- Save variables: `save('file','var1','var2',...,'format')`
- Load variables: `load('file','format')`

## Useful functions

The save and load functions:

- Save variables: `save('file','var1','var2',...,'format')`
- Load variables: `load('file','format')`

Random number generation:

- `rand(n,m)`:  $n \times m$  matrix of random numbers (uniform distribution )
- `randn(n,m)`:  $n \times m$  matrix of random numbers (standard normal distribution)
- `random('dist',parameters)`: random numbers following the distribution `dist`
- `rand('state',datenum(clock))`: enforce a specific seed
- `randperm(n)`: random permutation

# The sprintf function

Writing formatted data into a string:

- Command: `sprintf('string', variable1, variable2,...)`
- 'string': text composed of
  - Words, spaces, numbers
  - “% flags”, replaced by the value of variables, e.g. `'%g'`
  - Special characters, e.g. `'\n\t'`

# The sprintf function

Writing formatted data into a string:

- Command: `sprintf('string', variable1, variable2,...)`
- 'string': text composed of
  - Words, spaces, numbers
  - “% flags”, replaced by the value of variables, e.g. `'%g'`
  - Special characters, e.g. `'\n\t'`

Example.

```
1 a=pi; b=sprintf('%g',pi)
2 sprintf('%d',round(pi))
3 sprintf('%s','pi')
4 a=[1 2 3;2 5 6;3 7 8];
5 text=sprintf('size: %d by %d', size(a))
```

# File input/output

Basic idea: open a stream between MATLAB and a file





# File input/output

Basic idea: open a stream between MATLAB and a file



```
1 fd=fopen('file.txt', 'permission')
2 fclose(fd)
```

Different permissions to access a file:

- Read only: r
- Write in a new file: w
- Append to a file: a
- Read and write: r+
- Read and overwrite: w+
- Read and append: a+

# The fprintf and fscanf functions

Accessing a file:

- Write: `fprintf(fd, 'string', 'variables')`
- Read:
  - Following a known format: `fscanf(fd, 'format')`
    - Convert values into the specified format
    - Return an array containing the read elements
  - A whole line: `fgetl(fd)`

# The fprintf and fscanf functions

Accessing a file:

- Write: `fprintf(fd, 'string', 'variables')`
- Read:
  - Following a known format: `fscanf(fd, 'format')`
    - Convert values into the specified format
    - Return an array containing the read elements
  - A whole line: `fgetline(fd)`

Any opened stream must be closed

## Exercise

Given a text file where each line is composed of three fields, namely first-name, name and email, write a MATLAB function generating a text file where (i) the order of the lines is random and (ii) each line is composed of the same fields in the following order: name, first-name, and email.

## Exercise

sortnames.m

```
1 function sortnames(fininput, foutput)
2     fd1=fopen(fininput,'r');
3     i=1;
4     line=fgetl(fd1);
5     while line ~= -1
6         a=find(isspace(line),2);
7         info{i}=sprintf('%s %s %s\n', line(a(1)+1:a(2)-1), ...
8             line(1:a(1)-1), line(a(2)+1:end));
9         i=i+1; line=fgetl(fd1);
10    end
11    fclose(fd1);
12
13    fd2=fopen(foutput,'w');
14    for j=randperm(i-1)
15        fprintf(fd2,info{j});
16    end
17    fclose(fd2);
```

# Questions


In the previous code:

- How is the code indented?
- How to check the last line was reached, why?
- How to access the different fields?
- How to perform a random permutation?
- Each time a file is opened it **must** be \_\_\_\_\_


# Outline

- ① Basics on functions
- ② Common MATLAB functions
- ③ Recursion

# What is recursion?



What is recursion?



What is recursion?



What is recursion?





# Recursive acronyms

Famous acronyms:

- GNU: GNU's Not Unix
- WINE: WINE Is Not an Emulator
- PHP: PHP Hypertext Preprocessor
- LAME: LAME Ain't an MP3 Encoder



# Recursion in computer science

Basic idea behind recursion:

- General case: given a process  $P$  and some data  $D$ , describe  $P$  using itself together with a simplified version  $D'$  of  $D$
- Computer science case: inside the function  $P(D)$ , call the function  $P(D')$

# Recursion in computer science

Basic idea behind recursion:

- General case: given a process  $P$  and some data  $D$ , describe  $P$  using itself together with a simplified version  $D'$  of  $D$
- Computer science case: inside the function  $P(D)$ , call the function  $P(D')$

Example.

A child couldn't sleep, so her mother told her a story about a little frog, who couldn't sleep, so the frog's mother told her a story about a little bear, who couldn't sleep, so the bear's mother told her a story about a little weasel...who fell asleep. ...and the little bear fell asleep; ...and the little frog fell asleep; ...and the child fell asleep.

# A short recursive story

For the sake of simplicity we work with integers and map the child to 3, the frog to 2, the bear to 1, and the weasel to 0.

Algorithm. (*Bedtime story*)

---

**Input** : An integer  $n$  representing an animal or a child

**Output:** The child and all the animals asleep

```
1 Function Read( $n$ ):  
2   | if  $n = 0$  then sleep( $n$ );  
3   | else  $i \leftarrow n - 1$ ; Read( $i$ ); sleep( $n$ );  
4 end
```

---

Question.

Draw a simple diagram showing how the recursion is applied

# Numbers in words

For an automated information service a telephone company needs the digits of phone numbers to be read digit by digit. Therefore you are asked to rewrite a sequence of digits into words, with a space between each word; no space at the beginning and at the end.

# Numbers in words

## Algorithm. (*Numbers in words*)

---

**Input** : A large integer  $n$

**Output** :  $n$ , digit by digit, using words

```
1 Function PrintDigit( $n$ ):
2   case  $n$  do
3     0: print('zero'); 1: print('one'); 2: print('two');
4     3: print('three'); 4: print('four'); 5: print('five');
5     6: print('six'); 7: print('seven'); 8: print('eight');
6     9: print('nine'); else: error('not a digit');
7   end case
8 end
9 Function PrintDigits( $n$ ):
10  if  $n < 10$  then
11    PrintDigit ( $n$ )
12  else
13    PrintDigits ( $n \text{ div } 10$ );
14    print(' '); PrintDigit ( $n \text{ mod } 10$ )
15  end if
16 end
```

# Recursion vs. iteration

When to prefer recursion over iteration:

- Recursive algorithm more obvious than iterative one
- Depends on the language

In MATLAB, C and C++, iterative algorithms should be preferred

# Recursion vs. iteration

When to prefer recursion over iteration:

- Recursive algorithm more obvious than iterative one
- Depends on the language

In MATLAB, C and C++, iterative algorithms should be preferred

Memory usage



# Key points

- Why should functions be preferred over scripts?
- How to perform mathematical calculations in MATLAB?
- How to save the state of the workspace?
- What is recursion?
- When to use recursion?

Thank you!