

VE230 Homework 7

2021 Summer

P.8-22 A uniform sinusoidal plane wave in air with the following phasor expression for electric intensity

$$\mathbf{E}_i(x, z) = \mathbf{a}_y 10e^{-j(6x+8z)} \quad (\text{V/m})$$

is incident on a perfectly conducting plane at $z = 0$.

- Find the frequency and wavelength of the wave.
- Write the instantaneous expressions for $\mathbf{E}_i(x, z; t)$ and $\mathbf{H}_i(x, z; t)$, using a cosine reference.
- Determine the angle of incidence.
- Find $\mathbf{E}_r(x, z)$ and $\mathbf{H}_r(x, z)$ of the reflected wave.
- Find $\mathbf{E}_r(x, z)$ and $\mathbf{H}_r(x, z)$ of the total field.

P.8-29 Consider the situation of normal incidence at a lossless dielectric slab of thickness d in air as shown in Fig. 1 with

$$\epsilon_1 = \epsilon_3 = \epsilon_0 \quad \text{and} \quad \mu_1 = \mu_3 = \mu_0.$$




Figure 1: Normal incidence at multiple dielectric interfaces

Problems:

- Find \mathbf{E}_{r0} , \mathbf{E}_2^+ and \mathbf{E}_2^- , and \mathbf{E}_{r0} in terms of \mathbf{E}_{i0} , d , ϵ_2 , and μ_2 .
- Will there be reflection at interface $z = 0$ if $d = \lambda_2/4$? If $d = \lambda_2/2$? Explain.

P.8-33 A uniform plane wave with $\mathbf{E}_i(z) = \mathbf{a}_x E_{i0} e^{-j\beta_0 z}$ in air propagates normally through a thin copper sheet of thickness d , as shown in Fig. 2. Neglecting multiple reflections within the copper sheets, find:




Figure 2: Plane wave propagating through a thin copper sheet

- E_2^+, H_2^+
- E_2^-, H_2^-
- E_{30}, H_{30}
- $(\mathcal{P}_{av})_3 / (\mathcal{P}_{av})_i$

Calculate $(\mathcal{P}_{av})_3 / (\mathcal{P}_{av})_i$ for a thickness d that equals one skin depth at 10 (MHz). (Note that this pertains to the shielding effectiveness of the thin copper sheet.)

P.8-37 A uniform plane wave with perpendicular polarization presented by Eqs. (8-196) and (8-197) is incident on a plane interface at $z = 0$, as shown in Fig. 3. Assuming $\epsilon_2 < \epsilon_1$ and $\theta_i > \theta_c$,

$$\mathbf{E}_i(x, z) = \mathbf{a}_y E_{i0} e^{-j\beta_1(x \sin \theta_i + z \cos \theta_i)} \quad (8-196)$$

$$\mathbf{H}_i(x, z) = \frac{E_{i0}}{\eta_1} (-\mathbf{a}_x \cos \theta_i + \mathbf{a}_z \sin \theta_i) e^{-j\beta_1(x \sin \theta_i + z \cos \theta_i)}. \quad (8-197)$$




Figure 3: Uniform plane wave incident obliquely on a plane dielectric boundary

- Obtain the phasor expressions for the transmitted field ($\mathbf{E}_t, \mathbf{H}_t$)
- Verify that the average power transmitted into medium 2 vanishes.

P.8-40 Glass isosceles triangular prisms shown in Fig. 4 are used in optical instruments. Assuming $\epsilon_r = 4$ for glass, calculate the percentage of the incident light power reflected back by the prism.




Figure 4: Light reflection by a right isosceles triangular prism

P.8-45 By using the Snell's law of reflection

- Express Γ and τ in terms of ϵ_{r1} , ϵ_{r2} and θ_i
- Plot Γ and τ versus θ_i for $\epsilon_{r1}/\epsilon_{r2} = 2.25$ for both perpendicular and parallel polarizations.