Research Frontiers in Computational Electromagnetics: A Comprehensive Literature Review of Emerging Paradigms and Industrial Applications

The discipline of computational electromagnetics (CEM) is currently traversing a significant period of redefinition, moving beyond its traditional role as a set of deterministic numerical recipes toward a unified, intelligent framework that integrates high-performance computing (HPC), artificial intelligence (AI), and quantum-algorithmic foundations. As the global technological landscape pivots toward the implementation of sixth-generation (6G) wireless networks, sub-wavelength nanophotonic integration, and the widespread adoption of wide-bandgap (WBG) power electronics, the demand for simulation tools that offer unprecedented speed, accuracy, and multiscale capability has never been more acute.[1] Modern electromagnetic environments are characterized by a level of complexity that frequently exhausts the resources of classical solvers, necessitating a shift toward physics-informed machine learning (PIML) and heterogeneous hardware acceleration.[4] This report provides an exhaustive review of the current research landscape in CEM, identifying key trends, emerging methodologies, and the critical challenges that will define the field through the end of this decade.

Advancements in Deterministic Numerical Solvers and Stability Theory

The foundational pillars of CEM—the Finite-Difference Time-Domain (FDTD) method, the Finite Element Method (FEM), and the Method of Moments (MoM)—continue to undergo rigorous theoretical refinement to address the limitations of grid dispersion, non-conformal boundaries, and computational overhead in electrically large systems.[3] One of the most significant areas of contemporary research involves the pursuit of guaranteed stability in time-domain simulations involving complex, non-uniform meshes.

Stability Refinements in Time-Domain Methods

The FDTD method, historically valued for its ability to handle non-linear and anisotropic materials, has seen a resurgence in research focusing on the 3-D Summation-By-Parts (SBP) and Simultaneous Approximation Term (SAT) framework. This approach provides a mathematically rigorous way to enforce boundary conditions while ensuring that the discrete energy of the system mimics the continuous energy of Maxwell's equations, thereby preventing the late-time instabilities that often plague 3-D FDTD simulations.[8] Recent developments have

successfully extended these concepts to SBP-SAT FDTD methods for complex 3-D environments, providing a robust validation against analytical solutions.[8]

Furthermore, the challenge of multiscale simulation, where features vary from the micrometer to the meter scale, has led to the development of Flux-Corrected Continuity (FCC) FDTD methods on non-uniform grids.[8] These methods maintain stability even with arbitrary grid ratios, allowing for high-fidelity modeling of localized features—such as antenna feed structures—within a much larger computational domain without requiring a uniform refinement of the entire grid.[8] The integration of symmetric FDTD subgridding methods further ensures that energy conservation is maintained at the interfaces of disparate grid resolutions, a critical requirement for simulating transient phenomena in complex packaging environments.[8]

Adaptive Finite Element and High-Order Methods

In the frequency domain, research into the Finite Element Method (FEM) has prioritized the development of 3-D parallel automatic mesh generation and adaptive refinement strategies (AFEM). The difficulty in balancing processor loads for unstructured meshes remains a primary bottleneck in distributed computing environments.[9] Consequently, research is increasingly focusing on machine learning-based approaches to develop sophisticated data structures that implement dynamic load balancing for multicore and manycore platforms.[9] High-order methods, such as the Discontinuous Galerkin Time-Domain (DGTD) method, are being applied to specialized problems like the simulation of electromagnetic waves in magnetized cold plasma.[8] These solvers utilize global-local error-driven p-adaptive schemes to dynamically adjust the polynomial order of basis functions, optimizing the computational expenditure in regions of varying field gradients.[8]

Solver Methodology	**Core Discretization Principle**	**Primary Research Thrust (2024-2026)**	**Computational Advantage**
SBP-SAT FDTD	Finite Differences	Discrete energy stability for 3D grids	Long-term transient stability [8]
FCC-FDTD	Non-uniform Grids	Flux-corrected continuity for stability	Multiscale modeling efficiency [8]
AFEM	Unstructured Meshes	ML-enhanced parallel load balancing	Complex topology accuracy [9]

BZT-DGTD	Discontinuous Galerkin	Magnetized plasma wave interactions	High-order p-adaptive precision [8]
Hybrid SNFT-FDTD	Near-field Transform	Spherical near-field to far-field mapping	Human exposure assessment [11]

The Integration of Artificial Intelligence and Maxwell's Equations

The most transformative trend in contemporary CEM research is the convergence of deep learning and Maxwellian physics. This shift is characterized by the move from purely data-driven black-box models to Physics-Informed Neural Networks (PINNs) and neural operators that respect the fundamental conservation laws of electromagnetism.[5]

Physics-Informed Neural Networks (PINNs) in Electromagnetics

PINNs represent a paradigm where the governing partial differential equations (PDEs) are embedded directly into the loss function of the neural network. For electromagnetic applications, the loss function is typically formulated as a weighted sum of the residual of Maxwell's equations, the boundary conditions, and the available observational data.[5] This approach allows for mesh-free simulations that can generalize beyond the training set more reliably than traditional machine learning models.[5]

However, the training of PINNs for electromagnetic wave equations is notoriously difficult due to the multi-objective optimization landscape. Research in 2025 has highlighted the "gradient pathology" where the PDE residual loss (often involving high-order derivatives) can dominate the boundary condition loss, leading to solutions that are mathematically consistent with the field equations but physically incorrect due to boundary violations.[5] Advanced optimizers like MultiAdam and learning rate annealing algorithms are being developed to adaptively rebalance these loss terms, improving predictive accuracy by up to two orders of magnitude in multiscale physics scenarios.[12]

Neural Operators and Surrogate Modeling

Beyond PINNs, the use of neural operators, such as Fourier Neural Operators (FNOs), is emerging as a powerful method for rapid surrogate modeling. These operators learn the mapping between infinite-dimensional function spaces, allowing them to predict full-wave solutions across a continuous spectrum of wavelengths even when trained only on discrete sampled data.[15] Recent studies have demonstrated electromagnetic surrogate solvers that achieve normalized mean squared errors as low as 71% below current state-of-the-art models for untrained wavelengths, while providing inference speeds more than 42 times faster than

conventional numerical solvers.[15] This capability is critical for the real-time optimization of photonic integrated circuits and metasurfaces, where traditional trial-and-error simulation cycles are prohibitively expensive.[16]

Electromagnetic Engineering for 6G and the Terahertz Gap

As the telecommunications industry prepares for the 6G era, computational research is focused on the "terahertz gap"—the frequency range between 100 GHz and 10 THz where electronic and photonic technologies overlap.[2] This spectrum offers the ultra-high bandwidth required for data rates exceeding 100 Gbit/s but presents unique propagation challenges, including extreme path loss and atmospheric absorption by water vapor and fog.[2]

Modeling Reconfigurable Intelligent Surfaces (RIS)

A central research topic in 6G is the modeling and optimization of Reconfigurable Intelligent Surfaces (RIS), also known as smart radio surfaces. These are programmable structures composed of a large number of metamaterial elements that can modulate the phase, amplitude, and polarization of incident waves to steer beams toward users or create virtual lines-of-sight in obstructed environments.[2]

Computational efforts in this area are split between large-scale system modeling and unit-cell meta-atom design. Stochastic geometry is being leveraged to model the deployment of RIS-empowered networks and derive closed-form expressions for key performance metrics like energy efficiency and data rate.[23] At the component level, AI-augmented design tools are used to co-optimize the physical structure of the meta-atoms with the digital control sub-systems.[9] Indoor field trials have demonstrated that strategically placed RIS panels can improve link budgets in the 2.5–2.7 GHz band by more than 20 dB, a precursor to their role in alleviating THz-band spectrum congestion.[2]

Terahertz Transceiver and Antenna Design

The design of THz transceivers requires moving away from traditional mixer architectures due to high power demands. Research is exploring pre-distortion techniques where signal information is fed directly into the source, necessitating complex non-linear modeling to ensure that the transmitted signal remains "clean" after intentional pre-distortion.[19] Furthermore, the integration of antennas directly into semiconductor packages—Antenna-in-Package (AiP) technology—is critical for minimizing propagation losses at THz frequencies.[24] Computational research into III-V semiconductors, such as InP and SiGe, is focused on their ability to provide the necessary transconductance for low-noise amplifiers and power amplifiers operating above 200 GHz.[24]

Spectrum Band	Frequency Range	Key 6G Application	Primary Computational Challenge
Sub-6 GHz	< 6 GHz	Broad coverage, legacy support	High-dimensional MIMO interference [2]
cmWave	7–15 GHz	Workhorse 6G spectrum	Manageable attenuation modeling [24]
mmWave	24–100 GHz	High-speed hotspots	Non-line-of-sight blockage [2]
sub-THz	90–300 GHz	Localized extreme data rates	Severe path loss & AiP design [19]
THz Band	0.3–10 THz	Integrated sensing & VR/AR	Atmospheric absorption & noise [2]

Nanophotonics, Metamaterials, and Nonlocal Wave Manipulation

The field of nanophotonics is currently dominated by the research into nonlocal metasurfaces, where the electromagnetic response is not locally defined but depends on the collective interaction of the entire array of meta-atoms.[25] This nonlocality, often referred to as spatial dispersion, enables functionalities such as wide-angle imaging and high-Q wavefront shaping that are unattainable with local metasurface designs.[25]

Physical Mechanisms of Nonlocality

Nonlocal effects in metasurfaces are primarily driven by collective resonances, such as guided-mode resonances (GMR) and quasi-bound states in the continuum (quasi-BIC).[25] In GMR, periodic structures couple transversely propagating waveguide modes into radiative diffraction orders, redirecting energy flow based on the lattice vector.[25] Quasi-BICs are generated by introducing controlled symmetry breaking in meta-atom arrays, providing the support for high-Q light field control essential for narrowband filtering and efficient photon-pair generation.[26]

The computational modeling of these phenomena requires a departure from the Local Response Approximation (LRA). When meta-atom characteristic lengths become comparable to the operating wavelength, near-field coupling alters the magnetic and electric responses based on separation distance.[26] Research is focusing on inverse design methods that integrate these coupling effects into the optimization loop, allowing for the creation of 10-layer nonlocal metasurfaces that can simulate wide-angle imaging over several wavelengths of free-space propagation.[25]

Nonlinear and Active Meta-optics

Nonlinear metasurfaces are being developed for applications such as ultraviolet (UV) light generation via second-harmonic generation (SHG) and four-wave mixing.[27] Unlike bulk nonlinear crystals, these metasurfaces distribute the nonlinear process in the transverse direction, using nonlocal resonances to enhance frequency conversion while circumventing traditional phase-matching requirements.[27] Computational research into active metasurfaces is exploring the use of phase-change materials and mechanical manipulation—such as kirigami-inspired hinges—to achieve "giant tunability" of the optical response post-fabrication.[29] This mechano-optical synergy allows for the dynamic tuning of high-Q resonances across broad spectral ranges by adjusting interparticle spacing through flexible substrate extension.[29]

Multiphysics Modeling in Power Electronics and Biomedicine

Electromagnetic fields do not exist in isolation, and their interaction with thermal and mechanical domains is a critical area of research for power systems and medical devices.[3] The rise of Wide Bandgap (WBG) semiconductors like SiC and GaN has allowed for more efficient power conversion but has also introduced extreme power densities that require sophisticated electro-thermal-mechanical modeling.[31]

High-Voltage Systems and Power Electronics

For high-voltage AC cable joints, research involves 3D electromagnetic-thermal coupling models to analyze the impact of contact resistance and insulation defects.[33] Numerical simulations have quantified that water tree defects in XLPE insulation can cause temperature rises of 20°C and electric field distortions up to 30 kV/mm, leading to potential catastrophic failure.[33] In the automotive sector, multiphysics integration is used to model electric drive technology, where the motor, inverter, battery, and cooling packaging are analyzed as a unified system.[30] This approach considers thermally induced deformations, magnetic power losses, and acoustic emissions to increase the "first-time-right" rate of new designs.[30]

Computational Bioelectromagnetics

The assessment of electromagnetic field (EMF) exposure is a persistent research topic, especially with the deployment of 5G/6G array antennas. Research in 2025 has utilized hybrid spherical near-field transformation (SNFT) and FDTD methods to assess power absorption (SAR) and resultant temperature rises in anatomical head models exposed to 28 GHz beams.[11] These studies are crucial for establishing safety limits for D-MIMO antennas in industrial indoor environments and ensuring that the input power of base stations does not violate local health regulations.[11]

Application Area	Primary Physical Coupling	Key Computational Goal	Reference
Power Converters	Electromagnetic-Thermal	SiC/GaN heat dissipation & EMI	31
Cable Joints	Electro-Thermal-Mechanical	Water tree defect & breakdown analysis	33
5G/6G Antennas	EM-Biological	SAR & tissue temperature rise assessment	11
Biomedical MEMS	EM-Fluidic-Mechanical	Targeted drug delivery & biosensing	34
Electric Drives	EM-Acoustic-Thermal	Motor noise & efficiency optimization	30

High-Performance Computing and the Software Ecosystem

As simulations grow in complexity, the hardware and software architectures supporting CEM are evolving. The field is moving away from monolithic, CPU-bound solvers toward cluster-based platforms built around GPU and specialized accelerators.[3]

GPU Acceleration and Scalable Solvers

GPU-accelerated simulations have become a standard requirement for handling electrically

large systems, such as full-vehicle EMC analysis and high-frequency antenna arrays.[3] Modern software frameworks, such as FDTDX, leverage the JAX ecosystem to provide automatic compilation and computational graph optimization for multi-GPU scaling.[37] These tools enable memory-efficient automatic differentiation by exploiting the time-reversibility of Maxwell's equations, allowing for the optimization of nanophotonic structures with millions of design parameters that were previously computationally inaccessible.[37]

The Role of Digital Twins and Cloud Computing

Digital twin technology is becoming a staple in industrial CEM, providing a virtual replica of a physical system that updates in real-time using sensor data.[3] This enables predictive maintenance and performance tracking under varying environmental conditions in industries like aerospace and robotics.[3] Cloud-based CEM solvers are also expanding, providing the elastic scaling required for thousands of design iterations in modern optimization workflows.[10] However, energy efficiency and "time-to-solution" are increasingly replacing peak FLOPS as the primary metrics for evaluating HPC effectiveness in 2026.[36]

The Emergence of Quantum Computational Electromagnetics

Quantum computing offers the theoretical promise of exponential speedups for specific classes of electromagnetic problems, particularly the solution of large, sparse linear systems of equations.[40] While practical hardware is still in the developmental phase, the 2025-2026 research period has seen a surge in quantum-algorithmic development for Maxwell's equations.

Quantum Algorithms for Linear Systems

The Harrow-Hassidim-Lloyd (HHL) algorithm and the Quantum Singular Value Transformation (QSVT) are the primary candidates for solving the linear systems $\mathbf{Ax} = \mathbf{b}$ that arise in FEM and MoM discretizations.[40] QSVT, in particular, is being explored for its modularity and ability to implement inverse transformations using polynomial approximations of singular values.[42] Simulations on quantum simulators have demonstrated that QSVT can solve 1D Maxwell benchmarks with over 99.9% fidelity, though practical hardware implementation is currently limited by the difficulty of reading out the complete quantum state.[42]

Schrödingerisation and Unitary Evolution

Schrödingerisation is a novel technique that recasts non-conservative linear dynamical systems into the form of Schrödinger's equation, allowing for the simulation of electromagnetic wave propagation via unitary evolution on a quantum computer.[41] This method is particularly effective for handling artificial boundary problems and simulating waves in unbounded

domains.[41] Research is also exploring Quantum Physics-Informed Neural Networks (QPINNs), which use parameterized quantum circuits to solve time-dependent Maxwell equations while enforcing global energy conservation.[44]

Quantum Algorithm Family	Theoretical Speedup	Core CEM Application	Hardware Maturity
HHL / QSVT	Exponential (for inversion)	MoM/FEM matrix solutions	NISQ / Early Fault-Tolerant [40]
Schrödingerisation	Exponential (for dynamics)	Transient wave propagation	Simulation-phase [41]
LCHS	Sparse Matrix Scaling	Spatially varying parameters	R&D Prototype [41]
Variational (VQLS)	Heuristic Speedup	Near-term hardware solutions	Current NISQ devices [42]

Automated Mesh Generation and Data-Driven Pre-processing

The efficiency of a CEM simulation is often determined by the quality of the initial mesh, which historically required significant manual intervention.[46] Research is now focused on "mesh generation in the age of AI," aiming for optimality and automation to reduce the carbon footprint of large-scale HPC usage.[10]

AI-Driven Frame for Optimal Meshing

New AI-driven frameworks are being developed to predict near-optimal meshes by transferring knowledge from thousands of past simulations.[10] These models infer suitable isotropic and anisotropic spacing functions tailored to specific simulation goals, delivering accuracy comparable to expert-crafted meshes without the manual tuning.[10] For structured quad mesh generation, PINN-MG (Physics-Informed Neural Network Mesh Generation) uses attention networks to capture the mapping between computational and physical domains, generating high-quality meshes by solving underlying PDEs within the mesh generator itself.[46]

Handling Geometric Defects

Industrial CEM often deals with "triangle soup" or non-manifold CAD models that fail to mesh

correctly. Research into unconditionally robust tetrahedral meshing techniques is focusing on "cut-and-fix" and sphere-packing methods that can directly convert defective geometric inputs into analysis-ready volumetric meshes.[47] These methods avoid the computer-aided design modeling stage when possible, allowing for direct mesh modification to save time in rapid prototyping cycles.[47]

Future Research Gaps and Conclusion

While computational electromagnetics has reached a high level of maturity, several grand challenges remain. The shift to THz frequencies requires a fundamental reassessment of propagation models and transceiver architectures. The integration of AI, while promising, still faces hurdles regarding the interpretability and reliability of deep learning models in safety-critical applications like autonomous vehicle navigation and medical diagnostic tools.[48]

Research in the 2026-2030 timeframe is expected to prioritize:

- **The "Mosaic" Compute Stack:** A heterogeneous environment where CPUs, GPUs, and quantum processors work together to solve multiscale multiphysics problems.[49]
- **Sustainable CEM:** Developing energy-aware algorithms that prioritize time-to-solution and energy efficiency over peak performance.[36]
- **Sovereign AI Infrastructure:** The establishment of regional AI factories and sovereign cloud nodes to support sensitive industrial and national security simulations.[50]
- **Bridging the Software-Hardware Divide:** Using meta-optics and photonic computing to embed computation directly into the optical front-end, reducing the latency and energy costs of digital post-processing.[16]

In conclusion, computational electromagnetics is evolving from a verification tool into an intelligent design partner. The synergy between field theory, AI, and advanced hardware acceleration is paving the way for the realization of 6G connectivity, ultra-efficient power grids, and transformative biomedical technologies. The field's ability to navigate these complex, cross-disciplinary challenges will be the defining factor in the success of the next generation of global engineering innovations.

Works cited

1. IEEE Transactions on Microwave Theory and Techniques - MTT-S, accessed February 23, 2026, https://mtt.org/publications/t-mtt/
2. Key Enabling Technologies for 6G: The Role of UAVs, Terahertz Communication, and Intelligent Reconfigurable Surfaces in Shaping the Future of Wireless Networks - MDPI, accessed February 23, 2026, https://www.mdpi.com/2224-2708/14/2/30
3. Transformative Electromagnetic Simulation Trends for 2026 - Electro Magnetic Applications, Inc. - EMA, accessed February 23, 2026, https://www.ema3d.com/blog/transformative-electromagnetic-simulation-trends

-for-2026/
4. Open-Source Electromagnetic Simulation: FDTD, FEM, MoM - Epsilon Forge, accessed February 23, 2026, https://www.epsilonforge.com/post/open-source-electromagnetics/
5. Embedding Physics into Deep Learning: A Structured Review of ..., accessed February 23, 2026, https://www.preprints.org/manuscript/202504.2577/v1
6. Science of Computational Electromagnetics; a journey through its intellectual challenges, accessed February 23, 2026, https://ece.engin.umich.edu/event/science-of-computational-electromagnetics-a-journey-through-its-intellectual-challenges
7. Advanced Numerical Methods in Electromagnetics: Techniques and Applications, accessed February 23, 2026, https://www.researchgate.net/publication/387857357_Advanced_Numerical_Methods_in_Electromagnetics_Techniques_and_Applications
8. Special Issue on Frontiers in Computational Electromagnetics, accessed February 23, 2026, https://ieeeaps.org/ieee-tap/special-issues/past-special-issues/special-issue-on-frontiers-in-computational-electromagnetics
9. Project 2024 | Faculty of Engineering - McGill University, accessed February 23, 2026, https://www.mcgill.ca/engineering/students/undergraduate/research/student-section/projects/computer-electrical-software-projects/project-2024
10. Mesh generation in the age of AI: towards optimality, automation, and green computing, accessed February 23, 2026, https://www.lacan.upc.edu/mesh-generation-in-the-age-of-ai/
11. An Iterative FDTD/MoM Technique for Assessing Coupling Effects in Front of Base-Station Antennas | Semantic Scholar, accessed February 23, 2026, https://www.semanticscholar.org/paper/5a3bd4d48beeb82af04f36a4e70d40f24caa9033
12. Physics-Informed Neural Networks for Advanced Thermal Management in Electronics and Battery Systems: A Review of Recent Developments and Future Prospects - MDPI, accessed February 23, 2026, https://www.mdpi.com/2313-0105/11/6/204
13. What are Physics-Informed Neural Networks (PINNs)? Guide 2026 - Articsledge, accessed February 23, 2026, https://www.articsledge.com/post/physics-informed-neural-networks-pinns
14. A Survey of Physics-Informed AI for Complex Urban Systems - arXiv, accessed February 23, 2026, https://arxiv.org/html/2506.13777v1
15. Generalizing Deep Surrogate Solvers for Broadband Electromagnetic Field Prediction at Unseen Wavelengths - arXiv.org, accessed February 23, 2026, https://arxiv.org/html/2408.02971v3
16. Metaoptics merging computational optics and optical computing toward intelligent visual perception - PMC, accessed February 23, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12758549/
17. Data driven approaches in nanophotonics: a review of AI-enabled metadevices,

accessed February 23, 2026, https://pubs.rsc.org/en/content/articlehtml/2025/nr/d5nr02043c
18. Top 5 Emerging Trends in Nanophotonics - AZoNano, accessed February 23, 2026, https://www.azonano.com/article.aspx?ArticleID=6971
19. Terahertz Communication for a 6G Future | Advanced PCB Design Blog | Cadence, accessed February 23, 2026, https://resources.pcb.cadence.com/blog/2023-terahertz-communication-for-a-6g-future
20. Terahertz (THz) communication - The most promising concepts for 6G - TELCOMA Global, accessed February 23, 2026, https://www.telcomaglobal.com/p/terahertz-thz-communication-concepts-6g-networks
21. Introduction to the January 2026 Issue - IEEE Xplore, accessed February 23, 2026, https://ieeexplore.ieee.org/iel8/9171629/11353050/11352965.pdf
22. WS01. Reconfigurable Intelligent and Holographic Surfaces for 6G - IEEE WCNC 2025, accessed February 23, 2026, https://wcnc2025.ieee-wcnc.org/workshop/ws01-reconfigurable-intelligent-and-holographic-surfaces-6g
23. 6G Wireless Communications in the TeraHertz Band aided by Reconfigurable Intelligent Surfaces | 6G-TERARIS | Project | Fact Sheet | HORIZON - CORDIS, accessed February 23, 2026, https://cordis.europa.eu/project/id/101107131
24. 6G Market 2026-2036: Technology, Trends, Forecasts, Players - IDTechEx, accessed February 23, 2026, https://www.idtechex.com/en/research-report/6g-market/1126
25. Nonlocal metasurfaces for next-generation flat optics | National Science Open (NSO), accessed February 23, 2026, https://www.nso-journal.org/articles/nso/full_html/2025/06/NSO20250038/NSO20250038.html
26. Nonlocal metasurfaces for next-generation flat optics - National Science Open, accessed February 23, 2026, https://www.nso-journal.org/articles/nso/pdf/2025/06/NSO20250038.pdf
27. (PDF) Nonlinear nonlocal metasurfaces - ResearchGate, accessed February 23, 2026, https://www.researchgate.net/publication/370086679_Nonlinear_nonlocal_metasurfaces
28. Nonlinear Metasurfaces: A New Paradigm for Short-Wavelength Generation and Modulation, accessed February 23, 2026, https://pubs.acs.org/doi/10.1021/acs.jpcc.5c01186
29. Nonlocal Mechano-Optical Metasurfaces - PMC, accessed February 23, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12637858/
30. Why Multiphysics is Becoming Increasingly Important - All-About-Industries, accessed February 23, 2026, https://www.all-about-industries.com/why-multiphysics-is-becoming-increasingly-important-a-cc0c4a4ae654aab731fb2a1136fe4be4/
31. Advanced Electromagnetic Modeling and Simulation for Multidisciplinary

Engineering Systems - MDPI, accessed February 23, 2026, https://www.mdpi.com/topics/32V5A6306W
32. Magazine Archives - IEEE Power Electronics Society, accessed February 23, 2026, https://www.ieee-pels.org/pels-magazine/magazine-archives/
33. Electromagnetic-thermal multi-physics coupling simulation of cable joints: considering contact resistance and typical defects - Frontiers, accessed February 23, 2026, https://www.frontiersin.org/journals/energy-research/articles/10.3389/fenrg.2024.1475355/full
34. Prospects and Trends in Biomedical Microelectromechanical Systems (MEMS) Devices: A Review - MDPI, accessed February 23, 2026, https://www.mdpi.com/2218-273X/15/6/898
35. (PDF) Prospects and Trends in Biomedical Microelectromechanical Systems (MEMS) Devices: A Review - ResearchGate, accessed February 23, 2026, https://www.researchgate.net/publication/392841661_Prospects_and_Trends_in_Biomedical_Microelectromechanical_Systems_MEMS_Devices_A_Review
36. High Performance Computing in 2026 - Azura Consultancy, accessed February 23, 2026, https://www.azuraconsultancy.com/high-performance-computing-in-2026/
37. A flexible framework for large-scale FDTD simulations: open-source inverse design for 3D nanostructures - arXiv, accessed February 23, 2026, https://arxiv.org/html/2412.12360v2
38. Foundational Research Gaps and Future Directions for Digital Twins - PubMed, accessed February 23, 2026, https://pubmed.ncbi.nlm.nih.gov/39088664/
39. Full Program - SCA/HPCAsia 2026, accessed February 23, 2026, https://www.sca-hpcasia2026.jp/program.html
40. Quantum computing: foundations, algorithms, and emerging applications - Frontiers, accessed February 23, 2026, https://www.frontiersin.org/journals/quantum-science-and-technology/articles/10.3389/frqst.2025.1723319/full
41. [PDF] Quantum simulation of Maxwell's equations via Schrödingerisation - Semantic Scholar, accessed February 23, 2026, https://www.semanticscholar.org/paper/dd6464a686e4c8d758492846b33c8051b9391a2a
42. Quantum Singular Value Transformation for Solving the Time-Dependent Maxwell's Equations - arXiv, accessed February 23, 2026, https://arxiv.org/html/2507.09686v4
43. arXiv:2502.13630v1 [quant-ph] 19 Feb 2025, accessed February 23, 2026, https://arxiv.org/pdf/2502.13630
44. (PDF) Quantum Singular Value Transformation for Solving the Time-Dependent Maxwell's Equations - ResearchGate, accessed February 23, 2026, https://www.researchgate.net/publication/393684886_Quantum_Singular_Value_Transformation_for_Solving_the_Time-Dependent_Maxwell's_Equations
45. [2507.09686] Quantum Singular Value Transformation for Solving the Time-Dependent Maxwell's Equations - arXiv.org, accessed February 23, 2026,

https://arxiv.org/abs/2507.09686
46. PINN-MG: A physics-informed neural network for mesh generation - arXiv, accessed February 23, 2026, https://arxiv.org/html/2503.00814v1
47. Automatic mesh generation for electromagnetic simulation on complex industry products | Request PDF - ResearchGate, accessed February 23, 2026, https://www.researchgate.net/publication/392864205_Automatic_mesh_generation_for_electromagnetic_simulation_on_complex_industry_products
48. Tutorials | IEEE International Conference on Communications, accessed February 23, 2026, https://icc2026.ieee-icc.org/program/tutorials
49. Quantum Computing Moves from Theoretical to Inevitable | Bain & Company, accessed February 23, 2026, https://www.bain.com/insights/quantum-computing-moves-from-theoretical-to-inevitable-technology-report-2025/
50. IEEE Reveals 2026 Predictions for Top Tech Trends - HPCwire, accessed February 23, 2026, https://www.hpcwire.com/off-the-wire/ieee-reveals-2026-predictions-for-top-technology-trends/