

OpenCL Events



Oregon State
University

Mike Bailey


mjb@cs.oregonstate.edu



This work is licensed under a [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](https://creativecommons.org/licenses/by-nc-nd/4.0/)




Oregon State
University
Computer Graphics



OpenCL Events

2

An event is an object that communicates the status of OpenCL commands




From the OpenCL Notes:

11. Enqueue the Kernel Object for Execution

```
size_t globalWorkSize[ 3 ] = { NUM_ELEMENTS, 1, 1 };
size_t localWorkSize[ 3 ] = { LOCAL_SIZE, 1, 1 };

status = clEnqueueNDRangeKernel( cmdQueue, kernel, 1, NULL, globalWorkSize, localWorkSize, 0, NULL, NULL );
```



Creating an Event


4

event that will be thrown when this kernel is finished executing

```
cl_event waitKernelA, waitKernel B, waitKernelC;
```

```
status = clEnqueueNDRangeKernel( cmdQueue, kernel, 1, NULL, globalWorkSize, localWorkSize, 0, NULL, &waitKernelC );
```

event(s) to wait for before this kernel is allowed to execute



Waiting for Events from Previously-Executed Kernels

5

```
cl_event waitKernelA, waitKernelB, waitKernelC;
```

```
...
```

```
cl_event dependenciesAB[ 2 ];
```


```
dependenciesAB[ 0 ] = waitKernelA;
```

```
dependenciesAB[ 1 ] = waitKernelB;
```

```
status = clEnqueueNDRangeKernel( cmdQueue, kernelC, 1, NULL, globalWorkSize, localWorkSize, 2, dependenciesAB, NULL );
```

event that will be thrown when this kernel is finished executing

event(s) to wait for before this kernel is allowed to execute




Creating an Execution Graph Structure

6

```
cl_event waitKernelA, waitKernelB, waitKernelC;  
  
cl_event dependenciesAB[ 2 ];  
  
dependenciesAB[ 0 ] = waitKernelA;  
dependenciesAB[ 1 ] = waitKernelB;  
  
status = clEnqueueNDRangeKernel( cmdQueue, kernelC, 1, NULL, globalWorkSize, localWorkSize, 2, dependenciesAB, &waitKernelC );
```

event that will be thrown when this kernel is finished executing

event(s) to wait for before this kernel is allowed to execute



Creating the Full Execution Graph Structure


7

```
cl_event waitKernelA, waitKernelB, waitKernelC, waitKernelD;
```

```
cl_event dependenciesAB[ 2 ];  
dependenciesAB[ 0 ] = waitKernelA;  
dependenciesAB[ 1 ] = waitKernelB;
```

```
cl_event dependenciesCD[ 2 ];  
dependenciesCD[ 0 ] = waitKernelC;  
dependenciesCD[ 1 ] = waitKernelD;
```

```
status = clEnqueueNDRangeKernel( cmdQueue, kernelA, 1, NULL, globalWorkSize, localWorkSize, 0, NULL, &waitKernelA );  
status = clEnqueueNDRangeKernel( cmdQueue, kernelB, 1, NULL, globalWorkSize, localWorkSize, 0, NULL, &waitKernelB );  
status = clEnqueueNDRangeKernel( cmdQueue, kernelC, 1, NULL, globalWorkSize, localWorkSize, 2, dependenciesAB, &waitKernelC );  
status = clEnqueueNDRangeKernel( cmdQueue, kernelD, 1, NULL, globalWorkSize, localWorkSize, 0, NULL, &waitKernelD );  
status = clEnqueueNDRangeKernel( cmdQueue, kernelE, 1, NULL, globalWorkSize, localWorkSize, 2, dependenciesCD, NULL );
```



Waiting for One Event

8

```
cl_event waitKernelA, waitKernel B.
```

```
...
```

```
status = clEnqueueNDRangeKernel( cmdQueue, kernelC, 1, NULL, globalWorkSize, localWorkSize, 1, &waitKernelA, NULL );
```



event(s) to wait for


Placing a Barrier in the Command Queue

9

```
status = clEnqueueBarrier( cmdQueue );
```

Note: this *cannot* throw its own event

This does not complete until all commands enqueued before it have completed.



Placing an Event Marker in the Command Queue

10

```
cl_event waitMarker;  
status = clEnqueueMarker( cmdQueue, &waitMarker );
```

Note: this *can* throw its own event

This does not complete until all commands enqueued before it have completed.

This is just like a barrier, but it can throw an event to be waited for.

Waiting for Events Without Enqueueing Another Command

11

```
status = clWaitForEvents( 2, dependencies );
```



event(s) to wait for

This **blocks** until the specified events are thrown, so use it carefully!

I Like Synchronizing Things This Way

12

```
// wait until all queued tasks have taken place:

void
Wait( cl_command_queue queue )
{
    cl_event wait;
    cl_int    status;

    status = clEnqueueMarker( queue, &wait );
    if( status != CL_SUCCESS )
        fprintf( stderr, "Wait: clEnqueueMarker failed\n" );

    status = clWaitForEvents( 1, &wait );    // blocks until everything is done!
    if( status != CL_SUCCESS )
        fprintf( stderr, "Wait: clWaitForEvents failed\n" );
}
```



Oreg

University

Computer Graphics

Call this before starting the timer, before ending the timer, and before retrieving data from an array computed in an OpenCL program.

Getting Event Statuses Without Blocking

CL_EVENT_COMMAND_QUEUE
 CL_EVENT_CONTEXT
 CL_EVENT_COMMAND_TYPE
 CL_EVENT_COMMAND_EXECUTION_STATUS

Specify one of these

```
cl_int eventStatus;

status = clGetEventInfo( waitKernelC, CL_EVENT_COMMAND_EXECUTION_STATUS, sizeof(cl_int),
                        &eventStatus, NULL );
```

CL_EVENT_COMMAND_EXECUTION_STATUS
 returns one of these

CL_QUEUED
 CL_SUBMITTED
 CL_RUNNING
 CL_COMPLETE

cl_int is what type
 CL_EVENT_COMMAND_EXECUTION_STATUS
 returns



Note that this a nice way to check on event statuses without blocking. Thus, you could put this in a loop and go get some other work done in between calls.

