

# Exam 6 - Problem 1



# Exam 6 - Problem 1



Given the following code in C:

```
typedef struct {  
    short a;  
    char b;  
    char c;  
    char d;  
    short e;  
} s1;  
  
char *exam (s1 bird, s2 *tigers ) {  
    char v11;  
    ...  
}
```

```
typedef struct {  
    char e[5];  
    s1 f;  
} s2;
```

# Exam 6 - Problem 1




- a) **Draw** how the structures **s1** and **s2** would be stored in memory, clearly indicating the offsets from the start and the size of all the fields
- b) **Draw** the activation block of the **exam** function, clearly indicating the displacements relative to the EBP register necessary to access the parameters and local variables.

# Exam 6 - Problem 1



- a) **Draw** how the structures **s1** and **s2** would be stored in memory, clearly indicating the offsets from the start and the size of all the fields




8 bytes

```
typedef struct {  
    short a;  
    char b;  
    char c;  
    char d;  
    short e;  
} s1;
```

# Exam 6 - Problem 1




- a) **Draw** how the structures **s1** and **s2** would be stored in memory, clearly indicating the offsets from the start and the size of all the fields




# Exam 6 - Problem 1



- a) **Draw** how the structures **s1** and **s2** would be stored in memory, clearly indicating the offsets from the start and the size of all the fields



8 bytes




14 bytes

# Exam 6 - Problem 1



b) **Draw** the activation block of the exam function, clearly indicating the displacements relative to the EBP register necessary to access the parameters and local variables.



```
char *exam (s1 bird, s2 *tigers ){  
    char v11;  
    ...  
}
```