

Exam 9 - Problem 2



Exam 9 - Problem 2



Given the following function written in C:

```
void exam (int a, int b[100], int *c)
{ int d[100];
  int aux;
  ...
}
```



Exam 9 - Problem 2



a) Draw the activation block of the function.

Translate the following statements into x86 assembler assuming they are in the body of the exam subroutine:

b) `exam(0, d, &aux);`


c) `for (aux = 0; aux < 100; aux++)
 b[aux] = d[aux];`

d) `exam(a, b, c);`

Exam 9 - Problem 2



a)



Exam 9 - Problem 2



b) `exam(0, d, &aux);`

```
leal -4(%ebp), %eax      ; %eax = &aux
leal -404(%ebp), %ecx    ; %ecx = &d
pushl %eax               ; we pass the argument &aux
pushl %ecx               ; we pass the argument &d
pushl $0                 ; we pass the argument 0
call exam
```

Exam 9 - Problem 2



c) `for (aux = 0; aux < 100; aux++)`
 `b[aux] = d[aux];`

```
movl $0, %ecx           ; ecx represents aux (initially = 0)
for: cmpl $100, %ecx
jge endfor              ; if aux >= 100 jump to endfor label
leal -404(%ebp), %eax    ; %eax = @d
movl (%eax, %ecx, 4), %eax ; %eax = @d + aux*4 = d[aux]
movl 12(%ebp), %edx     ; %edx = @b
movl %eax, (%edx, %ecx, 4) ; b[aux] = d[aux]
incl %ecx               ; aux++
jmp for
endfor:
```

Exam 9 - Problem 2



d) `exam(a, b, c);`

<code>pushl 16(%ebp)</code>	<code>; we pass the argument c</code>
<code>pushl 12(%ebp)</code>	<code>; we pass the argument b</code>
<code>pushl 8(%ebp)</code>	<code>; we pass the argument a</code>
<code>call exam</code>	