Q-PALL PLASTIC PALLETS

Technical specifications
Datasheet, edition October 2026

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 150 closed deck 3 runners light

LIGHT | Closed deck | 3 runners

TOP



BOTTOM



Static load	Dynamic load	Racking load
2,500 kg	1,000 kg	–
on a flat floor	by forklift or pallet truck	Not for racking

DIMENSIONS AND WEIGHT

Article number	N.QP1210LB3RR-CD
Length	1200 mm
Width	1000 mm
Height	150 mm
Weight	8.5 kg

CONSTRUCTION AND MATERIAL

Top deck	Closed deck
Bottom	3 runners
Load class	Light
Nestable	No
Material	Mix HDPE / PP / LDPE
Colour	Black (standard), other colours on request
ISPM 15	Exempt (no treatment needed)

DELIVERY AND DOCUMENTATION

Production location	Nantes (FR)
Ordering in stacks	15 pallets per stack (stack dimensions approx. 1,200 x 1,000 x 2,370 mm)

SIMILAR VERSIONS AND PRODUCTION LOCATIONS


ARTICLE NUMBER	PRODUCTION LOCATION	DIMENSIONS (MM)	WEIGHT	STATIC	DYNAMIC	RACKING
N.QP1210LB3RR-CD This datasheet	Nantes (FR)	1200 x 1000 x 150	8.5 kg	2,500 kg	1,000 kg	–
2.QP1210LB3RR-CD	On request	1200 x 1000 x 158	10.6 kg	2,500 kg	1,000 kg	–

Click an article number for the page and datasheet of that version. We deliver from the factory closest to you. Small differences in height, weight and load capacity between the versions are possible.

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 150 closed deck 3 runners light

TECHNICAL DRAWING



Top view and side views of the pallet; below, the click-on runner (3 per pallet). Dimensions in mm.

TEST CONDITIONS AND TOLERANCES

- Dimensional tolerance of the pallet: +5 / -5 mm. Weight tolerance: +5 / -5 %.
- We test our pallets with an evenly distributed, stable and homogeneous load of bagged goods, for a predetermined period at an ambient temperature of 20 °C. Different load conditions may lead to different results and must be assessed separately.