Q-PALL PLASTIC PALLETS

Technical specifications
Datasheet, edition October 2026

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 150 closed anti-slip deck 5 runners medium

MEDIUM | Closed anti-slip deck | 5 runners

TOP



BOTTOM



6,000 kg	1,500 kg	1,000 kg
Static load on a flat floor	Dynamic load by forklift or pallet truck	Racking load in pallet racking

DIMENSIONS AND WEIGHT

Article number	4.QP1210MB5R-CD-AO
Length	1200 mm
Width	1000 mm
Height	150 mm
Weight	17.5 kg

CONSTRUCTION AND MATERIAL

Top deck	Closed anti-slip deck
Bottom	5 runners
Load class	Medium
Nestable	No
Anti-slip	Yes
Material	Mix HDPE / PP
Colour	Black (standard), other colours on request
ISPM 15	Exempt (no treatment needed)


DELIVERY AND DOCUMENTATION

Production location	Balk (NL)
Ordering in stacks	17 pallets per stack (stack dimensions approx. 1,200 x 1,000 x 2,550 mm)
PPWR (EU 2025/40)	Declaration of conformity available

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 150 closed anti-slip deck 5 runners medium

TECHNICAL DRAWING



Top view and side views, dimensions in mm.

TEST CONDITIONS AND TOLERANCES

- The racking load is determined in a test with 25 kg bags on a conventional pallet racking system.
- Dimensional tolerance of the pallet: +5 / -5 mm. Weight tolerance: +5 / -5 %.
- We test our pallets with an evenly distributed, stable and homogeneous load of bagged goods, for a predetermined period at an ambient temperature of 20 °C. Different load conditions may lead to different results and must be assessed separately.