Q-PALL PLASTIC PALLETS

Technical specifications
Datasheet, edition October 2026

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 160 open deck 3 runners heavy

HEAVY | Open deck | 3 runners

TOP



BOTTOM



7,500 kg	1,500 kg	1,375 kg
Static load on a flat floor	Dynamic load by forklift or pallet truck	Racking load in pallet racking

DIMENSIONS AND WEIGHT

Article number	4.QP1210HB3RR
Length	1200 mm
Width	1000 mm
Height	160 mm
Weight	19.3 kg

CONSTRUCTION AND MATERIAL

Top deck	Open deck
Bottom	3 runners
Load class	Heavy
Nestable	No
Material	Mix HDPE / PP
Colour	Black (standard), other colours on request
ISPM 15	Exempt (no treatment needed)

DELIVERY AND DOCUMENTATION

Production location	Balk (NL)
Ordering in stacks	15 pallets per stack (stack dimensions approx. 1,200 x 1,000 x 2,400 mm)
PPWR (EU 2025/40)	Declaration of conformity available

SIMILAR VERSIONS AND PRODUCTION LOCATIONS


ARTICLE NUMBER	PRODUCTION LOCATION	DIMENSIONS (MM)	WEIGHT	STATIC	DYNAMIC	RACKING
4.QP1210HB3RR (This datasheet)	Balk (NL)	1200 x 1000 x 160	19.3 kg	7,500 kg	1,500 kg	1,375 kg
3.QP1210HB3RR	On request	1200 x 1000 x 160	19.1 kg	7,500 kg	1,500 kg	1,375 kg
2.QP1210HB3RR	Marktoberdorf (DE)	1200 x 1000 x 158	20.3 kg	7,500 kg	1,500 kg	1,250 kg

Click an article number for the page and datasheet of that version. We deliver from the factory closest to you. Small differences in height, weight and load capacity between the versions are possible.

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 160 open deck 3 runners heavy

TECHNICAL DRAWING



Top view and side views, dimensions in mm.

TEST CONDITIONS AND TOLERANCES

- The racking load is determined in a test with 25 kg bags on a conventional pallet racking system.
- Dimensional tolerance of the pallet: +5 / -5 mm. Weight tolerance: +5 / -5 %.
- We test our pallets with an evenly distributed, stable and homogeneous load of bagged goods, for a predetermined period at an ambient temperature of 20 °C. Different load conditions may lead to different results and must be assessed separately.