Q-PALL PLASTIC PALLETS

Technical specifications
Datasheet, edition October 2026

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 150 open deck 3 runners light

LIGHT | Open deck | 3 runners

TOP



BOTTOM



2,500 kg	1,000 kg	—
Static load on a flat floor	Dynamic load by forklift or pallet truck	Racking load Not for racking

DIMENSIONS AND WEIGHT

Article number	2.QP1210LB3RR
Length	1200 mm
Width	1000 mm
Height	150 mm
Weight	8.5 kg

CONSTRUCTION AND MATERIAL

Top deck	Open deck
Bottom	3 runners
Load class	Light
Nestable	No
Material	Mix HDPE / PP / LDPE
Colour	Black (standard), other colours on request
ISPM 15	Exempt (no treatment needed)


DELIVERY AND DOCUMENTATION

Production location	On request
Ordering in stacks	15 pallets per stack (stack dimensions approx. 1,200 x 1,000 x 2,370 mm)
PPWR (EU 2025/40)	Declaration of conformity available

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 150 open deck 3 runners light

TECHNICAL DRAWING



Top view and side views of the pallet; below, the click-on runner (3 per pallet). Dimensions in mm.

TEST CONDITIONS AND TOLERANCES

- Dimensional tolerance of the pallet: +5 / -5 mm. Weight tolerance: +5 / -5 %.
- We test our pallets with an evenly distributed, stable and homogeneous load of bagged goods, for a predetermined period at an ambient temperature of 20 °C. Different load conditions may lead to different results and must be assessed separately.