

# Lab-3: Cache for Locks

Due: 11-19-2018 23:59 (UTC+8)

**Important update: we have updated the rpc library (librpc64.a). To avoid annoying git-merge issues, you can fetch the git repo in a new directory and replace your librpc64.a with the new one. The new rpc library will handle loss of rpc packets and provide exactly-once guarantee.**

```
% mkdir newdir; cd newdir; (enter a clean directory)
% git clone https://ipads.se.sjtu.edu.cn:1312/lab/cse-2018-fall.git;
% cd cse-2018-fall; git checkout lab3;
% cp rpc/librpc64.a path-to-your-lab-dir/rpc/;
```

## Introduction

In this lab you will build a lock server and client that cache locks at the client, reducing the load on the server and improving client performance. For example, suppose that an application using YFS creates 100 files in a directory. Your Lab 2 yfs\_client will probably send 100 acquire and release RPCs for the directory's lock. This lab will modify the lock client and server so that the lock client sends (in the common case) just one acquire RPC for the directory's lock, and caches the lock thereafter, only releasing it if another yfs\_client needs it.

The challenge in the lab is the protocol between the clients and the server. For example, when client 2 acquires a lock that client 1 has cached, the server must revoke that lock from client 1 by sending a revoke RPC to client 1. The server can give client 2 the lock only after client 1 has released the lock, which may be a long time after sending the revoke (e.g., if a thread on client 1 holds the lock for a long period). The protocol is further complicated by the fact that concurrent RPC requests and replies may not be delivered in the same order in which they were sent.

We'll test your caching lock server and client by seeing whether it reduces the amount of lock RPC traffic that your yfs\_client generates. We will test with both `RPC_LOSSY` set to 0 and `RPC_LOSSY` set to 5.

If you have questions about this lab, either in programming environment or requirement, please ask TA: Mo Zou([lostzoumo@gmail.com](mailto:lostzoumo@gmail.com)).

---

## Getting started

**At first, please remember to save your lab2 solution:**

```
% cd lab-cse/lab
```

```
% git commit -a -m "solution for lab2"
```

Then, pull from the repository:

```
% git pull
```

```
remote: Counting objects: 43, done.
```

```
...
```

```
...
```

```
* [new branch] lab3 -> origin/lab3
```

```
Already up-to-date
```

Then, change to lab3 branch:

```
% git checkout lab3
```

Merge with lab2, and solve the conflict by yourself (Git may not be able to figure out how to merge your changes with the new lab assignment (e.g., if you modified some of the code that the second lab assignment changes). In that case, git merge will tell you which files have conflicts, and you should first resolve the conflicts (by editing the relevant files) and then run 'git commit -a'):

```
% git merge lab2
```

```
Auto-merging fuse.cc
```

```
CONFLICT (content): Merge conflict in yfs_client.cc
```

```
Auto-merging yfs_client.cc
```

```
CONFLICT (content): Merge conflict in ifs_client.cc
```

```
Automatic merge failed; fix conflicts and then commit the result
```

```
...
```

After merge all of the conflicts, you should be able to compile successfully:

```
% make
```

if there's no error in make, 6 executable files **yfs\_client**, **lock\_server**, **lock\_tester**, **extent\_server**, **test-lab-3-a**, **test-lab-3-b** will be generated.

This will add these new files to your lab directory:

- **lock\_client\_cache.{cc,h}**: This will be the new lock client class that the **lock\_tester** and your **yfs\_client** should instantiate. **lock\_client\_cache** must receive revoke RPCs from the server (as well as retry RPCs, explained below), so we have provided you with code in the **lock\_client\_cache** constructor that picks a random port to listen on, creates an **rpcs** for that port, and constructs an id string with the client's IP address and port that the client can send to the server when requesting a lock. Note that although **lock\_client\_cache** extends the **lock\_client** class from Lab 2, you probably won't be able to reuse any code from the parent class; we use a subclass here so that **yfs\_client** can use the two implementations interchangeably. However, you might find some member variables useful (such as **lock\_client**'s RPC client **cl**).

- `lock_server_cache.{cc,h}`: Similarly, you will not necessarily be able to use any code from `lock_server`. `lock_server_cache` should be instantiated by [lock\\_smain.cc](#), which should also register the RPC handlers for the new class.
- `handle.{cc,h}`: this class maintains a cache of RPC connections to other servers. You will find it useful in your `lock_server_cache` when sending revoke and retry RPCs to lock clients. Look at the comments at the start of `handle.h`. You can pass the lock client's id string to `handle` to tell it which lock client to talk to.
- `tprintf.h`: this file defines a macro that prints out the time when a `printf` is invoked. You may find this helpful in debugging distributed deadlocks.

We have also made changes to the following files:

- `GNUmakefile`: links `lock_client_cache` into `lock_tester` and `yfs_client`, and link `lock_server_cache` into `lock_server`.
- `lock_tester.cc`: creates `lock_client_cache` objects.
- `lock_protocol.h`: Contains a second protocol for the RPCs that the lock server sends to the client.
- `lock_smain.cc`: `#include lock_server_cache.h` instead of `lock_server.h`

---

## Your Job

### Step One: Design the Protocol

Your lock client and lock server will each keep some state about each lock, and will have a protocol by which they change that state. Start by making a design (on paper) of the states, protocol, and how the protocol messages generate state transitions. Do this before you implement anything (though be prepared to change your mind in light of experience).

Here is the set of states we recommend for the client:

- `none`: client knows nothing about this lock
- `free`: client owns the lock and no thread has it
- `locked`: client owns the lock and a thread has it
- `acquiring`: the client is acquiring ownership
- `releasing`: the client is releasing ownership

A single client may have multiple threads waiting for the same lock, but only one thread per client ever needs to be interacting with the server; once that thread has acquired and released the lock it can wake up other threads, one of which can acquire the lock (unless the lock has been revoked and released back to the server). If you need a way to identify a thread, you can use its thread id (`tid`), which you can get using `pthread_self()`.

When a client asks for a lock with an `acquire` RPC, the server grants the lock and responds with `OK` if the lock is not owned by another client (i.e., the lock is free). If the lock is not free, and there are other clients waiting for the lock, the server responds with a `RETRY`. Otherwise, the server sends a `revoke` RPC to the owner of the

lock, and waits for the lock to be released by the owner. Finally, the server sends a retry to the next waiting client (if any), grants the lock and responds with OK.

Note that RETRY and retry are two different things. RETRY is the value the server returns for a acquire RPC to indicate that the requested lock is not currently available. retry is the RPC that the server sends the client which is scheduled to hold a previously requested lock next.

Once a client has acquired ownership of a lock, the client caches the lock (i.e., it keeps the lock instead of sending a release RPC to the server when a thread releases the lock on the client). The client can grant the lock to other threads on the same client without interacting with the server.

The server sends the client a revoke RPC to get the lock back. This request tells the client that it should send the lock back to the server when it releases the lock or right now if no thread on the client is holding the lock.

The server's per-lock state should include whether it is held by some client, the ID (host name and port number) of that client, and the set of other clients waiting for that lock. The server needs to know the holding client's ID in order to send it a revoke message when another client wants the lock. The server needs to know the set of waiting clients in order to send one of them a retry RPC when the holder releases the lock.

For your convenience, we have defined a new RPC protocol called rlock\_protocol in lock\_protocol.h to use when sending RPCs from the server to the client. This protocol contains definitions for the retry and revoke RPCs.

**Hint: don't hold any mutexes while sending an RPC.** An RPC can take a long time, and you don't want to force other threads to wait. Worse, holding mutexes during RPCs is an easy way to generate distributed deadlock.

The following questions might help you with your design (they are in no particular order):

- If a thread on the client is holding a lock and a second thread calls acquire(), what happens? You shouldn't need to send an RPC to the server.
- How do you handle a revoke on a client when a thread on the client is holding the lock? How do you handle a retry showing up on the client before the response on the corresponding acquire?

Hint: a client may receive a revoke RPC for a lock before it has received an OK response from its acquire RPC. Your client code will need to remember the fact that the revoke has arrived, and release the lock as soon as you are done with it. The same situation can arise with retry RPCs, which can arrive at the client before the corresponding acquire returns the RETRY failure code.

- How do you handle a revoke showing up on the client before the response on the corresponding acquire?

## Step Two: Lock Client and Server, and Testing with RPC\_LOSSY=0

**If you finished your design, or decided to refer to the design presented in the comments of the handout code, please move on.**

A reasonable first step would be to implement the basic design of your acquire protocol on both the client and the server, including having the server send revoke messages to the holder of a lock if another client requests it, and retry messages to the next waiting client.

Next you'll probably want to implement the release code path on both the client and the server. Of course, the client should only inform the server of the release if the lock has been revoked.

Also make sure you instantiate a `lock_server_cache` object in `lock_smain.cc`, and correctly register the RPC handlers.

Once you have your full protocol implemented, you can run it using the lock tester, just as in Lab 2. For now, don't bother testing with loss:

```
% export RPC_LOSSY=0
```

```
% ./lock_server 3772
```

Then, in another terminal:

```
% ./lock_tester 3772
```

Run `lock_tester`. You should pass all tests and see no timeouts. You can hit Ctrl-C in the server's window to stop it.

A lock client might be holding cached locks when it exits. This may cause another run of `lock_tester` using the same `lock_server` to fail when the lock server tries to send revokes to the previous client. To avoid this problem without worrying about cleaning up, you must restart the `lock_server` for each run of `lock_tester`.

### **Step Three: Testing the Lock Client and Server with `RPC_LOSSY=5`**

Now that it works without loss, you should try testing with `RPC_LOSSY=5`. Here you may discover problems with reordered RPCs and responses.

```
% export RPC_LOSSY=5
```

```
% ./lock_server 3772
```

Then, in another terminal:

```
% export RPC_LOSSY=5
```

```
% ./lock_tester 3772
```

Again, you must restart the `lock_server` for each run of `lock_tester`.

## Step Four: Run File System Tests

In the constructor for your `yfs_client`, you should now instantiate a `lock_client_cache` object, rather than a `lock_client` object. You will also have to include `lock_client_cache.h`. Once you do that, your YFS should just work under all the Lab 2 tests. We will run your code against all tests from Lab 2.

You should also compare running your YFS code with the two different lock clients and servers, with RPC count enabled at the lock server. For this reason, it would be helpful to keep your Lab 2 code around and intact, the way it was when you submitted it. As mentioned before, you can turn on RPC statistics using the `RPC_COUNT` environment variable. Look for a dramatic drop in the number of acquire (0x7001) RPCs between your Lab 2 and Lab 3 code during the `test-lab-3-b` test.

The file system tests should pass with `RPC_LOSSY` set as well. You can pass a `loss` parameter to [start.sh](#) and it will enable `RPC_LOSSY` automatically:

```
% ./start.sh 5 # sets RPC_LOSSY to 5
```

If you're having trouble, make sure that the Lab 2 tester passes. If it doesn't, then the issues are most likely with YFS under `RPC_LOSSY`, rather than your caching lock client.

## Evaluation Criteria

Our measure of performance is the number of acquire RPCs sent to your lock server while running `yfs_client` and `test-lab-3-b`.

The RPC library has a feature that counts unique RPCs arriving at the server. You can set the environment variable `RPC_COUNT` to `N` before you launch a server process, and it will print out RPC statistics every `N` RPCs. For example, in the bash shell you could do:

```
% export RPC_COUNT=25
```

```
% ./lock_server 3772
```

```
RPC STATS: 7001:23 7002:2
```

```
...
```

This means that the RPC with the procedure number 0x7001 (acquire in the original `lock_protocol.h` file) has been called 23 times, while RPC 0x7002 (release) has been called twice.

`test-lab-3-b` creates two subdirectories and creates/deletes 100 files in each directory, using each directory through only one of the two YFS clients. You should count the acquire RPCs for your lab 2 and for your lab 3 (**which means you should run test-lab-3-b in your lab 2 code**). If your lab 3 produces a factor of 10 fewer acquire RPCs, then

you are doing a good job. This performance goal is vague because the exact numbers depend a bit on how you use locks in `yfs_client`.

We will check the following:

- Your caching lock server passes `lock_tester` with `RPC_LOSSY=0` and `RPC_LOSSY=5`.
- Your file system using the caching lock client passes all the Lab 3 tests (a, b) with `RPC_LOSSY=0` and `RPC_LOSSY=5`.
- Your lab 2 code generates about a tenth as many acquire RPCs as your lab 3 code on `test-lab-3-b`.

---

## Handin procedure

After all above done:

### **% make handin**

That should produce a file called `lab3.tgz` in the directory. Change the file name to your student id:

### **% mv lab3.tgz lab3\_[your student id].tgz**

Then upload `lab3_[your student id].tgz` file to `ftp://SJTU.Ticholas.Huang:public@public.sjtu.edu.cn/upload/cse/lab3/` before the deadline. You are only given the permission to list and create new file, but no overwrite and read. So make sure your implementation has passed all the tests before final submit.

You will receive 80% credit if your software passes the same tests we gave you when we run your software on our machines, other credit will be given you after TA reviewing your lab code.