

```
/*
Noah Zhou
CNIT 272 Fall 2023
Lab Time: Friday 7:30 AM - 9:20 AM
*/
```

```
--*****
```

```
--Question 1
```

```
/*
List supplier id, name, and city of any supplied food with its price is more than
$7. Use
a nested query to find food items in the FOOD table that the price are more than
$7.
```

```
^ Use a subquery or also called a nested query
^ FOOD_SUPPLIER (and FOOD table inside of the subquery)
^ 5 rows selected
```

```
*/
SELECT supplier_id, supplier_name, supplier_city
FROM food_supplier
WHERE supplier_id IN
    (SELECT supplier_id FROM food WHERE price>7.00);
```

```
/*
```

```
Results:
```

SUP_SUPPLIER_NAME	SUPPLIER_CITY
Blu Blue Sky Deli	Oak Brook
Crn Crystal Market	Hinsdale
Dpz Downtowner Pizza	Chicago
Hsd Harper Street Deli	Chicago
Jmd Jebston Montrose Deli	Chicago

```
5 rows selected.
```

```
*/
```

```
--*****
```

```
--Question 2
```

```
/*
```

```
List the worker ID, first name, last name, and hire date of the workers with no
lunch
orders. Sort the list by Hire Date.
```

```
^ Type 'set linespace 200' in the first line to help with column wrapping, then
write your
query start in the second line.
```

```
^ Use a subquery with NOT IN
^ WORKER table (and LUNCH table inside of the subquery)
^ 8 rows selected
```

```
*/
```

```
set linespace 200
```

```
SELECT worker_id, first_name, last_name, hire_date
FROM worker
WHERE worker_id NOT IN
    (SELECT worker_id FROM lunch)
ORDER BY hire_date;
```

```
/*
```

```
Results:
WOR FIRST_NAME LAST_NAME      HIRE_DATE
-----
574 Cassie      Irwin          13-SEP-03
561 Maria       Bensen         15-SEP-07
580 Roy         Gonzalez       19-DEC-11
583 Tonya       Montre         07-MAR-12
569 Blair       Reynolds       07-FEB-13
558 Melody      Campbell       24-MAY-18
566 Tami        Tevona         21-AUG-19
588 Gail        Walsh          22-MAR-21
```

8 rows selected.

\*/

--\*\*\*\*\*

--Question 3

/\*

Find the food supplier id, the supplier name, product code, price and supplier city for all

Suppliers from the city of Chicago and food priced more than \$4. Sort by price.

^ Type 'set linespace 200' in the first line, then write your query start in the second line.

^ Use an inner join to obtain this result.

^ FOOD SUPPLIER and FOOD tables

^ Try using table aliases such as 'fs' for 'food\_supplier' to avoid typing long table names

over and over.

^ Note that the attribute Supplier\_ID is used in both tables

^ 11 rows selected.

\*/

set linespace 200

```
SELECT fs.supplier_id AS Supplier_ID, supplier_name AS Supplier_Name, description
AS Description, price AS Price
FROM food_supplier fs INNER JOIN food f ON fs.supplier_id = f.supplier_id
WHERE Price>4.00 AND supplier_city = 'Chicago'
ORDER BY Price;
```

/\*

Results:

SUP	SUPPLIER_NAME	DESCRIPTION	PRICE
---	-----	-----	-----
Hsd	Harper Street Deli	Chicken Soup	4.25
Foi	Fontinas Italian	Apple Pie	4.5
Hsd	Harper Street Deli	Yellow Cake	4.5
Foi	Fontinas Italian	Barley Soup	4.75
Lak	Lakeshore Bakery	Caprese	5.5
Hsd	Harper Street Deli	Chef Salad	5.75
Jmd	Jebston Montrose Deli	Potato Soup	6.25
Lak	Lakeshore Bakery	Spinach Salad	6.25
Jmd	Jebston Montrose Deli	Mushroom Pizza	8
Dpz	Downtowner Pizza	Cheese Pizza	8.5
Hsd	Harper Street Deli	Protein Box	9

11 rows selected.

\*/

```

--*****
--Question 4
/*
(The results of question 4 are not required to paste in your submission)
A) Find the last name, first name, department code, lunch date and lunch id, for
all
workers who placed lunch orders in May 2021(within May 1st,2021 to May 31st, 2021).
^ Use an inner join to obtain this result.
^ Use WORKER and LUNCH tables
^ Sort by the lunch date and the lunch id
^ 13 rows selected.

B) Find the last name, first name, department code, lunch date and lunch id, and
item
number for all workers who placed lunch orders in May 2021.
^ Builds on part 4A... notice that you add item number in the SELECT clause
^ Note that this involves 3 tables and 2 relationships.
^ Use WORKER, LUNCH, and LUNCH_ITEM tables
^ Sort by the lunch date, lunch id, and the item number
^ 57 rows selected.

C) Find the last name, first name, department code, lunch date and lunch id, and
item
number for all workers who placed lunch orders in May 2021.
Note that this involves 4 tables and 3 relationships (Build on Part 4B)
^ Use WORKER, LUNCH, LUNCH_ITEM, and FOOD tables
^ Same number of rows with 4B but need information from an additional
table(FOOD).
^ Note that FOOD to LUNCH_ITEM is a composite PK relationship.
^ 57 rows selected.
*/
--Question 4-A
SELECT last_name, first_name, dept_code, lunch_id, lunch_date
FROM worker w INNER JOIN lunch l ON w.worker_id = l.worker_id
WHERE lunch_date >= '01-MAY-2021' AND lunch_date <= '31-MAY-2021'
ORDER BY lunch_date, lunch_id;

--Question 4-B
SELECT last_name, first_name, dept_code, li.lunch_id, lunch_date, item_number
FROM worker w INNER JOIN lunch l ON w.worker_id = l.worker_id
INNER JOIN lunch_item li ON l.lunch_id = li.lunch_id
WHERE lunch_date >= '01-MAY-2021' AND lunch_date <= '31-MAY-2021'
ORDER BY lunch_date, lunch_id, item_number;

--Question 4-C
SELECT last_name, first_name, dept_code, li.lunch_id, lunch_date, item_number
FROM worker w INNER JOIN lunch l ON w.worker_id = l.worker_id
INNER JOIN lunch_item li ON l.lunch_id = li.lunch_id
INNER JOIN food f ON li.supplier_id = f.supplier_id AND li.product_code =
f.product_code
WHERE lunch_date >= '01-MAY-2021' AND lunch_date <= '31-MAY-2021'
ORDER BY lunch_date, lunch_id, item_number;
/*
--*****
--Question 5

```

```

/*
List the lunch ID, lunch date, the count of menu items per purchased lunch, and the
total price of a purchased lunch per lunch id. Only include lunch dates from the
second
half of May 2021 (May 16, 2021 - May 31, 2021). Label the total price expression as
TOTAL_PRICE and the count of items as COUNT. Format the TOTAL_PRICE in
currency format. Sort by the lunch date, then the lunch id.
^ Type 'col TOTAL_PRICE format $9999.99' in the first line to format the
TOTAL_PRICE in currency format, then write your query start in the second line.
^ This involves 3 tables and 2 relationships.
^ LUNCH, LUNCH_ITEM, FOOD tables
^ Note again that FOOD to LUNCH_ITEM is a composite PK relationship.
^ Group by the non-aggregated columns from the SELECT clause.
^ 13 rows selected.
*/
col TOTAL_PRICE format $9999.99

```

```

SELECT l.lunch_id, lunch_date, COUNT(menu_item) AS Count, SUM(price) AS Total_Price
FROM lunch l INNER JOIN lunch_item li ON l.lunch_id = li.lunch_id
INNER JOIN food f ON li.supplier_id = f.supplier_id AND li.product_code =
f.product_code
WHERE lunch_date >= '16-MAY-2021' AND lunch_date <= '31-MAY-2021'
GROUP BY lunch_date, l.lunch_id
ORDER BY l.lunch_id, lunch_date;
/*

```

Results:

LUNCH_ID	LUNCH_DAT	COUNT	TOTAL_PRICE
1	22-MAY-21	3	\$12.25
2	22-MAY-21	4	\$16.25
3	22-MAY-21	5	\$23.20
4	22-MAY-21	4	\$19.40
5	22-MAY-21	5	\$22.25
6	22-MAY-21	5	\$23.10
7	27-MAY-21	3	\$17.80
8	27-MAY-21	6	\$24.40
9	27-MAY-21	4	\$19.40
10	27-MAY-21	4	\$14.45
11	27-MAY-21	4	\$15.20

LUNCH_ID	LUNCH_DAT	COUNT	TOTAL_PRICE
12	27-MAY-21	5	\$24.95
13	27-MAY-21	5	\$21.10

13 rows selected.

```

*/

```

```

-- *****

```

--Question 6

```

/*
A) Count the number of lunches per lunch date purchased by workers who are not
assigned to any department and hired BETWEEN December 01, 2012, and April 01 2020.
Format the lunch date in the fmMONTH-YYYY format.
^ Use an inner join to obtain this result
^ WORKER and LUNCH tables
^ Label the lunch date as LD and the count as LUNCH_COUNT
^ Group by the non-aggregated column in the SELECT clause

```

^ Sort by LD.  
^ 2 rows selected.

B) Expand on 6A: Add a clause to remove any LD with a total lunch count greater than 2.

^ 1 row selected.  
\*/

--Question 6-A

```
SELECT TO_CHAR(lunch_date, 'fmMONTH,YYYY') AS LD, COUNT(lunch_id) AS Lunch_Count
FROM worker w INNER JOIN lunch l ON w.worker_id = l.worker_id
WHERE hire_date BETWEEN '01-DEC-2012' AND '01-APR-2020' AND dept_code IS NULL
GROUP BY TO_CHAR(lunch_date, 'fmMONTH,YYYY');
```

--Question 6-B

```
SELECT TO_CHAR(lunch_date, 'fmMONTH,YYYY') AS LD, COUNT(lunch_id) AS Lunch_Count
FROM worker w INNER JOIN lunch l ON w.worker_id = l.worker_id
WHERE hire_date BETWEEN '01-DEC-2012' AND '01-APR-2020' AND dept_code IS NULL
GROUP BY TO_CHAR(lunch_date, 'fmMONTH,YYYY')
HAVING COUNT(lunch_id)<3;
```

/\*

Results:

[Question 6-A]

LD	LUNCH_COUNT
JUNE, 2021	3
MAY, 2021	1

[Question 6-B]

LD	LUNCH_COUNT
MAY, 2021	1

\*/

--\*\*\*\*\*