


Ettercap MITM - cheat sheet

A general ARP-poisoning man-in-the-middle workflow with ettercap (GUI). Replace the placeholders (<...>) with your own values.



Step 1 - Prep Kali's network

Make sure Kali is on the same subnet as your targets, and ideally only that subnet (extra IPs make ettercap scan the wrong network). With NetworkManager, pin a single static lab IP:

```
sudo nmcli con mod "<connection name>" ipv4.method manual ipv4.addresses <kali-ip>/24
sudo nmcli con up "<connection name>"
```

```
ip -4 addr show <interface>      # confirm only the lab IP is present
```

Step 2 - Launch the GUI

```
sudo ettercap -G
```

Step 3 - In the GUI

1. Select your interface (e.g. eth0) and click the checkmark to start unified sniffing.
2. Menu -> Hosts -> Scan for hosts.
3. Menu -> Hosts -> Hosts list.
4. Click your first endpoint (server / gateway / DC) -> Add to Target 1.
5. Click your second endpoint (victim client) -> Add to Target 2.
6. MITM (globe) icon -> ARP poisoning -> tick "Sniff remote connections" -> OK.
7. Bottom log should show "ARP poisoning victims" with Group 1 and Group 2.

Step 4 - Verify it worked

On the victim machine:

```
arp -a
```

The target's IP should now show Kali's MAC address instead of its real one. That means traffic is flowing through Kali.

Step 5 - (optional) Capture traffic

Open Wireshark on the same interface and filter on the two target IPs:

```
ip.addr == <target1> && ip.addr == <target2>
```

Step 6 - Stop cleanly

MITM (globe) icon -> Stop MITM attack(s). This restores the real ARP entries.

Step 7 - Restore Kali's normal networking

If you changed it in Step 1, switch back to DHCP:

```
sudo nmcli con mod "<connection name>" ipv4.method auto  
sudo nmcli con up "<connection name>"
```

Key idea: it's just "two targets + ARP poisoning". Target 1 and Target 2 are the two endpoints whose traffic you want to sit between - often a client and the gateway/DC.