

Within this section, we will provide some common usage examples of SWATH-Lib.

0.1 Creating A Y-library for N-glycosylated peptide

Here we have a precursor sequence with the id **test_sequence** and the aa sequence **TTENDTFWKEF**, or in fasta format

```
>test_sequence
TTENDTFWKEF
```

Upon input into the fasta content box and process, display similar to Figure 0.1 should appear.




Figure 0.1: Example sequence input.

This sequence has an N-glycosylation sequon at position 4 and a tryptic digestion site right after position 9. With this library, we aimed to generate all HexNAc Y0, Y1, and Y2 transitions for the sequence at RT of 10 across all SWATH windows. The max charge allowed would be 2 and the annotated sequence at the modification position would include both RT and SWATH window value.

After in-silico digestion with trypsin, we would obtain two sequences (Figure 0.2), one before and one after the digestion site. The name of the sequences have also been automatically modified to show the starting and stopping positions of each digested fragment. Using the filter rule for N-glycosylation sequon, the GUI would identify and select all sequences with a sequon within those already selected.




Figure 0.2: Example sequence input after in-silico trypsin digestion and filtered for only those containing N-glycosylation sequon.

We currently have a tryptic digested sequence containing N-glycosylation sequon but without any modification and experiment settings applied to it. These settings can be selected within the **Queryset Input Settings** panel.

In Figure 0.3, we have the following settings selected,

- HexNAc Y0, Y1, and Y2 modifications.
- Retention time at 10.
- All SWATH windows.
- Y fragmentation ion-type
- Output sequence format include RT and SWATH window values at variable modification sites.

Queryset Input Settings

Static Modifications

- Propionamide (71.0371 Da)
- Carbamidomethyl (57.02 Da)

Non-Ytype Variable Modifications

- Phosphorylation (79.9663 Da)
- Sulfation (79.9568 Da)
- Carboxylation (43.9898 Da)
- Methylated Carboxylation (58.0055 Da)

Ytype Variable Modifications

- O-Mannose (Y1) (162.05 Da)
- HexNAc (Y0) (0 Da)
- HexNAc (Y1) (203.0794 Da)
- HexNAc (Y2) (406.1587 Da)

Retention Time

- 10
- 11
- 12
- 13

SWATH Windows

- 1149 - 1175
- 1174 - 1200
- 1199 - 1225
- 1224 - 1250

Extra Mass

0

Max Charge

2

Precursor Charge

2

Oxonium Ions

- Hex-2H₂O (127.0389 m/z)
- HexNAc-(H₂O)₂-COH₂ (138.055 m/z)
- Hex-H₂O (145.0495 m/z)
- Hex (163.0601 m/z)

Fragmentation ion-type

Y

Output Sequence Format At Variable Modifications

Retention Time & SWATH

Apply Modifications

Figure 0.3: Example modification settings for N-glycosylation library with 3 HexNAc Ytype transitions at RT 10 and across all default SWATH windows.

After application of modification settings, the result would be similar to Figure 0.4. Multiple HexNAc transitions are placed at N4 and the residue is colored green.

test_sequence_1_9 Edit

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

1- [T] [T] [E] [N] [D] [T] [F] [W] [K]

☐ b,y-run non-Ytype mods only

☐ Generate only for oxonium ion

HexNAc Y0: 1

☐ Filled all positions

☐ Multiple Pattern

HexNAc Y1: 1

☐ Filled all positions

☐ Multiple Pattern

HexNAc Y2: 1

☐ Filled all positions

☐ Multiple Pattern

Y

Figure 0.4: Example of a sequence with the settings above applied.

On submission, the progress bar would start. When a query is finished, the bar under it would turn green. The moment all queries result have finished and been collected, a **Save Compiled Results** button would appear under the **Submit Queries** button. The user can click on the button to save the library in .txt tabulated file format.