

ACM-ICPC Team Reference Document

Tula State University (Basalova, Perezyabov, Provotorin)

Contents

1	Templates	1
1.1	C++ Template	1
1.2	C++ Include	2
1.3	Py Template	2
2	Data Structures	2
2.1	Disjoint Set Union	2
2.2	Segment Tree	2
2.3	Segment Tree Propagate	3
2.4	Treap	3
2.5	Treap K	3
2.6	Treap Universal	4
2.7	Fenwick Tree	5
3	Algebra	5
3.1	Primes Sieve	5
3.2	Factorization	5
3.3	Euler Totient Function	6
3.4	Greatest Common Divisor	6
3.5	Binary Operations	6
3.6	Matrices	7
3.7	Fibonacci	7
3.8	Baby Step Giant Step	7
3.9	Combinations	7
3.10	Permutation	8
3.11	Fast Fourier Transform	8
3.12	Primitive Roots	9
3.13	Number Decomposition	9
3.14	millera Rabina	9
3.15	Factorial By Mod	9
3.16	Inverse By Mod	9
3.17	Gray Code	10
3.18	Primitive Root	10
3.19	Catalan Numbers	10
3.20	Formulae	10
4	Geometry	11
4.1	Vector	11
4.2	Planimetry	11
4.3	Graham	11
4.4	Formulae	11
5	Stringology	12
5.1	Z Function	12
5.2	Manacher	12
5.3	Trie	12
5.4	Prefix Function	12
5.5	Suffix Array	13

5.6	Bor	13
5.7	Hash	13

6	Dynamic Programming	14
6.1	Longest Increasing Subsequence	14
6.2	Longest Common Subsequence	14
6.3	Backpack	14
6.4	Dominos	15
7	Graphs	15
7.1	Graph Implementation	15
7.2	Graph Traversing	16
7.3	Topological Sort	16
7.4	Connected Components	16
7.5	2 Sat	17
7.6	Bridges	17
7.7	Articulation Points	18
7.8	Kuhn	18
7.9	Kruskal	18
7.10	LCA (binary Lifting)	19
7.11	LCA RMQ (segtree)	19
7.12	Maximum Flow	20
7.13	Eulerian Path	21
7.14	Eulerian Path Oriented	22
7.15	Shortest Paths	22
7.16	Prim	22
8	Miscellaneous	23
8.1	Ternary Search	23

1 Templates

1.1 C++ Template

```
using namespace std;

// DEFINES
#define precision(x) cout << fixed << setprecision(x);
#define fast cin.tie(0); ios::sync_with_stdio(0)
#define all(x) x.begin(), x.end()
#define rall(x) x.rbegin(), x.rend()
#define ff first
#define ss second
// #define nl endl
#define nl "\n"
#define sp " "
#define yes "Yes"
#define no "No"
#define int long long

// CONSTANTS
const int INF = 1e18;
// const int MOD = 1e9 + 7;
// const int MOD = 998244353;

// FSTREAMS
ifstream in("input.txt");
```

```

ofstream out("output.txt");

// RANDOM
const int RMIN = 1, RMAX = 1e9;

random_device rdev;
mt19937_64 reng(rdev());
uniform_int_distribution<mt19937_64::result_type> dist(RMIN
, RMAX);

// CUSTOM HASH
struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM = chrono::
            steady_clock::now().time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
};
// USAGE EXAMPLES:
//
// unordered_set<long long, custom_hash> safe_set;
// unordered_map<long long, int, custom_hash> safe_map;
// gp_hash_table<long long, int, custom_hash>
//     safe_hash_table;
//
// for pairs might be used like `3 * a + b` or `a ^ (b >>
//     1)`

// ENTRANCE
signed main() {
    precision(15);
    fast;
    prepr();
    int t = 1;
    cin >> t;
    while (t--) solve();
}

```

1.2 C++ Include

```

#include <iostream>
#include <iomanip>
#include <fstream>
#include <random>
#include <cmath>
#include <algorithm>
#include <string>
#include <vector>
#include <set>
#include <unordered_set>
#include <map>
#include <unordered_map>
#include <queue>
#include <deque>
#include <stack>
#include <list>
#include <bitset>

```

1.3 Py Template

```

from math import sqrt, ceil, floor, gcd
from random import randint
import sys

input = sys.stdin.readline().strip()

INF = int(1e18)
# MOD = int(1e9 + 7)
# MOD = 998244353

```

```

t = 1
t = int(input())
for _ in range(t):
    solve()

```

2 Data Structures

2.1 Disjoint Set Union

```

// Theme: Disjoint Set Union

struct dsu {
    vector<int> p, size;

    dsu(int n) {
        p.assign(n, 0); size.assign(n, 0);
        for (int i = 0; i < n; i++) {
            p[i] = i;
            size[i] = 1;
        }
    }

    int get(int v) {
        if (p[v] != v) p[v] = get(p[v]);
        return p[v];
    }

    void unite(int u, int v) {
        auto x = get(u), y = get(v);
        if (x == y) return;
        if (size[x] > size[y]) swap(x, y);
        p[x] = y; size[y] += size[x];
    }
};

```

2.2 Segment Tree

```

// Theme: Segment Tree

struct segtree {
    int size;
    vector<int> tree;

    void init(int n) {
        size = 1;
        while (size < n) size <= 1;
        tree.assign(2 * size - 1, 0);
    }

    void build(vector<int> &a, int x, int lx, int rx) {
        if (rx - lx == 1) {
            if (lx < a.size()) tree[x] = a[lx];
            return;
        }
        int m = (lx + rx) / 2;
        build(a, 2 * x + 1, lx, m);
        build(a, 2 * x + 2, m, rx);
        tree[x] = tree[2 * x + 1] + tree[2 * x + 2];
    }

    void build(vector<int> &a) {
        init(a.size());
        build(a, 0, 0, size);
    }

    // Complexity: O(log(n))
    void set(int i, int v, int x, int lx, int rx) {
        if (rx - lx == 1) {
            tree[x] = v;
            return;
        }
        int m = (lx + rx) / 2;
        if (i < m) set(i, v, 2 * x + 1, lx, m);
        else set(i, v, 2 * x + 2, m, rx);
        tree[x] = tree[2 * x + 1] + tree[2 * x + 2];
    }

    void set(int i, int v) {
        set(i, v, 0, 0, size);
    }

    // Complexity: O(log(n))

```

```

int sum(int l, int r, int x, int lx, int rx) {
    if (l <= lx && rx <= r) return tree[x];
    if (l >= rx || r <= lx) return 0;
    int m = (lx + rx) / 2;
    return sum(l, r, 2 * x + 1, lx, m) +
           sum(l, r, 2 * x + 2, m, rx);
}
int sum(int l, int r) {
    return sum(l, r, 0, 0, size);
}
};

```

2.3 Segment Tree Propagate

// Theme: Segment Tree With Propagation

```

struct segtree_prop {
    int size;
    vector<int> tree;

    void init(int n) {
        size = 1;
        while (size < n) size <= 1;
        tree.assign(2 * size - 1, 0);
    }

    void build(vector<int> &a, int x, int lx, int rx) {
        if (rx - lx == 1) {
            if (lx < a.size()) tree[x] = a[lx];
            return;
        }
        int m = (lx + rx) / 2;
        build(a, 2 * x + 1, lx, m);
        build(a, 2 * x + 2, m, rx);
        tree[x] = tree[2 * x + 1] + tree[2 * x + 2];
    }
    void build(vector<int> &a) {
        init(a.size());
        build(a, 0, 0, size);
    }

    void push(int x, int lx, int rx) {
        if (rx - lx == 1) return;
        tree[2 * x + 1] += tree[x];
        tree[2 * x + 2] += tree[x];
        tree[x] = 0;
    }

    // Complexity: O(log(n))
    void add(int v, int l, int r, int x, int lx, int rx) {
        push(x, lx, rx);
        if (rx <= l || r <= lx) return;
        if (l <= lx && rx <= r) {
            tree[x] += v;
            return;
        }
        int m = (lx + rx) / 2;
        add(v, l, r, 2 * x + 1, lx, m);
        add(v, l, r, 2 * x + 2, m, rx);
    }
    void add(int v, int l, int r) {
        add(v, l, r, 0, 0, size);
    }

    // Complexity: O(log(n))
    int get(int i, int x, int lx, int rx) {
        push(x, lx, rx);
        if (rx - lx == 1) return tree[x];
        int m = (lx + rx) / 2;
        if (i < m) return get(i, 2 * x + 1, lx, m);
        else return get(i, 2 * x + 2, m, rx);
    }
    int get(int i) {
        return get(i, 0, 0, size);
    }
};

```

2.4 Treap

// Theme: Treap (Tree + Heap)

// Node

```

struct node {
    int key, priority;
    shared_ptr<node> left, right;

    node(int key, int priority = INF) :
        key(key),
        priority(priority == INF ?
            reng() : priority) {}
};

// Treap
struct treap {
    shared_ptr<node> root;

    treap() {}

    treap(int root_key, int root_priority = INF) {
        root = shared_ptr<node>(new node(root_key,
            root_priority));
    }

    treap(shared_ptr<node> rt) {
        root = shared_ptr<node>(rt);
    }

    treap(const treap &tr) {
        root = shared_ptr<node>(tr.root);
    }

    // Complexity: O(log(N))
    pair<treap, treap> split(int k) {
        auto res = split(root, k);
        return { treap(res.ff), treap(res.ss) };
    }

    pair<shared_ptr<node>, shared_ptr<node>> split(
        shared_ptr<node> rt, int k) {
        if (!rt) return { nullptr, nullptr };
        else if (rt->key < k) {
            auto [rt1, rt2] = split(rt->right, k);
            rt->right = rt1;
            return { rt, rt2 };
        }
        else {
            auto [rt1, rt2] = split(rt->left, k);
            rt->left = rt2;
            return { rt1, rt };
        }
    }

    // Complexity: O(log(N))
    treap merge(const treap &tr) {
        root = shared_ptr<node>(merge(root, tr.root));
        return *this;
    }

    shared_ptr<node> merge(shared_ptr<node> rt1, shared_ptr<
        node> rt2) {
        if (!rt1) return rt2;
        if (!rt2) return rt1;
        if (rt1->priority < rt2->priority) {
            rt1->right = merge(rt1->right, rt2);
            return rt1;
        }
        else {
            rt2->left = merge(rt1, rt2->left);
            return rt2;
        }
    }
};

```

2.5 Treap K

// Theme: Treap With Segments

// Node

```

struct node_k {
    int key, priority, size;
    shared_ptr<node_k> left, right;

    node_k(int key, int priority = INF) :
        key(key),
        priority(priority == INF ?
            reng() : priority),
        size(1) {}
};

```

```

friend int sz(shared_ptr<node_k> nd) {
    return (nd ? nd->size : 0);
}

void upd() {
    size = sz(left) + sz(right) + 1;
}

// Treap
struct treap_k {
    shared_ptr<node_k> root;

    treap_k() {}

    treap_k(int root_key, int root_priority = INF) {
        root = shared_ptr<node_k>(new node_k(root_key,
            root_priority));
    }

    treap_k(shared_ptr<node_k> rt) {
        root = shared_ptr<node_k>(rt);
    }

    treap_k(const treap_k &tr) {
        root = shared_ptr<node_k>(tr.root);
    }

    // Complexity: O(log(N))
    pair<treap_k, treap_k> split_k(int k) {
        auto res = split_k(root, k);
        return { treap_k(res.ff), treap_k(res.ss) };
    }

    pair<shared_ptr<node_k>, shared_ptr<node_k>> split_k(
        shared_ptr<node_k> rt, int k) {
        if (!rt) return { nullptr, nullptr };
        else if (sz(rt) <= k) return { rt, nullptr };
        else if (sz(rt->left) + 1 <= k) {
            auto [rt1, rt2] = split_k(rt->right, k - sz(rt->
                left) - 1);
            rt->right = rt1;
            rt->upd();
            return { rt, rt2 };
        }
        else {
            auto [rt1, rt2] = split_k(rt->left, k);
            rt->left = rt2;
            rt->upd();
            return { rt1, rt };
        }
    }

    // Complexity: O(log(N))
    treap_k merge_k(const treap_k &tr) {
        root = shared_ptr<node_k>(merge_k(root, tr.root));
        return *this;
    }

    shared_ptr<node_k> merge_k(shared_ptr<node_k> rt1,
        shared_ptr<node_k> rt2) {
        if (!rt1) return rt2;
        if (!rt2) return rt1;
        if (rt1->priority < rt2->priority) {
            rt1->right = merge_k(rt1->right, rt2);
            rt1->upd();
            return rt1;
        }
        else {
            rt2->left = merge_k(rt1, rt2->left);
            rt2->upd();
            return rt2;
        }
    }
};

```

2.6 Treap Universal

```

// Theme: Treap (Tree + Heap)
// Supports both explicit and implicit keys (not
// simultaneously ofc)
// Core operations are all O(log n) average

mt19937 rng(378);

```

```

struct Node {
    int x, y, size; // "x" is key or payload, "y" is
        priority
    Node* left, * right;

    Node(int val): x(val), y(rng() % 1'000'000'000), size(1)
        , left(nullptr), right(nullptr) {}
};

int get_size(Node* root) {
    if (root == nullptr) return 0;
    return root->size;
}

void update(Node* root) {
    if (root == nullptr) return;
    root->size = get_size(root->left) + 1 + get_size(root->
        right);
}

// split by value (for explicit keys)
pair<Node*, Node*> split(Node* root, int v) {
    if (root == nullptr) return {nullptr, nullptr};
    if (root->x <= v) {
        auto res = split(root->right, v);
        root->right = res.first;
        update(root);
        return {root, res.second};
    }
    else {
        auto res = split(root->left, v);
        root->left = res.second;
        update(root);
        return {res.first, root};
    }
}

// split by size (for implicit keys)
pair<Node*, Node*> split_k(Node* root, int k) {
    if (root == nullptr) return {nullptr, nullptr};
    if (get_size(root) <= k) return {root, nullptr};
    if (k == 0) return {nullptr, root};

    int left_size = get_size(root->left);
    if (left_size >= k) {
        auto res = split_k(root->left, k);
        root->left = res.second;
        update(root);
        return {res.first, root};
    }
    else {
        auto res = split_k(root->right, k - left_size - 1);
        root->right = res.first;
        update(root);
        return {root, res.second};
    }
}

// merge for both explicit and implicit keys
Node* merge(Node* root1, Node* root2) {
    if (root1 == nullptr) return root2;
    if (root2 == nullptr) return root1;

    if (root1->y < root2->y) {
        root1->right = merge(root1->right, root2);
        update(root1);
        return root1;
    }
    else {
        root2->left = merge(root1, root2->left);
        update(root2);
        return root2;
    }
}

// insert for explicit keys (use split_k for implicit keys)
Node* insert(Node* root, int v) {
    auto subs = split(root, v);
    return merge(merge(subs.first, new Node(v)), subs.
        second);
}

// debug helper
void print_node(Node* root, bool end = false) {
    if (root->left != nullptr) print_node(root->left);
    cout << root->x << " ";
    if (root->right != nullptr) print_node(root->right);
    if (end) cout << "\n";
}

```

2.7 Fenwick Tree

```
// Theme: Fenwick Tree
// Core operations are O(log n)

struct Fenwick {
    vector<int> data;

    explicit Fenwick(int n) {
        data.assign(n + 1, 0);
    }
    explicit Fenwick(vector<int>& arr): Fenwick(arr.size())
    {
        for (int i = 1; i <= arr.size(); ++i) {
            add(i, arr[i - 1]);
        }
    }

    // Nested loops (also vector) for multi-dimensional.
    // Also in add().
    // (x & -x) = last non-zero bit
    int sum(int right) {
        int res = 0;
        for (int i = right; i > 0; i -= (i & -i)) {
            res += data[i];
        }
        return res;
    }
    int sum(int left, int right) {
        return sum(right) - sum(left - 1); // inclusion-
        exclusion principle
    }

    void add(int idx, int x) {
        for (int i = idx; i < data.size(); i += (i & -i)) {
            data[i] += x;
        }
    }

    // CONCEPT (didn't test it). Should work if all real
    // values are non-negative.
    int lower_bound(int s) {
        int k = 0;
        int logn = (int)(log2(data.size() - 1) + 1); //
        maybe rewrite this line
        for (int b = logn; b >= 0; --b) {
            if (k + (1 << b) < data.size() && data[k + (1 <<
                b)] < s) {
                k += (1 << b);
                s -= data[k];
            }
        }
        return k;
    }
};
```

3 Algebra

3.1 Primes Sieve

```
// Theme: Prime Numbers

// Algorithm: Eratosthenes Sieve
// Complexity: O(N*log(log(N)))

// 0 - Prime,
// != 0 - Lowest Prime Divisor
auto get_sieve(int n) {
    vector<int> sieve(n); // Sieve
    sieve[0] = sieve[1] = 1;

    for (int i = 2; i * i < n; i++)
        if (!sieve[i])
            for (int j = i * i; j < n; j += i)
                sieve[j] = i;

    return sieve;
}

// Algorithm: Prime Numbers With Sieve
// Complexity: O(N*log(log(N)))

auto get_primes(int n) {
```

```
    vector<int> primes, sieve = get_sieve(n);

    for (int i = 2; i < sieve.size(); i++)
        if (!sieve[i])
            primes.push_back(i);

    return primes;
}

// Algorithm: Linear Algorithm
// Complexity: O(N)

// lp[i] = Lowest Prime Divisor
auto get_sieve_primes(int n, vector<int> &primes) {
    vector<int> lp(n);
    lp[0] = lp[1] = 1;

    for (int i = 2; i < n; i++) {
        if (!lp[i]) {
            lp[i] = i;
            primes.push_back(i);
        }
        for (int j = 0; j < primes.size() &&
            primes[j] <= lp[i] &&
            i * primes[j] < n; j++)
            lp[i * primes[j]] = primes[j];
    }

    return lp;
}
```

3.2 Factorization

```
// Theme: Factorization

// Algorithm: Trivial Algorithm
// Complexity: O(sqrt(N))

auto factors(int n) {
    vector<int> factors;

    for (int i = 2; i * i <= n; i++) {
        if (n % i)
            continue;
        while (n % i == 0)
            n /= i;
        factors.push_back(i);
    }

    if (n != 1)
        factors.push_back(n);

    return factors;
}

// Algorithm: Factorization With Sieve
// Complexity: O(N*log(log(N)))

auto factors_sieve(int n) {
    vector<int> factors,
    sieve = get_sieve(n + 1);

    while (sieve[n]) {
        factors.push_back(sieve[n]);
        n /= sieve[n];
    }

    if (n != 1)
        factors.push_back(n);

    return factors;
}

// Algorithm: Factorization With Primes
// Complexity: O(sqrt(N)/log(sqrt(N)))

auto factors_primes(int n) {
    vector<int> factors,
    primes = get_primes(n + 1);

    for (auto &i : primes) {
        if (i * i > n)
            break;
        if (n % i)
            continue;
```

```

    while (n % i == 0)
        n /= i;
    factors.push_back(i);
}

if (n != 1)
    factors.push_back(n);

return factors;
}

// Algorithm: Ferma Test
// Complexity: O(K*log(N))

bool ferma(int n) {
    if (n == 2)
        return true;

    uniform_int_distribution<int> distA(2, n - 1);

    for (int i = 0; i < 1000; i++) {
        int a = distA(reng);
        if (gcd(a, n) != 1 ||
            binpow(a, n - 1, n) != 1)
            return false;
    }

    return true;
}

// Algorithm: Pollard Rho Algorithm
// Complexity: O(N^(1/4))

int get_random_number(int l, int r) {
    random_device random_device;
    mt19937 generator(random_device());
    uniform_int_distribution<int> distribution(l, r);

    return distribution(generator);
}

int f(int x, int c, int n) {
    return ((x * x + c) % n);
}

int ff(int n) {
    int g = 1;
    for (int i = 0; i < 5; i++) {
        int x = get_random_number(1, n);
        int c = get_random_number(1, n);
        int h = 0;
        while (g == 1) {
            x = f(x, c, n) % n;
            int y = f(f(x, c, n), c, n) % n;
            g = gcd(abs(x - y), n);
            if (g == n) {
                g = 1;
            }
            h++;
        }

        if (h > 4 * (int)pow(n, 1.0 / 4)) {
            break;
        }
    }

    if (g > 1) {
        return g;
    }

    return -1;
}

signed main() {
    // ...read n...
    vector<int> a;
    while (n > 1) {
        int m = ff(n);
        if (m > 0) {
            n = n / m;
            a.push_back(m);
        } else {
            break;
        }
    }

    vector<int> ans;
    a.push_back(n);

```

```

for (auto &it : a) {
    int i = 2;
    int m = it;
    while (i * i <= m) {
        if (m % i == 0) {
            ans.push_back(i);
            m = m / i;
        } else {
            i += 1;
        }
    }

    ans.push_back(m);
}

sort(all(ans));
}

```

3.3 Euler Totient Function

```

// Theme: Euler Totient Function

// Algorithm: Euler Product Formula
// Complexity: O(sqrt(N))

//  $\phi = n(1 - 1/p_1)(1 - 1/p_2) \dots$ ,  $i = 1, \dots$ 
int phi(int n) {
    if (n == 1) return 1;

    auto f = factors(n);

    int res = n;
    for (auto &p : f)
        res -= res / p;

    return res;
}

```

3.4 Greatest Common Divisor

```

// Theme: Greatest Common Divisor

// Algorithm: Simple Euclidean Algorithm
// Complexity: O(log(N))

int gcd(int a, int b) {
    while (b) {
        a %= b;
        swap(a, b);
    }
    return a;
}

// Algorithm: Extended Euclidean Algorithm
// Complexity: O(log(N))

// d = gcd(a, b)
// x * a + y * b = d
// returns {d, x, y}
vector<int> euclid(int a, int b) {
    if (!a) return { b, 0, 1 };
    auto v = euclid(b % a, a);
    int d = v[0], x = v[1], y = v[2];
    return { d, y - (b / a) * x, x };
}

```

3.5 Binary Operations

```

// Theme: Binary Operations

// Algorithm: Binary Multiplication
// Complexity: O(log(b))

int binmul(int a, int b, int p = 0) {
    int res = 0;
    while (b) {
        if (b & 1) res = p ? (res + a) % p : (res + a);
        a = p ? (a + a) % p : (a + a);
    }
}

```

```

        b >>= 1;
    }
    return res;
}

// Algorithm: Binary Exponentiation
// Complexity: O(log(b))

int binpow(int a, int b, int p = 0) {
    int res = 1;
    while (b) {
        if (b & 1) res = p ? (res * a) % p : (res * a);
        a = p ? (a * a) % p : (a * a);
        b >>= 1;
    }
    return res;
}

```

3.6 Matrices

```

// Theme: Matrix Operations

template <typename T>
using row = vector<T>;
template <typename T>
using matrix = vector<vector<T>>;

// Algorithm: Matrix-Matrix Multiplication
// Complexity: O(N*K*M)

auto m_prod(matrix<int> &a, matrix<int> &b, int p = 0) {
    int n = a.size(), k = a[0].size(), m = b[0].size();

    matrix<int> res(n, row<int>(m));

    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            for (int z = 0; z < k; z++)
                res[i][j] = p ? (res[i][j] + a[i][z] * b[z][j])
                : (res[i][j] + a[i][z] * b[z][j]);

    return res;
}

// Algorithm: Matrix-Vector Multiplication
// Complexity: O(N*M)

auto m_prod(matrix<int> &a, row<int> &b, int p = 0) {
    int n = a.size(), m = b.size();

    row<int> res(n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            res[i] = p ? (res[i] + a[i][j] * b[j] % p) % p
            : (res[i] + a[i][j] * b[j]);

    return res;
}

// Algorithm: Fast Matrix Exponentiation
// Complexity: O(N^3*log(K))

auto m_binpow(matrix<int> a, int x, int p = 0) {
    int n = a.size();

    matrix<int> res(n, row<int>(n));
    for (int i = 0; i < n; i++) res[i][i] = 1;

    while (x) {
        if (x & 1) res = m_prod(res, a, p);
        a = m_prod(a, a, p);
        x >>= 1;
    }

    return res;
}

```

3.7 Fibonacci

```

// Theme: Fibonacci Sequence

// Algorithm: Fibonacci Numbers With Matrix Exponentiation
// Complexity: O(log(N))

int fibonacci(int n) {
    row<int> first_two = { 1, 0 };
    if (n <= 2) return first_two[2 - n];

    matrix<int> fib(2, row<int>(2, 0));
    fib[0][0] = 1; fib[0][1] = 1;
    fib[1][0] = 1; fib[1][1] = 0;

    fib = m_binpow(fib, n - 2);

    row<int> last_two = m_prod(fib, first_two);

    return last_two[0];
}

```

3.8 Baby Step Giant Step

```

// Theme: Discrete Logarithm

// Algorithm: Baby-Step Giant-Step Algorithm
// Complexity: O(sqrt(p)*log(p))

//  $a^x \equiv b \pmod{p}$ ,  $(a, p) = 1$ 
//  $a^{(i * m + j)} \equiv b \pmod{p}$ ,  $m = \text{ceil}(\sqrt{p})$ 
//  $a^{(i * m)} \equiv b * a^{(-j)} \pmod{p}$ 
int baby_giant_step(int a, int b, int p) {
    //  $a^{(-1)} \equiv a^{(p - 2)} \pmod{p}$ 
    int m = ceil(sqrt(p)), _a = binpow(a, p - 2, p);

    //  $s[b * a^{(-j)}] = j$ 
    unordered_map<int, int> s;
    for (int j = 0, t = b; j < m; j++, t = t * _a % p) s[t] = j;

    for (int i = 0; i < m; i++) {
        //  $s.\text{find}(a^{(i * m)})$ 
        auto f = s.find(binpow(a, i * m, p));
        //  $i * m + j$ 
        if (f != s.end()) return i * m + f->ss;
    }

    return -1;
}

```

3.9 Combinations

```

// Theme: Combination Number

// Algorithm: Online Multiplication-Division
// Complexity: O(k)

//  $C_n^k$  - from n by k
int C(int n, int k) {
    int res = 1;

    for (int i = 1; i <= k; i++) {
        res *= n - k + i;
        res /= i;
    }

    return res;
}

// Algorithm: Pascal Triangle Preprocessing
// Complexity: O(N^2)

auto pascal(int n) {
    //  $C[i][j] = C_{i+j}^i$ 
    vector<vector<int>> C(n + 1, vector<int>(n + 1, 1));
    for (int i = 1; i < n + 1; i++)
        for (int j = 1; j < n + 1; j++)
            C[i][j] = C[i - 1][j] + C[i][j - 1];

    return C;
}

// Algorithm: Pascal Triangle Preprocessing

```

```
// Complexity: O(N + log(p))
ll nCk(ll n, ll k, ll p){
    return ((fact[n] * inv(fact[k], p) % p) * inv(fact[n-k],
    p)) % p;
}
```

3.10 Permutation

```
// Theme: Permutations

// Algorithm: Next Lexicological Permutation
// Complexity: O(N)

bool perm(vector<int> &v) {
    int n = v.size();

    for (int i = n - 1; i >= 1; i--) {
        if (v[i - 1] < v[i]) {
            reverse(v.begin() + i, v.end());

            int j = distance(v.begin(),
            upper_bound(v.begin() + i, v.end(), v[i - 1]));

            swap(v[i - 1], v[j]);
            return true;
        }
    }

    return false;
}
```

3.11 Fast Fourier Transform

```
// Theme: Fast Fourier Transform

// Algorithm: Fast Fourier Transform (Complex)
// Complexity: O(N*log(N))

using cd = complex<double>;
const double PI = acos(-1);

auto fft(vector<cd> a, bool invert = 0) {
    // n = 2 ^ x
    int n = a.size();

    // Bit-Reversal Permutation (0000, 1000, 0100, 1100,
    // 0010, ...)
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j >= bit; bit >>= 1) j -= bit;
        j += bit;
        if (i < j) swap(a[i], a[j]);
    }

    for (int len = 2; len <= n; len <= 1) {
        // Complex Root Of One
        double ang = 2 * PI / len * (invert ? -1 : 1);
        cd lroot(cos(ang), sin(ang));

        for (int i = 0; i < n; i += len) {
            cd root(1);
            for (int j = 0; j < len / 2; j++) {
                cd u = a[i + j], v = a[i + j + len / 2] * root;
                a[i + j] = (u + v);
                a[i + j + len / 2] = (u - v);
                root = (root * lroot);
            }
        }
    }

    if (invert) {
        for (int i = 0; i < n; i++) a[i] /= n;
    }

    return a;
}

// Module (7340033 = 7 * (2 ^ 20) + 1)
// Primiive Root (5 ^ (2 ^ 20) == 1 mod 7340033)
```

```
// Inverse Primitive Root (5 * 4404020 == 1 mod 7340033)
// Maximum Degree Of Two (2 ^ 20)

const int mod = 7340033;
const int proot = 5;
const int proot_1 = 4404020;
const int pw = 1 << 20;

// Algorithm: Discrete Fourier Transform (Inverse Roots)
// Complexity: O(N*log(N))

auto fft(vector<int> a, bool invert = 0) {
    // n = 2 ^ x
    int n = a.size();

    // Bit-Reversal Permutation (0000, 1000, 0100, 1100,
    // 0010, ...)
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j >= bit; bit >>= 1) j -= bit;
        j += bit;
        if (i < j) swap(a[i], a[j]);
    }

    for (int len = 2; len <= n; len <= 1) {
        // Primitive Root Or Inverse Root (Inverse
        // Transform)
        int lroot = invert ? proot_1 : proot;

        // Current Primitive Root
        lroot = binpow(lroot, pw / len, mod);

        for (int i = 0; i < n; i += len) {
            int root = 1;
            for (int j = 0; j < len / 2; j++) {
                int u = a[i + j], v = a[i + j + len / 2] *
                root % mod;
                a[i + j] = (u + v) % mod;
                a[i + j + len / 2] = (u - v + mod) % mod;
                root = (root * lroot) % mod;
            }
        }

        if (invert) {
            int _n = binpow(n, mod - 2, mod);
            for (int i = 0; i < n; i++) a[i] = (a[i] * _n) % mod;
        }

        return a;
    }
}

// Algorithm: Discrete Fourier Transform
// Complexity: O(N*log(N))

auto fft(vector<int> &a, bool invert = 0) {
    // n = 2 ^ x
    int n = a.size();

    // Bit-Reversal Permutation (0000, 1000, 0100, 1100,
    // 0010, ...)
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j >= bit; bit >>= 1) j -= bit;
        j += bit;
        if (i < j) swap(a[i], a[j]);
    }

    for (int len = 2; len <= n; len <= 1) {
        // Current Primitive Root
        int lroot = binpow(proot, pw / len, mod);

        for (int i = 0; i < n; i += len) {
            int root = 1;
            for (int j = 0; j < len / 2; j++) {
                int u = a[i + j], v = a[i + j + len / 2] *
                root % mod;
                a[i + j] = (u + v) % mod;
                a[i + j + len / 2] = (u - v + mod) % mod;
                root = (root * lroot) % mod;
            }
        }

        if (invert) {
            int _n = binpow(n, mod - 2, mod);
            for (int i = 0; i < n; i++) a[i] = (a[i] * _n) % mod;
        }

        return a;
    }
}
```



```

        reverse(a.begin() + 1, a.end());
        int _n = binpow(n, mod - 2, mod);
        for (int i = 0; i < n; i++) a[i] = (a[i] * _n) % mod
    };
    return a;
}

```

3.12 Primitive Roots

```

// Module (7 == 3 * (2 ^ 1) + 1)
// Primitive Root (3)
// Primitive Root {2 ^ 1} (6)
// Inverse Root {2 ^ 1} (6)
// Degree Of Two (2)

```

```

// const int mod = 7
// const int proot = 6
// const int proot_1 = 6
// const int pw = 1 << 1

```

```

// Module (13 == 3 * (2 ^ 2) + 1)
// Primitive Root (2)
// Primitive Root {2 ^ 2} (8)
// Inverse Root {2 ^ 2} (5)
// Degree Of Two (4)

```

```

// const int mod = 13
// const int proot = 8
// const int proot_1 = 5
// const int pw = 1 << 2

```

3.13 Number Decomposition

```

// Theme: Integer Numbers Decomposition With Composite
// Module

```

```

// Module
// m = (p1 ^ m1) * (p2 ^ m2) * ... * (pn ^ mn)
int m;
// Prime Divisors Of Module
vector<int> p;

```

```

struct num {
    // GCD(x, m) = 1
    int x;
    // Powers Of Primes
    vector<int> a;

    num() : x(0), a(vector<int>(p.size())) { }

    // n = (p1 ^ a1) * (p2 ^ a2) * ... * (pn ^ an) * x
    num(int n) : x(0), a(vector<int>(p.size())) {
        if (!n) return;
        for (int i = 0; i < p.size(); i++) {
            int ai = 0;
            while (n % p[i] == 0) {
                n /= p[i];
                ai++;
            }
            a[i] = ai;
        }
        x = n;
    }
}

```

```

num operator*(const num &nm) {
    vector<int> new_a(p.size());
    for (int i = 0; i < p.size(); i++)
        new_a[i] = a[i] + nm.a[i];
    num res; res.a = new_a;
    res.x = x * nm.x % m;
    return res;
}

```

```

num operator/(const num &nm) {
    vector<int> new_a(p.size());
    for (int i = 0; i < p.size(); i++)
        new_a[i] = a[i] - nm.a[i];
    num res; res.a = new_a;
    int g = euclid(nm.x, m)[1];
}

```

```

    g += m; g %= m;
    res.x = x * g % m;
    return res;
}

int toint() {
    int res = x;
    for (int i = 0; i < p.size(); i++)
        res = res * binpow(p[i], a[i], m) % m;
    return res;
}
};

```

3.14 millera Rabina

```

// Theme: Checking is number prime
// Complexity: O(const)

```

```

typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
    int ret = a * b - M * ull(1.L / M * a * b);
    return ret + M * (ret < 0) - M * (ret >= (int)M);
}

ull modpow(ull b, ull e, ull mod) {
    ull ans = 1;
    for (; e; b = modmul(b, b, mod), e /= 2) {
        if (e & 1) {
            ans = modmul(ans, b, mod);
        }
    }
    return ans;
}

```

```

bool isPrime(ull n) {
    if (n < 2 || (n % 6) % 4 != 1) {
        return (n | 1) == 3;
    }
    ull A[] = {2, 325, 9375, 28178, 450775, 9780504,
               1795265022},
        s = __builtin_ctzll(n - 1), d = n >> s;
    for (ull a : A) { // ^ count trailing zeroes
        ull p = modpow(a % n, d, n), i = s;
        while (p != 1 && p != n - 1 && a % n && i--) {
            p = modmul(p, p, n);
        }
        if (p != n - 1 && i != s) {
            return 0;
        }
    }
    return 1;
}

```

3.15 Factorial By Mod

```

int factmod (int n, int p) {
    int res = 1;
    while (n > 1) {
        res = (res * ((n/p) % 2 ? p-1 : 1)) % p;
        for (int i=2; i<=n%p; ++i)
            res = (res * i) % p;
        n /= p;
    }
    return res % p;
}

```

3.16 Inverse By Mod

```

int gcd(int a, int b, int &x, int &y) {
    if (a == 0) {
        x = 0;
        y = 1;
        return b;
    }

    int temp_x = 0, temp_y = 0;
    int gcd_result = gcd(b % a, a, temp_x, temp_y);
    x = temp_y - (b / a) * temp_x;
    y = temp_x;
}

```

```

    return gcd_result;
}

int obr_by_mod(int a, int m) {
    int x = 0, y = 0;
    int temp = gcd(a, m, x, y);

    return (x % m + m) % m;
}

```

3.17 Gray Code

// Theme: Gray's code

```

int g(int n) {
    return n ^ (n >> 1);
}

int rev_g(int g) {
    int n = 0;
    for (; g; g >>= 1)
        n ^= g;
    return n;
}

```

3.18 Primitive Root

// Theme: Euler Totient Function
 // Complexity: $O(\sqrt{\phi(n)})$

```

int generator(int p) {
    vector<int> fact;
    int phi = p - 1, n = phi;
    for (int i = 2; i * i <= n; ++i)
        if (n % i == 0) {
            fact.push_back(i);
            while (n % i == 0)
                n /= i;
        }
    if (n > 1)
        fact.push_back(n);

    for (int res = 2; res <= p; ++res) {
        bool ok = true;
        for (size_t i = 0; i < fact.size() && ok; ++i)
            ok &= powmod(res, phi / fact[i], p) != 1;
        if (ok)
            return res;
    }
    return -1;
}

```

3.19 Catalan Numbers

```

ll powr(ll n, ll p) {
    if (p == 0)
        return 1;
    if (p == 1)
        return n;
    if (p & 1LL)
        return (powr(n, p - 1) * n) % MD;
    else {
        ll x = powr(n, p / 2) % MD;
        return (x * x) % MD;
    }
}

ll inverse(ll n) {
    return (powr(n, MD - 2)) % MD;
}

ll ft[MX];

void fact() {
    ll i;
    ft[0] = 1;
    for (i = 1; i < MX; i++) {
        ft[i] = (ft[i - 1] * i) % MD;
    }
}

```

```

}

ll nCr(ll n, ll r) {
    ll x = ft[n];
    ll y = inverse((ft[r] * ft[n - r]) % MD) % MD;
    return (x * y) % MD;
}

ll catalan(ll n) {
    ll x = nCr(2 * n, n);
    return (x * inverse((n + 1))) % MD;
}

int main() {
    fact();
    cout << catalan(5) << endl;
}

```

3.20 Formulae

Combinations.

$$C_n^k = \frac{n!}{(n-k)!k!}$$

$$C_n^0 + C_n^1 + \dots + C_n^n = 2^n$$

$$C_{n+1}^{k+1} = C_n^{k+1} + C_n^k$$

$$C_n^k = \frac{n}{k} C_{n-1}^{k-1}$$

Striling approximation.

$$n! \approx \sqrt{2\pi n} \frac{n^n}{e^n}$$

Euler's theorem.

$$a^{\phi(m)} \equiv 1 \pmod{m}, \gcd(a, m) = 1$$

Ferma's little theorem.

$$a^{p-1} \equiv 1 \pmod{p}, \gcd(a, p) = 1, p - \text{prime.}$$

Catalan number.

$$C_0 = 0, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}$$

$$C_n = \frac{2(2n-1)}{n+1} C_{n-1}$$

$$C_n = \frac{(2n)!}{n!(n+1)!}$$

Arithmetic progression.

$$S_n = \frac{a_1 + a_n}{2} n = \frac{2a_1 + d(n-1)}{2} n$$

Geometric progression.

$$S_n = \frac{b_1(1-q^n)}{1-q} n$$

Infinitely decreasing geometric progression.

$$S_n = \frac{b_1}{1-q} n$$

Sums.

$$\sum_{i=1}^n i = \frac{n(n+1)}{2},$$

$$\sum_{i=1}^n i^2 = \frac{n(2n+1)(n+1)}{6},$$

$$\sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4},$$

$$\sum_{i=1}^n i^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30},$$

$$\sum_{i=a}^b c^i = \frac{c^{b+1} - c^a}{c-1}, c \neq 1.$$

4 Geometry

4.1 Vector

// Theme: Mathematical 3-D Vector

```
template <typename T>
struct vec {
    T x, y, z;
    vec(T x = 0, T y = 0, T z = 0) : x(x), y(y), z(z) {}
    vec<T> operator+(const vec<T> &v) const {
        return vec<T>(x + v.x, y + v.y, z + v.z);
    }
    vec<T> operator-(const vec<T> &v) const {
        return vec<T>(x - v.x, y - v.y, z - v.z);
    }
    vec<T> operator*(T k) const {
        return vec<T>(k * x, k * y, k * z);
    }
    friend vec<T> operator*(T k, const vec<T> &v) {
        return vec<T>(v.x * k, v.y * k, v.z * k);
    }
    vec<T> operator/(T k) {
        return vec<T>(x / k, y / k, z / k);
    }
    T operator*(const vec<T> &v) const {
        return x * v.x + y * v.y + z * v.z;
    }
    vec<T> operator^(const vec<T> &v) const {
        return { y * v.z - z * v.y, z * v.x - x * v.z, x * v
            .y - y * v.x };
    }
    auto operator<=>(const vec<T> &v) const = default;
    bool operator==(const vec<T> &v) const = default;
    T norm() const {
        return x * x + y * y + z * z;
    }
    double abs() const {
        return sqrt(norm());
    }
    double cos(const vec<T> &v) const {
        return ((*this) * v) / (abs() * v.abs());
    }
    friend ostream &operator<<(ostream &out, const vec<T> &v)
    {
        return out << v.x << sp << v.y << sp << v.z;
    }
    friend istream &operator>>(istream &in, vec<T> &v) {
        return in >> v.x >> v.y >> v.z;
    }
};
```

4.2 Planimetry

// Theme: Planimetry Objects

```
// Point
template <typename T>
struct point {
    T x, y;

    point() : x(0), y(0) {}
    point(T x, T y) : x(x), y(y) {}
};
```

```
// Rectangle
template <typename T>
struct rectangle {
    point<T> ld, ru;

    rectangle(const point<T> &ld, const point<T> &ru) :
        ld(ld), ru(ru) {}
};
```

4.3 Graham

// Theme: Convex Hull

// Algorithm: Graham Algorithm

// Complexity: $O(N \log(N))$

```
auto graham(const vector<vec<int>> &points) {
    vec<int> p0 = points[0];

    for (auto p : points)
        if (p.y < p0.y ||
            p.y == p0.y && p.x > p0.x)
            p0 = p;

    for (auto &p : points) {
        p.x -= p0.x;
        p.y -= p0.y;
    }

    sort(all(points), [] (vec<int> &p1, vec<int> &p2) {
        return (p1 ^ p2).z > 0 ||
            (p1 ^ p2).z == 0 && p1.norm() > p2.norm(); });

    vector<vec<int>> hull;
    for (auto &p : points) {
        while (hull.size() >= 2 &&
            (((p - hull.back()) ^ (hull[hull.size() - 1] - hull[
                hull.size() - 2])).z >= 0)
            hull.pop_back();
        hull.push_back(p);
    }

    for (auto &p : hull) {
        p.x += p0.x;
        p.y += p0.y;
    }

    return hull;
}
```

4.4 Formulae

Triangles.

Radius of circumscribed circle:

$$R = \frac{abc}{4S}.$$

Radius of inscribed circle:

$$r = \frac{S}{p}.$$

Side via medians:

$$a = \frac{2}{3} \sqrt{2(m_b^2 + m_c^2) - m_a^2}.$$

Median via sides:

$$m_a = \frac{1}{2} \sqrt{2(b^2 + c^2) - a^2}.$$

Bisector via sides:

$$l_a = \frac{2\sqrt{bcp(p-a)}}{b+c}.$$

Bisector via two sides and angle:

$$l_a = \frac{2bc \cos \frac{\alpha}{2}}{b+c}.$$

Bisector via two sides and divided side:

$$l_a = \sqrt{bc - a_b a_c}.$$

Right triangles.

a, b - cathets, c - hypotenuse.

h - height to hypotenuse, divides c to c_a and

$$c_b. \quad \begin{cases} h^2 = c_a \cdot c_b, \\ a^2 = c_a \cdot c, \\ b^2 = c_b \cdot c. \end{cases}$$

Quadrangles.

Sides of circumscribed quadrangle:

$$a + c = b + d.$$

Square of circumscribed quadrangle:

$$S = \frac{Pp}{2} = pr.$$

Angles of inscribed quadrangle:

$$\alpha + \gamma = \beta + \delta = 180^\circ.$$

Square of inscribed quadrangle:

$$S = \sqrt{(p-a)(p-b)(p-c)(p-d)}.$$

Circles.

Intersection of circle and line:

$$\begin{cases} (x-x_0)^2 + (y-y_0)^2 = R^2 \\ y = ax + b \end{cases}$$

Task comes to solution of $\alpha x^2 + \beta x + \gamma = 0$, where

$$\begin{cases} \alpha = (1+a^2), \\ \beta = (2a(b-y_0) - 2x_0), \\ \gamma = (x_0^2 + (b-y_0)^2 - R^2). \end{cases}$$

Intersection of circle and circle:

$$\begin{cases} (x-x_0)^2 + (y-y_0)^2 = R_0^2 \\ (x-x_1)^2 + (y-y_1)^2 = R_1^2 \end{cases}$$

$$y = \frac{1}{2} \frac{(R_1^2 - R_0^2) + (x_0^2 - x_1^2) + (y_0^2 - y_1^2)}{y_0 - y_1} - \frac{x_0 - x_1}{y_0 - y_1} x$$

Task comes to intersection of circle and line.

5 Stringology

5.1 Z Function

```
// Theme: Z-Function

// Algorithm: Linear Algorithm
// Complexity: O(N)

auto z_func(const string &s) {
    int n = s.size();
    vector<int> z(n);

    for (int i = 1, l = 0, r = 0; i < n; i++) {
        if (i <= r) z[i] = min(r - i + 1, z[i - l]);

        while (i + z[i] < n && s[z[i]] == s[i + z[i]]) z[i]++;

        if (i + z[i] - 1 > r) {
            l = i;
            r = i + z[i] - 1;
        }
    }

    return z;
}
```

5.2 Manacher

```
// Theme: Palindromes

// Algorithm: Manacher Algorithm
// Complexity: O(N)

int manacher(const string &s) {
    int n = s.size();
    vector<int> d1(n), d2(n);

    for (int i = 0, l = 0, r = -1; i < n; i++) {
        int k = i > r ? 1 : min(d1[l + r - i], r - i + 1);
        while (i + k < n && i - k >= 0 && s[i + k] == s[i - k]) k++;
        d1[i] = k;
        if (i + k - 1 > r) {
            l = i - k + 1;
            r = i + k - 1;
        }
    }

    for (int i = 0, l = 0, r = -1; i < n; i++) {
```

```
        int k = i > r ? 0 : min(d2[l + r - i + 1], r - i + 1);
        while (i + k < n && i - k - 1 >= 0 && s[i + k] == s[i - k - 1]) k++;
        d2[i] = k;
        if (i + k - 1 > r) {
            l = i - k;
            r = i + k - 1;
        }
    }

    int res = 0;
    for (int i = 0; i < n; i++) {
        res += d1[i] + d2[i];
    }

    return res;
}
```

5.3 Trie

```
// Theme: Trie

// Algorithm: Aho-Corasick
// Complexity: O(N)

struct trie {
    // Vertex
    struct vertex {
        vector<int> next;
        bool leaf;
    };

    // Alphabet size
    static const int N = 26;
    // Maximum Vertex Number
    static const int MX = 2e5 + 1;

    // Vertices Vector
    vector<vertex> t;
    int sz;

    trie(): sz(1) {
        t.resize(MX);
        t[0].next.assign(N, -1);
    }

    void add_str(const string &s) {
        int v = 0;
        for (int i = 0; i < s.length(); i++) {
            char c = s[i] - 'a';
            if (t[v].next[c] == -1) {
                t[sz].next.assign(N, -1);
                t[v].next[c] = sz++;
            }
            v = t[v].next[c];
        }
        t[v].leaf = true;
    }
};
```

5.4 Prefix Function

```
// Theme: Prefix function

// Algorithm: Knuth-Morris-Pratt Algorithm
// Complexity: O(N)

auto pref_func(const string &s) {
    int n = s.size();
    vector<int> pi(n);

    for (int i = 1; i < n; i++) {
        int j = pi[i - 1];

        while (j > 0 && s[i] != s[j]) j = pi[j - 1];

        if (s[i] == s[j]) j++;

        pi[i] = j;
    }
}
```

```

    return pi;
}

```

5.5 Suffix Array

```

// Theme: Suffix array
// Algorithm: Binary Algorithm With Count Sort
// Complexity: O(N*log(N))

void count_sort(vector<int> &p, vector<int> &c) {
    int n = p.size();
    vector<int> cnt(n), p_new(n), pos(n);

    for (auto &x : c) cnt[x]++;

    pos[0] = 0;
    for (int i = 1; i < n; i++)
        pos[i] = pos[i - 1] + cnt[i - 1];

    for (auto &x : p) {
        int i = c[x];
        p_new[pos[i]] = x;
        pos[i]++;
    }

    p = p_new;
}

auto suffix_array(const string &str) {
    string s = str + '$';
    int n = s.size();

    vector<int> p(n), c(n);
    vector<pair<char, int>> a(n);

    for (int i = 0; i < n; i++) a[i] = { str[i], i };

    sort(a.begin(), a.end());

    for (int i = 0; i < n; i++) p[i] = a[i].second;

    c[p[0]] = 0;
    for (int i = 1; i < n; i++)
        c[p[i]] = c[p[i - 1]] + (a[i].first != a[i - 1].first);

    int k = 0;
    while ((1 << k) < n) {
        for (int i = 0; i < n; i++)
            p[i] = (p[i] - (1 << k) + n) % n;

        count_sort(p, c);

        vector<int> c_new(n);

        c_new[p[0]] = 0;
        for (int i = 1; i < n; i++) {
            pair<int, int> prev = { c[p[i - 1]], c[(p[i - 1] + (1 << k)) % n] };
            pair<int, int> now = { c[p[i]], c[(p[i] + (1 << k)) % n] };
            c_new[p[i]] = c_new[p[i - 1]] + (now != prev);
        }

        c = c_new;
        k++;
    }

    return p;
}

```

5.6 Bor

```

// Theme: Checking is number prime
// Complexity: O(sum(s.size()))

int K = 26;
int MAXN = 2 * 1e5 + 1;

struct vertex {
    vector<int> next;
}

```

```

vector<int> count_v;
bool leaf;
};

vector<vertex> t(MAXN);
int sz;

void add_string(string &s) {
    int v = 0;
    for (size_t i = 0; i < s.length(); ++i) {
        char c = s[i] - 'a';
        if (t[v].next[c] == -1) {
            t[sz].next.assign(K, -1);
            t[sz].count_v.assign(K, 0);
            t[v].next[c] = sz++;
        }
        t[v].count_v[c]++;
        v = t[v].next[c];
    }

    t[v].leaf = true;
}

string dfs(int k) {
    string result = "";
    int init = 0;
    while (k != 0) {
        int temp = 0;
        for (int i = 0; i < t[init].next.size(); i++) {
            if (t[init].count_v[i] && t[init].count_v[i] + temp >= k) {
                k -= t[init].count_v[i];
                init = t[init].next[i];
                k -= temp;
                if (t[init].leaf) {
                    k--;
                }
                result += char(i + 'a');
                break;
            } else if (t[init].count_v[i]) {
                temp += t[init].count_v[i];
            }
        }
    }

    return result;
}

signed main() {
    t[0].next.assign(K, -1);
    t[0].count_v.assign(K, 0);
    sz = 1;

    int n = 0;
    cin >> n;
    for (int i = 0; i < n; i++) {
        string s = "";
        cin >> s;
        bool flag = true;
        for (int i = 0; i < s.size(); i++) {
            if (!isdigit(s[i])) {
                flag = false;
                break;
            }
        }
        if (flag) {
            int k = stoi(s);
            cout << dfs(k) << endl;
        } else {
            add_string(s);
        }
    }
}

```

5.7 Hash

```

// Algorithm: String hash

#define forn(i, n) for (int i = 0; i < (int)(n); i++)
#define sz(a) (int)(a).size()

typedef long long ll;
typedef unsigned long long ull;

struct num {
    static const int MA = 1e9 + 7, MB = 1e9 + 9;
}

```

```

int a, b;

num() {}
num(int x) : a(x), b(x) {}
num(int a, int b) : a(a), b(b) {}

num operator+(const num &x) const { return num((a + x.a)
    % MA, (b + x.b) % MB); }
num operator-(const num &x) const { return num((a + MA -
    x.a) % MA, (b + MB - x.b) % MB); }
num operator*(int x) const { return num(((11)a * x) % MA,
    ((11)b * x) % MB); }
num operator*(const num &x) const { return num(((11)a * x
    .a) % MA, ((11)b * x.b) % MB); }
bool operator==(const num &x) const { return a == x.a &&
    b == x.b; }

explicit operator ll() const { return (11)a * MB + b + 1;
    } // > 0
};

template <class hash_t>
struct StrComparator {
    static const int P;
    static vector<hash_t> deg;

    int n;
    const char *s;
    hash_t *h;

    StrComparator(int n, const char *s) : n(n), s(s) {
        h = new hash_t[n + 1];
        h[0] = 0;
        for (i = 1; i <= n; ++i)
            h[i] = h[i - 1] * P + s[i - 1];
        deg.reserve(n);
        while (sz(deg) <= n)
            deg.push_back(*deg.rbegin() * P);
    }

    hash_t substr(int i, int len) const { return h[i + len] -
        h[i] * deg[len]; }

    int lcp(int i, int j) {
        int L = 0, R = n - max(i, j);
        while (L < R) {
            int M = (L + R + 1) / 2;
            if (substr(i, M) == substr(j, M))
                L = M;
            else
                R = M - 1;
        }
        return L;
    }

    int cmp(int a, int b) {
        int LEN = n - max(a, b), L = lcp(a, b);
        return L < LEN ? (int)s[a + L] - s[b + L] : b - a;
    }

    bool operator()(int i, int j) { return cmp(i, j) < 0; }
};

template <class hash_t>
vector<hash_t> StrComparator<hash_t>::deg(1, hash_t(1));
template <class hash_t>
const int StrComparator<hash_t>::P = max(239, rand());

/*
    std::string s = "Hello World!";
    const int length = s.length();
    char* char_array = new char[length + 1];
    strcpy(char_array, s.c_str());
*/

/**
 * Usage:
 * StrComparator<num> h(length, s); // int length, char *s
 * h.substr(0, 3) == h.substr(1, 3); //
    сравнения равенства подстрок за O(1)
 * h.cmp(2, 3); // сравнения наибольшего и наименьшего
    суффиксов за O(log n)
 *
 * int p[n]; for (i = 0; i < n; ++i) p[i] = i;
 * sort(p, p + n, h); // сортировать суффиксы, суффиксы массива за
    O(n log^2 n)
 */

```

6 Dynamic Programming

6.1 Longest Increasing Subsequence

// Theme: Longest Increasing Subsequence

// Algorithm: LIS via binary search
 // Complexity: $O(N \log(N))$

```

vector<int> lis(vector<int>& arr) {
    int n = arr.size();
    vector<int> dp(n + 1, INF); dp[0] = -INF;
    vector<int> pos(n + 1, -1), previous(n, -1);
    int length = 0;
    for (int i = 0; i < n; ++i) {
        int j = lower_bound(dp.begin(), dp.end(), arr[i]) -
            dp.begin();
        if (dp[j - 1] < arr[i] && arr[i] < dp[j]) {
            dp[j] = arr[i];
            pos[j] = i;
            previous[i] = pos[j - 1];
            length = max(length, j);
        }
    }

    vector<int> res;
    int p = pos[length];
    while (p != -1) {
        res.push_back(arr[p]);
        p = previous[p];
    }
    reverse(res.begin(), res.end());
    return res;
}

```

6.2 Longest Common Subsequence

// Theme: Longest Common Subsequence

// Algorithm: LCS via simple dynamic
 // Complexity: $O(n \cdot m)$

```

vector<int> lis(vector<int>& arr) {
    int n = arr.size();
    vector<int> dp(n + 1, INF); dp[0] = -INF;
    vector<int> pos(n + 1, -1), previous(n, -1);
    int length = 0;
    for (int i = 0; i < n; ++i) {
        int j = lower_bound(dp.begin(), dp.end(), arr[i]) -
            dp.begin();
        if (dp[j - 1] < arr[i] && arr[i] < dp[j]) {
            dp[j] = arr[i];
            pos[j] = i;
            previous[i] = pos[j - 1];
            length = max(length, j);
        }
    }

    vector<int> res;
    int p = pos[length];
    while (p != -1) {
        res.push_back(arr[p]);
        p = previous[p];
    }
    reverse(res.begin(), res.end());
    return res;
}

```

6.3 Backpack

// Theme: DP backpack
 // Complexity: $O(\text{const})$

```

vector<int> result;

void getResult(int k, int s, vector<vector<int>>& dp,
    vector<int>& mass) {

```

```

if (dp[k][s] == 0) {
    return;
}

if (dp[k][s - 1] == dp[k][s]) {
    getResult(k, s - 1, dp, mass);
} else {
    getResult(k - mass[s - 1], s - 1, dp, mass);
    result.push_back(s);
}
}

signed main() {
    int n, w;
    cin >> n >> w;
    vector<int> m(n + 1);
    vector<int> c(n + 1);

    long long test = 0;
    for (int i = 0; i < n; ++i) {
        cin >> m[i] >> c[i];
        test += m[i];
    }

    test = min(test, w); // чтобынебылом1

    vector<vector<int>> dp(test + 1, vector<int>(n + 1, 0));
    for (int k = 1; k < n + 1; k++) {
        for (int i = 0; i < test + 1; i++) {
            for (int count = 0; count <= 1; count++) { // циклдо
                count <= (min(kolvo_predm[k возможно( сделать- 1
                ], test / c[i]) + 1) - согранич.
                количествомпредметов
                // еслинеограниченноеколичествопредметовза0(nW)
                // dp[i][k] = dp[i][k - 1]
                // if (m[k] <= i) {
                // dp[i][k] = max(dp[i][k], dp[i][j - m[k]] + c[k -
                1]);
                // }
                if (i - m[k - 1] * count >= 0) {
                    dp[i][k] = max(dp[i][k], dp[i - m[k - 1] * count][k
                    - 1] + c[k - 1] * count);
                }
            }
        }
    }

    cout << dp[test][n] << endl;

    getResult(test, n, dp, m);

    for (int i = 0; i < result.size(); i++) {
        if (result[i] != 0) {
            cout << result[i] << " ";
        }
    }
}

```

6.4 Dominos

```

// Theme: DP Dominos
// Complexity: O(N*M*2^M)

unsigned long long int dp[20][20][5000];

int main() {
    unsigned long long int n, m, i, j, k, 12, r;

    cin >> n >> m;
    char tiling[20][20];
    for (i = 0; i < n; i++) {
        for (j = 0; j < m; j++)
            tiling[i][j] = '.';
    }
    for (k = 0; k < n + 1; k++) {
        for (j = 0; j < m; j++) {
            for (unsigned long long int mask = 0; mask < (unsigned
                long long int)pow(2, m); mask++) {
                if (k != 0 & j != 0 & mask != 0)
                    dp[k][j][mask] = 0;
                else
                    dp[k][j][mask] = 1;
            }
        }
    }
}

```

```

for (k = 0; k < n; k++) {
    for (j = 0; j < m; j++) {
        for (unsigned long long int mask = 0; mask < (unsigned
            long long int)pow(2, m); mask++) {
            if (k < n - 1 && tiling[k][j] == '.' && tiling[k +
                1][j] == '.' && (mask & (1 << j)) == 0)
                dp[k + ((j + 1) / m)][(j + 1) % m][mask + (1 << j)]
                    += dp[k][j][mask];
            if (j < m - 1 && tiling[k][j] == '.' && tiling[k][j
                + 1] == '.' && (mask & (3 << j)) == 0)
                dp[k + ((j + 1) / m)][(j + 1) % m][mask + (2 << j)]
                    += dp[k][j][mask];
            if (((1 << j) & mask) != 0 || tiling[k][j] != '.')
                dp[k + ((j + 1) / m)][(j + 1) % m][(mask | (1 << j)
                    ) - (1 << j)] += dp[k][j][mask];
        }
    }
}

cout << binpow(2, n * m / 2, 1000000007) * (dp[n][0][0] %
    1000000007) % 1000000007;
}

```

7 Graphs

7.1 Graph Implementation

```

// Theme: Graph Implementation

////////////////////////////////////
// Adjacency List (Unoriented)
////////////////////////////////////

int sz;

vector<vector<int>> graph;

graph.assign(n, {});

for (int i = 0; i < n; i++) {
    int u, v; cin >> u >> v; --u --v;
    graph[u].push_back(v);
    graph[v].push_back(u);
}

////////////////////////////////////
// Adjacency List (Oriented)
////////////////////////////////////

int sz;

vector<vector<int>> graph;
vector<vector<int>> rgraph;

graph.assign(n, {});
rgraph.assign(n, {});

for (int i = 0; i < n; i++) {
    int u, v; cin >> u >> v; --u --v;
    graph[u].push_back(v);
    rgraph[v].push_back(u);
}

////////////////////////////////////
// Edges List (Unoriented)
////////////////////////////////////

int sz;

vector<pair<int, int>> edges;
vector<vector<int>> graph;

graph.assign(n, {});

for (int i = 0; i < n; i++) {
    int u, v; cin >> u >> v; --u; --v;
    edges.push_back({ u, v });
    graph[u].push_back(i);
    graph[v].push_back(i);
}

////////////////////////////////////
// Edges List + Structure (Unoriented)

```

```

////////////////////////////////////
struct edge {
    int u, v, w;
    edge(int u, int v, int w = 0)
        : u(u), v(v), w(w) { }
};

int sz;

vector<edge> edges;
vector<vector<int>> graph;

graph.assign(n, {});

for (int i = 0; i < n; i++) {
    int u, v, w; cin >> u >> v >> w; --u; --v;
    edges.push_back({ u, v, w });
    graph[u].push_back(i);
    graph[v].push_back(i);
}

////////////////////////////////////
// Edges List + Structure + Net Flows (Oriented)
////////////////////////////////////

struct edge {
    int to, cap, flow, weight;
    edge(int to, int cap, int flow = 0, int weight = 0)
        : to(to), cap(cap), flow(flow), weight(weight) { }
    int res() {
        return cap - flow;
    }
};

int sz;

vector<edge> edges;
vector<vector<int>> fgraph;

fgraph.assign(n, {});

void add_edge(int u, int v, int limit, int flow = 0, int
    weight = 0) {
    fgraph[u].push_back(edges.size());
    edges.push_back({ v, limit, flow, weight });
    fgraph[v].push_back(edges.size());
    edges.push_back({ u, 0, 0, -weight });
}

////////////////////////////////////
// Adjacency Matrix
////////////////////////////////////

vector<vector<int>> graph;

for (int i = 0; i < n; i++)
    for (int j = 0; j < n; j++)
        cin >> graph[i][j];

```

7.2 Graph Traversing

```

// Theme: Graph Traversing

vector<vector<int>> graph;
vector<int> used;

// Algorithm: Depth-First Search (Adjacency List)
// Complexity: O(N + M)

void dfs(int cur, int p = -1) {
    used[cur] = 1;

    for (auto &to : graph[cur]) {
        if (to == p || used[to]) continue;
        dfs(to, cur);
    }
}

// Algorithm: Breadth-First Search (Adjacency List)
// Complexity: O(N + M)

void bfs(int u) {
    queue<int> q; q.push(u);

```

```

while (q.size()) {
    int cur = q.front(); q.pop();

    for (auto &to : graph[cur]) {
        if (used[to]) continue;
        q.push(to);
    }
}

```

7.3 Topological Sort

```

// Theme: Topological Sort

vector<vector<int>> graph;
vector<int> used;

// Algorithm: Topological Sort
// Complexity: O(N + M)

vector<int> topsort;

void dfs_topsort(int cur, int p = -1) {
    used[cur] = 1;

    for (auto &to : graph[cur]) {
        if (to == p || used[to]) continue;
        dfs(to, cur);
    }

    topsort.push_back(cur);
}

for (int u = 0; u < n; u++)
    if (!used[u])
        dfs_topsort(u);

reverse(all(topsort));

```

7.4 Connected Components

```

// Theme: Connectivity Components

vector<vector<int>> graph;
vector<int> used;

// Algorithm: Connected Components
// Complexity: O(N + M)

vector<vector<int>> cc;

void dfs_cc(int cur, int p = -1) {
    used[cur] = 1;
    cc.back().push_back(cur);

    for (auto &to : graph[cur]) {
        if (to == p || used[to]) continue;
        dfs_cc(to, cur);
    }
}

for (int u = 0; u < n; u++)
    if (!used[u])
        dfs_cc(u);

// Algorithm: Strongly Connected Components
// Complexity: O(N + M)

vector<vector<int>> rgraph;

vector<vector<int>> topsort;

vector<vector<int>> scc;

void dfs_scc(int cur, int p = -1) {
    used[cur] = 1;
    scc.back().push_back(cur);

    for (auto &to : rgraph[cur]) {
        if (to == p || used[to]) continue;
        dfs_scc(to, cur);
    }
}

```



```

}

for (auto &u: topsort)
    if (!used[u])
        dfs_scc(u);

```

7.5 2 Sat

// Theme: 2-SAT

// Algorithm: Adding Edges To 2-SAT

```

vector<vector<int>> ts_graph;
vector<vector<int>> ts_rgraph;
vector<int> used;
vector<int> top_sort;

```

// Vertex By Var Number

```

int to_vert(int x) {
    if (x < 0) {
        return ((abs(x) - 1) << 1) ^ 1;
    }
    else {
        return (x - 1) << 1;
    }
}

```

// Adding Implication

```

void add_impl(int a, int b) {
    ts_graph[a].insert(b);
    ts_rgraph[b].insert(a);
}

```

// Adding Disjunction

```

void add_or(int a, int b) {
    add_impl(a ^ 1, b);
    add_impl(b ^ 1, a);
}

```

//topsort

```

void dfs(int v){
    used[v] = 1;
    for(auto to:ts_graph[v]){
        if(!used[to])dfs(to);
    }
    top_sort.push_back(v);
}

```

//scc

```

vector<vector<long long int>> scc;
void dfs_scc(long long int cur, long long int p = -1) {
    used[cur] = 1;
    scc.back().push_back(cur);
    for (auto to : rgr[cur]) {
        if (to == p || used[to]) continue;
        dfs_scc(to, cur);
    }
}

```

int main(){

```

    ...
    used.resize(n,0);
    for(i=0;i<n;i++){
        if(!used[i])dfs(i);
    }
    reverse(top_sort.begin(), top_sort.end());
    for(auto it:top_sort){
        if (!used[u]) {
            scc.push_back({});
            dfs_scc(u);
        }
    }
    vector<long long int>v_scc;
    v_scc.assign(2 * n, -1);

    for (int i = 0; i < scc.size(); i++)
        for (auto& u : scc[i])
            v_scc[u] = i;

    vector<long long int> values(2 * n, -1);

    for (int i = 0; i < 2 * n; i += 2)
        if (v_scc[i] == v_scc[i ^ 1]) {
            cout << "NO\n";
            return 0;
        }
}

```

```

    else {
        if (v_scc[i] < v_scc[i ^ 1]) {
            values[i] = 0;
            values[i ^ 1] = 1;
        }
        else {
            values[i] = 1;
            values[i ^ 1] = 0;
        }
    }
}
}

```

7.6 Bridges

// Theme: Bridges And ECC

```

vector<pair<int, int>> edges;
vector<vector<int>> graph;
vector<int> used;

```

```

vector<int> height;
vector<int> up;

```

// Algorithm: Bridges

// Complexity: O(N + M)

```

vector<int> bridges;

```

```

void dfs_bridges(int cur, int p = -1) {
    used[cur] = 1;
    up[cur] = height[cur];
    for (auto &ind : g[cur]) {
        int to = cur ^ edges[ind].ff ^ edges[ind].ss;
        if (to == p) continue;
        if (used[to]) {
            up[cur] = min(up[cur], height[to]);
        }
        else {
            height[to] = height[cur] + 1;
            dfs_bridges(to, cur);
            up[cur] = min(up[cur], up[to]);
            if (up[to] > height[cur])
                bridges.push_back(ind);
        }
    }
}

```

// Algorithm: ECC

// Complexity: O(N + M)

```

vector<int> st;

```

```

vector<int> add_comp(vector<int> &st, int sz) {
    vector<int> comp;

```

```

    while (st.size() > sz) {
        comp.push_back(st.back());
        st.pop_back();
    }

```

```

    return comp;
}

```

```

vector<vector<int>> ecc;

```

```

void dfs_bridges_comps(int cur, int p = -1) {
    used[cur] = 1;
    up[cur] = height[cur];

```

```

    for (auto &ind : g[cur]) {
        int to = cur ^ edges[ind].ff ^ edges[ind].ss;
        if (to == p) continue;
        if (used[to]) {
            up[cur] = min(up[cur], height[to]);
        }
        else {
            int sz = st.size();
            st.push_back(to);
            height[to] = height[cur] + 1;
            dfs_bridges_comps(to, cur);
            up[cur] = min(up[cur], up[to]);
            if (up[to] > height[cur])
                ecc.push_back(add_comp(st, sz));
        }
    }
}

```

7.7 Articulation Points

```
// Theme: Articulation Points And VCC

vector<pair<int, int>> edges;
vector<vector<int>>> graph;
vector<int> used;

vector<int> height;
vector<int> up;

// Algorithm: Articulation Points
// Complexity: O(N + M)

set<int> art_points;

void dfs_artics(int cur, int p = -1) {
    used[cur] = 1;
    up[cur] = height[cur];

    int desc_count = 0;

    for (auto &ind : g[cur]) {
        int to = cur ^ edges[ind].ff ^ edges[ind].ss;
        if (to == p) continue;
        if (used[to]) {
            up[cur] = min(up[cur], height[to]);
        }
        else {
            desc_count++;
            height[to] = height[cur] + 1;
            dfs_artics(to, cur);
            up[cur] = min(up[cur], up[to]);
            if (up[to] >= height[cur] && p != -1)
                art_points.insert(cur);
        }
    }

    if (p == -1 && desc_count > 1) {
        art_points.insert(cur);
    }
}

// Algorithm: VCC
// Complexity: O(N + M)

vector<vector<int>>> vcc;

void dfs_artics_comps(int cur, int p = -1) {
    used[cur] = 1;
    up[cur] = height[cur];

    for (auto &ind : g[cur]) {
        int to = cur ^ edges[ind].ff ^ edges[ind].ss;
        if (to == p) continue;
        if (used[to]) {
            up[cur] = min(up[cur], height[to]);
            if (height[to] < height[cur]) st.push_back(ind);
        }
        else {
            int sz = st.size();
            st.push_back(ind);
            height[to] = height[cur] + 1;
            dfs_artics_comps(to, cur);
            up[cur] = min(up[cur], up[to]);
            if (up[to] >= height[cur])
                vcc.push_back(add_comp(st, sz));
        }
    }
}
```

7.8 Kuhn

```
// Maximum Matching

// Algorithm: Kuhn Algorithm
// Complexity: O(|Left Part|^3)

vector<vector<int>>> bigraph;
vector<int> used;

vector<int> mt;

bool kuhn(int u) {
```

```
    if (used[u]) return false;

    used[u] = 1;

    for (auto &v : bigraph[u]) {
        if (mt[v] == -1 || kuhn(mt[v])) {
            mt[v] = u;
            return true;
        }
    }

    return false;
}

int main() {
    ... чтение графа...

    mt.assign(k, -1);
    for (int v=0; v<n; ++v) {
        used.assign(n, false);
        try_kuhn(v);
    }

    for (int i=0; i<k; ++i)
        if (mt[i] != -1)
            printf ("%d %d\n", mt[i]+1, i+1);
}
```

7.9 Kruskal

```
#include <iostream>
#include <vector>
#include <algorithm>

using namespace std;

struct dsu {
    vector<int> p, size;

    dsu(int n) {
        p.assign(n, 0); size.assign(n, 0);
        for (int i = 0; i < n; i++) {
            p[i] = i;
            size[i] = 1;
        }
    }

    int get(int v) {
        if (p[v] != v) p[v] = get(p[v]);
        return p[v];
    }

    void unite(int u, int v) {
        auto x = get(u), y = get(v);
        if (x == y) return;
        if (size[x] > size[y]) swap(x, y);
        p[x] = y; size[y] += size[x];
    }
};

int sz;

struct edge {
    long long int u, v, w;
    edge(long long int uu, long long int vv, long long int ww) : u(uu), v(vv), w(ww) {};
};

vector<edge> edges;
vector<vector<int>>> graph;

// Algorithm: Kruskal Algorithm
// Complexity: O(M)

vector<edge> mst;

void kruskal() {
    dsu d(sz);

    auto tedges = edges;
    sort(tedges.begin(), tedges.end(), [](edge& e1, edge& e2) { return e1.w < e2.w; });

    for (auto& e : tedges) {
        if (d.get(e.u) != d.get(e.v)) {
```

```

        mst.push_back(e);
        d.unite(e.u, e.v);
    }
}

int main() {
    long long int n, m, i, j, k, a, b, c;
    cin >> n >> m;
    for (i = 0; i < m; i++) {
        cin >> a >> b >> c;
        a--; b--;
        edge e(a, b, c);
        edges.push_back(e);
    }
    sz = n;
    kruskal();
    long long int ans = 0;
    for (auto it : mst) ans += it.w;
    cout << ans;
}

```

7.10 LCA (binary Lifting)

```

// Theme: Lowest Common Ancestor

// Algorithm: Binary Lifting
// Complexity: Preprocessing  $O(N * \log(N))$  and request  $O(\log(N))$ 

vector<vector<int>>> g;
vector<int> d;
vector<vector<int>>> dp;
vector<int> used;

void dfs(int v, int p = -1) {
    if (p == -1) {
        p = v;
        d[v] = 0;
    } else {
        d[v] = d[p] + 1;
    }

    dp[0][v] = p;
    for (int i = 1; i < dp.size(); i++) {
        dp[i][v] = dp[i - 1][dp[i - 1][v]];
    }
    for (int to : g[v]) {
        if (to != p) {
            dfs(to, v);
        }
    }
}

int lca(int a, int b) {
    if (d[a] > d[b]) {
        swap(a, b);
    }

    for (int i = dp.size() - 1; i >= 0; i--) {
        if (d[dp[i][b]] >= d[a]) {
            b = dp[i][b];
        }
    }

    if (a == b) {
        return a;
    }

    for (int i = dp.size() - 1; i >= 0; i--) {
        if (dp[i][a] != dp[i][b]) {
            a = dp[i][a];
            b = dp[i][b];
        }
    }

    return dp[0][a];
}

signed main() {
    int n = 0, m = 0; // n - vertex count, m - requests
    g.resize(n);
    d.resize(n);
    dp.resize((int)log2(n) + 1);
    used.assign(n, 0);
}

```

```

for (int i = 0; i < dp.size(); i++) {
    dp[i].resize(n);
}

// ...reading graph...

dfs(0);

// ...lca(u - 1, v - 1) + 1
}

```

7.11 LCA RMQ (segtree)

```

// Theme: Lowest Common Ancestor

// Algorithm: RMQ (segtree)
// Complexity: Preprocessing  $O(N)$  and request  $O(\log(N))$ 

typedef vector<vector<int>>> graph;
typedef vector<int>::const_iterator const_graph_iter;

vector<int> lca_h, lca_dfs_list, lca_first, lca_tree;
vector<char> lca_dfs_used;

void lca_dfs(const graph &g, int v, int h = 1) {
    lca_dfs_used[v] = true;
    lca_h[v] = h;
    lca_dfs_list.push_back(v);
    for (const_graph_iter i = g[v].begin(); i != g[v].end(); i++) {
        if (!lca_dfs_used[*i]) {
            lca_dfs(g, *i, h + 1);
            lca_dfs_list.push_back(v);
        }
    }
}

void lca_build_tree(int i, int l, int r) {
    if (l == r)
        lca_tree[i] = lca_dfs_list[l];
    else {
        int m = (l + r) >> 1;
        lca_build_tree(i + i, l, m);
        lca_build_tree(i + i + 1, m + 1, r);
        if (lca_h[lca_tree[i + i]] < lca_h[lca_tree[i + i + 1]])
            lca_tree[i] = lca_tree[i + i];
        else
            lca_tree[i] = lca_tree[i + i + 1];
    }
}

void lca_prepare(const graph &g, int root) {
    int n = (int)g.size();
    lca_h.resize(n);
    lca_dfs_list.reserve(n * 2);
    lca_dfs_used.assign(n, 0);
    lca_dfs(g, root);
    int m = (int)lca_dfs_list.size();
    lca_tree.assign(lca_dfs_list.size() * 4 + 1, -1);
    lca_build_tree(1, 0, m - 1);
    lca_first.assign(n, -1);
    for (int i = 0; i < m; i++) {
        int v = lca_dfs_list[i];
        if (lca_first[v] == -1)
            lca_first[v] = i;
    }
}

int lca_tree_min(int i, int sl, int sr, int l, int r) {
    if (sl == l && sr == r)
        return lca_tree[i];
    int sm = (sl + sr) >> 1;
    if (r <= sm)
        return lca_tree_min(i + i, sl, sm, l, r);
    if (l > sm)
        return lca_tree_min(i + i + 1, sm + 1, sr, l, r);
    int ans1 = lca_tree_min(i + i, sl, sm, l, r);
    int ans2 = lca_tree_min(i + i + 1, sm + 1, sr, sm + 1, r);
    return lca_h[ans1] < lca_h[ans2] ? ans1 : ans2;
}

int lca(int a, int b) {
    int left = lca_first[a],
        right = lca_first[b];
    if (left > right)

```

```

    swap(left, right);
    return lca_tree_min(1, 0, (int)lca_dfs_list.size() - 1,
        left, right);
}

signed main() {
    int n = 0, m = 0; // n - vertex count, m - requests
    graph g(n);

    // ...reading graph...

    lca_prepare(g, 0);

    // ...lca(u - 1, v - 1) + 1
}

```

7.12 Maximum Flow

// Theme: Maximum Flow

```

struct edge {
    int to, limit, flow;
    edge(int to, int limit, int flow) : to(to), limit(limit),
        flow(flow) {}
    int res() {
        return limit - flow;
    }
};

void add_edge(int u, int v, int limit, int flow) {
    fgraph[u].push_back(edges.size());
    edges.push_back({ v, limit, flow });
    fgraph[v].push_back(edges.size());
    edges.push_back({ u, 0, 0 });
}

int s, t, sz;
vector<edge> edges;
vector<vector<int>> fgraph;

vector<int> used;

// Algorithm: Ford-Fulkerson Algorithm
// Complexity: O(MF)

int dfs_fordfulk(int u, int bound, int flow = INF) {
    if (used[u]) return 0;
    if (u == t) return flow;

    used[u] = 1;

    for (auto &ind : fgraph[u]) {
        auto &e = edges[ind],
            &_e = edges[ind ^ 1];
        int to = e.to, res = e.res();

        if (res < bound) continue;

        int pushed = dfs_fordfulk(to, bound, min(res, flow))
            ;

        if (pushed) {
            e.flow += pushed;
            _e.flow -= pushed;
            return pushed;
        }
    }

    return 0;
}

// Algorithm: Edmonds-Karp Algorithm
// Complexity: O(N(M^2))

vector<int> p;
vector<int> pe;

void augment(int pushed) {
    int cur = t;
    while (cur != s) {
        auto &e = edges[pe[cur]],
            &_e = edges[pe[cur] ^ 1];
        e.flow += pushed;
        _e.flow -= pushed;
    }
}

```

```

        cur = p[cur];
    }
}

int bfs_edmskarp(int u, int bound) {
    p.assign(sz, -1);
    pe.assign(sz, -1);

    int pushed = 0;

    queue<pair<int, int>> q;
    q.push({ u, INF });

    used[u] = 1;

    while (q.size()) {
        auto [v, f] = q.front(); q.pop();

        for (auto &ind : fgraph[v]) {
            auto &e = edges[ind];
            int to = e.to, res = e.res();

            if (used[to] || res < bound) continue;

            p[to] = v;
            pe[to] = ind;
            used[to] = 1;

            if (to == t) {
                pushed = min(f, res);
                break;
            }

            q.push({ to, min(f, res) });
        }
    }

    if (pushed)
        augment(pushed);

    return pushed;
}

// Algorithm: Dinic Algorithm
// Complexity: O((N^2)M)

vector<int> d;

bool bfs_dinic(int u, int bound) {
    d.assign(sz, INF); d[u] = 0;

    queue<int> q; q.push(u);

    while (q.size()) {
        int v = q.front(); q.pop();

        for (auto &ind : fgraph[v]) {
            auto &e = edges[ind];
            int to = e.to, res = e.res();

            if (d[v] + 1 >= d[to] || res < bound) continue;

            d[to] = d[v] + 1;
            q.push(to);
        }
    }

    return d[t] != INF;
}

vector<int> lst;

int dfs_dinic(int u, int mxf = INF) {
    if (u == t) return mxf;

    int smf = 0;

    for (int i = lst[u]; i < fgraph[u].size(); i++) {
        int ind = fgraph[u][i];

        auto &e = edges[ind],
            &_e = edges[ind ^ 1];
        int to = e.to, res = e.res();

        if (d[to] == d[u] + 1 && res) {
            int pushed = dfs_dinic(to, min(res, mxf - smf));

            if (pushed) {

```

```

        smf += pushed;
        e.flow += pushed;
        _e.flow -= pushed;
    }
}

lst[u]++;

if (smf == mx)
    return smf;
}

return smf;
}

int dinic(int u) {
    int pushed = 0;

    for (int bound = 1; bound < 30; bound << 1) {
        while (true) {
            bool bfs_ok = bfs_dinic(u, bound);
            if (!bfs_ok) break;

            lst.assign(sz, 0);

            while (true) {
                int dfs_pushed = dfs_dinic(u);
                if (!dfs_pushed) break;

                pushed += dfs_pushed;
            }
        }
    }

    return pushed;
}

// Algorithm: Maximum Flow Of Minimum Cost (SPFA)
// Complexity: ...

vector<int> d;
vector<int> p;
vector<int> pe;

void augment(int pushed) {
    int cur = t;
    while (cur != s) {
        auto &e = edges[pe[cur]];
        _e = edges[pe[cur] ^ 1];
        e.flow += pushed;
        _e.flow -= pushed;
        cur = p[cur];
    }
}

int bfs_spfa(int u, int flow = INF) {
    d.assign(sz, INF); d[u] = 0;
    p.assign(sz, -1);
    pe.assign(sz, -1);

    queue<pair<int, int>> q; q.push({ u, flow });
    vector<int> in_q(sz, 0); in_q[u] = 1;

    int pushed = 0;

    while (q.size()) {
        auto [v, f] = q.front(); q.pop();

        in_q[v] = 0;

        if (v == t) {
            pushed = f;
            break;
        }

        for (auto &ind : fgraph[v]) {
            auto &e = edges[ind];
            int to = e.to, res = e.res(),
                w = e.weight;

            if (d[v] + w >= d[to] || !res) continue;

            d[to] = d[v] + w;
            p[to] = v;
            pe[to] = ind;

            if (!in_q[to]) {

```

```

                in_q[to] = 1;
                q.push({ to, min(f, res) });
            }
        }

        if (pushed)
            augment(pushed);

        return pushed;
    }
}

```

7.13 Eulerian Path

```

// Theme: Eulerian Path

int sz;

vector<vector<int>> graph;

// Algorithm: Eulerian Path
// Complexity: O(M)

vector<int> eul;

// 0 - path not exist
// 1 - cycle exists
// 2 - path exists
int euler_path() {
    vector<int> deg(sz);

    for (int i = 0; i < sz; i++)
        for (int j = 0; j < sz; j++)
            deg[i] += g[i][j];

    int v1 = -1, v2 = -1;
    for (int i = 0; i < sz; i++)
        if (deg[i] & 1)
            if (v1 == -1) v1 = i;
            else if (v2 == -1) v2 = i;
            else return 0;

    if (v1 != -1) {
        if (v2 == -1)
            return 0;
        graph[v1][v2]++;
        graph[v2][v1]++;
    }

    stack<int> st;

    for (int i = 0; i < sz; i++) {
        if (deg[i]) {
            st.push(i);
            break;
        }
    }

    while (st.size()) {
        int u = st.top();

        int ind = -1;

        for (int i = 0; i < sz; i++)
            if (graph[u][i]) {
                ind = i;
                break;
            }

        if (ind == -1) {
            eul.push_back(u);
            st.pop();
        }
        else {
            graph[u][ind]--;
            graph[ind][u]--;
            st.push(ind);
        }
    }

    int res = 2;
    if (v1 != -1) {
        res = 1;

        for (int i = 0; i < eul.size() - 1; i++)

```

```

        if (eul[i] == v1 && eul[i + 1] == v2 ||
            eul[i] == v2 && eul[i + 1] == v1) {
            vector<int> teul;
            for (int j = i + 1; j < eul.size(); j++)
                teul.push_back(eul[j]);
            for (int j = 0; j <= i; j++)
                teul.push_back(eul[j]);
            eul = teul;
            break;
        }
    }

    for (int i = 0; i < sz; i++)
        for (int j = 0; j < sz; j++)
            if (graph[i][j])
                return 0;

    return res;
}

```

7.14 Eulerian Path Oriented

```

// Theme: Eulerian Path

// Algorithm: Eulerian Path
// Complexity: O(M)

// Algo doesn't validate the path to be correct.
// If the path exists, it will be found.
// Result way has to be reversed after execution.

struct Edge {
    int v, u;
    bool deleted = false;
};

vector<Edge> edges;

vector<deque<int>> graph;
vector<int> way;

void euler(int v, int last = -1) {
    while (!graph[v].empty()) {
        int idx = graph[v].front(); graph[v].pop_front();
        auto& e = edges[idx];
        if (e.deleted) continue;
        e.deleted = true; // If graph is not oriented, also
                          // delete reverse edge[v ^ 1]
        euler(e.u, idx);
    }
    if (last != -1) way.push_back(last);
}

```

7.15 Shortest Paths

```

// Theme: Shortest Paths

int sz;

vector<edge> edges;
vector<vector<int>> graph;

// Algorithm: Dijkstra Algorithm
// Complexity: O(M*log(N))

vector<int> d;
vector<int> p;

void dijkstra(int u) {
    d.assign(sz, INF); d[u] = 0;
    p.assign(sz, -1);

    priority_queue<pair<int, int>> q;
    q.push({ 0, u });

    while (q.size()) {
        int dist = -q.top().ff, v = q.top().ss; q.pop();

        if (dist > d[v]) continue;

        for (auto &ind : graph[v]) {
            int to = v ^ edges[ind].u ^ edges[ind].v,

```

```

            w = edges[ind].w;
            if (d[v] + w < d[to]) {
                d[to] = d[v] + w;
                p[to] = v;
                q.push({ -d[to], -to });
            }
        }
    }

// Algorithm: Shortest Path Faster Algorithm
// Complexity: ...

vector<int> d;

void bfs_spfa(int u) {
    d.assign(sz, INF); d[u] = 0;

    queue<int> q; q.push(u);
    vector<int> in_q(sz, 0); in_q[u] = 1;

    while (q.size()) {
        auto [v, f] = q.front(); q.pop();

        in_q[v] = 0;

        for (auto &ind : graph[v]) {
            int to = v ^ edges[ind].u ^ edges[ind].v,
                w = edges[ind].w;
            if (d[v] + w < d[to]) {
                d[to] = d[v] + w;
                if (!in_q[to]) {
                    in_q[to] = 1;
                    q.push(to);
                }
            }
        }
    }

// Algorithm: Belman-Ford Algorithm
// Complexity: (N*M)

vector<int> d;

void bfa(int u) {
    d.assign(sz, INF); d[u] = 0;

    for (;;) {
        bool any = false;

        for (auto &e : edges) {
            if (d[e.u] != INF && d[e.u] + e.w < d[e.v]) {
                d[e.v] = d[e.u] + e.w;
                any = true;
            }
            if (d[e.v] != INF && d[e.v] + e.w < d[e.u]) {
                d[e.u] = d[e.v] + e.w;
                any = true;
            }
        }

        if (!any) break;
    }

// Algorithm: Floyd-Warshall Algorithm
// Complexity: O(N^3)

vector<vector<int>> d;

void fwa() {
    d.assign(sz, vector<int>(sz, INF));

    for (int i = 0; i < sz; i++)
        for (int j = 0; j < sz; j++)
            for (int k = 0; k < sz; k++)
                if (d[i][k] != INF && d[k][j] != INF)
                    d[i][j] = min(d[i][j], d[i][k] + d[k][j]);
}

// Algorithm: Minimal spanning tree (dense graph)
// Complexity: O(N^2)

```

7.16 Prim

```

int n;
vector<vector<int>> g;
const int INF = 1000000000;

vector<bool> used(n);
vector<int> min_e(n, INF), sel_e(n, -1);
min_e[0] = 0;
for (int i = 0; i < n; ++i) {
    int v = -1;
    for (int j = 0; j < n; ++j)
        if (!used[j] && (v == -1 || min_e[j] < min_e[v]))
            v = j;
    if (min_e[v] == INF) {
        cout << "No MST!";
        exit(0);
    }
    used[v] = true;
    if (sel_e[v] != -1)
        cout << v << " " << sel_e[v] << endl;
    for (int to = 0; to < n; ++to)
        if (g[v][to] < min_e[to]) {
            min_e[to] = g[v][to];
            sel_e[to] = v;
        }
}

// Algorithm: Minimal spanning tree (dense graph)
// Complexity: O(M*log(N))

int n;
vector<vector<pair<int, int>>> g;
const int INF = 1000000000;

vector<int> min_e(n, INF), sel_e(n, -1);
min_e[0] = 0;
set<pair<int, int>> q;
q.insert(make_pair(0, 0));
for (int i = 0; i < n; ++i) {
    if (q.empty()) {
        cout << "No MST!";
        exit(0);
    }
    int v = q.begin()->second;
    q.erase(q.begin());
    if (sel_e[v] != -1)
        cout << v << " " << sel_e[v] << endl;
    for (size_t j = 0; j < g[v].size(); ++j) {
        int to = g[v][j].first,
            cost = g[v][j].second;
        if (cost < min_e[to]) {
            q.erase(make_pair(min_e[to], to));
            min_e[to] = cost;
            sel_e[to] = v;
            q.insert(make_pair(min_e[to], to));
        }
    }
}

```

```

        f2 = f1;
        m1 = l + (r - 1) / (1 + phi);
        f1 = f(m1);
    }
    else {
        l = m1;
        m1 = m2;
        f1 = f2;
        m2 = r - (r - 1) / (1 + phi);
        f2 = f(m2);
    }
}

return f((l + r) / 2);
}

// Algorithm: Discrete Search
// Complexity: O(log(N))

double discr_tern_srch(int l, int r) {
    while (r - l > 2) {
        int m1 = l + (r - 1) / 3,
            m2 = r - (r - 1) / 3;
        if (f(m1) < f(m2))
            r = m2;
        else
            l = m1;
    }

    return min(f(l), min(f(l + 1), f(r)));
}

```

8 Miscellaneous

8.1 Ternary Search

```

// Theme: Ternary Search

// Algorithm: Continuous Search With Golden Ratio
// Complexity: O(log(N))

// Golden Ratio
// Phi = 1.618...
double phi = (1 + sqrt(5)) / 2;

double cont_tern_srch(double l, double r) {
    double m1 = l + (r - l) / (1 + phi),
        m2 = r - (r - l) / (1 + phi);

    double f1 = f(m1), f2 = f(m2);

    int count = 200;
    while (count--) {
        if (f1 < f2) {
            r = m2;
            m2 = m1;

```