

ACM-ICPC Team Reference Document

Tula State University (Fursov, Perezyabov, Vasin)

Contents

1	Templates	1
1.1	C++ Template	1
1.2	C++ Include	2
1.3	Py Template	2
2	Data Structures	2
2.1	Disjoint Set Union	2
2.2	Segment Tree	2
2.3	Segment Tree Propagate	2
2.4	Treap	3
2.5	Treap K	3
3	Algebra	4
3.1	Primes Sieve	4
3.2	Factorization	4
3.3	Euler Totient Function	5
3.4	Greatest Common Divisor	5
3.5	Binary Operations	5
3.6	Matrices	5
3.7	Fibonacci	6
3.8	Baby Step Giant Step	6
3.9	Combinations	6
3.10	Permutation	6
3.11	Fast Fourier Transform	6
3.12	Primitive Roots	7
3.13	Number Decomposition	12
3.14	Formulae	12
4	Geometry	12
4.1	Vector	12
4.2	Planimetry	13
4.3	Graham	13
4.4	Formulae	13
5	Stringology	14
5.1	Z Function	14
5.2	Manacher	14
5.3	Trie	14
5.4	Prefix Function	14
5.5	Suffix Array	14
6	Dynamic Programming	15
6.1	Increasing Subsequence	15
7	Graphs	15
7.1	Graph Implementation	15
7.2	Graph Traversing	16
7.3	Topological Sort	16
7.4	Connected Components	16
7.5	2 Sat	16
7.6	Bridges	17

7.7	Articulation Points	17
7.8	Kuhn	18
7.9	Kruskal	18
7.10	Lowest Common Ancestor	18
7.11	Shortest Paths	18
7.12	Maximum Flow	19
7.13	Eulerian Path	21

8	Miscellaneous	21
8.1	Ternary Search	21

1 Templates

1.1 C++ Template

```
#include <bits/stdc++.h>

using namespace std;

// DEFINES
#define precision(x) cout << fixed << setprecision(x);
#define fast cin.tie(0); ios::sync_with_stdio(0)
#define all(x) x.begin(), x.end()
#define rall(x) x.rbegin(), x.rend()
#define ff first
#define ss second
// #define nl endl
#define nl "\n"
#define sp " "
#define yes "Yes"
#define no "No"
#define int long long

// CONSTANTS
const int INF = 1e18;
// const int MOD = 1e9 + 7;
// const int MOD = 998244353;

// FSTREAMS
ifstream in("input.txt");
ofstream out("output.txt");

// RANDOM
const int RMIN = 1, RMAX = 1e9;

random_device rdev;
mt19937_64 reng(rdev());
uniform_int_distribution<mt19937_64::result_type> dist(RMIN
, RMAX);

// GLOBALS

// SOLUTION
void solve() {

}
```

```
// PREPROCESSING
void prepr() { }

// ENTRANCE
signed main() {
    precision(15);
    fast;
    prepr();
    int t = 1;
    cin >> t;
    while (t--) solve();
}
```

1.2 C++ Include

```
#include <iostream>
#include <iomanip>
#include <fstream>
#include <random>
#include <cmath>
#include <algorithm>
#include <string>
#include <vector>
#include <set>
#include <unordered_set>
#include <map>
#include <unordered_map>
#include <queue>
#include <deque>
#include <stack>
#include <list>
#include <bitset>
```

1.3 Py Template

```
from math import sqrt, ceil, floor, gcd
from random import randint
import sys
```

```
def inpt():
    return sys.stdin.readline().strip()
```

```
input = inpt
```

```
INF = int(1e18)
# MOD = int(1e9 + 7)
# MOD = 998244353
```

```
def solve():
    pass
```

```
t = 1
t = int(input())
for _ in range(t):
    solve()
```

2 Data Structures

2.1 Disjoint Set Union

```
// Theme: Disjoint Set Union
```

```
struct dsu {
    vector<int> p, size;

    dsu(int n) {
        p.assign(n, 0); size.assign(n, 0);
        for (int i = 0; i < n; i++) {
            p[i] = i;
            size[i] = 1;
        }
    }
};
```

```
    }
}

int get(int v) {
    if (p[v] != v) p[v] = get(p[v]);
    return p[v];
}

void unite(int u, int v) {
    auto x = get(u), y = get(v);
    if (x == y) return;
    if (size[x] > size[y]) swap(x, y);
    p[x] = y; size[y] += size[x];
}
};
```

2.2 Segment Tree

```
// Theme: Segment Tree
```

```
struct segtree {
    int size;
    vector<int> tree;

    void init(int n) {
        size = 1;
        while (size < n) size <= 1;
        tree.assign(2 * size - 1, 0);
    }

    void build(vector<int> &a, int x, int lx, int rx) {
        if (rx - lx == 1) {
            if (lx < a.size()) tree[x] = a[lx];
            return;
        }
        int m = (lx + rx) / 2;
        build(a, 2 * x + 1, lx, m);
        build(a, 2 * x + 2, m, rx);
        tree[x] = tree[2 * x + 1] + tree[2 * x + 2];
    }

    void build(vector<int> &a) {
        init(a.size());
        build(a, 0, 0, size);
    }

    // Complexity: O(log(n))
    void set(int i, int v, int x, int lx, int rx) {
        if (rx - lx == 1) {
            tree[x] = v;
            return;
        }
        int m = (lx + rx) / 2;
        if (i < m) set(i, v, 2 * x + 1, lx, m);
        else set(i, v, 2 * x + 2, m, rx);
        tree[x] = tree[2 * x + 1] + tree[2 * x + 2];
    }

    void set(int i, int v) {
        set(i, v, 0, 0, size);
    }

    // Complexity: O(log(n))
    int sum(int l, int r, int x, int lx, int rx) {
        if (l <= lx && rx <= r) return tree[x];
        if (l >= rx || r <= lx) return 0;
        int m = (lx + rx) / 2;
        return sum(l, r, 2 * x + 1, lx, m) +
            sum(l, r, 2 * x + 2, m, rx);
    }

    int sum(int l, int r) {
        return sum(l, r, 0, 0, size);
    }
};
```

2.3 Segment Tree Propagate

```
// Theme: Segment Tree With Propagation
```

```
struct segtree_prop {
    int size;
    vector<int> tree;

    void init(int n) {
```

```

    size = 1;
    while (size < n) size <= 1;
    tree.assign(2 * size - 1, 0);
}

void build(vector<int> &a, int x, int lx, int rx) {
    if (rx - lx == 1) {
        if (lx < a.size()) tree[x] = a[lx];
        return;
    }
    int m = (lx + rx) / 2;
    build(a, 2 * x + 1, lx, m);
    build(a, 2 * x + 2, m, rx);
    tree[x] = tree[2 * x + 1] + tree[2 * x + 2];
}

void build(vector<int> &a) {
    init(a.size());
    build(a, 0, 0, size);
}

void push(int x, int lx, int rx) {
    if (rx - lx == 1) return;
    tree[2 * x + 1] += tree[x];
    tree[2 * x + 2] += tree[x];
    tree[x] = 0;
}

// Complexity: O(log(n))
void add(int v, int l, int r, int x, int lx, int rx) {
    push(x, lx, rx);
    if (rx <= l || r <= lx) return;
    if (l <= lx && rx <= r) {
        tree[x] += v;
        return;
    }
    int m = (lx + rx) / 2;
    add(v, l, r, 2 * x + 1, lx, m);
    add(v, l, r, 2 * x + 2, m, rx);
}

void add(int v, int l, int r) {
    add(v, l, r, 0, 0, size);
}

// Complexity: O(log(n))
int get(int i, int x, int lx, int rx) {
    push(x, lx, rx);
    if (rx - lx == 1) return tree[x];
    int m = (lx + rx) / 2;
    if (i < m) return get(i, 2 * x + 1, lx, m);
    else return get(i, 2 * x + 2, m, rx);
}

int get(int i) {
    return get(i, 0, 0, size);
}
};

```

2.4 Treap

// Theme: Treap (Tree + Heap)

```

// Node
struct node {
    int key, priority;
    shared_ptr<node> left, right;

    node(int key, int priority = INF) :
        key(key),
        priority(priority == INF ?
            reng() : priority) {}
};

// Treap
struct treap {
    shared_ptr<node> root;

    treap() {}

    treap(int root_key, int root_priority = INF) {
        root = shared_ptr<node>(new node(root_key,
            root_priority));
    }

    treap(shared_ptr<node> rt) {
        root = shared_ptr<node>(rt);
    }
};

```

```

treap(const treap &tr) {
    root = shared_ptr<node>(tr.root);
}

// Complexity: O(log(N))
pair<treap, treap> split(int k) {
    auto res = split(root, k);
    return { treap(res.ff), treap(res.ss) };
}

pair<shared_ptr<node>, shared_ptr<node>> split(
    shared_ptr<node> rt, int k) {
    if (!rt) return { nullptr, nullptr };
    else if (rt->key < k) {
        auto [rt1, rt2] = split(rt->right, k);
        rt->right = rt1;
        return { rt, rt2 };
    }
    else {
        auto [rt1, rt2] = split(rt->left, k);
        rt->left = rt2;
        return { rt1, rt };
    }
}

// Complexity: O(log(N))
treap merge(const treap &tr) {
    root = shared_ptr<node>(merge(root, tr.root));
    return *this;
}

shared_ptr<node> merge(shared_ptr<node> rt1, shared_ptr<
    node> rt2) {
    if (!rt1) return rt2;
    if (!rt2) return rt1;
    if (rt1->priority < rt2->priority) {
        rt1->right = merge(rt1->right, rt2);
        return rt1;
    }
    else {
        rt2->left = merge(rt1, rt2->left);
        return rt2;
    }
}
};

```

2.5 Treap K

// Theme: Treap With Segments

```

// Node
struct node_k {
    int key, priority, size;
    shared_ptr<node_k> left, right;

    node_k(int key, int priority = INF) :
        key(key),
        priority(priority == INF ?
            reng() : priority),
        size(1) {}

    friend int sz(shared_ptr<node_k> nd) {
        return (nd ? nd->size : 0);
    }

    void upd() {
        size = sz(left) + sz(right) + 1;
    }
};

// Treap
struct treap_k {
    shared_ptr<node_k> root;

    treap_k() {}

    treap_k(int root_key, int root_priority = INF) {
        root = shared_ptr<node_k>(new node_k(root_key,
            root_priority));
    }

    treap_k(shared_ptr<node_k> rt) {
        root = shared_ptr<node_k>(rt);
    }
};

```

```

treap_k(const treap_k &tr) {
    root = shared_ptr<node_k>(tr.root);
}

// Complexity: O(log(N))
pair<treap_k, treap_k> split_k(int k) {
    auto res = split_k(root, k);
    return { treap_k(res.ff), treap_k(res.ss) };
}

pair<shared_ptr<node_k>, shared_ptr<node_k>> split_k(
    shared_ptr<node_k> rt, int k) {
    if (!rt) return { nullptr, nullptr };
    else if (sz(rt) <= k) return { rt, nullptr };
    else if (sz(rt->left) + 1 <= k) {
        auto [rt1, rt2] = split_k(rt->right, k - sz(rt->
            left) - 1);
        rt->right = rt1;
        rt->upd();
        return { rt, rt2 };
    }
    else {
        auto [rt1, rt2] = split_k(rt->left, k);
        rt->left = rt2;
        rt->upd();
        return { rt1, rt };
    }
}

// Complexity: O(log(N))
treap_k merge_k(const treap_k &tr) {
    root = shared_ptr<node_k>(merge_k(root, tr.root));
    return *this;
}

shared_ptr<node_k> merge_k(shared_ptr<node_k> rt1,
    shared_ptr<node_k> rt2) {
    if (!rt1) return rt2;
    if (!rt2) return rt1;
    if (rt1->priority < rt2->priority) {
        rt1->right = merge_k(rt1->right, rt2);
        rt1->upd();
        return rt1;
    }
    else {
        rt2->left = merge_k(rt1, rt2->left);
        rt2->upd();
        return rt2;
    }
}
};

```

3 Algebra

3.1 Primes Sieve

```

// Theme: Prime Numbers

// Algorithm: Eratosthenes Sieve
// Complexity: O(N*log(log(N)))

// = 0 - Prime,
// != 0 - Lowest Prime Divisor
auto get_sieve(int n) {
    vector<int> sieve(n); // Sieve
    sieve[0] = sieve[1] = 1;

    for (int i = 2; i * i < n; i++)
        if (!sieve[i])
            for (int j = i * i; j < n; j += i)
                sieve[j] = i;

    return sieve;
}

// Algorithm: Prime Numbers With Sieve
// Complexity: O(N*log(log(N)))

auto get_primes(int n) {
    vector<int> primes, sieve = get_sieve(n);

    for (int i = 2; i < sieve.size(); i++)

```

```

        if (!sieve[i])
            primes.push_back(i);

    return primes;
}

// Algorithm: Linear Algorithm
// Complexity: O(N)

// lp[i] = Lowest Prime Divisor
auto get_sieve_primes(int n, vector<int> &primes) {
    vector<int> lp(n);
    lp[0] = lp[1] = 1;

    for (int i = 2; i < n; i++) {
        if (!lp[i]) {
            lp[i] = i;
            primes.push_back(i);
        }
        for (int j = 0; j < primes.size() &&
            primes[j] <= lp[i] &&
            i * primes[j] < n; j++)
            lp[i * primes[j]] = primes[j];
    }

    return lp;
}

```

3.2 Factorization

```

// Theme: Factorization

// Algorithm: Trivial Algorithm
// Complexity: O(sqrt(N))

auto factors(int n) {
    vector<int> factors;

    for (int i = 2; i * i <= n; i++) {
        if (n % i) continue;
        while (n % i == 0) n /= i;
        factors.push_back(i);
    }

    if (n != 1)
        factors.push_back(n);

    return factors;
}

// Algorithm: Factorization With Sieve
// Complexity: O(N*log(log(N)))

auto factors_sieve(int n) {
    vector<int> factors,
        sieve = get_sieve(n + 1);

    while (sieve[n]) {
        factors.push_back(sieve[n]);
        n /= sieve[n];
    }

    if (n != 1)
        factors.push_back(n);

    return factors;
}

// Algorithm: Factorization With Primes
// Complexity: O(sqrt(N)/log(sqrt(N)))

auto factors_primes(int n) {
    vector<int> factors,
        primes = get_primes(n + 1);

    for (auto &i : primes) {
        if (i * i > n) break;
        if (n % i) continue;
        while (n % i == 0) n /= i;
        factors.push_back(i);
    }

    if (n != 1)
        factors.push_back(n);
}

```

```

    return factors;
}

// Algorithm: Fermat Test
// Complexity:  $O(K \cdot \log(N))$ 

bool fermat(int n) {
    if (n == 2) return true;

    uniform_int_distribution<int> distA(2, n - 1);

    for (int i = 0; i < 1000; i++) {
        int a = distA(reng);
        if (gcd(a, n) != 1 ||
            binpow(a, n - 1, n) != 1)
            return false;
    }

    return true;
}

// Algorithm: Pollard Rho Algorithm
// Complexity:  $O(N^{1/4})$ 

int f(int x, int c, int n) {
    return ((x * x) % n + c) % n;
}

int pollard_rho(int n) {
    if (n % 2 == 0) return 2;

    uniform_int_distribution<int> distC(1, n), distX(1, n);

    int c = distC(reng), x = distX(reng);
    int y = x;

    int g = 1;

    while (g == 1) {
        x = f(x, c, n);
        y = f(f(y, c, n), c, n);
        g = gcd(abs(x - y), n);
    }

    return g;
}

// Algorithm: Pollard Rho Factorization + Fermat Test
// Complexity:  $O(N^{1/4} \cdot \log(N))$ 

void factors_pollard_rho(int n, vector<int> &factors) {
    if (n == 1) return;

    if (fermat(n)) {
        factors.push_back(n);
        return;
    }

    int d = pollard_rho(n);

    factors_pollard_rho(d, factors);
    factors_pollard_rho(n / d, factors);
}

```

3.3 Euler Totient Function

```
// Theme: Euler Totient Function
// Algorithm: Euler Product Formula
// Complexity: O(sqrt(N))

// phi = n(1 - 1 / p_i), i = 1,...
int phi(int n) {
    if (n == 1) return 1;

    auto f = factors(n);

    int res = n;
    for (auto &p : f)
        res -= res / p;

    return res;
}
```

3.4 Greatest Common Divisor

```
// Theme: Greatest Common Divisor

// Algorithm: Simple Euclidean Algorithm
// Complexity:  $O(\log(N))$ 

int gcd(int a, int b) {
    while (b) {
        a %= b;
        swap(a, b);
    }
    return a;
}

// Algorithm: Extended Euclidean Algorithm
// Complexity:  $O(\log(N))$ 

// d = gcd(a, b)
// x * a + y * b = d
// returns {d, x, y}
vector<int> euclid(int a, int b) {
    if (!a) return { b, 0, 1 };
    auto v = euclid(b % a, a);
    int d = v[0], x = v[1], y = v[2];
    return { d, y - (b / a) * x, x };
}
```

3.5 Binary Operations

```
// Theme: Binary Operations

// Algorithm: Binary Multiplication
// Complexity:  $O(\log(b))$ 

int binmul(int a, int b, int p = 0) {
    int res = 0;
    while (b) {
        if (b & 1) res = p ? (res + a) % p : (res + a);
        a = p ? (a + a) % p : (a + a);
        b >>= 1;
    }
    return res;
}

// Algorithm: Binary Exponentiation
// Complexity:  $O(\log(b))$ 

int binpow(int a, int b, int p = 0) {
    int res = 1;
    while (b) {
        if (b & 1) res = p ? (res * a) % p : (res * a);
        a = p ? (a * a) % p : (a * a);
        b >>= 1;
    }
    return res;
}
```

3.6 Matrices

[illegible]

```

    return res;
}

// Algorithm: Matrix-Vector Multiplication
// Complexity: O(N*M)

auto m_prod(matrix<int> &a, row<int> &b, int p = 0) {
    int n = a.size(), m = b.size();

    row<int> res(n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            res[i] = p ? (res[i] + a[i][j] * b[j] % p) % p
            : (res[i] + a[i][j] * b[j]);

    return res;
}

// Algorithm: Fast Matrix Exponentiation
// Complexity: O(N^3*log(K))

auto m_binpow(matrix<int> a, int x, int p = 0) {
    int n = a.size();

    matrix<int> res(n, row<int>(n));
    for (int i = 0; i < n; i++) res[i][i] = 1;

    while (x) {
        if (x & 1) res = m_prod(res, a, p);
        a = m_prod(a, a, p);
        x >>= 1;
    }

    return res;
}

```

3.7 Fibonacci

```

// Theme: Fibonacci Sequence

// Algorithm: Fibonacci Numbers With Matrix Exponentiation
// Complexity: O(log(N))

int fibonacci(int n) {
    row<int> first_two = { 1, 0 };
    if (n <= 2) return first_two[2 - n];

    matrix<int> fib(2, row<int>(2, 0));
    fib[0][0] = 1; fib[0][1] = 1;
    fib[1][0] = 1; fib[1][1] = 0;

    fib = m_binpow(fib, n - 2);

    row<int> last_two = m_prod(fib, first_two);

    return last_two[0];
}

```

3.8 Baby Step Giant Step

```

// Theme: Discrete Logarithm

// Algorithm: Baby-Step Giant-Step Algorithm
// Complexity: O(sqrt(p)*log(p))

//  $a^x \equiv b \pmod{p}$ ,  $(a, p) = 1$ 
//  $a^{(i * m + j)} \equiv b \pmod{p}$ ,  $m = \text{ceil}(\sqrt{p})$ 
//  $a^{(i * m)} \equiv b * a^{(-j)} \pmod{p}$ 
int baby_giant_step(int a, int b, int p) {
    //  $a^{(-1)} \equiv a^{(p-2)} \pmod{p}$ 
    int m = ceil(sqrt(p)), _a = binpow(a, p - 2, p);

    //  $s[b * a^{(-j)}] = j$ 
    unordered_map<int, int> s;
    for (int j = 0, t = b; j < m; j++, t = t * _a % p) s[t] = j;

    for (int i = 0; i < m; i++) {
        //  $s.find(a^{(i * m)})$ 
        auto f = s.find(binpow(a, i * m, p));
    }
}

```

```

        //  $i * m + j$ 
        if (f != s.end()) return i * m + f->ss;
    }

    return -1;
}

```

3.9 Combinations

```

// Theme: Combination Number

// Algorithm: Online Multiplication-Division
// Complexity: O(k)

//  $C_n^k$  - from n by k
int C(int n, int k) {
    int res = 1;

    for (int i = 1; i <= k; i++) {
        res *= n - k + i;
        res /= i;
    }

    return res;
}

// Algorithm: Pascal Triangle Preprocessing
// Complexity: O(N^2)

auto pascal(int n) {
    //  $C[i][j] = C_{i+j}^i$ 
    vector<vector<int>> C(n + 1, vector<int>(n + 1, 1));
    for (int i = 1; i < n + 1; i++)
        for (int j = 1; j < n + 1; j++)
            C[i][j] = C[i - 1][j] + C[i][j - 1];

    return C;
}

```

3.10 Permutation

```

// Theme: Permutations

// Algorithm: Next Lexicological Permutation
// Complexity: O(N)

bool perm(vector<int> &v) {
    int n = v.size();

    for (int i = n - 1; i >= 1; i--) {
        if (v[i - 1] < v[i]) {
            reverse(v.begin() + i, v.end());

            int j = distance(v.begin(),
                upper_bound(v.begin() + i, v.end(), v[i - 1]));

            swap(v[i - 1], v[j]);
            return true;
        }
    }

    return false;
}

```

3.11 Fast Fourier Transform

```

// Theme: Fast Fourier Transform

// Algorithm: Fast Fourier Transform (Complex)
// Complexity: O(N*log(N))

using cd = complex<double>;
const double PI = acos(-1);

auto fft(vector<cd> a, bool invert = 0) {
    //  $n = 2^x$ 
    int n = a.size();
}

```

```

// Bit-Reversal Permutation (0000, 1000, 0100, 1100,
// 0010, ...)
for (int i = 1, j = 0; i < n; i++) {
    int bit = n >> 1;
    for (; j >= bit; bit >>= 1) j -= bit;
    j += bit;
    if (i < j) swap(a[i], a[j]);
}

for (int len = 2; len <= n; len <= 1) {
    // Complex Root Of One
    double ang = 2 * PI / len * (invert ? -1 : 1);
    cd lroot(cos(ang), sin(ang));

    for (int i = 0; i < n; i += len) {
        cd root(1);
        for (int j = 0; j < len / 2; j++) {
            cd u = a[i + j], v = a[i + j + len / 2] * root;
            a[i + j] = (u + v);
            a[i + j + len / 2] = (u - v);
            root = (root * lroot);
        }
    }
}

if (invert) {
    for (int i = 0; i < n; i++) a[i] /= n;
}

return a;
}

// Module (7340033 = 7 * (2 ^ 20) + 1)
// Primiive Root (5 ^ (2 ^ 20) == 1 mod 7340033)
// Inverse Primitive Root (5 * 4404020 == 1 mod 7340033)
// Maximum Degree Of Two (2 ^ 20)

const int mod = 7340033;
const int proot = 5;
const int proot_1 = 4404020;
const int pw = 1 << 20;

// Algorithm: Discrete Fourier Transform (Inverse Roots)
// Complexity: O(N*log(N))

auto fft(vector<int> a, bool invert = 0) {
    // n = 2 ^ x
    int n = a.size();

    // Bit-Reversal Permutation (0000, 1000, 0100, 1100,
    // 0010, ...)
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j >= bit; bit >>= 1) j -= bit;
        j += bit;
        if (i < j) swap(a[i], a[j]);
    }

    for (int len = 2; len <= n; len <= 1) {
        // Primitive Root Or Inverse Root (Inverse
        // Transform)
        int lroot = invert ? proot_1 : proot;

        // Current Primitive Root
        lroot = binpow(lroot, pw / len, mod);

        for (int i = 0; i < n; i += len) {
            int root = 1;
            for (int j = 0; j < len / 2; j++) {
                int u = a[i + j], v = a[i + j + len / 2] *
                    root % mod;
                a[i + j] = (u + v) % mod;
                a[i + j + len / 2] = (u - v + mod) % mod;
                root = (root * lroot) % mod;
            }
        }
    }

    if (invert) {
        int _n = binpow(n, mod - 2, mod);
        for (int i = 0; i < n; i++) a[i] = (a[i] * _n) % mod;
    }

    return a;
}

```

```

}

// Algorithm: Discrete Fourier Transform
// Complexity: O(N*log(N))

auto fft(vector<int> &a, bool invert = 0) {
    // n = 2 ^ x
    int n = a.size();

    // Bit-Reversal Permutation (0000, 1000, 0100, 1100,
    // 0010, ...)
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j >= bit; bit >>= 1) j -= bit;
        j += bit;
        if (i < j) swap(a[i], a[j]);
    }

    for (int len = 2; len <= n; len <= 1) {
        // Current Primitive Root
        int lroot = binpow(proot, pw / len, mod);

        for (int i = 0; i < n; i += len) {
            int root = 1;
            for (int j = 0; j < len / 2; j++) {
                int u = a[i + j], v = a[i + j + len / 2] *
                    root % mod;
                a[i + j] = (u + v) % mod;
                a[i + j + len / 2] = (u - v + mod) % mod;
                root = (root * lroot) % mod;
            }
        }
    }

    if (invert) {
        reverse(a.begin() + 1, a.end());
        int _n = binpow(n, mod - 2, mod);
        for (int i = 0; i < n; i++) a[i] = (a[i] * _n) % mod;
    }

    return a;
}

```

3.12 Primitive Roots

```

// Module (7 == 3 * (2 ^ 1) + 1)
// Primitive Root (3)
// Primitive Root {2 ^ 1} (6)
// Inverse Root {2 ^ 1} (6)
// Degree Of Two (2)

// const int mod = 7
// const int proot = 6
// const int proot_1 = 6
// const int pw = 1 << 1

// Module (13 == 3 * (2 ^ 2) + 1)
// Primitive Root (2)
// Primitive Root {2 ^ 2} (8)
// Inverse Root {2 ^ 2} (5)
// Degree Of Two (4)

// const int mod = 13
// const int proot = 8
// const int proot_1 = 5
// const int pw = 1 << 2

// Module (19 == 9 * (2 ^ 1) + 1)
// Primitive Root (2)
// Primitive Root {2 ^ 1} (18)
// Inverse Root {2 ^ 1} (18)
// Degree Of Two (2)

// const int mod = 19
// const int proot = 18
// const int proot_1 = 18
// const int pw = 1 << 1

```

```

// Module (37 == 9 * (2 ^ 2) + 1)
// Primitive Root (2)
// Primitive Root {2 ^ 2} (31)
// Inverse Root {2 ^ 2} (6)
// Degree Of Two (4)

// const int mod = 37
// const int proot = 31
// const int proot_1 = 6
// const int pw = 1 << 2

// Module (73 == 9 * (2 ^ 3) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 3} (10)
// Inverse Root {2 ^ 3} (22)
// Degree Of Two (8)

// const int mod = 73
// const int proot = 10
// const int proot_1 = 22
// const int pw = 1 << 3

// Module (97 == 3 * (2 ^ 5) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 5} (28)
// Inverse Root {2 ^ 5} (52)
// Degree Of Two (32)

// const int mod = 97
// const int proot = 28
// const int proot_1 = 52
// const int pw = 1 << 5

// Module (109 == 27 * (2 ^ 2) + 1)
// Primitive Root (6)
// Primitive Root {2 ^ 2} (33)
// Inverse Root {2 ^ 2} (76)
// Degree Of Two (4)

// const int mod = 109
// const int proot = 33
// const int proot_1 = 76
// const int pw = 1 << 2

// Module (163 == 81 * (2 ^ 1) + 1)
// Primitive Root (2)
// Primitive Root {2 ^ 1} (162)
// Inverse Root {2 ^ 1} (162)
// Degree Of Two (2)

// const int mod = 163
// const int proot = 162
// const int proot_1 = 162
// const int pw = 1 << 1

// Module (193 == 3 * (2 ^ 6) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 6} (125)
// Inverse Root {2 ^ 6} (105)
// Degree Of Two (64)

// const int mod = 193
// const int proot = 125
// const int proot_1 = 105
// const int pw = 1 << 6

// Module (433 == 27 * (2 ^ 4) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 4} (238)
// Inverse Root {2 ^ 4} (282)
// Degree Of Two (16)

// const int mod = 433
// const int proot = 238
// const int proot_1 = 282

```

```

// const int pw = 1 << 4

// Module (487 == 243 * (2 ^ 1) + 1)
// Primitive Root (3)
// Primitive Root {2 ^ 1} (486)
// Inverse Root {2 ^ 1} (486)
// Degree Of Two (2)

// const int mod = 487
// const int proot = 486
// const int proot_1 = 486
// const int pw = 1 << 1

// Module (577 == 9 * (2 ^ 6) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 6} (557)
// Inverse Root {2 ^ 6} (375)
// Degree Of Two (64)

// const int mod = 577
// const int proot = 557
// const int proot_1 = 375
// const int pw = 1 << 6

// Module (769 == 3 * (2 ^ 8) + 1)
// Primitive Root (11)
// Primitive Root {2 ^ 8} (562)
// Inverse Root {2 ^ 8} (26)
// Degree Of Two (256)

// const int mod = 769
// const int proot = 562
// const int proot_1 = 26
// const int pw = 1 << 8

// Module (1153 == 9 * (2 ^ 7) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 7} (1096)
// Inverse Root {2 ^ 7} (445)
// Degree Of Two (128)

// const int mod = 1153
// const int proot = 1096
// const int proot_1 = 445
// const int pw = 1 << 7

// Module (1297 == 81 * (2 ^ 4) + 1)
// Primitive Root (10)
// Primitive Root {2 ^ 4} (355)
// Inverse Root {2 ^ 4} (464)
// Degree Of Two (16)

// const int mod = 1297
// const int proot = 355
// const int proot_1 = 464
// const int pw = 1 << 4

// Module (1459 == 729 * (2 ^ 1) + 1)
// Primitive Root (3)
// Primitive Root {2 ^ 1} (1458)
// Inverse Root {2 ^ 1} (1458)
// Degree Of Two (2)

// const int mod = 1459
// const int proot = 1458
// const int proot_1 = 1458
// const int pw = 1 << 1

// Module (2593 == 81 * (2 ^ 5) + 1)
// Primitive Root (7)
// Primitive Root {2 ^ 5} (1997)
// Inverse Root {2 ^ 5} (335)
// Degree Of Two (32)

```



```
// const int mod = 2593
// const int proot = 1997
// const int proot_1 = 335
// const int pw = 1 << 5
```

```
// Module (2917 == 729 * (2 ^ 2) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 2} (2863)
// Inverse Root {2 ^ 2} (54)
// Degree Of Two (4)
```

```
// const int mod = 2917
// const int proot = 2863
// const int proot_1 = 54
// const int pw = 1 << 2
```

```
// Module (3457 == 27 * (2 ^ 7) + 1)
// Primitive Root (7)
// Primitive Root {2 ^ 7} (540)
// Inverse Root {2 ^ 7} (685)
// Degree Of Two (128)
```

```
// const int mod = 3457
// const int proot = 540
// const int proot_1 = 685
// const int pw = 1 << 7
```

```
// Module (3889 == 243 * (2 ^ 4) + 1)
// Primitive Root (11)
// Primitive Root {2 ^ 4} (1925)
// Inverse Root {2 ^ 4} (1396)
// Degree Of Two (16)
```

```
// const int mod = 3889
// const int proot = 1925
// const int proot_1 = 1396
// const int pw = 1 << 4
```

```
// Module (10369 == 81 * (2 ^ 7) + 1)
// Primitive Root (13)
// Primitive Root {2 ^ 7} (5758)
// Inverse Root {2 ^ 7} (6762)
// Degree Of Two (128)
```

```
// const int mod = 10369
// const int proot = 5758
// const int proot_1 = 6762
// const int pw = 1 << 7
```

```
// Module (12289 == 3 * (2 ^ 12) + 1)
// Primitive Root (11)
// Primitive Root {2 ^ 12} (1331)
// Inverse Root {2 ^ 12} (7968)
// Degree Of Two (4096)
```

```
// const int mod = 12289
// const int proot = 1331
// const int proot_1 = 7968
// const int pw = 1 << 12
```

```
// Module (17497 == 2187 * (2 ^ 3) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 3} (14518)
// Inverse Root {2 ^ 3} (7565)
// Degree Of Two (8)
```

```
// const int mod = 17497
// const int proot = 14518
// const int proot_1 = 7565
// const int pw = 1 << 3
```

```
// Module (18433 == 9 * (2 ^ 11) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 11} (17660)
```

```
// Inverse Root {2 ^ 11} (18123)
// Degree Of Two (2048)
```

```
// const int mod = 18433
// const int proot = 17660
// const int proot_1 = 18123
// const int pw = 1 << 11
```

```
// Module (39367 == 19683 * (2 ^ 1) + 1)
// Primitive Root (3)
// Primitive Root {2 ^ 1} (39366)
// Inverse Root {2 ^ 1} (39366)
// Degree Of Two (2)
```

```
// const int mod = 39367
// const int proot = 39366
// const int proot_1 = 39366
// const int pw = 1 << 1
```

```
// Module (52489 == 6561 * (2 ^ 3) + 1)
// Primitive Root (7)
// Primitive Root {2 ^ 3} (37459)
// Inverse Root {2 ^ 3} (37783)
// Degree Of Two (8)
```

```
// const int mod = 52489
// const int proot = 37459
// const int proot_1 = 37783
// const int pw = 1 << 3
```

```
// Module (65537 == 1 * (2 ^ 16) + 1)
// Primitive Root (3)
// Primitive Root {2 ^ 16} (3)
// Inverse Root {2 ^ 16} (21846)
// Degree Of Two (65536)
```

```
// const int mod = 65537
// const int proot = 3
// const int proot_1 = 21846
// const int pw = 1 << 16
```

```
// Module (139969 == 2187 * (2 ^ 6) + 1)
// Primitive Root (13)
// Primitive Root {2 ^ 6} (8104)
// Inverse Root {2 ^ 6} (40191)
// Degree Of Two (64)
```

```
// const int mod = 139969
// const int proot = 8104
// const int proot_1 = 40191
// const int pw = 1 << 6
```

```
// Module (147457 == 9 * (2 ^ 14) + 1)
// Primitive Root (10)
// Primitive Root {2 ^ 14} (94083)
// Inverse Root {2 ^ 14} (163)
// Degree Of Two (16384)
```

```
// const int mod = 147457
// const int proot = 94083
// const int proot_1 = 163
// const int pw = 1 << 14
```

```
// Module (209953 == 6561 * (2 ^ 5) + 1)
// Primitive Root (10)
// Primitive Root {2 ^ 5} (198463)
// Inverse Root {2 ^ 5} (179931)
// Degree Of Two (32)
```

```
// const int mod = 209953
// const int proot = 198463
// const int proot_1 = 179931
// const int pw = 1 << 5
```

```
// Module (331777 == 81 * (2 ^ 12) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 12} (100795)
// Inverse Root {2 ^ 12} (281060)
// Degree Of Two (4096)
```

```
// const int mod = 331777
// const int proot = 100795
// const int proot_1 = 281060
// const int pw = 1 << 12
```

```
// Module (472393 == 59049 * (2 ^ 3) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 3} (407677)
// Inverse Root {2 ^ 3} (406705)
// Degree Of Two (8)
```

```
// const int mod = 472393
// const int proot = 407677
// const int proot_1 = 406705
// const int pw = 1 << 3
```

```
// Module (629857 == 19683 * (2 ^ 5) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 5} (255372)
// Inverse Root {2 ^ 5} (55433)
// Degree Of Two (32)
```

```
// const int mod = 629857
// const int proot = 255372
// const int proot_1 = 55433
// const int pw = 1 << 5
```

```
// Module (746497 == 729 * (2 ^ 10) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 10} (371573)
// Inverse Root {2 ^ 10} (21163)
// Degree Of Two (1024)
```

```
// const int mod = 746497
// const int proot = 371573
// const int proot_1 = 21163
// const int pw = 1 << 10
```

```
// Module (786433 == 3 * (2 ^ 18) + 1)
// Primitive Root (10)
// Primitive Root {2 ^ 18} (1000)
// Inverse Root {2 ^ 18} (710149)
// Degree Of Two (262144)
```

```
// const int mod = 786433
// const int proot = 1000
// const int proot_1 = 710149
// const int pw = 1 << 18
```

```
// Module (839809 == 6561 * (2 ^ 7) + 1)
// Primitive Root (7)
// Primitive Root {2 ^ 7} (500841)
// Inverse Root {2 ^ 7} (2262)
// Degree Of Two (128)
```

```
// const int mod = 839809
// const int proot = 500841
// const int proot_1 = 2262
// const int pw = 1 << 7
```

```
// Module (995329 == 243 * (2 ^ 12) + 1)
// Primitive Root (7)
// Primitive Root {2 ^ 12} (712513)
// Inverse Root {2 ^ 12} (946681)
// Degree Of Two (4096)
```

```
// const int mod = 995329
// const int proot = 712513
// const int proot_1 = 946681
// const int pw = 1 << 12
```

```
// Module (1179649 == 9 * (2 ^ 17) + 1)
// Primitive Root (19)
// Primitive Root {2 ^ 17} (612074)
// Inverse Root {2 ^ 17} (1093705)
// Degree Of Two (131072)
```

```
// const int mod = 1179649
// const int proot = 612074
// const int proot_1 = 1093705
// const int pw = 1 << 17
```

```
// Module (1492993 == 729 * (2 ^ 11) + 1)
// Primitive Root (7)
// Primitive Root {2 ^ 11} (143225)
// Inverse Root {2 ^ 11} (1126252)
// Degree Of Two (2048)
```

```
// const int mod = 1492993
// const int proot = 143225
// const int proot_1 = 1126252
// const int pw = 1 << 11
```

```
// Module (1769473 == 27 * (2 ^ 16) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 16} (374254)
// Inverse Root {2 ^ 16} (643391)
// Degree Of Two (65536)
```

```
// const int mod = 1769473
// const int proot = 374254
// const int proot_1 = 643391
// const int pw = 1 << 16
```

```
// Module (199065 == 24883 * (2 ^ 3) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 3} (18290)
// Inverse Root {2 ^ 3} (115385)
// Degree Of Two (8)
```

```
// const int mod = 199065
// const int proot = 18290
// const int proot_1 = 115385
// const int pw = 1 << 3
```

```
// Module (2654209 == 81 * (2 ^ 15) + 1)
// Primitive Root (11)
// Primitive Root {2 ^ 15} (1985530)
// Inverse Root {2 ^ 15} (2369076)
// Degree Of Two (32768)
```

```
// const int mod = 2654209
// const int proot = 1985530
// const int proot_1 = 2369076
// const int pw = 1 << 15
```

```
// Module (5038849 == 19683 * (2 ^ 8) + 1)
// Primitive Root (29)
// Primitive Root {2 ^ 8} (4318906)
// Inverse Root {2 ^ 8} (2727143)
// Degree Of Two (256)
```

```
// const int mod = 5038849
// const int proot = 4318906
// const int proot_1 = 2727143
// const int pw = 1 << 8
```

```
// Module (5308417 == 81 * (2 ^ 16) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 16} (3305774)
// Inverse Root {2 ^ 16} (3708247)
// Degree Of Two (65536)
```

```
// const int mod = 5308417
```

```
// const int proot = 3305774
// const int proot_1 = 3708247
// const int pw = 1 << 16

// Module (8503057 == 531441 * (2 ^ 4) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 4} (4589209)
// Inverse Root {2 ^ 4} (2906831)
// Degree Of Two (16)

// const int mod = 8503057
// const int proot = 4589209
// const int proot_1 = 2906831
// const int pw = 1 << 4

// Module (11337409 == 177147 * (2 ^ 6) + 1)
// Primitive Root (7)
// Primitive Root {2 ^ 6} (3744116)
// Inverse Root {2 ^ 6} (9616850)
// Degree Of Two (64)

// const int mod = 11337409
// const int proot = 3744116
// const int proot_1 = 9616850
// const int pw = 1 << 6

// Module (14155777 == 27 * (2 ^ 19) + 1)
// Primitive Root (7)
// Primitive Root {2 ^ 19} (2742784)
// Inverse Root {2 ^ 19} (1606624)
// Degree Of Two (524288)

// const int mod = 14155777
// const int proot = 2742784
// const int proot_1 = 1606624
// const int pw = 1 << 19

// Module (19131877 == 4782969 * (2 ^ 2) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 2} (19127503)
// Inverse Root {2 ^ 2} (4374)
// Degree Of Two (4)

// const int mod = 19131877
// const int proot = 19127503
// const int proot_1 = 4374
// const int pw = 1 << 2

// Module (28311553 == 27 * (2 ^ 20) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 20} (4493789)
// Inverse Root {2 ^ 20} (13207632)
// Degree Of Two (1048576)

// const int mod = 28311553
// const int proot = 4493789
// const int proot_1 = 13207632
// const int pw = 1 << 20

// Module (57395629 == 14348907 * (2 ^ 2) + 1)
// Primitive Root (10)
// Primitive Root {2 ^ 2} (19864209)
// Inverse Root {2 ^ 2} (37531420)
// Degree Of Two (4)

// const int mod = 57395629
// const int proot = 19864209
// const int proot_1 = 37531420
// const int pw = 1 << 2

// Module (63700993 == 243 * (2 ^ 18) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 18} (48698706)
// Inverse Root {2 ^ 18} (16386043)
```

```
// Degree Of Two (262144)

// const int mod = 63700993
// const int proot = 48698706
// const int proot_1 = 16386043
// const int pw = 1 << 18

// Module (71663617 == 2187 * (2 ^ 15) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 15} (37080182)
// Inverse Root {2 ^ 15} (7507216)
// Degree Of Two (32768)

// const int mod = 71663617
// const int proot = 37080182
// const int proot_1 = 7507216
// const int pw = 1 << 15

// Module (86093443 == 43046721 * (2 ^ 1) + 1)
// Primitive Root (2)
// Primitive Root {2 ^ 1} (86093442)
// Inverse Root {2 ^ 1} (86093442)
// Degree Of Two (2)

// const int mod = 86093443
// const int proot = 86093442
// const int proot_1 = 86093442
// const int pw = 1 << 1

// Module (102036673 == 1594323 * (2 ^ 6) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 6} (50805973)
// Inverse Root {2 ^ 6} (42074539)
// Degree Of Two (64)

// const int mod = 102036673
// const int proot = 50805973
// const int proot_1 = 42074539
// const int pw = 1 << 6

// Module (113246209 == 27 * (2 ^ 22) + 1)
// Primitive Root (7)
// Primitive Root {2 ^ 22} (58671006)
// Inverse Root {2 ^ 22} (62639419)
// Degree Of Two (4194304)

// const int mod = 113246209
// const int proot = 58671006
// const int proot_1 = 62639419
// const int pw = 1 << 22

// Module (120932353 == 59049 * (2 ^ 11) + 1)
// Primitive Root (5)
// Primitive Root {2 ^ 11} (40826043)
// Inverse Root {2 ^ 11} (93710416)
// Degree Of Two (2048)

// const int mod = 120932353
// const int proot = 40826043
// const int proot_1 = 93710416
// const int pw = 1 << 11

// Module (998244353 == 119 * (2 ^ 23) + 1)
// Primitive Root (3)
// Primitive Root {2 ^ 23} (15311432)
// Inverse Root {2 ^ 23} (469870224)
// Degree Of Two (8388608)

// const int mod = 998244353
// const int proot = 15311432
// const int proot_1 = 469870224
// const int pw = 1 << 23

// Module (1000000007 == 500000003 * (2 ^ 1) + 1)
```

```
// Primitive Root (5)
// Primitive Root {2 ^ 1} (1000000006)
// Inverse Root {2 ^ 1} (1000000006)
// Degree Of Two (2)

// const int mod = 1000000007
// const int proot = 1000000006
// const int proot_1 = 1000000006
// const int pw = 1 << 1
```

3.13 Number Decomposition

```
// Theme: Integer Numbers Decomposition With Composite
// Module

// Module
// m = (p1 ^ m1) * (p2 ^ m2) * ... * (pn ^ mn)
int m;
// Prime Divisors Of Module
vector<int> p;

struct num {
    // GCD(x, m) = 1
    int x;
    // Powers Of Primes
    vector<int> a;

    num() : x(0), a(vector<int>(p.size())) { }

    // n = (p1 ^ a1) * (p2 ^ a2) * ... * (pn ^ an) * x
    num(int n) : x(0), a(vector<int>(p.size())) {
        if (!n) return;
        for (int i = 0; i < p.size(); i++) {
            int ai = 0;
            while (n % p[i] == 0) {
                n /= p[i];
                ai++;
            }
            a[i] = ai;
        }
        x = n;
    }

    num operator*(const num &nm) {
        vector<int> new_a(p.size());
        for (int i = 0; i < p.size(); i++)
            new_a[i] = a[i] + nm.a[i];
        num res; res.a = new_a;
        res.x = x * nm.x % m;
        return res;
    }

    num operator/(const num &nm) {
        vector<int> new_a(p.size());
        for (int i = 0; i < p.size(); i++)
            new_a[i] = a[i] - nm.a[i];
        num res; res.a = new_a;
        int g = euclid(nm.x, m)[1];
        g += m; g %= m;
        res.x = x * g % m;
        return res;
    }

    int toint() {
        int res = x;
        for (int i = 0; i < p.size(); i++)
            res = res * binpow(p[i], a[i], m) % m;
        return res;
    }
};
```

3.14 Formulae

Combinations.

$$C_n^k = \frac{n!}{(n-k)!k!}$$

$$C_n^0 + C_n^1 + \dots + C_n^n = 2^n$$

$$C_{n+1}^{k+1} = C_n^{k+1} + C_n^k$$

$$C_n^k = \frac{n}{k} C_{n-1}^{k-1}$$

Striling approximation.

$$n! \approx \sqrt{2\pi n} \frac{n^n}{e^n}$$

Euler's theorem.

$$a^{\phi(m)} \equiv 1 \pmod{m}, \gcd(a, m) = 1$$

Ferma's little theorem.

$$a^{p-1} \equiv 1 \pmod{p}, \gcd(a, p) = 1, p - \text{prime.}$$

Catalan number.

$$C_0 = 0, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}$$

$$C_n = \frac{2(2n-1)}{n+1} C_{n-1}$$

$$C_n = \frac{(2n)!}{n!(n+1)!}$$

Arithmetic progression.

$$S_n = \frac{a_1 + a_n}{2} n = \frac{2a_1 + d(n-1)}{2} n$$

Geometric progression.

$$S_n = \frac{b_1(1-q^n)}{1-q} n$$

Infinitely decreasing geometric progression.

$$S_n = \frac{b_1}{1-q} n$$

Sums.

$$\sum_{i=1}^n i = \frac{n(n+1)}{2},$$

$$\sum_{i=1}^n i^2 = \frac{n(2n+1)(n+1)}{6},$$

$$\sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4},$$

$$\sum_{i=1}^n i^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30},$$

$$\sum_{i=a}^b c^i = \frac{c^{b+1} - c^a}{c-1}, c \neq 1.$$

4 Geometry

4.1 Vector

// Theme: Mathematical 3-D Vector

```
template <typename T>
struct vec {
    T x, y, z;
    vec(T x = 0, T y = 0, T z = 0) : x(x), y(y), z(z) { }
    vec<T> operator+(const vec<T> &v) const {
        return vec<T>(x + v.x, y + v.y, z + v.z);
    }
    vec<T> operator-(const vec<T> &v) const {
        return vec<T>(x - v.x, y - v.y, z - v.z);
    }
    vec<T> operator*(T k) const {
        return vec<T>(k * x, k * y, k * z);
    }
    friend vec<T> operator*(T k, const vec<T> &v) {
        return vec<T>(v.x * k, v.y * k, v.z * k);
    }
    vec<T> operator/(T k) {
        return vec<T>(x / k, y / k, z / k);
    }
    T operator*(const vec<T> &v) const {
        return x * v.x + y * v.y + z * v.z;
    }
    vec<T> operator^(const vec<T> &v) const {
```

```

        return { y * v.z - z * v.y, z * v.x - x * v.z, x * v
            .y - y * v.x };
    }
    auto operator<=>(const vec<T> &v) const = default;
    bool operator==(const vec<T> &v) const = default;
    T norm() const {
        return x * x + y * y + z * z;
    }
    double abs() const {
        return sqrt(norm());
    }
    double cos(const vec<T> &v) const {
        return ((*this) * v) / (abs() * v.abs());
    }
    friend ostream &operator<<(ostream &out, const vec<T> &v
        ) {
        return out << v.x << sp << v.y << sp << v.z;
    }
    friend istream &operator>>(istream &in, vec<T> &v) {
        return in >> v.x >> v.y >> v.z;
    }
};

```

4.2 Planimetry

// Theme: Planimetry Objects

```

// Point
template <typename T>
struct point {
    T x, y;

    point() : x(0), y(0) { }
    point(T x, T y) : x(x), y(y) { }
};

```

```

// Rectangle
template <typename T>
struct rectangle {
    point<T> ld, ru;

    rectangle(const point<T> &ld, const point<T> &ru) :
        ld(ld), ru(ru) { }
};

```

4.3 Graham

// Theme: Convex Hull

// Algorithm: Graham Algorithm
 // Complexity: $O(N \cdot \log(N))$

```

auto graham(const vector<vec<int>> &points) {
    vec<int> p0 = points[0];

    for (auto p : points)
        if (p.y < p0.y ||
            p.y == p0.y && p.x > p0.x)
            p0 = p;

    for (auto &p : points) {
        p.x -= p0.x;
        p.y -= p0.y;
    }

    sort(all(points), [] (vec<int> &p1, vec<int> &p2) {
        return (p1 ^ p2).z > 0 ||
            (p1 ^ p2).z == 0 && p1.norm() > p2.norm(); });

    vector<vec<int>> hull;
    for (auto &p : points) {
        while (hull.size() >= 2 &&
            (((p - hull.back()) ^ (hull[hull.size() - 1] - hull[
                hull.size() - 2])).z >= 0)
            hull.pop_back();
        hull.push_back(p);
    }

    for (auto &p : hull) {
        p.x += p0.x;
        p.y += p0.y;
    }
}

```

```

    }

    return hull;
}

```

4.4 Formulae

Triangles.

Radius of circumscribed circle:

$$R = \frac{abc}{4S}.$$

Radius of inscribed circle:

$$r = \frac{S}{p}.$$

Side via medians:

$$a = \frac{2}{3} \sqrt{2(m_b^2 + m_c^2) - m_a^2}.$$

Median via sides:

$$m_a = \frac{1}{2} \sqrt{2(b^2 + c^2) - a^2}.$$

Bisector via sides:

$$l_a = \frac{2\sqrt{bcp(p-a)}}{b+c}.$$

Bisector via two sides and angle:

$$l_a = \frac{2bc \cos \frac{\alpha}{2}}{b+c}.$$

Bisector via two sides and divided side:

$$l_a = \sqrt{bc - a_b a_c}.$$

Right triangles.

a, b - cathets, c - hypotenuse.

h - height to hypotenuse, divides c to c_a and

c_b .

$$\begin{cases} h^2 = c_a \cdot c_b, \\ a^2 = c_a \cdot c, \\ b^2 = c_b \cdot c. \end{cases}$$

Quadrangles.

Sides of circumscribed quadrangle:

$$a + c = b + d.$$

Square of circumscribed quadrangle:

$$S = \frac{Pr}{2} = pr.$$

Angles of inscribed quadrangle:

$$\alpha + \gamma = \beta + \delta = 180^\circ.$$

Square of inscribed quadrangle:

$$S = \sqrt{(p-a)(p-b)(p-c)(p-d)}.$$

Circles.

Intersection of circle and line:

$$\begin{cases} (x - x_0)^2 + (y - y_0)^2 = R^2 \\ y = ax + b \end{cases}$$

Task comes to solution of $\alpha x^2 + \beta x + \gamma = 0$,

where

$$\begin{cases} \alpha = (1 + a^2), \\ \beta = (2a(b - y_0) - 2x_0), \\ \gamma = (x_0^2 + (b - y_0)^2 - R^2). \end{cases}$$

Intersection of circle and circle:

$$\begin{cases} (x - x_0)^2 + (y - y_0)^2 = R_0^2 \\ (x - x_1)^2 + (y - y_1)^2 = R_1^2 \end{cases}$$

$$y = \frac{1}{2} \frac{(R_1^2 - R_0^2) + (x_0^2 - x_1^2) + (y_0^2 - y_1^2)}{y_0 - y_1} - \frac{x_0 - x_1}{y_0 - y_1} x$$

Task comes to intersection of circle and line.

5 Stringology

5.1 Z Function

```
// Theme: Z-Function

// Algorithm: Linear Algorithm
// Complexity: O(N)

auto z_func(const string &s) {
    int n = s.size();
    vector<int> z(n);

    for (int i = 1, l = 0, r = 0; i < n; i++) {
        if (i <= r) z[i] = min(r - i + 1, z[i - l]);

        while (i + z[i] < n && s[z[i]] == s[i + z[i]]) z[i]++;

        if (i + z[i] - 1 > r) {
            l = i;
            r = i + z[i] - 1;
        }
    }

    return z;
}
```

5.2 Manacher

```
// Theme: Palindromes

// Algorithm: Manacher Algorithm
// Complexity: O(N)

int manacher(const string &s) {
    int n = s.size();
    vector<int> d1(n), d2(n);

    for (int i = 0, l = 0, r = -1; i < n; i++) {
        int k = i > r ? 1 : min(d1[l + r - i], r - i + 1);
        while (i + k < n && i - k >= 0 && s[i + k] == s[i - k]) k++;
        d1[i] = k;
        if (i + k - 1 > r) {
            l = i - k + 1;
            r = i + k - 1;
        }
    }

    for (int i = 0, l = 0, r = -1; i < n; i++) {
        int k = i > r ? 0 : min(d2[l + r - i + 1], r - i + 1);
        while (i + k < n && i - k - 1 >= 0 && s[i + k] == s[i - k - 1]) k++;
        d2[i] = k;
        if (i + k - 1 > r) {
            l = i - k;
            r = i + k - 1;
        }
    }

    int res = 0;
    for (int i = 0; i < n; i++) {
        res += d1[i] + d2[i];
    }

    return res;
}
```

5.3 Trie

```
// Theme: Trie

// Algorithm: Aho-Corasick
// Complexity: O(N)

struct trie {
    // Vertex
    struct vertex {
```

```
        vector<int> next;
        bool leaf;
    };

    // Alphabet size
    static const int N = 26;
    // Maximum Vertex Number
    static const int MX = 2e5 + 1;

    // Vertices Vector
    vector<vertex> t;
    int sz;

    trie(): sz(1) {
        t.resize(MX);
        t[0].next.assign(N, -1);
    }

    void add_str(const string &s) {
        int v = 0;
        for (int i = 0; i < s.length(); i++) {
            char c = s[i] - 'a';
            if (t[v].next[c] == -1) {
                t[sz].next.assign(N, -1);
                t[v].next[c] = sz++;
            }
            v = t[v].next[c];
        }
        t[v].leaf = true;
    }
};
```

5.4 Prefix Function

```
// Theme: Prefix function

// Algorithm: Knuth-Morris-Pratt Algorithm
// Complexity: O(N)

auto pref_func(const string &s) {
    int n = s.size();
    vector<int> pi(n);

    for (int i = 1; i < n; i++) {
        int j = pi[i - 1];

        while (j > 0 && s[i] != s[j]) j = pi[j - 1];

        if (s[i] == s[j]) j++;

        pi[i] = j;
    }

    return pi;
}
```

5.5 Suffix Array

```
// Theme: Suffix array

// Algorithm: Binary Algorithm With Count Sort
// Complexity: O(N*log(N))

void count_sort(vector<int> &p, vector<int> &c) {
    int n = p.size();
    vector<int> cnt(n), p_new(n), pos(n);

    for (auto &x : c) cnt[x]++;

    pos[0] = 0;
    for (int i = 1; i < n; i++)
        pos[i] = pos[i - 1] + cnt[i - 1];

    for (auto &x : p) {
        int i = c[x];
        p_new[pos[i]] = x;
        pos[i]++;
    }

    p = p_new;
}
```

```

auto suffix_array(const string &str) {
    string s = str + '$';
    int n = s.size();

    vector<int> p(n), c(n);
    vector<pair<char, int>> a(n);

    for (int i = 0; i < n; i++) a[i] = { str[i], i };

    sort(a.begin(), a.end());

    for (int i = 0; i < n; i++) p[i] = a[i].second;

    c[p[0]] = 0;
    for (int i = 1; i < n; i++)
        c[p[i]] = c[p[i - 1]] + (a[i].first != a[i - 1].first);

    int k = 0;
    while ((1 << k) < n) {
        for (int i = 0; i < n; i++)
            p[i] = (p[i] - (1 << k) + n) % n;

        count_sort(p, c);

        vector<int> c_new(n);

        c_new[p[0]] = 0;
        for (int i = 1; i < n; i++) {
            pair<int, int> prev = { c[p[i - 1]], c[(p[i - 1] + (1 << k)) % n] };
            pair<int, int> now = { c[p[i]], c[(p[i] + (1 << k)) % n] };
            c_new[p[i]] = c_new[p[i - 1]] + (now != prev);
        }

        c = c_new;
        k++;
    }

    return p;
}

```

6 Dynamic Programming

6.1 Increasing Subsequence

```

// Theme: Longest Increasing Subsequence

// Algorithm: Binary Search Algorithm
// Complexity: O(N*log(N))

auto inc_subseq(const vector<int> &a) {
    int n = a.size();
    vector<int> dp(n + 1, INF), pos(n + 1), prev(n), subseq;

    int len = 0;
    dp[0] = -INF;
    pos[0] = -1;

    for (int i = 0; i < n; i++) {
        int j = distance(dp.begin(), upper_bound(all(dp), a[i]));
        if (dp[j - 1] < a[i] && a[i] < dp[j]) {
            dp[j] = a[i];
            pos[j] = i;
            prev[i] = pos[j - 1];
            len = max(len, j);
        }
    }

    int p = pos[len];
    while (p != -1) {
        subseq.push_back(a[p]);
        p = prev[p];
    }
    reverse(subseq.begin(), subseq.end());

    return subseq;
}

```

7 Graphs

7.1 Graph Implementation

```

// Theme: Graph Implementation

////////////////////////////////////
// Adjacency List (Unoriented)
////////////////////////////////////

int sz;

vector<vector<int>> graph;

graph.assign(n, {});

for (int i = 0; i < n; i++) {
    int u, v; cin >> u >> v; --u --v;
    graph[u].push_back(v);
    graph[v].push_back(u);
}

////////////////////////////////////
// Adjacency List (Oriented)
////////////////////////////////////

int sz;

vector<vector<int>> graph;
vector<vector<int>> rgraph;

graph.assign(n, {});
rgraph.assign(n, {});

for (int i = 0; i < n; i++) {
    int u, v; cin >> u >> v; --u --v;
    graph[u].push_back(v);
    rgraph[v].push_back(u);
}

////////////////////////////////////
// Edges List (Unoriented)
////////////////////////////////////

int sz;

vector<pair<int, int>> edges;
vector<vector<int>> graph;

graph.assign(n, {});

for (int i = 0; i < n; i++) {
    int u, v; cin >> u >> v; --u; --v;
    edges.push_back({ u, v });
    graph[u].push_back(i);
    graph[v].push_back(i);
}

////////////////////////////////////
// Edges List + Structure (Unoriented)
////////////////////////////////////

struct edge {
    int u, v, w;
    edge(int u, int v, int w = 0)
        : u(u), v(v), w(w) {}
};

int sz;

vector<edge> edges;
vector<vector<int>> graph;

graph.assign(n, {});

for (int i = 0; i < n; i++) {
    int u, v, w; cin >> u >> v >> w; --u; --v;
    edges.push_back({ u, v, w });
    graph[u].push_back(i);
    graph[v].push_back(i);
}

////////////////////////////////////
// Edges List + Structure + Net Flows (Oriented)
////////////////////////////////////

```

```

struct edge {
    int to, cap, flow, weight;
    edge(int to, int cap, int flow = 0, int weight = 0)
        : to(to), cap(cap), flow(flow), weight(weight) {}
    int res() {
        return cap - flow;
    }
};

int sz;

vector<edge> edges;
vector<vector<int>> fgraph;

fgraph.assign(n, {});

void add_edge(int u, int v, int limit, int flow = 0, int
    weight = 0) {
    fgraph[u].push_back(edges.size());
    edges.push_back({ v, limit, flow, weight });
    fgraph[v].push_back(edges.size());
    edges.push_back({ u, 0, 0, -weight });
}

//////////////////////
// Adjacency Matrix
//////////////////////

vector<vector<int>> graph;

for (int i = 0; i < n; i++)
    for (int j = 0; j < n; j++)
        cin >> graph[i][j];

```

7.2 Graph Traversing

```

// Theme: Graph Traversing

vector<vector<int>> graph;
vector<int> used;

// Algorithm: Depth-First Search (Adjacency List)
// Complexity: O(N + M)

void dfs(int cur, int p = -1) {
    used[cur] = 1;

    for (auto &to : graph[cur]) {
        if (to == p || used[to]) continue;
        dfs(to, cur);
    }
}

// Algorithm: Breadth-First Search (Adjacency List)
// Complexity: O(N + M)

void bfs(int u) {
    queue<int> q; q.push(u);

    while (q.size()) {
        int cur = q.front(); q.pop();

        for (auto &to : graph[cur]) {
            if (used[to]) continue;
            q.push(to);
        }
    }
}

```

7.3 Topological Sort

```

// Theme: Topological Sort

vector<vector<int>> graph;
vector<int> used;

// Algorithm: Topological Sort
// Complexity: O(N + M)

vector<int> topsort;

void dfs_topsort(int cur, int p = -1) {

```

```

    used[cur] = 1;

    for (auto &to : graph[cur]) {
        if (to == p || used[to]) continue;
        dfs(to, cur);
    }

    topsort.push_back(cur);
}

for (int u = 0; u < n; u++)
    if (!used[u])
        dfs_topsort(u);

reverse(all(topsort));

```

7.4 Connected Components

```

// Theme: Connectivity Components

vector<vector<int>> graph;
vector<int> used;

// Algorithm: Connected Components
// Complexity: O(N + M)

vector<vector<int>> cc;

void dfs_cc(int cur, int p = -1) {
    used[cur] = 1;
    cc.back().push_back(cur);

    for (auto &to : graph[cur]) {
        if (to == p || used[to]) continue;
        dfs_cc(to, cur);
    }
}

for (int u = 0; u < n; u++)
    if (!used[u])
        dfs_cc(u);

// Algorithm: Strongly Connected Components
// Complexity: O(N + M)

vector<vector<int>> rgraph;

vector<vector<int>> topsort;

vector<vector<int>> scc;

void dfs_scc(int cur, int p = -1) {
    used[cur] = 1;
    scc.back().push_back(cur);

    for (auto &to : rgraph[cur]) {
        if (to == p || used[to]) continue;
        dfs_scc(to, cur);
    }
}

for (auto &u: topsort)
    if (!used[u])
        dfs_scc(u);

```

7.5 2 Sat

```

// Theme: 2-SAT

// Algorithm: Adding Edges To 2-SAT

vector<vector<int>> ts_graph;
vector<vector<int>> ts_rgraph;
vector<int> used;
vector<int> top_sort;

// Vertex By Var Number
int to_vert(int x) {
    if (x < 0) {
        return ((abs(x) - 1) << 1) ^ 1;
    }
    else {

```



```

        return (x - 1) << 1;
    }
}

// Adding Implication
void add_impl(int a, int b) {
    ts_graph[a].insert(b);
    ts_rgraph[b].insert(a);
}

// Adding Disjunction
void add_or(int a, int b) {
    add_impl(a ^ 1, b);
    add_impl(b ^ 1, a);
}

//topsort
void dfs(int v){
    used[v] = 1;
    for(auto to:ts_graph[v]){
        if(!used[to])dfs(to);
    }
    top_sort.push_back(v);
}

//scc
vector<vector<long long int>> scc;
void dfs_scc(long long int cur, long long int p = -1) {
    used[cur] = 1;
    scc.back().push_back(cur);
    for (auto to : rgr[cur]) {
        if (to == p || used[to]) continue;
        dfs_scc(to, cur);
    }
}

int main(){
    ...
    used.resize(n,0);
    for(i=0;i<n;i++){
        if(!used[i])dfs(i);
    }
    reverse(top_sort.begin(), top_sort.end());
    for(auto it:top_sort){
        if (!used[u]) {
            scc.push_back({});
            dfs_scc(u);
        }
    }
    vector<long long int>v_scc;
    v_scc.assign(2 * n, -1);

    for (int i = 0; i < scc.size(); i++)
        for (auto& u : scc[i])
            v_scc[u] = i;

    vector<long long int> values(2 * n, -1);

    for (int i = 0; i < 2 * n; i += 2)
        if (v_scc[i] == v_scc[i ^ 1]) {
            cout << "NO\n";
            return 0;
        }
        else {
            if (v_scc[i] < v_scc[i ^ 1]) {
                values[i] = 0;
                values[i ^ 1] = 1;
            }
            else {
                values[i] = 1;
                values[i ^ 1] = 0;
            }
        }
}

```

7.6 Bridges

// Theme: Bridges And ECC

```

vector<pair<int, int>> edges;
vector<vector<int>> graph;
vector<int> used;

vector<int> height;
vector<int> up;

```

// Algorithm: Bridges
// Complexity: $O(N + M)$

```

vector<int> bridges;

void dfs_bridges(int cur, int p = -1) {
    used[cur] = 1;
    up[cur] = height[cur];
    for (auto &ind : g[cur]) {
        int to = cur ^ edges[ind].ff ^ edges[ind].ss;
        if (to == p) continue;
        if (used[to]) {
            up[cur] = min(up[cur], height[to]);
        }
        else {
            height[to] = height[cur] + 1;
            dfs_bridges(to, cur);
            up[cur] = min(up[cur], up[to]);
            if (up[to] > height[cur])
                bridges.push_back(ind);
        }
    }
}

```

// Algorithm: ECC
// Complexity: $O(N + M)$

```

vector<int> st;

vector<int> add_comp(vector<int> &st, int sz) {
    vector<int> comp;

    while (st.size() > sz) {
        comp.push_back(st.back());
        st.pop_back();
    }

    return comp;
}

vector<vector<int>> ecc;

void dfs_bridges_comps(int cur, int p = -1) {
    used[cur] = 1;
    up[cur] = height[cur];

    for (auto &ind : g[cur]) {
        int to = cur ^ edges[ind].ff ^ edges[ind].ss;
        if (to == p) continue;
        if (used[to]) {
            up[cur] = min(up[cur], height[to]);
        }
        else {
            int sz = st.size();
            st.push_back(to);
            height[to] = height[cur] + 1;
            dfs_bridges_comps(to, cur);
            up[cur] = min(up[cur], up[to]);
            if (up[to] > height[cur])
                ecc.push_back(add_comp(st, sz));
        }
    }
}

```

7.7 Articulation Points

// Theme: Articulation Points And VCC

```

vector<pair<int, int>> edges;
vector<vector<int>> graph;
vector<int> used;

```

```

vector<int> height;
vector<int> up;

```

// Algorithm: Articulation Points
// Complexity: $O(N + M)$

```

set<int> art_points;

void dfs_artics(int cur, int p = -1) {
    used[cur] = 1;
    up[cur] = height[cur];

    int desc_count = 0;

```

```

for (auto &ind : g[cur]) {
    int to = cur ^ edges[ind].ff ^ edges[ind].ss;
    if (to == p) continue;
    if (used[to]) {
        up[cur] = min(up[cur], height[to]);
    }
    else {
        desc_count++;
        height[to] = height[cur] + 1;
        dfs_artics(to, cur);
        up[cur] = min(up[cur], up[to]);
        if (up[to] >= height[cur] && p != -1)
            art_points.insert(cur);
    }
}

if (p == -1 && desc_count > 1) {
    art_points.insert(cur);
}
}

// Algorithm: VCC
// Complexity: O(N + M)

vector<vector<int>> vcc;

void dfs_artics_comps(int cur, int p = -1) {
    used[cur] = 1;
    up[cur] = height[cur];

    for (auto &ind : g[cur]) {
        int to = cur ^ edges[ind].ff ^ edges[ind].ss;
        if (to == p) continue;
        if (used[to]) {
            up[cur] = min(up[cur], height[to]);
            if (height[to] < height[cur]) st.push_back(ind);
        }
        else {
            int sz = st.size();
            st.push_back(ind);
            height[to] = height[cur] + 1;
            dfs_artics_comps(to, cur);
            up[cur] = min(up[cur], up[to]);
            if (up[to] >= height[cur])
                vcc.push_back(add_comp(st, sz));
        }
    }
}

```

7.8 Kuhn

```

// Maximum Matching

// Algorithm: Kuhn Algorithm
// Complexity: O(|Left Part|^3)

vector<vector<int>> bigraph;
vector<int> used;

vector<int> mt;

bool kuhn(int u) {
    if (used[u]) return false;

    used[u] = 1;

    for (auto &v : bigraph[u]) {
        if (mt[v] == -1 || kuhn(mt[v])) {
            mt[v] = u;
            return true;
        }
    }

    return false;
}

```

7.9 Kruskal

```

// Theme: Minimum Spanning Tree

int sz;

```

```

vector<edge> edges;
vector<vector<int>> graph;

// Algorithm: Kruskal Algorithm
// Complexity: O(M)

vector<edge> mst;

void kruskal() {
    dsu d(sz);

    auto tedges = edges;
    sort(all(tedges), [] (edge &e1, edge &e2) { return e1.w
        < e2.w; });

    for (auto &e : tedges) {
        if (d.get(e.u) != d.get(e.v)) {
            mst.push_back(e);
            d.unite(e.u, e.v);
        }
    }
}

```

7.10 Lowest Common Ancestor

```

// Theme: Lowest Common Ancestor

// Algorithm: Binary Lifting
// Complexity: O(N * log(N) * log(N))

vector<vector<int>> graph;
vector<vector<int>> up;
vector<int> tin, tout;

int timer;

// l == log(N) (~20)
int l;

void dfs(int cur, int p = -1) {
    tin[cur] = timer++;

    up[cur][0] = p;
    for (int i = 1; i <= l; i++)
        up[cur][i] = up[up[cur][i - 1]][i - 1];

    for (auto &to : graph[cur]) {
        if (to == p) continue;
        dfs(to, cur);
    }

    tout[cur] = timer++;
}

void preprocess(int u) {
    l = (int) ceil(log2(sz));
    up.assign(sz, vector<int>(l + 1));
    timer = 0;
    dfs(u, u);
}

bool is_anc(int u, int v) {
    return tin[u] <= tin[v] && tout[u] >= tout[v];
}

int lca(int u, int v) {
    if (is_anc(u, v))
        return v;
    if (is_anc(v, u))
        return v;
    for (int i = l; i >= 0; --i) {
        if (!is_anc(up[v][i], u))
            v = up[v][i];
    }
    return up[v][0];
}

```

7.11 Shortest Paths

```

// Theme: Shortest Paths

```

```

int sz;

vector<edge> edges;
vector<vector<int>> graph;

// Algorithm: Dijkstra Algorithm
// Complexity:  $O(M \log(N))$ 

vector<int> d;
vector<int> p;

void dijkstra(int u) {
    d.assign(sz, INF); d[u] = 0;
    p.assign(sz, -1);

    priority_queue<pair<int, int>> q;
    q.push({ 0, u });

    while (q.size()) {
        int dist = -q.top().ff, v = q.top().ss; q.pop();

        if (dist > d[v]) continue;

        for (auto &ind : graph[v]) {
            int to = v ^ edges[ind].u ^ edges[ind].v,
                w = edges[ind].w;
            if (d[v] + w < d[to]) {
                d[to] = d[v] + w;
                p[to] = v;
                q.push({ -d[to], -to });
            }
        }
    }
}

// Algorithm: Shortest Path Faster Algorithm
// Complexity: ...

vector<int> d;

void bfs_spfa(int u) {
    d.assign(sz, INF); d[u] = 0;

    queue<int> q; q.push(u);
    vector<int> in_q(sz, 0); in_q[u] = 1;

    while (q.size()) {
        auto [v, f] = q.front(); q.pop();

        in_q[v] = 0;

        for (auto &ind : graph[v]) {
            int to = v ^ edges[ind].u ^ edges[ind].v,
                w = edges[ind].w;
            if (d[v] + w < d[to]) {
                d[to] = d[v] + w;
                if (!in_q[to]) {
                    in_q[to] = 1;
                    q.push(to);
                }
            }
        }
    }
}

// Algorithm: Belman-Ford Algorithm
// Complexity:  $(N * M)$ 

vector<int> d;

void bfa(int u) {
    d.assign(sz, INF); d[u] = 0;

    for (;;) {
        bool any = false;

        for (auto &e : edges) {
            if (d[e.u] != INF && d[e.u] + e.w < d[e.v]) {
                d[e.v] = d[e.u] + e.w;
                any = true;
            }
            if (d[e.v] != INF && d[e.v] + e.w < d[e.u]) {
                d[e.u] = d[e.v] + e.w;
                any = true;
            }
        }

        if (!any) break;
    }
}

```

```

    }
}

// Algorithm: Floyd-Warshall Algorithm
// Complexity:  $O(N^3)$ 

vector<vector<int>> d;

void fwa() {
    d.assign(sz, vector<int>(sz, INF));

    for (int i = 0; i < sz; i++)
        for (int j = 0; j < sz; j++)
            for (int k = 0; k < sz; k++)
                if (d[i][k] != INF && d[k][j] != INF)
                    d[i][j] = min(d[i][j], d[i][k] + d[k][j]);
}

```

7.12 Maximum Flow

```

// Theme: Maximum Flow

int s, t, sz;

vector<edge> edges;
vector<vector<int>> fgraph;

vector<int> used;

// Algorithm: Ford-Fulkerson Algorithm
// Complexity:  $O(MF)$ 

int dfs_fordfulk(int u, int bound, int flow = INF) {
    if (used[u]) return 0;
    if (u == t) return flow;

    used[u] = 1;

    for (auto &ind : fgraph[u]) {
        auto &e = edges[ind],
            &_e = edges[ind ^ 1];
        int to = e.to, res = e.res();

        if (res < bound) continue;

        int pushed = dfs_fordfulk(to, bound, min(res, flow));

        if (pushed) {
            e.flow += pushed;
            _e.flow -= pushed;
            return pushed;
        }
    }

    return 0;
}

// Algorithm: Edmonds-Karp Algorithm
// Complexity:  $O(N(M^2))$ 

vector<int> p;
vector<int> pe;

void augment(int pushed) {
    int cur = t;
    while (cur != s) {
        auto &e = edges[pe[cur]],
            &_e = edges[pe[cur] ^ 1];
        e.flow += pushed;
        _e.flow -= pushed;
        cur = p[cur];
    }
}

int bfs_edmskarp(int u, int bound) {
    p.assign(sz, -1);
    pe.assign(sz, -1);

    int pushed = 0;

    queue<pair<int, int>> q;
    q.push({ u, INF });

    used[u] = 1;
}

```

```

while (q.size()) {
    auto [v, f] = q.front(); q.pop();

    for (auto &ind : fgraph[v]) {
        auto &e = edges[ind];
        int to = e.to, res = e.res();

        if (used[to] || res < bound) continue;

        p[to] = v;
        pe[to] = ind;
        used[to] = 1;

        if (to == t) {
            pushed = min(f, res);
            break;
        }

        q.push({ to, min(f, res) });
    }
}

if (pushed)
    augment(pushed);

return pushed;
}

// Algorithm: Dinic Algorithm
// Complexity:  $O((N^2)M)$ 

vector<int> d;

bool bfs_dinic(int u, int bound) {
    d.assign(sz, INF); d[u] = 0;

    queue<int> q; q.push(u);

    while (q.size()) {
        int v = q.front(); q.pop();

        for (auto &ind : fgraph[v]) {
            auto &e = edges[ind];
            int to = e.to, res = e.res();

            if (d[v] + 1 >= d[to] || res < bound) continue;

            d[to] = d[v] + 1;
            q.push(to);
        }
    }

    return d[t] != INF;
}

vector<int> lst;

int dfs_dinic(int u, int mx = INF) {
    if (u == t) return mx;

    int smf = 0;

    for (int i = lst[u]; i < fgraph[u].size(); i++) {
        int ind = fgraph[u][i];

        auto &e = edges[ind],
            &_e = edges[ind ^ 1];
        int to = e.to, res = e.res();

        if (d[to] == d[u] + 1 && res) {
            int pushed = dfs_dinic(to, min(res, mx - smf));

            if (pushed) {
                smf += pushed;
                e.flow += pushed;
                _e.flow -= pushed;
            }
        }

        lst[u]++;

        if (smf == mx)
            return smf;
    }

    return smf;
}

```

```

int dinic(int u) {
    int pushed = 0;

    for (int bound = 1ll << 30; bound; bound >>= 1) {
        while (true) {
            bool bfs_ok = bfs_dinic(u, bound);
            if (!bfs_ok) break;

            lst.assign(sz, 0);

            while (true) {
                int dfs_pushed = dfs_dinic(u);
                if (!dfs_pushed) break;

                pushed += dfs_pushed;
            }
        }
    }

    return pushed;
}

// Algorithm: Maximum Flow Of Minimum Cost (SPFA)
// Complexity: ...

vector<int> d;
vector<int> p;
vector<int> pe;

void augment(int pushed) {
    int cur = t;
    while (cur != s) {
        auto &e = edges[pe[cur]],
            &_e = edges[pe[cur] ^ 1];
        e.flow += pushed;
        _e.flow -= pushed;
        cur = p[cur];
    }
}

int bfs_spfa(int u, int flow = INF) {
    d.assign(sz, INF); d[u] = 0;
    p.assign(sz, -1);
    pe.assign(sz, -1);

    queue<pair<int, int>> q; q.push({ u, flow });
    vector<int> in_q(sz, 0); in_q[u] = 1;

    int pushed = 0;

    while (q.size()) {
        auto [v, f] = q.front(); q.pop();

        in_q[v] = 0;

        if (v == t) {
            pushed = f;
            break;
        }

        for (auto &ind : fgraph[v]) {
            auto &e = edges[ind];
            int to = e.to, res = e.res(),
                w = e.weight;

            if (d[v] + w >= d[to] || !res) continue;

            d[to] = d[v] + w;
            p[to] = v;
            pe[to] = ind;

            if (!in_q[to]) {
                in_q[to] = 1;
                q.push({ to, min(f, res) });
            }
        }
    }

    if (pushed)
        augment(pushed);

    return pushed;
}

```

7.13 Eulerian Path

```
// Theme: Eulerian Path

int sz;

vector<vector<int>> graph;

// Algorithm: Eulerian Path
// Complexity: O(M)

vector<int> eul;

// 0 - path not exist
// 1 - cycle exists
// 2 - path exists
int euler_path() {
    vector<int> deg(sz);

    for (int i = 0; i < sz; i++)
        for (int j = 0; j < sz; j++)
            deg[i] += g[i][j];

    int v1 = -1, v2 = -1;
    for (int i = 0; i < sz; i++)
        if (deg[i] & 1)
            if (v1 == -1) v1 = i;
            else if (v2 == -1) v2 = i;
            else return 0;

    if (v1 != -1) {
        if (v2 == -1)
            return 0;
        graph[v1][v2]++;
        graph[v2][v1]++;
    }

    stack<int> st;

    for (int i = 0; i < sz; i++) {
        if (deg[i]) {
            st.push(i);
            break;
        }
    }

    while (st.size()) {
        int u = st.top();

        int ind = -1;

        for (int i = 0; i < sz; i++)
            if (graph[u][i]) {
                ind = i;
                break;
            }

        if (ind == -1) {
            eul.push_back(u);
            st.pop();
        }
        else {
            graph[u][ind]--;
            graph[ind][u]--;
            st.push(ind);
        }
    }

    int res = 2;
    if (v1 != -1) {
        res = 1;

        for (int i = 0; i < eul.size() - 1; i++)
            if (eul[i] == v1 && eul[i + 1] == v2 ||
                eul[i] == v2 && eul[i + 1] == v1) {
                vector<int> teul;
                for (int j = i + 1; j < eul.size(); j++)
                    teul.push_back(eul[j]);
                for (int j = 0; j <= i; j++)
                    teul.push_back(eul[j]);
                eul = teul;
                break;
            }
    }

    for (int i = 0; i < sz; i++)
        for (int j = 0; j < sz; j++)
            if (graph[i][j])
```

```
        return 0;

    return res;
}
```

8 Miscellaneous

8.1 Ternary Search

```
// Theme: Ternary Search

// Algorithm: Continuous Search With Golden Ratio
// Complexity: O(log(N))

// Golden Ratio
// Phi = 1.618...
double phi = (1 + sqrt(5)) / 2;

double cont_tern_srch(double l, double r) {
    double m1 = l + (r - l) / (1 + phi),
           m2 = r - (r - l) / (1 + phi);

    double f1 = f(m1), f2 = f(m2);

    int count = 200;
    while (count--) {
        if (f1 < f2) {
            r = m2;
            m2 = m1;
            f2 = f1;
            m1 = l + (r - l) / (1 + phi);
            f1 = f(m1);
        }
        else {
            l = m1;
            m1 = m2;
            f1 = f2;
            m2 = r - (r - l) / (1 + phi);
            f2 = f(m2);
        }
    }

    return f((l + r) / 2);
}

// Algorithm: Discrete Search
// Complexity: O(log(N))

double discr_tern_srch(int l, int r) {
    while (r - l > 2) {
        int m1 = l + (r - l) / 3,
            m2 = r - (r - l) / 3;
        if (f(m1) < f(m2))
            r = m2;
        else
            l = m1;
    }

    return min(f(l), min(f(l + 1), f(r)));
}
```