Packet to Release

A practical method for preparing and verifying campaign distribution

Version 1.0.0 | November 10, 2026 | Brendon Coleman

Method definition and scope

Packet to Release turns an existing content packet into a bounded release with a record for every intended destination. It covers source recovery, asset selection, platform preparation, authorization, scheduling, verification, and later reconciliation. A packet may come from Source to Series, Trend Chaser, another production workflow, or a collection of supplied files.

The method keeps the original material, the selected revision, the owner's instruction, and the resulting provider record connected. An operator can then explain what was sent, where it was sent, what was verified, and what remains unresolved.

The governing rule

Preserve the relationship between source, revision, authority, action, and evidence. Advance each status only when the corresponding event has been observed. A prepared asset, an authorized release, a verified schedule, a published post, and a measured result are separate facts.

Place alongside the existing methods

Method	Primary job	Handoff
Source to Series	Develop traceable written, visual, and video derivatives.	Content packet with source lineage.
Trend Chaser	Prepare and verify a merchandise release.	Product and creative release packet.
Packet to Release	Distribute a packet and reconcile the resulting records.	Calendar, receipts, manual handoffs, and later results.

These methods can connect without becoming mandatory dependencies. A release can use any suitable packet. Existing source IDs, campaign IDs, and approval records should travel with it. [F1, F2]

First demonstrated execution

On November 10, 2026, five unique Zeely videos were prepared for four confirmed destinations through ChatGPT agents and Metricool. Twenty schedules were read back and matched, covering November 11-24. Five personal Facebook captions were supplied for manual use. Publication and performance had not been observed at the saved checkpoint. [R1, R3]

This edition documents that execution and the continuation procedure. It supplies reusable records and a proposed Signal Agent handoff. Installing an integration, publishing this method, and starting background monitoring are separate actions.

1 Preserve and reconcile the packet

Capture the request and recover context

Create a release record before changing provider state. Record the requested outcome, source packet, destination scope, time window, timezone, exclusions, and choices delegated to the operator. Retain the owner's actual instruction or a durable reference to it. Look for an existing run before starting a second one.

Search the supplied packet and relevant prior records for the source material, scripts, captions, and decisions. Record where each recovered item came from and which version it belongs to. Similar filenames and remembered themes are leads; they do not establish that two files are the same revision.

Identify the selected assets

Inventory every supplied file with an asset ID, original reference, digest when available, dimensions, duration, and intended role. Use byte comparisons or hashes to identify exact duplicates. A visually similar revision may still contain a meaningful difference and needs inspection.

Select one release revision for each intended asset. Keep a duplicate linked to its retained counterpart so the reason for exclusion is recoverable. Count unique assets before multiplying them across destinations. This run received six uploads and retained five unique videos. [R1]

Preserve revisions and inspect the audience experience

Keep originals unchanged. Correct spelling, subtitles, framing, audio, or other defects in separate outputs, with a change note and source-to-output link. Inspect the changed region and relevant boundaries. Retain the checks that support any claim that duration, audio, or other properties were preserved.

Review the video, caption, title, and destination link together. Confirm that they describe the same item and preserve the source meaning. A successful media probe establishes technical properties; it does not establish that spoken words, claims, or visual implications are accurate.

Record caption provenance explicitly

Provenance	What the record means
Recovered original	The actual prior caption was located and linked to its source.
Reconstructed from sources	New wording was written from recovered scripts, media, or context.
New	A new caption was composed for the current release.
Platform adaptation	A derivative changes format or length while retaining its parent revision.

Record provenance per caption. In the worked example, two showcase captions were recovered and three speaking-video captions were reconstructed. Platform versions are further derivatives. Calling the entire set original would erase that distinction. [R1, R3]

Stage output: a preserved source packet, selected asset revisions, a caption register, and a short list of unresolved issues. Continue independent preparation where an issue affects only part of the batch.

2 Prepare the destinations and calendar

Resolve destination identity

Read the current connected accounts through the available authorized interface. Record each platform, account identity, provider reference, publishing route, and observation time. A display name alone can be ambiguous. Confirm the intended destination in the context of the owner's request.

Treat connection and authorization as different facts. An account appearing in a connector is not by itself an instruction to use it. When the owner has already authorized all of a confirmed set, retain that scope and continue without requesting it again.

Represent manual routes explicitly. In the worked example, the four automated destinations were a Facebook Page, Instagram, TikTok, and YouTube. Personal Facebook remained manual; Metricool's connection documentation excludes personal and creator Facebook profiles. [R1, M1]

Create one logical item per intended destination

Map each selected asset revision and caption revision to its destination, format, title if needed, audience/privacy settings, disclosures, and proposed time. Give that item a stable internal ID. The map determines the batch count; a full asset-by-account cross-product is appropriate only when the owner intends it.

Check the current connector contract and platform requirements. Preserve meaningful false values as carefully as true values. Record any text normalization, such as a platform's line-break behavior, so a deliberate adaptation is distinguishable from unexpected corruption. [M2-M4]

Build a calendar with a stated basis

Use available timing information, existing queue entries, content sequence, and the requested cadence. Record when timing information was obtained and whether it applies to the whole window. If the data is unavailable, state the editorial basis for the proposed times.

Write an explicit date, local time, timezone, and UTC offset for every item. An IANA timezone allows daylight-saving rules to be applied to the intended date. Check the existing calendar for duplicates and conflicts before creating new entries.

Separate related assets enough to avoid unnecessary repetition. In this run, first-week Metricool timing scores informed placement and weekday patterns were reused in week two. That describes the scheduling decision; it does not demonstrate improved reach. [R1]

Make the manual handoff usable

- Supply the exact selected media, complete caption, intended destination, and suggested date.
- Name any step that must be performed inside the platform, rather than leaving a generic reminder.
- Keep manual completion unconfirmed until the owner or platform supplies evidence.

Stage output: a versioned asset-to-destination map and a concrete calendar, with automated and manual items counted separately.

3 Apply authority and divide the work

Use the authorization already present

Bind the release to the owner's actual instruction. Record the permitted assets or concept, destinations, release actions, window, and delegated choices. A blank approval template starts as not granted. Preparing a release does not itself authorize posting it.

An explicit scheduling instruction can authorize the normal work required to execute that scope. Do not turn the method into repeated confirmation prompts. If a necessary decision is missing, complete the preparation that can be done and present the concrete affected choice.

Distinguish scope authorization from individual payload review. In this example the owner authorized twenty posts across the confirmed accounts and delegated timing across roughly two weeks. That does not establish a separate signature or individual inspection of every final caption and file digest. Record the limitation accurately. [R1]

Evaluate changes against the recorded scope

Change	Response
Routine formatting or timing within delegated choices	Proceed and record the change.
Correction that preserves the selected meaning and falls within the authorized work	Verify the correction and retain its revision link.
New account, materially changed message, new audience, paid spend, or substantially expanded release	Prepare the change and obtain the missing scope decision.
A defect affecting only some items	Hold or repair the affected items; preserve unrelated verified work.

Give parallel agents bounded tasks

Independent preparation can run in parallel: media inspection, context recovery, copy preparation, and evidence review. Give each task defined inputs, an output location, and the decisions it may make. Preserve the owner's instructions across every handoff.

One coordinator should own the release map and external writes for a run. In the worked example, submission proceeded one destination at a time after the prepared material converged. This made each provider response attributable to one intended item. [R3]

A reviewer may independently compare expected and observed records. An agent's confidence is not evidence, and a delegated review does not create human authorization. Record the result and unresolved questions at the same granularity as the item being reviewed.

Checkpoint before external actions

Save the selected revisions, destination map, applicable authorization, and next intended action. On resumption, read that checkpoint and the provider state before issuing another write. Use the same logical item IDs for the same intended jobs.

Stage output: a concrete authorized scope, named unresolved decisions if any, and a single execution plan tied to the selected revisions.

4 Submit and verify each schedule

Establish the supported media handoff

Use the current publishing surface and its documented inputs. If media handling is uncertain, validate it with the smallest useful authorized step. A draft of an intended future post can serve that purpose when supported; retain and activate that same logical item after verification.

In this run, absolute local MP4 paths supplied through the connector's mediaFiles input were accepted and returned Metricool-hosted media references. Each unique video was uploaded once and its returned reference reused for the other destinations. This is an observation about that connector execution. [R3]

Retain the local selected-file digest and the provider media reference together. Matching a returned URL establishes which remote reference was selected. It does not prove remote byte identity unless remote bytes or an authoritative digest were also checked.

Submit with an item level receipt

Before each write, identify the intended item, selected map revision, applicable authorization, provider, and attempt ID. After the write, retain the response and any provider post ID, UUID, status, or media reference. Preserve provider identifiers as strings.

A successful submission response is an intermediate result. Read the provider's calendar or item record after submission and compare it with the prepared item. Keep any normalizations visible in the comparison.

Verify the complete returned record

Check	Required comparison
Destination	Correct platform and exact intended account.
Media and copy	Selected media reference, complete caption, and title.
Timing	Date, local time, timezone, and applicable offset.
Publishing mode	Draft status, automatic publication, and intended format.
Platform settings	Audience, privacy, disclosure, and other required values.
Batch reconciliation	Expected IDs and counts; missing and extra records.

Mark an item as scheduling verified only after its comparisons pass. A matching total alone is insufficient: twenty returned rows could contain a duplicate and a missing item. Verify both identity and content, then compare totals by destination.

Checkpoint after confirmed writes and at meaningful batch boundaries. Retain partial success if later items fail. Return the verified calendar, item receipts, manual handoff, and unresolved items.

Stage output: a verified scheduling record for each matched item. In the example, all twenty items were non-draft, automatic-publication schedules with provider status PENDING. That status did not establish publication. [R1]

5 Recover without creating duplicates

Classify the observation before choosing an action

A timeout or disconnected session does not show whether a write was committed. Before retrying, read the relevant schedule window or item endpoint. Match a known stable reference first; otherwise compare destination, time, media, and content. If multiple candidates remain, keep the outcome uncertain.

An empty result establishes absence only when the relevant account, time window, pagination, and any outstanding processing have been resolved. An incomplete or potentially stale read remains an unknown outcome.

Observed result	Next step
Existing item matches the intended revision	Retain the item and its receipt; do not create it again.
Existing item differs	Record the mismatch and evaluate an update within scope.
Confirmed rejection with no created item	Correct the rejected input and retry the affected item.
Confirmed absence after reconciliation	Create the intended item if authorization still applies.
Unknown, inaccessible, or multiple possible matches	Preserve uncertainty and resolve it before another create.

Keep logical identity across provider changes

Store the stable internal item ID, provider reference, latest provider ID, and prior IDs. In this execution, activating the initial draft returned a different numeric post ID while retaining its UUID. The UUID values were large enough that conversion to JavaScript numbers could lose precision, so they must remain strings. [R3]

Do not assume every provider exposes an immutable identifier or enforces idempotency. Where available, follow the provider's current contract. The internal record is still needed to connect attempts, revisions, and observed results.

Make targeted repairs

The initial Facebook update was rejected because the returned object included settings for an inactive network. Removing the irrelevant Twitter and Instagram default blocks resolved the update while preserving the Facebook content and schedule. [R3]

This supports a narrow repair rule: use the error and current schema to identify the invalid fields. Do not strip unrelated settings indiscriminately, drop explicit false values, or replay an entire response object without checking whether it is valid write input.

Preserve successful work

Resume only the unresolved items. Link each correction or retry to the prior attempt and the authorization that covers it. A later defect must not silently change the meaning of a previously authorized item. Deletion, withdrawal, or a new destination requires its own applicable scope.

The final snapshot proves the saved end state. It does not preserve every intermediate request and response. Future runs should retain a dated attempt log at submission and reconciliation time rather than relying solely on a retrospective narrative. [R1, R3]

6 Keep outcomes and learning separate

Use independent state fields

State	What can establish it	Example checkpoint
Readiness	Checks of the selected media, copy, links, and settings.	Checked for selected items
Authorization	An actual owner instruction covering the action.	Granted within scope
Scheduling	Provider records read back and matched.	20 verified
Publication	A later platform or provider publication record.	Not observed
Performance	Retrieved metrics with source and time window.	Not collected

Retain the provider's raw state separately from the method's interpretation. One state does not automatically advance another. For mixed batches, report counts and exceptions rather than promoting the whole release because some items succeeded.

Reconcile publication after the scheduled time

When publication checking is part of the requested work or later authorized, inspect each scheduled outcome. Retain the actual platform post identity, URL when available, publication time, retrieval time, and evidence source. Use the same internal item ID to connect this result to the schedule.

A reported failure, an inaccessible post, and an unknown outcome are different observations. Investigate before resubmitting. Apply the duplicate-prevention procedure to uncertain publication as well as uncertain scheduling. For manual routes, record an owner-supplied receipt with its stated evidence limits.

Record removal or revision after publication as a new event. Preserve the prior observation and the reason for the change rather than rewriting history.

Collect measurements with their meaning

Choose a measurement window that serves the campaign question. Record platform, metric name, value, unit or definition, window start and end, retrieval time, and source. An unavailable value stays unknown; zero is reserved for an observed zero.

Keep differences in platform definitions visible. Separate observations from interpretation and proposed changes. A count of views does not by itself establish understanding, persuasion, or sales attributable to this release.

The owner described the workflow as saving substantial effort. No timed baseline or controlled comparison was collected in this run, so this edition makes no numerical time-saving, engagement, or conversion claim. [R3]

Return evidence to the campaign

Attach verified observations to the existing campaign record. Keep unsuccessful attempts and unresolved issues available for later correction. A scheduled or popular item does not become canonical merely because of that outcome.

These continuation stages are documented procedures. This package does not create a background monitor or imply that later events have already been checked.

7 Worked example for the Zeely release

The November 10 checkpoint records five unique videos scheduled once on each of four networks. The release window spans fourteen calendar days, November 11-24, 2026, although the calendar interface can display it across three weekly views. All times below use America/Indianapolis, UTC-05:00 for these dates. [R1]

Asset	Facebook Page	Instagram	TikTok	YouTube
A01 Black tee showcase	Nov 11 12:00 pm	Nov 11 10:15 am	Nov 12 10:00 am	Nov 12 4:00 pm
A02 Faith humor video	Nov 13 10:00 am	Nov 13 10:15 am	Nov 16 6:00 pm	Nov 16 4:00 pm
A03 Backbone video	Nov 17 10:00 am	Nov 18 10:15 am	Nov 18 10:00 am	Nov 18 4:00 pm
A04 White tee showcase	Nov 20 10:00 am	Nov 20 10:15 am	Nov 20 10:30 am	Nov 20 4:00 pm
A05 Cycle video	Nov 24 10:00 am	Nov 24 10:15 am	Nov 23 6:00 pm	Nov 24 4:00 pm

Preparation that affected the release

One of the six uploads was an exact duplicate of the black tee showcase. Excluding it kept the intended batch at twenty items. The two showcase captions were recovered from the earlier packet. The other three captions were rebuilt from recovered scripts and observed media. [R1, R3]

Two subtitle defects were corrected in new files: backbown became backbone, and They show out became They show up. The correction record reports unchanged extracted audio and retained video timing properties. The scheduled items point to the corrected revisions. [R1, R2]

Recorded platform choices

The Facebook Page and Instagram items used Reel settings. TikTok items used public privacy, own-brand commercial disclosure, and AI-generated-content disclosure. YouTube items used Shorts settings, public privacy, an explicit not-made-for-kids value, AI disclosure, and individual titles. These are recorded choices for this batch, not defaults for every future campaign. [R1]

Checkpoint result

At 2026-11-10 23:24:27 UTC, the read-back contained twenty expected and twenty matched items, five per network, with no unexpected entries. All were non-draft and set for automatic publication. Provider status was PENDING. Five personal Facebook captions were a separate manual handoff. No manual publication or automated publication outcome was established by this checkpoint. [R1]

The accompanying worked-example JSON retains this schedule with generic asset references. The private execution record holds the actual account identifiers, captions, provider IDs, media references, and planner links.

8 What this execution establishes

Observed results and their limits

Finding	Evidence boundary
Five assets became twenty matching schedules.	The saved provider read-back and item comparisons support this end state.
Corrected files were selected for release.	Local digests and selected remote references are linked; remote bytes were not independently hashed.
Source recovery and reconstruction were combined.	Two recovered captions and three reconstructed captions have different provenance.
The owner authorized the batch.	Authorization covered the release scope; it was not a separate signature on every final payload.
The process was executed with ChatGPT and Metricool.	The evidence does not establish a native Signal Agent integration.
Publication and performance can be reconciled later.	Those stages had not been demonstrated at this snapshot.

Operational lessons

Deduplication belongs before destination expansion. A duplicate carried into a four-destination map would create four unwanted jobs. Revision selection belongs before upload so a corrected asset is not confused with the original. [R1]

Provider success must be read back. A draft, a scheduled item, and a live post can have different statuses even when the calendar card looks plausible. Verify the explicit flags and the destination settings, then preserve the time of that observation. [R1]

Technical adaptation belongs in the adapter record. The local-file upload and the inactive-network update repair worked in this run, but neither should become an assumption about every future connector. Check the current contract when a new environment or version changes the handoff. [R3]

Keep the audit claim proportional to the record

The final receipt and checkpoint support an independent comparison of counts, destinations, captions, selected media references, schedule times, and recorded settings. The subtitle receipt supports the recorded correction checks. Earlier draft creation, rejected updates, and ID transitions are described by the execution history; the compact final receipt alone cannot replay that sequence. [R1-R3]

A future run should preserve a small event record at each meaningful transition: attempted action, timestamp, intended item and revision, response reference, observed state, and next decision. Keep private account and access details in the private run record. Reusable examples need the method and evidence limits without exposing that material.

A public copy of the method can explain and summarize the case. It is not a substitute for access to the underlying private receipts when a reviewer needs to authenticate the execution.

9 Handoff to Signal Agent

Attach the method to the existing campaign model

Signal Agent can use Packet to Release as a distribution procedure attached to a campaign. Preserve the campaign's existing source, content packet, approval, and evidence identifiers. The records in this package describe the information needed for a handoff; they are not a new canonical database or a deployed API.

An implementation should accept a concrete packet and bounded authorization, expose current capabilities, execute through an available adapter, and return item-level evidence. Manual destinations should remain visible as work with an owner and a completion state.

Method record	Purpose in the campaign
Release request	Connect the source packet, requested outcome, scope, and existing authorization.
Asset and destination map	Bind exact asset and caption revisions to destinations, times, and settings.
Approval scope	Retain who authorized what, the evidence, delegated choices, and later changes.
Item execution record	Connect attempts, read-backs, reconciliation, publication, and measurements.

Separate orchestration from provider behavior

The coordinator owns the release map, state transitions, and receipts. A provider adapter owns the supported create, update, read, and outcome operations. Preparation agents return candidate outputs and checks; they do not silently change destination scope or grant approval.

Treat platform settings as explicit data with a checked schema. Retain raw provider states alongside normalized states. Keep secrets and access-bearing links out of public logs. Store provider identifiers as strings and record revision changes without discarding prior evidence.

Acceptance checks for a future implementation

- Resuming an interrupted run preserves matching existing jobs and acts only on unresolved items.
- A successful scheduling response cannot automatically mark publication or performance complete.
- An out-of-scope destination or material change cannot inherit unrelated approval.
- Manual items, partial failures, unknown outcomes, and unavailable metrics remain visible.
- The exported record is sufficient to compare intended items with observed provider state.

Implementation work should verify these behaviors against the actual adapter. This edition demonstrates the operator workflow through ChatGPT and Metricool; it supplies a concrete integration target for Signal Agent. No installation or deployment is represented by this documentation.

10 Reuse the method on the next packet

Start with the four records

Copy the four JSON templates into a new release record outside the method package. Replace null only with known information. Add one map item and one execution record per intended destination pairing. For manual items, leave automated scheduling unattempted and use the publication fields when evidence arrives.

References can point to existing campaign files and records. No particular database, signature system, or endpoint is required. Keep the record compact enough to maintain while preserving the source-to-result connection.

Operational checklist

- Capture the packet, requested outcome, destinations, window, timezone, and existing authorization.
- Recover the relevant context; distinguish original captions, reconstructions, and new writing.
- Deduplicate files, select revisions, correct defects, and retain the original-to-output links.
- Resolve destination identity and create one concrete item per intended destination.
- Prepare platform settings and a calendar with a stated timing basis.
- Check the map against the owner's actual scope and delegated choices.
- Submit through the supported interface, retain each receipt, and read back the result.
- Match content and settings as well as counts; reconcile missing, extra, or uncertain items.
- Return the verified calendar, manual handoffs, receipts, and remaining work.
- Add publication evidence and measurements only when those events are observed.

Definition of a complete scheduling handoff

Every intended automated item has either a matched provider schedule or an explicit unresolved status with a next action. Every manual item has the selected material and instructions. The batch record preserves the applicable authorization and enough evidence to resume without reconstructing decisions from memory.

A release may finish this stage while publication and performance remain pending. The final response should state those boundaries directly and give the owner the concrete files and receipts.

Package contents

The package includes the handbook in PDF, editable Word, and plain text; four JSON templates; the sanitized worked example; the operational checklist and record guide; an invocation text; a Signal Agent handoff; a change log; and a file manifest. The full private release archive remains separate.

The invocation text is a reusable natural-language instruction for an operator with the appropriate tools and access. It does not install a skill or start a recurring task. Method version 1.0.0 records this first documented edition; later corrections should retain their own change notes.

11 Evidence and reference register

Case findings refer to the saved November 10, 2026 observation, not a later live check. The public example summarizes selected fields; private source records are retained separately. Platform documentation was checked on November 10, 2026 and should be rechecked when capabilities or requirements affect a future run.

Execution evidence

R1 Verified release record. REVOLUTION Metricool Schedule Receipt, schema zeely.metricool.scheduled_release.v1, observed at 2026-11-10T23:24:27.571Z. Includes authorization scope, selected destinations, twenty item comparisons, schedule settings, manual captions, duplicate exclusion, and correction references. The separately retained checkpoint supports end-state comparison.

R2 Subtitle correction receipt. November 10, 2026. Records source and output file references, output and audio digests, an audio-preserved check, output technical properties, and boundary-review image references. The final release record contains the selected output hashes.

R3 Execution and recovery history. November 10, 2026 conversation and retained working records. Supports caption provenance, the local-file connector handoff, initial draft activation, targeted update repair, ID transition, and the owner's qualitative report of effort saved. The compact final snapshot does not reproduce the entire event sequence.

Related method references

F1 Brendon Coleman, Source to Series Method, handbook version 1.0, November 7, 2026. Defines source and claim lineage, derivative preparation, review, release authorization, and correction propagation.

F2 Brendon Coleman, Trend Chaser, method and operating instructions available November 10, 2026. Covers a traceable Printful-to-Shopify merchandise release, selected artwork, provider verification, authorization, checkpoints, and a resumable receipt.

Metricool primary documentation

M1 How to connect Facebook to Metricool
https://help.metricool.com/how-to-connect-facebook-to-metricool-5ark1

M2 Schedule and Post on Instagram
https://help.metricool.com/schedule-and-post-on-instagram-6b6q5

M3 Schedule and Post on TikTok
https://help.metricool.com/schedule-and-post-on-tiktok-bkepi

M4 Schedule and Publish on YouTube
https://help.metricool.com/schedule-and-publish-on-youtube-gof0k

Version and publication status

Version 1.0.0 documents the completed scheduling stage and the proposed continuation and integration records. This package has not been published to a public registry or installed in Signal Agent. No license for the new method package or campaign media is declared here.