# **Day 21 - Time for some ELForensics**

### Scenario


One of the 'little helpers' logged into his workstation only to realize that the database connector file has been replaced, and he can't find th naughty list anymore. Furthermore, upon executing the database connector file, a taunting message was displayed, hinting that the file was moved to another location.

McEager has been notified, and he will put the pieces together to find the database connector file.

Watch DarkStar's Video On Solving The Task Here.

Task: Find where the database connector file is hidden using forensic-like investigative techniques.


You can use the **AttackBox** and **Remmina** to connect to the remote machine. Make sure the remote machine is deployed before proceeding. Click on the plus icon as shown below.



For Server provide (10.10.219.166) as the IP address provided to you for the remote machine. The credentials for the user account is:

- User name: littlehelper
- User password: iLove5now!

access the RDP port of the remote host using remmina



## now go to document directory & there's 2 files

### & that's the hash for db.exe

```
PS C:\Users\littlehelper\Documents> get-content '.\db file hash.txt'
Filename: db.exe
MD5 Hash: 596690FFC54AB6101932856E6A78E3A1
PS C:\Users\littlehelper\Documents> _
```

getting the md5 hash for the mysterious deebee.exe

```
PS C:\Users\littlehelper\Documents> get-filehash -algorithm md5 .\deebee.exe

Algorithm Hash
----
MD5 5F037501FB542AD2D9B06EB12AED09F0
```

using strings to find the flag in the mysterious executable

```
args
Object
Accessing the Best Festival Company Database..
Done.
Using SSO to log in user...
Loading menu, standby...
THM{f6187e6cbeb1214139ef313e108cb6f9}
Set-Content -Path .\lists.exe -value $(Get-ConDocuments\db.exe).Path -ReadCount 0 -Encoding
```

list out all of the Alternate Data Stream (ADS) from the deebee.exe & found the Stream (hidedb) seems kinda sus

```
PS C:\Users\littlehelper\Documents> get-item -path .\deebee.exe -stream
PSPath:
              : Microsoft.PowerShell.Core\FileSystem::C:\Users\littlehelper\Documents\
                deebee.exe::$DATA
PSParentPath |
              : Microsoft.PowerShell.Core\FileSystem::C:\Users\littlehelper\Documents
PSChildName |
              : deebee.exe::$DATA
PSDrive:
PSProvider
              : Microsoft.PowerShell.Core\FileSystem
PSIsContainer : False
FileName
              : C:\Users\littlehelper\Documents\deebee.exe
Stream
              : :$DATA
              : 5632
Length
PSPath:
              : Microsoft.PowerShell.Core\FileSystem::C:\Users\littlehelper\Documents\
                deebee.exe:hidedb
              : Microsoft.PowerShell.Core\FileSystem::C:\Users\littlehelper\Documents
PSParentPath
PSChildName
              : deebee.exe:hidedb
PSDrive
PSProvider
              : Microsoft.PowerShell.Core\FileSystem
PSIsContainer : False
FileName
              : C:\Users\littlehelper\Documents\deebee.exe
              : hidedb
Stream
              : 6144
Length
```

## use wmic to create a process call of the deebee.exe:hidedb

```
PS C:\Users\littlehelper\Documents> wmic process call create $(Resolve-path C:\Users\littlehelper\Documents\deebee.exe:hidedb)
Executing (Win32_Process)->Create()
Method execution successful.
Out Parameters:
instance of __PARAMETERS
{
         ProcessId = 2212;
         ReturnValue = 0;
};

PS C:\Users\littlehelper\Documents> __
```

& we found the flag!

```
C:\Users\littlehelper\Documents\deebee.exe:hidedb

Choose an option:
e1) Nice List
2) Naughty List
3) Exit

THM{088731ddc7b9fdeccaed982b07c297c}

Select an option: __
```