

Log Location and Descriptions: The Basics

With StorNext, there two main types of log files:

- **Capture State:** This is the collection of information from the platform tools and Storage Manager logs. A capture state is also called a *snapshot* or a *collect log*. Tech Support asks for these logs when troubleshooting a StorNext File System and StorNext Storage Manager installation.
- **cvgather:** This is the collection of StorNext-File-System-specific logs. Tech Support asks for these logs when troubleshooting a StorNext-File-System-only installation.

Capture State

StorNext logs are constantly updated and stored on the system. You can access and review logs from the system, or you can collect a snapshot of the system logs at a given point in time. The capture state is saved in a ZIP file. The following table shows the folders contained in this ZIP file, and includes notes about the most important folders.

	(/usr/adic/DSM)	StorNext File System and StorNext Storage Manager Issues /data/<file system name>/log (aka /<file system name>/logs/cvlogs) • Includes status and errors regarding the file system. /debug/nssdbg.out • Includes failover/heartbeat activities
	(user/adic/MSM)	StorNext Storage Manager Issues /logs/tac/tac_00 * • Includes information related to the library.
	(usr/adic/tomcat)	StorNext GUI Issues /logs/stornextgui.log • Includes GUI-related issues.
	(/usr/adic/tsm)	StorNext Storage Manager Issues /logs/history/hist_01 * • Includes a history of what users did (TSM CLI commands). /logs/tac/backup.log • Includes a list of backup issues. /logs/tac/tac_00 * • Includes information about data movement.
	(/var/log*)	StorNext File System Issues On Linux systems, the system log resides in /var/log/messages On Windows systems, the system log is the system event log. It contains error and status messages for the operating system and all products installed on the system.

* Old files are named numerically (i.e., tac_00_1, tac_00_2)

cvgather

The **cvgather** program is used to collect debug information from a file system. It creates a tar file of the system's StorNext File System debug logs, configuration, version information, and disk devices.

The **cvgather** program collects client debug information on client machines, server information on server machines, and portmapper information from both clients and servers. It also collects system log files and StorNext File System log files.

The log files created by **cvgather** are named as follows:

- Pattern: **hostname_filesystemname.logfilename**
- Example: **Linux_nh-node-1_snfs1.cvlog**

In the example, **Linux_nh-node-1** is the **hostname**, **snfs1** is the **filesystemname** used with the **cvgather** command, and **.cvlog** is the **logfilename** used for all collections of logs created by **cvgather**.

When a new **.cvlog** file is created, older versions of this file are renamed. For example:

- **Linux_nh-node-1_snfs1.cvlog** is the most recent version of that file.
- **Linux_nh-node-1_snfs1.cvlog_1** is the second most recent version.
- **Linux_nh-node-1_snfs1.cvlog_2** is the third most recent version.

The log files are tar'd and don't have a specific folder structure. However, the log files included are similar to what is included in a capture state, minus the Storage Manager logs.