

markdown2html5-base

Full Markdown Functionality Reference

This reference covers all 17 feature categories:

- headings (with custom IDs),
- inline styling (bold/italic/strikethrough/highlight/sub/sup/underline/code),
- links,
- images,
- fenced code blocks,
- horizontal rules,
- lists (unordered/ordered/task),
- blockquotes,
- tables (with alignment and table foot),
- definition lists,
- footnotes,
- ruby annotations,
- emoji shortcodes,
- typography/legal marks,
- hard line breaks,
- HTML comments,
- backslash escaping,
- and paragraph handling.

Programmatic Usage

```
from markdown2html5_base import MarkdownToHTML
converter = MarkdownToHTML()
html = converter.convert("# Hello")
print(html)
```

1. Headings (H1-H6)

Markdown	Output HTML
# Heading 1	Heading 1
## Heading 2	Heading 2
### Heading 3	Heading 3
#### Heading 4	Heading 4
##### Heading 5	Heading 5
##### Heading 6	Heading 6

Custom ID: ## Section {#sec1} => <h2 id="sec1">Section</h2>

2. Inline Text Styling

Markdown	Output HTML
bold italic	bold italic
___bold italic___	bold italic
bold	bold
__bold__	bold
italic	italic
italic	italic
~~strikethrough~~	<s>strikethrough</s>
==highlight==	<mark>highlight</mark>
~subscript~	_{subscript}
^^underline^^	<ins>underline</ins>
^superscript^	^{superscript}
`code`	<code>code</code>

3. Links and Images

Markdown	Output HTML
[text](url)	text
![alt](src)	

4. Fenced Code Blocks

```
```python
def hello():
 print("Hi")
```

=>

```
```html
<pre><code>def hello():
    print("Hi")
</code></pre>
```

5. Horizontal Rules

--- / *** / ___ (3+ chars) => <hr>

6. Lists

- **Unordered:** * Item or - Item => Item

- **Ordered:** 1. Item => `<ol><li>Item</li></ol>`
- **Task:** * [] todo => `<input type="checkbox" disabled> todo * [x] done
=> <input type="checkbox" checked disabled> done`

7. Blockquotes

`> text => <blockquote><p>text</p></blockquote>` Blank lines within a blockquote split into separate `<p>` tags.

8. Tables

Supports `<thead>`, `<tbody>`, `<tfoot>`, and alignment:

Separator	Alignment
<code>:---</code>	left
<code>:---:</code>	center
<code>---:</code>	right

Footer: `|=|` separator after body rows renders `<tfoot>`.

9. Definition Lists

Term

: Definition 1

: Definition 2

=>

```
<dl>
  <dt>Term</dt>
  <dd>Definition 1</dd>
  <dd>Definition 2</dd>
</dl>
```

10. Footnotes

Reference: ^[1] => `<sup id="fnref:1"><a href="#fn:1" class="footnote-ref">1</a></sup>`

Definition: ^[1]: Text at bottom => rendered in `<div class="footnotes"><ol>...</ol></div>`

11. Ruby Annotations

{日本語 | にほんご} => `<ruby> 日本語 <rp>(</rp><rt> にほんご </rt><rp>)</rp></ruby>`

12. Emoji Shortcodes

:joy: :smile: :heart: :thumbsup: :thumbsdown: :wink: :tada: :rocket: :fire:
:star: :cry: :thinking:

13. Typography and Legal Marks

Input	Output
(c)	copy
(r)	reg
(tm)	tm
+/-	plum
!=	ne
<=	le
>=	ge
<< / >>	guillemets
1/2	half
1/4	quarter
3/4	three-quarters
...	ellipsis
---	em dash
--	en dash

Smart quotes: "text" => curly double, 'text' => curly single

14. Hard Line Breaks

End line with two spaces or backslash: `<br />`

15. HTML Comments

[comment]: # => `<!--comment-->`

16. Backslash Escaping

Escape any special char: `\*`, `\#`, `\[`, etc. Escapable: `' * _ { } [ ] ( ) # + - . ! | ~ ^ = : < >`

17. Paragraphs

Consecutive text lines merge into `<p>`. Blank lines separate paragraphs. Empty line after list close => `<!-- -->` preserves whitespace.