

markdown2html5-base

Full Markdown Functionality Reference

This reference covers all `markdown2html5-base` features.

Table of Contents

- [Programmatic Usage](#)
- [1. Headings \(H1-H6\)](#)
- [2. Inline Text Styling](#)
- [3. Links and Images](#)
- [4. Fenced Code Blocks](#)
- [5. Horizontal Rules](#)
- [6. Lists](#)
- [7. Blockquotes](#)
- [8. Tables](#)
- [9. Definition Lists](#)
- [10. Footnotes](#)
- [11. Language Markers](#)
- [12. Ruby Annotations](#)
- [13. Emoji Shortcodes](#)
- [14. Typography and Legal Marks](#)
- [15. Hard Line Breaks](#)
- [16. HTML Comments](#)
- [17. YAML Front Matter](#)
- [18. Backslash Escaping](#)
- [19. Paragraphs](#)
- [20. CSS Styles](#)

Programmatic Usage

```
from markdown2html5_base import MarkdownToHTML
converter = MarkdownToHTML()
html = converter.convert("# Hello")
print(html)
```

1. Headings (H1-H6)

Markdown	Output HTML
# Heading 1	Heading 1
## Heading 2	Heading 2
### Heading 3	Heading 3
#### Heading 4	Heading 4
##### Heading 5	Heading 5
##### Heading 6	Heading 6

Custom ID: ## Section {#sec1} => <h2 id="sec1">Section</h2>

2. Inline Text Styling

Markdown	Output HTML
bold italic	bold italic
___bold italic___	bold italic
bold	bold
__bold__	bold
italic	italic
italic	italic
~~strikethrough~~	<s>strikethrough</s>
==highlight==	<mark>highlight</mark>
~subscript~	_{subscript}
^^underline^^	<u>underline</u>
^superscript^	^{superscript}
`code`	<code>code</code>

3. Links and Images

Markdown	Output HTML
[text](url)	text
![alt](src)	<figure></figure>
![alt](src "Title")	<figure> <figcaption>Title</figcaption></figure>

4. Fenced Code Blocks

A language tag after the opening fence (three backticks before and after the code) is rendered as a `<div class="code-lang">/python/</div>` label above the `<code>` element:

```
<div class="code-lang">&sol;python&sol;</div><pre><code>def hello():
    print("Hi")</code></pre>
```

Without a language tag, the code renders plainly as `<pre><code>`.

5. Horizontal Rules

`---` / `***` / `___` (3+ chars) => `<hr>`

6. Lists

- 1. **Unordered:** `* Item` or `- Item` => `<ul><li>Item</li></ul>`
- 2. **Ordered:** `1. Item` => `<ol><li>Item</li></ol>`
- 3. **Task:**
 - `* [ ] todo` => `<li><input type="checkbox" disabled> todo</li>`
 - `* [x] done` => `<li><input type="checkbox" checked disabled> done</li>`

7. Blockquotes

`> text` => `<blockquote><p>text</p></blockquote>` : blank lines within a blockquote split into separate `<p>` tags.

8. Tables

Supports `<thead>`, `<tbody>`, `<tfoot>`, and alignment:

Separator	Alignment
<code>:---</code>	left
<code>:---:</code>	center
<code>---:</code>	right

Footer: a row of `=` signs below the separator columns, after the body rows, renders a `<tfoot>`.

```
| Product | Qty | Price |
| :----- | :-: | ----: |
| Apples  | 2   | $3.00 |
| Bananas | 3   | $1.50 |
| Cherries| 1   | $4.00 |
|=====|=====|=====|
| Total   | 6   | $8.50 |
```

=>

```

<table>
  <thead>
    <tr>
      <th style="text-align:left;">Product</th>
      <th style="text-align:center;">Qty</th>
      <th style="text-align:right;">Price</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td style="text-align:left;">Apples</td>
      <td style="text-align:center;">2</td>
      <td style="text-align:right;">$3.00</td>
    </tr>
    <tr>
      <td style="text-align:left;">Bananas</td>
      <td style="text-align:center;">3</td>
      <td style="text-align:right;">$1.50</td>
    </tr>
    <tr>
      <td style="text-align:left;">Cherries</td>
      <td style="text-align:center;">1</td>
      <td style="text-align:right;">$4.00</td>
    </tr>
  </tbody>
  <tfoot>
    <tr>
      <td style="text-align:left;">Total</td>
      <td style="text-align:center;">6</td>
      <td style="text-align:right;">$8.50</td>
    </tr>
  </tfoot>
</table>

```

9. Definition Lists

```

Term
: Definition 1
: Definition 2

```

=>

```

<dl>
  <dt>Term</dt>
  <dd>Definition 1</dd>
  <dd>Definition 2</dd>
</dl>

```

10. Footnotes

Reference: `[^1]` => `<sup id="fnref:1"><a href="#fn:1" class="footnote-ref">1</a></sup>`

Definition: `[^1]: Text` at bottom => rendered in `<div class="footnotes"><ol>...</ol></div>`

11. Language Markers

Annotate blocks or inline text with a language using a valid BCP 47 tag (e.g. `de`, `fr`, `zh-Hans`).

- **Block level:** Place `{:lang}` (with a space after it) at the very start of a line, before the Markdown tag. It renders as the global `lang` attribute on the resulting element and needs no closing marker:

```
{:de} # Überschrift
{:fr} Un paragraphe français.
{:ru} - Пункт списка
{:de} > Ein Zitat
{:de} | Kopf | Kopf |
      | ----- | ----- |
      | Zelle | Zelle |
```

=>

```
<h1 lang="de">Überschrift</h1>
<p lang="fr">Un paragraphe français.</p>
<ul lang="ru">
  <li>Пункт списка</li>
</ul>
<blockquote lang="de">...</blockquote>
<table lang="de">...</table>
```

- **Inline level:** Wrap text with `{:lang}...{:}` to render a `<span lang="...">`:

A French phrase `{:fr}"L'État c'est moi"{:}` is traditionally attributed to King Louis XIV of France.

=>

```
<p>A French phrase <span lang="fr">"L'État c'est moi"</span> is traditionally attributed to King
Louis XIV of France</p>
```

12. Ruby Annotations

`{日本語|にほんご}` => `<ruby>日本語<rp>(</rp><rt>にほんご</rt><rp>)</rp></ruby>`

13. Emoji Shortcodes

- `:joy:` 😄
- `:smile:` 😊

- `:heart:` 
- `:thumbsup:` 
- `:thumbsdown:` 
- `:wink:` 
- `:tada:` 
- `:rocket:` 
- `:fire:` 
- `:star:` 
- `:cry:` 
- `:thinking:` 
- `:100:` 
- `:sparkles:` 
- `:eyes:` 
- `:bulb:` 
- `:warning:` 
- `:ok:` 
- `:check_mark:` 

14. Typography and Legal Marks

Name	Input	HTML Output
Copyright	(c)	©
Trademark	(tm)	™
Registered Trademark	(r)	®
Plus-Minus	+/-	±
Not Equal To	!=	≠
Logical Equivalence	<=>	⇔
Less-Than or Equal To	<=	≤
Greater-Than or Equal To	>=	≥
Right Arrow	->	→
Left Arrow	<-	←
Up Arrow	↑	↑
Down Arrow	↓	↓
Logical Implication	=>	⇒
Solidus (Slash)	/	/
Reverse Solidus (Backslash)	\	\
One-Half	1/2	½
One-Third	1/3	⅓
Two-Thirds	2/3	⅔
One-Quarter	1/4	¼
Three-Quarters	3/4	¾
Left Angle Quote	<<	«
Right Angle Quote	>>	»
Left Double Quote	“	“
Right Double Quote	”	”
Smart Double Quotes	"text"	“text”
Smart Single Quotes	'text'	‘text’
Straight Apostrophe	'	'
Em Dash	---	—
En Dash	--	–
Ellipsis	...	…
Non-Breaking Space	 	

15. Hard Line Breaks

End line with two spaces or backslash: `<br />`

16. HTML Comments

`[comment]: # => <!--comment-->`

17. YAML Front Matter

If the file begins with a YAML front matter block between `---` lines, the converter emits a complete HTML5 document with the metadata in `<head>` and the body content between `<body>` tags. Without front matter, the output stays a bare HTML fragment. The `--css` option (or `include_css=True`) embeds the default `<style>` block regardless of whether front matter is present.

```
---
lang: en
title: My Document
author: Jane Doe
description: A short description.
keywords: python, markdown, html5
published: 2026-08-09
---
```

- `lang` becomes the `<html lang="...">` attribute (a valid BCP 47 tag).
- `title` becomes the `<title>` element.
- `author`, `description`, `keywords`, and `published` become `<meta name="..." content="..." />` tags.
- A default `<style>` block with viewing-friendly CSS is embedded in `<head>`.

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="utf-8" />
    <meta name="author" content="Jane Doe" />
    <meta name="description" content="A short description." />
    <meta name="keywords" content="python, markdown, html5" />
    <title>My Document</title>
    <meta name="published" content="2026-08-09" />
    <style>
      /* default viewing-friendly CSS */
    </style>
  </head>
  <body>
    ...
  </body>
</html>
```

Any other keys are ignored, and if the file has no front matter at all, the output remains a bare fragment (unless `--css / include_css=True` is used, in which case it becomes a full document).

18. Backslash Escaping

Escape any special char: `\*`, `\#`, `\[`, etc.

Escapable: `\`*_{}[]()#+-.!|~^=:<>`

19. Paragraphs

Consecutive text lines merge into `<p>`. Blank lines separate paragraphs.

Empty line after list close => `<!-- -->` preserves whitespace.

20. CSS Styles

The converter (with `--css` option or `include_css=True`) embeds a default `<style>` block in `<head>` that provides viewing-friendly styling, regardless of YAML front matter. This predefined CSS rules includes:

```
body {
  padding: 20px;
  font-family: "Noto Serif", "Liberation Serif", "Times New Roman", Times, serif;
  font-size: 18px;
  line-height: 1.4;
  color: #000000;
  background-color: #ffffff;
}
h1 {
  margin-top: 1.2em;
  margin-bottom: 0.6em;
  font-family: "Noto Sans", "Liberation Sans", Arial, sans-serif;
  font-weight: bold;
  font-size: 32px;
  hyphens: auto;
  word-break: normal;
  overflow-wrap: break-word;
  text-wrap: balance;
}
h2 {
  margin-top: 1.2em;
  margin-bottom: 0.6em;
  font-family: "Noto Sans", "Liberation Sans", Arial, sans-serif;
  font-weight: bold;
  font-size: 28px;
  hyphens: auto;
  word-break: normal;
  overflow-wrap: break-word;
  text-wrap: balance;
}
h3 {
  margin-top: 1.2em;
  margin-bottom: 0.6em;
  font-family: "Noto Sans", "Liberation Sans", Arial, sans-serif;
  font-weight: bold;
  font-size: 24px;
  hyphens: auto;
  word-break: normal;
  overflow-wrap: break-word;
  text-wrap: balance;
}
h4 {
  margin-top: 1.2em;
  margin-bottom: 0.6em;
  font-family: "Noto Sans", "Liberation Sans", Arial, sans-serif;
  font-weight: bold;
  font-size: 20px;
  hyphens: auto;
  word-break: normal;
  overflow-wrap: break-word;
  text-wrap: balance;
}
```

```
h5 {
  margin-top: 1.2em;
  margin-bottom: 0.6em;
  font-family: "Noto Sans", "Liberation Sans", Arial, sans-serif;
  font-weight: bold;
  font-size: 18px;
  hyphens: auto;
  word-break: normal;
  overflow-wrap: break-word;
  text-wrap: balance;
}
h6 {
  margin-top: 1.2em;
  margin-bottom: 0.6em;
  font-family: "Noto Sans", "Liberation Sans", Arial, sans-serif;
  font-weight: bold;
  font-size: 18px;
  font-style: italic;
  hyphens: auto;
  word-break: normal;
  overflow-wrap: break-word;
  text-wrap: balance;
}
p {
  hyphens: auto;
  hyphenate-limit-chars: 6 3 3;
  word-break: normal;
  overflow-wrap: break-word;
}
hr {
  height: 4px;
  margin: 20px 0;
  border: none;
  background-color: #000000;
}
blockquote {
  margin-left: 0;
  padding-left: 20px;
  border-left: 8px solid #f5f5f5;
  hyphens: auto;
  hyphenate-limit-chars: 6 3 3;
  word-break: normal;
  overflow-wrap: break-word;
}
mark {
  padding: 0 2px;
  border-radius: 4px;
  background-color: #ffff00;
  color: #000000;
}
a:link { color: #0000cd; }
a:visited { color: #9400d3; }
a:hover { outline: none; color: #000080; }
```

```
a:focus { outline: none; color: #000080; }
a:active { color: #dc143c; }
ol {
  hyphens: auto;
  hyphenate-limit-chars: 6 3 3;
  word-break: normal;
  overflow-wrap: break-word;
}
ul {
  hyphens: auto;
  hyphenate-limit-chars: 6 3 3;
  word-break: normal;
  overflow-wrap: break-word;
}
li {
  position: relative;
  padding-left: 20px;
  hyphens: auto;
  hyphenate-limit-chars: 6 3 3;
  word-break: normal;
  overflow-wrap: break-word;
}
dt {
  font-weight: bold;
  hyphens: auto;
  word-break: break-word;
  overflow-wrap: anywhere;
}
dd {
  position: relative;
  margin-left: 0;
  padding-left: 20px;
  font-style: italic;
  hyphens: auto;
  hyphenate-limit-chars: 6 3 3;
  word-break: normal;
  overflow-wrap: break-word;
}
code {
  padding: 2px 4px;
  border-radius: 4px;
  font-family: "Noto Sans Mono", "Liberation Mono", "Courier New", Courier, monospace;
  font-size: 0.9em;
  line-height: 1;
  hyphens: none !important;
  white-space: normal;
  word-break: break-all;
  overflow-wrap: anywhere;
}
pre {
  max-width: 100%;
  margin: 0;
  padding: 20px;
```

```

border: 1px solid #000000;
background-color: #f5f5f5;
overflow: auto;
scrollbar-color: #000000 transparent;
white-space: pre-wrap;
word-break: break-all;
overflow-wrap: anywhere;
}
pre > code {
  display: block;
  margin: 0;
  padding: 0;
  border: none;
  border-radius: 0;
  line-height: 1.2;
  background-color: transparent;
  overflow: visible;
  hyphens: none !important;
  white-space: pre;
  word-break: normal;
  overflow-wrap: normal;
}
div.code-lang {
  display: block;
  padding: 10px 20px;
  font-family: "Noto Sans Mono", "Liberation Mono", "Courier New", Courier, monospace;
  font-size: 0.9em;
  line-height: 1;
  background-color: #000000;
  color: #ffffff;
  font-weight: bold;
}
table {
  margin: 20px 0;
  border-collapse: collapse;
}
th { padding: 10px 12px; border: 1px solid #000000; font-weight: bold; }
td { padding: 10px 12px; border: 1px solid #000000; }
thead tr { background-color: #000000; color: #ffffff; }
thead th { hyphens: auto; word-break: break-word; overflow-wrap: anywhere; }
thead td { hyphens: auto; word-break: break-word; overflow-wrap: anywhere; }
tbody th { hyphens: auto; word-break: break-word; overflow-wrap: anywhere; }
tbody td { hyphens: auto; word-break: break-word; overflow-wrap: anywhere; }
tfoot tr { background-color: #f5f5f5; font-style: italic; }
tfoot th { hyphens: auto; word-break: break-word; overflow-wrap: anywhere; }
tfoot td { hyphens: auto; word-break: break-word; overflow-wrap: anywhere; }
figure {
  display: block;
  margin: 0;
}
figure img {
  display: block;
  max-width: 100%;

```

```
    height: auto;
}
figcaption {
    text-align: left;
    font-style: italic;
    hyphens: auto;
    hyphenate-limit-chars: 6 3 3;
    word-break: normal;
    overflow-wrap: break-word;
}
ruby { ruby-position: over; ruby-align: space-around; }
rt {
    letter-spacing: 0.05em;
    font-size: 0.55em;
    line-break: strict;
    white-space: nowrap;
    overflow-wrap: normal;
}
rp { display: none; }
span[lang="ja"] {
    font-family: "Noto Serif CJK JP", "Source Han Serif JP", "源ノ明朝", "Source Han Serif", "Hiragino Mincho ProN", "Hiragino Mincho Pro", "IPAexMincho", "IPAMincho", "MS PMincho", "MS Mincho", serif;
    word-break: break-all;
    line-break: normal;
}
span[lang="zh-CN"] {
    font-family: "Noto Serif CJK SC", "Source Han Serif SC", "思源宋体", "Source Han Serif CN", "Source Han Serif", "Songti SC", "FandolSong", "WenQuanYi Bitmap Song", "SimSun", serif;
    word-break: break-all;
    line-break: normal;
}
span[lang="zh-Hans"] {
    font-family: "Noto Serif CJK SC", "Source Han Serif SC", "思源宋体", "Source Han Serif CN", "Source Han Serif", "Songti SC", "FandolSong", "WenQuanYi Bitmap Song", "SimSun", serif;
    word-break: break-all;
    line-break: normal;
}
span[lang="zh-TW"] {
    font-family: "Noto Serif CJK TC", "Source Han Serif TC", "思源宋體", "Source Han Serif TW", "Source Han Serif", "Apple LiSung", "LiSong Pro", "HanaMinA", "PMingLiU", "MingLiU", serif;
    word-break: break-all;
    line-break: normal;
}
span[lang="zh-Hant"] {
    font-family: "Noto Serif CJK TC", "Source Han Serif TC", "思源宋體", "Source Han Serif TW", "Source Han Serif", "Apple LiSung", "LiSong Pro", "HanaMinA", "PMingLiU", "MingLiU", serif;
    word-break: break-all;
    line-break: normal;
}
span[lang="zh-HK"] {
    font-family: "Noto Serif CJK HK", "Source Han Serif HK", "思源宋體 香港", "思源宋體", "Source Han Serif", "Apple LiSung", "LiSong Pro", "HanaMinA", "MingLiU_HKSCS", "PMingLiU", "MingLiU", serif;
    word-break: break-all;
}
```

```
    line-break: normal;
}
span[lang="ko"] {
    font-family: "Noto Serif CJK KR", "Source Han Serif KR", "본명조", "Source Han Serif",
    "AppleMyungjo", "UnBatang", "은바탕", "Batang", serif;
    word-break: break-all;
    line-break: normal;
}
```