

markdown2html5-base

Full Markdown Functionality Reference

This reference covers all 17 feature categories:

- headings (with custom IDs),
- inline styling (bold/italic/strikethrough/highlight/sub/sup/underline/code),
- links,
- images,
- fenced code blocks,
- horizontal rules,
- lists (unordered/ordered/task),
- blockquotes,
- tables (with alignment and table foot),
- definition lists,
- footnotes,
- ruby annotations,
- emoji shortcodes,
- typography/legal marks,
- hard line breaks,
- HTML comments,
- backslash escaping,
- and paragraph handling.

Programmatic Usage

```
```python
from markdown2html5_base import MarkdownToHTML
converter = MarkdownToHTML()
html = converter.convert("# Hello")
print(html)
```
```

1. Headings (H1-H6)

| Markdown | Output HTML |
|-----------------|--------------------|
| # Heading 1 | <h1>Heading 1</h1> |
| ## Heading 2 | <h2>Heading 2</h2> |
| ### Heading 3 | <h3>Heading 3</h3> |
| #### Heading 4 | <h4>Heading 4</h4> |
| ##### Heading 5 | <h5>Heading 5</h5> |
| ##### Heading 6 | <h6>Heading 6</h6> |

Custom ID: `## Section {#sec1}` => `<h2 id="sec1">Section</h2>`

2. Inline Text Styling

| Markdown | Output HTML |
|--------------------------------|--|
| <code>***bold italic***</code> | <code>bold italic</code> |
| <code>___bold italic___</code> | <code>bold italic</code> |
| <code>**bold**</code> | <code>bold</code> |
| <code>__bold__</code> | <code>bold</code> |
| <code>*italic*</code> | <code>italic</code> |
| <code>_italic_</code> | <code>italic</code> |
| <code>~~strikethrough~~</code> | <code><s>strikethrough</s></code> |
| <code>==highlight==</code> | <code><mark>highlight</mark></code> |
| <code>~subscript~</code> | <code><sub>subscript</sub></code> |
| <code>^^underline^^</code> | <code><ins>underline</ins></code> |
| <code>^superscript^</code> | <code><sup>superscript</sup></code> |
| <code>`code`</code> | <code><code>code</code></code> |

3. Links and Images

| Markdown | Output HTML |
|--------------------------|---|
| <code>[text](url)</code> | <code>text</code> |
| <code>![alt](src)</code> | <code></code> |

4. Fenced Code Blocks

```
```python
def hello():
 print("Hi")=>
```

=>

```
```html
<pre><code>def hello():
    print("Hi")
</code></pre><pre><code>def hello():
    print("Hi")
</code></pre>
```

5. Horizontal Rules

--- / *** / ___ (3+ chars) => <hr>

6. Lists

1. **Unordered:** * Item or - Item => Item

2. **Ordered:** 1. Item => Item

3. **Task:**

* [] todo => <input type="checkbox" disabled> todo

* [x] done => <input type="checkbox" checked disabled> done

7. Blockquotes

> text => <blockquote><p>text</p></blockquote> Blank lines within a blockquote split into separate <p> tags.

8. Tables

Supports <thead>, <tbody>, <tfoot>, and alignment:

Separator	Alignment
:---	left
:---:	center
---:	right

Footer: |=| separator after body rows renders <tfoot>.

9. Definition Lists

Term
: Definition 1
: Definition 2

=>

```
<dl>
  <dt>Term</dt>
  <dd>Definition 1</dd>
  <dd>Definition 2</dd>
</dl>
```

10. Footnotes

Reference: [^1] => ^{1}

Definition: [^1]: Text at bottom => rendered in <div class="footnotes">...</div>

11. Ruby Annotations

{日本語|にほんご} => <ruby>日本語<rp>(</rp><rt>にほんご</rt><rp>)</rp></ruby>

12. Emoji Shortcodes

:joy: :smile: :heart: :thumbsup: :thumbsdown: :wink: :tada: :rocket: :fire: :star: :cry:
:thinking:

13. Typography and Legal Marks

Input	Output
(c)	copy
(r)	reg
(tm)	tm
+/-	plusmn
!=	ne
<=	le
>=	ge
<< / >>	guillemets
1/2	half
1/4	quarter
3/4	three-quarters
...	ellipsis
---	em dash
--	en dash

Smart quotes: "text" => curly double, 'text' => curly single

14. Hard Line Breaks

End line with two spaces or backslash:

15. HTML Comments

[comment]: # => <!--comment-->

16. Backslash Escaping

Escape any special char: *, \#, \[, etc. Escapable: \`*_{}[]()#+-.!|~^=:<>

17. Paragraphs

Consecutive text lines merge into `<p>` . Blank lines separate paragraphs. Empty line after list close => `<!-- -->` preserves whitespace.