

Full Markdown Functionality Reference

This reference covers all 20 feature categories:

- headings (with custom IDs),
- inline styling (bold/italic/strikethrough/highlight/sub/sup/underline/code),
- links and images,
- fenced code blocks,
- horizontal rules,
- lists (unordered/ordered/task),
- blockquotes,
- tables (with alignment and table foot),
- definition lists,
- footnotes,
- language markers,
- ruby annotations,
- emoji shortcodes,
- typography/legal marks,
- hard line breaks,
- HTML comments,
- YAML front matter,
- predefined CSS styles,
- backslash escaping,
- and paragraph handling.

Programmatic Usage

```
from markdown2html5_base import MarkdownToHTML
converter = MarkdownToHTML()
html = converter.convert("# Hello")
print(html)
```

1. Headings (H1-H6)

Markdown	Output HTML
# Heading 1	Heading 1
## Heading 2	Heading 2
### Heading 3	Heading 3
#### Heading 4	Heading 4
##### Heading 5	Heading 5
##### Heading 6	Heading 6

Custom ID: ## Section {#sec1} => <h2 id="sec1">Section</h2>

2. Inline Text Styling

Markdown	Output HTML
<code>***bold italic***</code>	<code>bold italic</code>
<code>___bold italic___</code>	<code>bold italic</code>
<code>**bold**</code>	<code>bold</code>
<code>__bold__</code>	<code>bold</code>
<code>*italic*</code>	<code>italic</code>
<code>_italic_</code>	<code>italic</code>
<code>~~strikethrough~~</code>	<code><s>strikethrough</s></code>
<code>==highlight==</code>	<code><mark>highlight</mark></code>
<code>~subscript~</code>	<code><sub>subscript</sub></code>
<code>^^underline^^</code>	<code><u>underline</u></code>
<code>^superscript^</code>	<code><sup>superscript</sup></code>
<code>`code`</code>	<code><code>code</code></code>

3. Links and Images

Markdown	Output HTML
<code>[text](url)</code>	<code>text</code>
<code>![alt](src)</code>	<code></code>
<code>![alt](src "Title")</code>	<code></code>

4. Fenced Code Blocks

```
def hello():
    print("Hi")
```

=>

```
<pre><code>def hello():
    print("Hi")</code></pre>
```

5. Horizontal Rules

`---` / `***` / `___` (3+ chars) => `<hr>`

6. Lists

- 1. **Unordered:** `* Item` or `- Item` => `<ul><li>Item</li></ul>`
- 2. **Ordered:** `1. Item` => `<ol><li>Item</li></ol>`
- 3. **Task:**
 - `* [ ] todo` => `<li><input type="checkbox" disabled> todo</li>`
 - `* [x] done` => `<li><input type="checkbox" checked disabled> done</li>`

7. Blockquotes

> text => `<blockquote><p>text</p></blockquote>` Blank lines within a blockquote split into separate `<p>` tags.

8. Tables

Supports `<thead>`, `<tbody>`, `<tfoot>`, and alignment:

Separator	Alignment
<code>:---</code>	left
<code>:---:</code>	center
<code>---:</code>	right

Footer: a row of `=` signs in the separator columns after body rows renders `<tfoot>`.

```
| Product | Qty | Price |
| :----- | :-: | ----: |
| Apples  | 2   | $3.00 |
| Bananas | 3   | $1.50 |
| Cherries| 1   | $4.00 |
|=====|=====|
| Total   | 6   | $8.50 |
```

=>

```
<table>
  <thead>
    <tr>
      <th style="text-align:left;">Product</th>
      <th style="text-align:center;">Qty</th>
      <th style="text-align:right;">Price</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td style="text-align:left;">Apples</td>
      <td style="text-align:center;">2</td>
      <td style="text-align:right;">$3.00</td>
    </tr>
    <tr>
      <td style="text-align:left;">Bananas</td>
      <td style="text-align:center;">3</td>
      <td style="text-align:right;">$1.50</td>
    </tr>
    <tr>
      <td style="text-align:left;">Cherries</td>
      <td style="text-align:center;">1</td>
      <td style="text-align:right;">$4.00</td>
    </tr>
  </tbody>
  <tfoot>
    <tr>
      <td style="text-align:left;">Total</td>
      <td style="text-align:center;">6</td>
      <td style="text-align:right;">$8.50</td>
    </tr>
  </tfoot>
</table>
```

9. Definition Lists

Term
: Definition 1
: Definition 2

=>

```
<dl>
  <dt>Term</dt>
  <dd>Definition 1</dd>
  <dd>Definition 2</dd>
</dl>
```

10. Footnotes

Reference: `[^1]` => `<sup id="fnref:1"><a href="#fn:1" class="footnote-ref">1</a></sup>`

Definition: `[^1]: Text` at bottom => rendered in `<div class="footnotes"><ol>...</ol></div>`

11. Language Markers

Annotate blocks or inline text with a language using a valid BCP 47 tag (e.g. `de`, `fr`, `zh-Hans`).

- **Block level:** Place `{:lang}` (with a space after it) at the very start of a line, before the Markdown tag. It renders as the global `lang` attribute on the resulting element and needs no closing marker:

```
{:de} # Überschrift
{:fr} Un paragraphe français.
{:ru} - Пункт списка
{:de} > Ein Zitat
{:de} | Kopf | Kopf |
      | ---- | ---- |
      | Zelle | Zelle |
```

=>

```
<h1 lang="de">Überschrift</h1>
<p lang="fr">Un paragraphe français.</p>
<ul lang="ru">
  <li>Пункт списка</li>
</ul>
<blockquote lang="de">...</blockquote>
<table lang="de">...</table>
```

- **Inline level:** Wrap text with `{:lang}...{:}` to render a `<span lang="...">`:

A French phrase `{:fr}"L'État c'est moi"{:}` is traditionally attributed to King Louis XIV of France.

=>

<p>A French phrase “L'État c'est moi” is traditionally attributed to King Louis XIV of France</p>

12. Ruby Annotations

{日本語|にほんご} => <ruby>日本語<rp>(</rp><rt>にほんご</rt><rp>)</rp></ruby>

13. Emoji Shortcodes

- :joy: 😄
- :smile: 😊
- :heart: ❤️
- :thumbsup: 👍
- :thumbsdown: 👎
- :wink: 😉
- :tada: 🎉
- :rocket: 🚀
- :fire: 🔥
- :star: ★
- :cry: 😭
- :thinking: 🤔
- :100: 100
- :sparkles: ✨
- :eyes: 👁️
- :bulb: 💡
- :warning: ⚠️
- :ok: 👌
- :check_mark: ✓

14. Typography and Legal Marks

Name	Input	HTML Output
Copyright	(c)	©
Trademark	(tm)	™
Registered Trademark	(r)	®
Plus-Minus	+/-	±
Not Equal To	!=	≠
Logical Equivalence	<=>	⇔
Less-Than or Equal To	<=	≤
Greater-Than or Equal To	>=	≥
Left Arrow	->	→
Right Arrow	<-	←
Up Arrow	:uparrow:	↑
Down Arrow	:dnarrow:	↓
Logical Implication	=>	⇒
One-Half	1/2	½
One-Third	1/3	⅓
Two-Thirds	2/3	⅔
One-Quarter	1/4	¼
Three-Quarters	3/4	¾
Left Angle Quote	<<	«
Right Angle Quote	>>	»
Smart Double Quotes	"text"	“text”
Smart Single Quotes	'text'	‘text’
Straight Apostrophe	'	'
Em Dash	---	—
En Dash	--	–
Ellipsis	...	…

15. Hard Line Breaks

End line with two spaces or backslash: `<br />`

16. HTML Comments

[comment]: # => `<!--comment-->`

17. YAML Front Matter

If the file begins with a YAML front matter block between `---` lines, the converter emits a complete HTML5 document with the metadata in `<head>` and the body content between `<body>` tags. Without front matter, the output stays a bare HTML fragment.

```
---
lang: en
title: My Document
author: Jane Doe
description: A short description.
keywords: python, markdown, html5
published: 2026-08-09
---
```

- `lang` becomes the `<html lang="...">` attribute (a valid BCP 47 tag).
- `title` becomes the `<title>` element.
- `author`, `description`, `keywords`, and `published` become `<meta name="..." content="..." />` tags.
- A default `<style>` block with print-friendly CSS is embedded in `<head>`.

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="utf-8" />
    <meta name="author" content="Jane Doe" />
    <meta name="description" content="A short description." />
    <meta name="keywords" content="python, markdown, html5" />
    <title>My Document</title>
    <meta name="published" content="2026-08-09" />
    <style>
      /* default print-friendly CSS */
    </style>
  </head>
  <body>
    ...
  </body>
</html>
```

Any other keys are ignored, and if the file has no front matter at all, the output remains a bare fragment.

18. Backslash Escaping

Escape any special char: `\*`, `\#`, `\[`, etc.

Escapable: `\`*_{}[]()#+-.!|~^=:<>`

19. Paragraphs

Consecutive text lines merge into `<p>`. Blank lines separate paragraphs.

Empty line after list close => `<!-- -->` preserves whitespace.

20. CSS Styles

The converter embeds a default `<style>` block in `<head>` (available as `MarkdownToHTML.DOCUMENT_CSS`) that provides view-friendly styling. This predefined CSS rules includes:

```
body {
  font-family: "Noto Serif", "Liberation Serif", "Times New Roman", Times, serif;
  font-size: 18px;
  line-height: 1.4;
  padding: 20px;
  color: #000000;
}
h1, h2, h3, h4, h5, h6 {
  font-family: "Noto Sans", "Liberation Sans", Arial, sans-serif;
  font-weight: bold;
  margin-top: 1.2em;
  margin-bottom: 0.6em;
}
h1 {
  font-size: 32px;
}
h2 {
  font-size: 28px;
}
h3 {
  font-size: 24px;
}
h4 {
  font-size: 20px;
}
h5, h6 {
  font-size: 18px;
}
h6 {
  font-style: italic;
}
li {
  position: relative;
  margin-left: 20px;
  padding-left: 4px;
}
dt {
  font-weight: bold;
}
dd {
  font-style: italic;
  position: relative;
  margin-left: 0;
  padding-left: 40px;
}
blockquote {
  border-left: 4px solid #808080;
  margin-left: 10px;
  padding-left: 20px;
  margin-top: 10px;
  margin-bottom: 10px;
}
a:link {
  color: #0000cd;
}
a:visited {
  color: #9400d3;
}
a:hover, a:focus {
  color: #000080;
}
```



```

outline: none;
}
a:active {
color: #dc143c;
}
mark {
background-color: #ffff00;
padding: 0px 2px;
border-radius: 4px;
}
code {
font-family: "Noto Sans Mono", "Liberation Mono", Courier, monospace;
background-color: #f5f5f5;
padding: 2px 4px;
border-radius: 4px;
font-size: 0.9em;
}
pre {
background-color: #f5f5f5;
border: 1px solid #808080;
border-radius: 2px;
margin: 0;
padding: 20px;
max-width: 100%;
overflow: auto;
scrollbar-color: #808080 transparent;
}
pre > code {
display: block;
line-height: 1.2;
background-color: transparent;
margin: 0;
padding: 0;
border: none;
border-radius: 0;
overflow: visible;
}
table {
border-collapse: collapse;
margin: 20px 0;
width: 100%;
}
th, td {
padding: 10px 12px;
border: 1px solid #808080;
}
thead tr {
background-color: #808080;
color: #ffffff;
}
th {
font-weight: bold;
}
tfoot tr {
background-color: #f5f5f5;
font-style: italic;
border-top: 4px solid #808080;
}
span[lang="ja"] {
font-family: "Noto Serif CJK JP", "Source Han Serif JP", "源ノ明朝", "Source Han Serif", "Hiragino Mincho ProN", "Hiragino Mincho Pro", "IPAexMincho", "IPAMincho", "MS PMincho", "MS Mincho", serif;

```

```
}
span[lang="zh-CN"], span[lang="zh-Hans"] {
  font-family: "Noto Serif CJK SC", "Source Han Serif SC", "思源宋体", "Source Han Serif CN", "Source Han Serif", "Songti SC", "FandolSong", "WenQuanYi Bitmap Song", "SimSun", serif;
}
span[lang="zh-TW"], span[lang="zh-Hant"] {
  font-family: "Noto Serif CJK TC", "Source Han Serif TC", "思源宋體", "Source Han Serif TW", "Source Han Serif", "Apple LiSung", "LiSong Pro", "HanaMinA", "PMingLiU", "MingLiU", serif;
}
span[lang="zh-HK"] {
  font-family: "Noto Serif CJK HK", "Source Han Serif HK", "思源宋體 香港", "思源宋體", "Source Han Serif", "Apple LiSung", "LiSong Pro", "HanaMinA", "MingLiU_HKSCS", "PMingLiU", "MingLiU", serif;
}
span[lang="ko"] {
  font-family: "Noto Serif CJK KR", "Source Han Serif KR", "본명조", "Source Han Serif", "AppleMyungjo", "UnBatang", "은바탕", "Batang", serif;
}
ruby {
  ruby-position: over;
  ruby-align: center;
}
rt {
  font-size: 0.55em;
  letter-spacing: 0.05em;
  line-break: strict;
}
rp {
  display: none;
}
hr {
  border: none;
  height: 4px;
  background-color: #808080;
  margin: 20px 0px;
}
```