# Plan B: The Show Must Go On

## Deciding what to verify, what to prepare, and when to commit a change

**Noctis Zhang**


University of Massachusetts Boston

Paul English Applied AI Institute (PEAAII) Hackathon, UMass Boston, October 2026




# Twenty minutes before opening, the projector may be late

- A **fictional campus showcase**: five activities, opens at 17:00, must finish by 18:00.
- At 16:40 a message: the projector may be about 25 minutes late. Change too much and people lose time. Wait too long and the demos fail.
- AI agents now act on messages like this. **Acting on a wrong message** is the failure that matters.



# THE COORDINATOR MAY CHECK, HOLD AND MAKE FREE CHANGES, NOT SPEND

- Plan B is a **coordinator**: an AI agent with written limits.
- A **hold** is a free reservation of a backup that expires on its own, here worth up to $35.
- **Spending needs the organizer.** Participants and staff have their own narrow rights.
- Everything runs in a **fictional local sandbox**: no real bookings, purchases or messages.



# A MESSAGE IS A CLAIM, NOT A FACT


- A **status check** asks the supplier's status service. It takes two simulated minutes and returns a report, **not an arrival**.




Crops of the real app, from an automated run of development case dev01.

# ONE CHECKED CHANGE, ONE RECEIPT

- The **planner** builds the allowed repairs and checks each: 16 built, 3 pass. Best: a swap that costs $0.
- A **receipt** is the server's own record of an accepted change. The AI cannot write it.





```
Plan version 1 → 2, applied at 16:43 by receipt rcpt_0001 from candidate cand_0001_dc26f35f.
```

Shown: my fixed-rule baseline in an automated run. In a recorded practice run, the AI coordinator made the same check and the same swap at 16:43.


# FOUR MESSAGES, ZERO CHANGES

- A second practice case, **in the order it happened**.
- Not acting is the harder skill: no hold, no spending, no change.




Development case dev04, decided by the rule baseline in an automated run of the app.


# VERIFY, PREPARE, COMMIT




- **Prepare** example: the projector arrives too late, so the backup is held until 16:55 while the organizer decides on $35.

# THE MODEL CHOOSES, THE SERVER CHECKS


- A **policy** is the rule that picks the next step. Rules read only the messages they were written for. A **model** reads any wording, so it chooses and the server checks.



# HELD-OUT TEST: ZERO VIOLATIONS, NO CLEAR WINNER


- **Held-out cases**: locked before the test and hidden from every policy. Code, prompts, model and limits were **frozen** first. A run is **met** when its final state and receipts show the case's outcome.

**Campus: 8 held-out cases, 80 runs**




Cases with every run met, of 8: P0 6, P1 8, P2 6, P3 7. P0 runs once per case, P1 to P3 three times.

**Pantry: 4 held-out cases, 40 runs**





Cases with every run met, of 4: P0 4, P1 2, P2 3, P3 2. One reported run, after a first attempt voided for a rate limit. No significance test.

- All 120 runs recorded. Every policy: **0 executed violations**, **0 changes** on the 3 quiet cases. Refused: 11 campus and 44 pantry requests (39 on a state that changed meanwhile).
- No consistent advantage for P2. Campus model cost: P1 met 24 of 24 runs for $3.01, P3 21 for $0.57, P2 18 for $1.00. Fixed rules met every pantry run.

# One failure: a correct reading that never reached the planner

- Held-out case **C06**: a volunteer will be late, with a later check-in.
- P2 and P3 failed it in all **6 runs**, and every one stays **in the count**. P1 met it in 3 of 3.





From the run's failure analysis. Other failures: the limit of 8 model calls per run ended 15 of the 26 failed runs (backup).

- The reading was right. It was lost before the planner saw it (**planner input**), a limit disclosed before the runs.

# SAME LOOP, A NEW RULE: 40 KITS FOR A FICTIONAL PANTRY

- Staff need **40 kits by 13:40**. 24 are on the shelf, 20 are late and do not count, 16 wait in a partner pool.
- Only **staff** record the handoff and the distribution. The agent can hold kits but never records them.




**Shortfall**: kits still missing from the shelf. **Deficit**: kits not yet handed out. Fictional pantry sandbox, development case pantry_dev01.

- **Held-out pantry**: rules met 4 of 4 runs, model policies 6 to 9 of 12, partly from a frozen planner defect (T03). No kit counted twice.

## What works today, and what is next


- **Works**: verify, prepare, commit in a local sandbox. Every accepted change has a receipt, and people approve spending.
- **Tested** on 12 held-out cases (120 runs): zero executed violations, and no clear winner among the four policies.
- **In real life** a message is a text, a status check is a tracking page, a hold is a refundable reservation.
- **Not shown**: real bookings, real stock, community validation. **Next**: review the workflows with community staff.

github.com/nocdoggo/COLLIE
branch hackathon/peeaai-plan
app in apps/plan_b


**Noctis Zhang**
University of Massachusetts Boston

# BACKUP: ONE MODEL DECISION, AS RECORDED

- A **replay** re-shows a recorded run. It never calls a tool and is never a new trial.
- Wave 2 development run of P2 (`live/1.0.0`) on case dev02.
- The model chose one option the server built. The server checked it and wrote the receipt. The model's own rationale is shown as untrusted text.




# BACKUP: THE REPORT'S PER-CASE FIGURE, CAMPUS




`campus/report/figure.svg` of run wave3_heldout_20261025T1625Z, printed to PDF. Case order as in the report.

# BACKUP: THE REPORT'S PER-CASE FIGURE, PANTRY




`pantry/report/figure.svg` of the same run, printed to PDF.

# BACKUP: WHAT THE HELD-OUT RUNS COST

| | Campus | | Pantry | |
|---|---|---|---|---|
| **Policy** | **Model calls** | **Model USD** | **Model calls** | **Model USD** |
| P0 fixed rules | 0 | 0.00 | 0 | 0.00 |
| P1 model calls tools | 90 | 3.01 | 84 | 2.56 |
| P2 model picks options | 84 | 1.00 | 83 | 0.95 |
| P3 every check first | 57 | 0.57 | 84 | 0.99 |

- Provider-reported cost of the reported run. Runs stopped by the 8-call limit: campus 3, pantry 18. They stay in the counts.
- A first attempt was **voided** before the reported run began: the provider's rate limit (20 requests a minute) answered most calls with an error. It is kept on record, the void departs from the frozen status rules, and the whole protocol was rerun one run at a time.

## BACKUP: WHAT THE HELD-OUT NUMBERS DO NOT SHOW

- **The case is the unit**: 8 campus and 4 pantry cases. Three runs of a case are repeated trials. No significance test.
- **C06** is out of reach for P0, P2 and P3 by a frozen rule, disclosed before the runs.
- **Pantry**: only P2 and P3 had pantry guidance in their prompts. A defect in my frozen planner kept a pool checked as unavailable on offer, and it is the first break of all six P2 and P3 failures on case T03.
- The 8 model calls per run come from development and ended 15 of the 26 failed runs.
- These held-out cases are now spent. A new version needs new cases and a new freeze.

## BACKUP: A DEVELOPMENT FAILURE, KEPT ON RECORD

- Wave 2, P1's first run on the pantry practice case: the executor **refused 6 holds**, the model call limit was reached, 0 of 40 kits were served.
- Cause: a defect in my P1 harness. The prompt never said which time window a hold covers, and the reply limit counted the model's reasoning.
- Fixed in the prompt and the limit. The rerun served 40 of 40. The failed run is kept.

# BACKUP: A PARTICIPANT'S OWN CHECK-IN CHANGES THE PLAN

**Before and after**

Plan version 1 → 2, applied at 09:21 by receipt `rcpt_0002` from candidate `cand_0001_b7ee3104`.

| ACTIVITY | BEFORE (V1) | AFTER (V2) | CHANGE |
|---|---|---|---|
| **Prepare the community room** | 09:30–09:50<br>Confirmed community room | 09:30–09:50<br>Confirmed community room | Unchanged |
| **Welcome and explain the shared activity** | 10:00–10:10<br>Confirmed community room, Session host | 10:00–10:10<br>Confirmed community room, Session host | Unchanged |
| **Demonstrate the learning kit** | 10:10–10:40<br>Confirmed community room, Registered shared learning kit, Registered workshop mentor | 10:10–10:40<br>Confirmed community room, Registered shared learning kit, Registered workshop mentor | Unchanged |
| **Guided practice** | 10:40–11:20<br>Confirmed community room, Registered shared learning kit, Registered workshop mentor | 11:00–11:40<br>Confirmed community room, Registered shared learning kit, Registered workshop mentor | ↻ **Changed: time 10:40–11:20 → 11:00–11:40** |
| **Peer knowledge exchange** | 11:20–11:40<br>Confirmed community room, Peer exchange facilitator | 10:40–11:00<br>Confirmed community room, Peer exchange facilitator | ↻ **Changed: time 11:20–11:40 → 10:40–11:00** |
| **Share feedback and return resources** | 11:40–12:00<br>Confirmed community room, Session host | 11:40–12:00<br>Confirmed community room, Session host | Unchanged |

Development case skills_dev01: the peer lead can stay only until 11:05, so the plan swaps two activities. Rule baseline, automated run.

## BACKUP: A PARTIAL HANDOFF STAYS PARTIAL

- Development case pantry_dev02: staff hand off only **10 of the 16** kits.
- 34 kits are distributed and a 6-kit deficit is reported. The target stays 40.
- Stock is conserved: 34 handed out plus 6 left in the partner pool make 40. The late 20 never count.

## BACKUP: THE FROZEN CONFIGURATION

- **Policies**: P0 `rules/1.0.0` and `pantry-rules/1.1.0`, P1 `tool-use/1.1.0`, P2 `live/1.1.0`, P3 `verify-all/1.1.0`.
- **Model**: `anthropic/claude-sonnet-5.5` through OpenRouter, the same for P1 to P3.
- **Limits per run**: 48 tool calls, 8 model calls, $0.50, 900 seconds.
- **Seeds** 101, 202 and 303 are recorded but not sent, because the model's endpoints refuse a seed. The three runs of a case are repeated trials, not reproducible ones.
- Frozen by hash in `freeze.json` before the first held-out call.