## Volume 3

# DSSAT version 3

Editors:

Gordon Y. Tsuji Goro Uehara Sharon Balas IBSNAT, The International Benchmark Sites Network for Agrotechnology Transfer, is a network consisting of the contractor (University of Hawaii), its subcontractors and many global collaborators. Together they have created a network of national, regional and international agricultural research for the transfer of agrotechnology among global partners in both developed and lesser developed countries.

From 1982 to 1987, IBSNAT was a program of the U.S. Agency for International Development under a cost-reimbursement Contract, No. DAN-4054-C-00-2071-00, with the University of Hawaii. From 1987 to 1993, the contract was replaced with a Cooperative Agreement, No. DAN-4054-A-00-7081-00, between the University of Hawaii and USAID.

Correct Citation: G.Y. Tsuji, G. Uehara and S. Balas (eds.). 1994. DSSAT v3. University of Hawaii, Honolulu, Hawaii.

Copyright © University of Hawaii 1994

All reported opinions, conclusions and recommendations are those of the authors (contractors) and not those of the funding agency or the United States govern-

LIBRARY OF CONGRESS 94-19296
ISBN 1-886684-03-0 (VOLUME 3)
ISBN 1-886684-00-6 (3 VOLUME SET)

## DSSAT v3



Volume 3-1
SEASONAL ANALYSIS

VOLUME 3-2
SEQUENCE ANALYSIS

Volume 3-3 WeatherMan

VOLUME 3-4

GENOTYPE COEFFICIENT

CALCULATOR

## TABLE OF CONTENTS

Volume 3-1. Seasonal Analysis	1
Chapter One. Introduction	3
System Requirements	4
CHAPTER TWO. CREATING MODEL INPUT FILES FOR SEASONAL	
ANALYSIS	5
Chapter Three. Running Seasonal Analysis Experiments	13
Overview	13
An Example	14
Information and Error Messages	17
Chapter Four. Analyzing Seasonal Analysis Experiments	23
Overview	23
An Example	24
Analyze Biophysical Variables	26
GRAPHICS MAIN MENU	28
Analyze Economic Variables	34
ECONOMIC EVALUATION MAIN MENU	34
MODIFY HARDCOPY OPTIONS	44
SELECTING ANOTHER INPUT FILE FOR ANALYSIS	48
Information and Error Messages	48
References	55
Appendix A. Combining Yield and Price Distributions	57
AN ILLUSTRATION	58
Appendix B. Three Decision Criteria	59
Mean-Variance (EV) Analysis	59
STOCHASTIC DOMINANCE (SD) ANALYSIS	59
Mean-Gini Dominance (MGD) Analysis	60
An Example	60

#### FIGURES

FIGURE 1. STEPS IN SEASONAL ANALYSIS	4
FIGURE 2. MENU OPTIONS FOR THE SEASONAL ANALYSIS PROGRAM	23
FIGURE 3. STOCHASTIC PRICE-COST DISTRIBUTIONS	38
TABLES	
TABLE 1. SEASONAL EXPERIMENT LISTING FILE EXP.LST	5
TABLE 2. PART OF MODEL INPUT FILE UFGA7812.SNX	7
TABLE 3. SUMMARY OUTPUT LISTING FILE SEASONAL.LST	13
TABLE 4. SUMMARY OUTPUT FILE UFGA7812.SNS (FIRST 20 DATA RECORDS ONLY)	18
TABLE 5. PRICE-COST FILE DEFAULT.PRI	37
TABLE 6. SAMPLE SECTION OF GRAPH.INI	45
TABLE 7. PRINTER TYPES SUPPORTED BY THE GRAPHICS PROGRAM	46
TABLE 8. EXPERIMENT DATA CODES FILE DATA.CDE - SUMMARY SECTION ONLY	47
TABLE 9. PART OF SEASONAL ANALYSIS RESULTS FILE UFGA7812.SNF	<b>?</b> 49

VOLUME 3-2. SEQUENCE ANALYSIS	67
Chapter One. Introduction	69
SYSTEM REQUIREMENTS	70
Chapter Two. Creating Model Input Files for Sequence	
ANALYSIS	73
FILEX FOR SEQUENCE ANALYSIS	73
TIMING CONTROLS	78
SIMULATION CONTROL OPTIONS	79
Chapter Three. Running Sequence Analysis Experiments	81
Overview	81
AN EXAMPLE	82
Information and Error Messages	84
Chapter Four. Analyzing Sequence Analysis Experiments	89
Overview	89
AN EXAMPLE	90
Analyze Biophysical Variables	93
GRAPHICS-REGRESSION MAIN MENU	96
Analyzing More than One Crop at a Time	107
Analyze Economic Variables	112
ECONOMIC EVALUATION MAIN MENU	112
MODIFY HARDCOPY OPTIONS	121
SELECTING ANOTHER INPUT FILE FOR ANALYSIS	126
Information and Error Messages	126
References	133
Appendix. The Stability of Output Variables from	
Replicated Sequence Experiments	135
Figures	
FIGURE 1. STEPS IN SEQUENCE ANALYSIS	71
FIGURE 2. MENU OPTIONS FOR THE SEQUENCE ANALYSIS PROGRAM	90

	FIGURE 3.	. "SIMULATED" SEQUENCE OUTPUTS FOR $N = 100, 20, 10,$	
		AND 5, RESPECTIVELY.	136
T	ABLES		
	TABLE 1.	SEQUENCE EXPERIMENT LISTING FILE EXP.LST	73
	TABLE 2.	A SAMPLE FILEX FOR CROP SEQUENCING: EBAF1101.SQX	<b>(</b> 75
	TABLE 3.	SUMMARY MODEL OUTPUT LISTING FILE SEQUENCE.LST	81
	TABLE 4.	SUMMARY OUTPUT FILE EBAF1101.SQS (FIRST 20	
		DATA RECORDS ONLY)	85
	TABLE 5.	PART OF THE DEFAULT SEQUENCE PRICE FILE, DEFAULT.PRQ	115
	TABLE 6.	SAMPLE SECTION OF GRAPH.INI	123
	TABLE 7.	PRINTER TYPES SUPPORTED BY THE GRAPHICS PROGRAM	124
	TABLE 8.	EXPERIMENT DATA CODES FILE DATA.CDE - SUMMARY	
		Section Only	125
	TABLE 9.	PART OF SEQUENCE ANALYSIS RESULTS FILE EPAF1101.SQR	127

Volume 3-3. WeatherMan	137
Chapter One. Introduction	139
PROGRAM DESCRIPTION	139
Overview of Functions	140
System Requirements	140
CHAPTER TWO. GETTING STARTED	141
STARTING WEATHERMAN	141
WeatherMan User Interface	141
COMMON DIALOG BOXES	144
Steps for Cleaning and Converting Weather Data	147
Chapter Three. Introductory Tutorial	149
Browse the Menu and Online Help	149
SELECT A NEW STATION	149
IMPORT DAILY WEATHER FILES	150
CALCULATE WEATHER GENERATOR PARAMETERS	152
GENERATE WEATHER DATA	152
CALCULATE STATISTICS	153
CALCULATE STATISTICS FOR THE GENERATED DATA	153
GRAPH OBSERVED DAILY TEMPERATURE	153
GRAPH STATISTICS FOR OBSERVED AND GENERATED DATA	154
EXPORT DAILY WEATHER FILES	155
Chapter Four. Weatherman Reference Guide	157
VARIABLES	157
FILE MENU	157
STATION MENU	160
IMPORT/EXPORT MENU	164
GENERATE MENU	173
Analyze Menu	179
OPTIONS MENU	186
QUIT MENU	192

REFERENCES	S	193
APPENDIX A	A. Abbreviations Used in WeatherMan	195
DAILY W	EATHER <b>V</b> ARIABLES	195
SUMMAR	/ FILES	195
Appendix E	3. Climate File Format	197
TABLES		
TABLE 1.	USER INTERFACE ITEMS AND THEIR FUNCTIONS IN	
	WeatherMan	142
TABLE 2.	LIST OF ESSENTIAL STEPS FOR CREATING A COMPLETE DAILY	
	WEATHER DATA FILE WITH THE CORRECT FORMAT AND UNITS	
	FROM RAW DATA IN WEATHERMAN	148
TABLE 3.	WEATHERMAN VARIABLES AND ASSOCIATED UNITS	158
TABLE 4.	Weather Station Information Required for a New	
	STATION	162
TABLE 5.	EXPLANATION OF ERROR CODES USED TO FLAG SUSPECT OR	
	ERRONEOUS DATA	170
TABLE 6.	EXPLANATION OF IMPORT OPTIONS	171
TABLE 7.	EXPLANATION OF EXPORT OPTIONS	175
TABLE 8.	EXPLANATION OF DATA FILL OPTIONS	176
TABLE 9.	EXPLANATION OF STATISTICS TIME GROUPINGS	182

Volume 3-4. Genotype Coefficient	
CALCULATOR	201
Chapter One. Introduction	203
PROGRAM COMPONENTS	203
System Requirements	207
Chapter Two. Getting Started	209
CHAPTER THREE. RUNNING GENCALC	211
DETERMINE GENETIC COEFFICIENTS	211
Discussion	221
References	223
Appendix A. GenCalc Model Requirements	225
Appendix B. Configuration File (DSSATPRO.FLE)	231
Appendix C. Abbreviations	233
FIGURE	
FIGURE 1. GENCALC COMPONENTS	204
TABLES	
TABLE 1. REQUIREMENTS FOR CROP MODELS TO WORK UNDER	
GENCALC	225
TABLE 2. EXAMPLE OF A CULTIVAR (GENOTYPE) COEFFICIENT FILE	227
TABLE 3. EXAMPLE OF THE REQUIRED SECTION OF THE	
OVERVIEW.OUT FILE	228
TABLE 4. EXAMPLE OF AN EXPERIMENT DETAILS FILE	229
TABLE 5. EXAMPLE CONTENTS OF THE DSSATPRO.FLE FILE	232

## VOLUME 3-1



P.K. Thornton, G. Hoogenboom, P.W. Wilkens, J.W. Jones

# CHAPTER ONE. INTRODUCTION

The Seasonal Analysis program allows the user to perform comparisons of simulations obtained by running the DSSAT v3 crop models with different combinations of inputs. A simulation experiment, which may be made up of many treatments and may be replicated through time using different weather years, is set up by the user, the models are run, and the user can then analyze the results using the seasonal analysis program. The "seasonal" aspect of the driver and analysis programs relates to the fact that what is being run are experiments of single cropping seasons; while these may be replicated, there are no carry-over effects from one season or crop to the subsequent season or crop. Those types of experiments can be simulated and analyzed using the sequence driver and analysis programs (see Volume 3-2, Thornton et al. 1994, of this book for a description of these programs).

Seasonal Analysis is useful for comparing methods of managing a crop in particular environments, such as different planting dates, varieties, or fertilizer application regimes, for example. If such comparisons are made across many different types of weather years, then the variability associated with crop performance, as a function of the interactions between weather and other factors of the physical environment, can be isolated and quantified. The information produced can be used to help pre-screen a wide variety of different options, the most promising of which might then warrant further evaluation and, eventually, field testing.

There are three basic steps involved in Seasonal Analysis:

- 1. The creation of an appropriate model input file;
- 2. Running the crop model(s) using a special controller program called the seasonal

analysis driver;

3. Analyzing the results of the simulation using the Seasonal Analysis program.

The links between these steps are shown in Figure 1. Seasonal analyses are run from the DSSAT v3 Shell (see Volume 1-3, Hunt et al. 1994, of this book) under the menu item ANALYSES. The three steps are explained in Chapter 2 herein.




FIGURE 1. STEPS IN SEASONAL ANALYSIS.

#### System Requirements

The useable portion of your system's 640 Kb RAM should be at least 520 Kb in size for the models to run and for the analysis program and graphics to work.

If the driver or analysis program still does not work properly, one problem may be associated with the number of BUFFERS and FILES defined in CONFIG.SYS. These will need to be set to at least 20 each.

Replicated seasonal simulations on an 8086 or 80286 system may take a great deal of time. In such cases, the number of replicates should be kept to a minimum. Seasonal analysis, like the rest of the DSSAT3, will operate without a math coprocessor, but this is not recommended

# CHAPTER TWO. CREATING MODEL INPUT FILES FOR SEASONAL ANALYSIS

The program XCreate (see Volume 1-4, Imamura 1994, of this book for a description of this program) can be used to create model input files (FILEXs) for running seasonal analyses. (For a description of FILEX, see Volume 2-1, Jones et al. 1994, of this book.) Alternatively, these files can be created using an ASCII text editor. The advantage of using the program XCreate is that the experiment listing file EXP.LST is updated automatically (see Volume 2-1, Jones et al. 1994, of this book for a description of EXP.LST). If you create a seasonal analysis FILEX yourself using an ASCII editor, then you must either update EXP.LST yourself, or run the File Manager Utility program (by opening the SEASONAL — "Inputs" menu items of the DSSAT v3 Shell) for the FILEX to be accessible to the seasonal analysis driver.

Seasonal analysis model input files created with XCreate have the extension SNX. You may also put FILEXs that refer to a particular crop in EXP.LST, using the "Experiment" option mode of FILEX creation found in the XCreate program. Thus you could run a FILEX called UFGA9201.MZX, as long as this file was listed in the listing file EXP.LST in the directory that contains the seasonal analysis input files, which is usually DSSAT3\SEASONAL (see Table 1 for an example of the EXP.LST file).

#### TABLE 1. SEASONAL EXPERIMENT LISTING FILE EXP.LST.

\*EXPERIMENT LIST

- @# FILENAME EXT ENAME
- 1 UFGA7801 SNX GAINESVILLE, SOYBEAN, IRRIGATED AND RAINFED
- 2 UFGA7802 SNX EXAMPLE SEASONAL ANALYSIS, SB+MZ
- 3 UFGA7805 SNX PLANTING DATE EXPERIMENT, 1978 BRAGG, GNV
- 4 UFGA8201 SNX GAINESVILLE, FLORIDA, MAIZE, IR\*N-FERT
- 5 UFGA7812 SNX GAINESVILLE, FLORIDA, SB IRRIGATION EXPERIMENT

An example of a seasonal analysis FILEX is shown in Table 2. Though not all of the SIMULATION CONTROL blocks of FILEX appear in Table 2, you can print a full listing of this file, UFGA7812.SNX, found on the DSSAT v3 distribution diskette. Refer to the shaded portions in Table 2 when reading the following paragraphs.

In the \*TREATMENTS section of the file, treatments are specified as for a regular experiment. You need to ensure that the treatment numbers are in ascending, consecutive order (treatment numbers are specified in the two columns with header @N). In Seasonal Analysis, the options "R," "O" and "C" should always be left at their default values of 1, 0 and 0, respectively.

Because the example experiment UFGA7812SN is a comparison of automatic irrigation schedules, the example found in Table 2 requires 6 simulation control sections, as specified by the simulation control factor levels SM, under \*TREATMENTS.

In the \*SIMULATION CONTROLS blocks in Table 2, there are a number of simulation control options that are generally important for Seasonal Analyses. These are described as follows.

#### **NYERS**

NYERS is the number of replicates for the experiment and should have a value between 1 and 30. You may need to check the availability of historical weather data files if you are running a number of replicates and the weather data switch WTHER (one of the METHODS options found in the \*SIMULATION CONTROLS block) is set to "M" (measured). In this case, make sure that you have at least NYERS+1 complete years of historical weather data available. Most often, seasonal analyses are run using simulated weather with this switch set to "W" (as set in Table 2) or "S." "W" is for the WGEN (Richardson and Wright 1984) weather generator and "S" is for the SIMMETEO (Geng et al. 1988) weather generator. In either of these cases, the climate file for the site (with extension CLI) will be used by the model.

#### **NREPS**

NREPS should be left at the default value of 1. It has no meaning for Seasonal Analysis.

#### **RSEED**

RSEED is the random number seed for weather generation. RSEED is used only if the WTHER option is set to "W" or "S." If you start a simulation from the same starting date (SDATE) with the same seed, you will obtain the same sequence of random numbers, and hence the same sequence of daily weather.

#### TABLE 2. PART OF MODEL INPUT FILE UFGA7812.SNX.

\*EXP.DETAILS: UFGA7812SN GAINESVILLE, FLORIDA, SB IRRIGATION EXPERIMENT

*TREATMENTS @N R O C TNAME 1 1 0 0 RAINF 2 1 0 0 AUTOM 3 1 0 0 AUTOM 4 1 0 0 AUTOM 5 1 0 0 AUTOM 6 1 0 0 AUTOM	ED ATIC 90 ATIC 70 ATIC 50 ATIC 30	) % ) % ) % ) %		1 1 1	-FAC FL SA 1 1 0 1 0 1 0 1 0 1 0 1 0		MI MF 1 0 0 0 0	MT ME 0 0 0 0 0 0 0 0 0 0 0 0	MH SM 0 1 0 2 0 3 0 4 0 5 0 6	
*CULTIVARS  @C CR INGENO CI  1 SB IB0001 B										
*FIELDS @L ID_FIELD WS' 1 UFGA0001 UF				FLDT IB000					ID_SOII IBSB91	
*INITIAL CONDT' @C PCR ICDAT 1 SB 78166 @C ICBL SH20 1 5 0.086 1 15 0.086 1 30 0.086 1 45 0.086 1 60 0.086 1 90 0.076 1 120 0.076 1 150 0.130 1 180 0.258	ICRT 100 SNH4 0.6 0.6 0.6 0.6 0.6 0.6	ICND -99 SNO3 1.5 1.5 1.5 1.5 0.6 0.5 0.5		ICRE 1.00						
*PLANTING DETA @P PDATE EDATE 1 78166 -99	PPOP			PLDS R		PLRD 0			PENV -99.0	
*RESIDUES AND @R RDATE RCOD 1 78166 IB001	RAMT 1000	RESN	RESP	RESK	RINP 100	RDEP 15				
@N GENERAL  1 GE @N OPTIONS 1 OP @N METHODS 1 ME	NYERS 20 WATER Y	1 NITRO Y INCON	S SYMBI Y LIGHT	78166 PHOSP N EVAPO	9875 POTAS N INFIL	DISES N PHOTO		 		
@N MANAGEMENT 1 MA @N OUTPUTS 1 OU	R	OVVEW	R SUMRY	R FROPT	M		WATER N		DISES	LONG N

@	AUTOMATIC M	ANAGEMI	ENT									
	PLANTING			PH2OL	PH2OU	PH2OD	PSTMX	PSTMN				
	PL		200					10				
@N	IRRIGATION							IREFF				
	IR	30		100				0.75				
@N	NITROGEN											
	NI	30			IB001							
@N	RESIDUES	RIPCN	RTIME	RIDEP								
	RE	100										
@N	HARVEST	HFRST	HLAST	HPCNP	HPCNR							
	НА		365									
@N	GENERAL	NYERS	NREPS	START	SDATE	RSEED	SNAME					
2	GE	20	1	S	78166	9875						
@N	OPTIONS	WATER	NITRO	SYMBI	PHOSP	POTAS	DISES					
	OP		Y			N						
@N	METHODS	WTHER	INCON	LIGHT	EVAPO	INFIL	PHOTO					
	ME	W					С					
@N	MANAGEMENT	PLANT	IRRIG	FERTI	RESID	HARVS						
2	MA	R	A	R	R	M						
@N	OUTPUTS	FNAME	OVVEW	SUMRY	FROPT	GROTH	CARBN	WATER	NITRO	MINER	DISES	LONG
	OU										N	N
@	AUTOMATIC M	ANAGEMI	ENT									
@N	PLANTING							PSTMN				
_	PL		200					10				
	IRRIGATION											
2	IR NITROGEN	30	90	100	IB001	IB001	10	0.75				
		NMDEP	NMTHR									
	NI	30			IB001	IB001						
@N	RESIDUES	RIPCN	RTIME	RIDEP								
	RE	100	1									
	HARVEST											
2	HA	0	365	100	0							
63-	CHAIRD 3.7		MDED =	G	an	Darre	C) 17.14					
	GENERAL						SNAME				• •	
	GE	20			78166							
	OPTIONS		NITRO									
	OP		Υ		N							
(A)TA	METHODS	WTHER	INCON									
						S	C					
6	ME	W					· ·					
6 @N	MANAGEMENT	PLANT	IRRIG	FERTI	RESID	HARVS	0					
6 @N 6	MANAGEMENT MA	PLANT R	IRRIG A	FERTI R	RESID R	HARVS M					D. C.	
6 @N 6 @N	MANAGEMENT	PLANT R	IRRIG A OVVEW	FERTI R SUMRY	RESID R	HARVS M	CARBN				DISES N	

@	AUTOMATIC M	ANAGEMI	ENT					
@N	PLANTING	PFRST	PLAST	PH2OL	PH2OU	PH2OD	PSTMX	PSTMN
6	PL	155	200	40	100	30	40	10
@N	IRRIGATION	IMDEP	ITHRL	ITHUR	IROFF	IMETH	IRAMT	IREFF
6	IR	30	10	100	IB001	IB001	10	0.75
@N	NITROGEN	NMDEP	${\tt NMTHR}$	NAMNT	NCODE	NAOFF		
6	NI	30	50	25	IB001	IB001		
@N	RESIDUES	RIPCN	RTIME	RIDEP				
6	RE	100	1	20				
@N	HARVEST	HFRST	HLAST	HPCNP	HPCNR			
6	HA	0	365	100	0			

#### **FNAME**

FNAME is one of the OUTPUTS switches found in the \*SIMULATION CONTROLS blocks. If this switch is set to "N," then the summary output file from the model runs will be named SUMMARY.SNS. If FNAME is set to "Y," then the summary output file name will be the same as the model FILEX name, except that the last letter of the extension will be changed from "X" to "S." Thus, for the experiment FILEX shown in Table 2 which has the name UFGA7812.SNX, the summary output file will be named UFGA7812.SNS since the switch FNAME is set to "Y."

#### **SUMRY**

SUMRY is one of the OUTPUTS switches found in the \*SIMULATION CONTROLS blocks. For seasonal simulations, this controller should always be set to "A" (append); otherwise the summary output file will be successively overwritten by each treatment and earlier outputs will be lost. In Table 2, the other OUTPUT switches are set to "N" to prevent within-season output from the models. Since seasonal simulations with many replicates can produce prodigious quantities of output data, it makes sense to turn these output files off, unless you need them specifically.

You should note that if there are multiple simulation control sections in FILEX, then the driver program will use the values of NYERS, WTHER, RSEED, FNAME and SUMRY that pertain to the lowest valid simulation control level in the file. In other words, the value of NYERS, the number of replicates, in the lowest simulation control factor level (SM=1), is used for all other treatments; in Table 2, for example, NYERS is set to 20. You could not, therefore, run an experiment that has 4 replicates for Treatment 1 and 10 replicates for Treatment 2, for instance; this would not make much sense anyway.

For the specific experiment in Table 2, the first treatment is set up as a rainfed treatment (see \*TREATMENTS). Thus the IRRIG switch, which is a MANAGE-MENT option in the \*SIMULATION CONTROLS block is set to "N" for "no irrigation" in block 1(i.e., N=1).

For subsequent treatments, automatic irrigation is to be applied, but the threshold at which water is applied, in terms of the percentage of soil water in the profile, is changed; this is the primary experimental variable. In the second \*SIMULATION

CONTROLS block (i.e., N=2) in Table 2, the IRRIG switch is set to "A" for "automatic". The corresponding information in the AUTOMATIC MANAGEMENT section of the file, under IRRIGATION, shows that IMDEP is set to 30 and ITHRL to 90. Thus irrigation will be applied automatically when available soil water is less than or equal to a value of 90 percent (ITHRL) of what the soil can hold in the top 30 cm of the profile (IMDEP).

Compare this with the \*SIMULATION CONTROLS block number 6 (i.e., N=6)) where, under AUTOMATIC MANAGEMENT, ITHRL has a value of 10 (i.e., the soil water trigger will operate when available water reaches 10 percent of field capacity in the top 30 cm). Note that all other switches in each of the SIMULATION CONTROLS blocks in Table 2 are the same.

In general, you may mix crops in a seasonal analysis FILEX. Thus you can compare performance of different crops in the same experiment. Treatment 1 might involve maize, and Treatment 2 dry bean, for example.

# CHAPTER THREE. RUNNING SEASONAL ANALYSIS EXPERIMENTS

#### OVERVIEW

The seasonal analysis driver program takes the FILEX selected or created by the user, and runs through each treatment in the experiment, calling the appropriate crop model. It is very important to understand that the seasonal driver can be used for any experiment that does not involve a sequence. Thus, as far as the driver is concerned, it makes no difference if FILEX describes a real 10-treatment single year experiment, or if it describes a hypothetical 4-treatment simulation experiment to be replicated twenty times. The driver can thus be used to generate replicated experiment output files, or it may simply be used to run all the treatments pertaining to a real-world experiment automatically.

The driver is a FORTRAN program that allows the user to pick a specific entry from EXP.LST (i.e., a particular FILEX; see Volume 2-1, Jones et al. 1994, of this book for a description of EXP.LST). This FILEX is then read and various controls are set. Each treatment specified in this FILEX is then run in its order of appearance in the \*TREATMENTS section of the FILEX. The appropriate model is called for each treatment (the model is run under the command of the driver program), and it will be run for as many replicates as are specified by NYERS in the FILEX. When all the treatments of the selected simulation or real-world experiment have been run, the results listing file SEASONAL.LST (see the example in Table 3) is updated with the name and description of the summary output file produced. The user can then quit the program or choose another FILEX for running with the seasonal driver.

The seasonal driver can be run in a stand-alone mode or through the DSSAT v3 Shell (see Volume 3-1, Hunt et al. 1994, of this book for a description of the Shell).

#### TABLE 3. SUMMARY OUTPUT LISTING FILE SEASONAL.LST.

\*SEASONAL LIST

@# FILENAME EXT ENAME

- 1 UFGA7801 SNS GAINESVILLE, SOYBEAN, IRRIGATED AND RAINFED
- 2 UFGA7802 SNS EXAMPLE SEASONAL ANALYSIS, SB+MZ
- 3 UFGA7812 SNS GAINESVILLE, FLORIDA, SB IRRIGATION EXPERIMENT

It is important to note that in whichever mode the driver is run, the program expects to find all the model program(s) in the same directory. In the case of the DSSAT v3 Shell, this will generally be the C:\DSSAT3 directory. If model executable files are not found in that directory, then an error message is printed and the user must arrange the executable files so that this condition is met. The file DSSATPRO.FLE (see the Appendix to Volume 1 of this book for a description of this file) is also expected to be in this same directory, with appropriate pointers to the relevant directories.

From within DSSAT v3, the current directory for seasonal runs will generally be DSSAT3\SEASONAL, where such files as EXP.LST, SEASONAL.LST and appropriate FILEXs are stored.


The file EXP.LST may contain up to 99 experiments, a limit imposed by the file structure. Up to 99 treatments may be simulated using the driver (again a limit imposed by FILEX), but it should be noted that the seasonal analysis program has a limit of handling a maximum of 20 treatments and 30 replicates (i.e., a total of 600 separate model runs).

#### An Example


On activating the "Simulate" option under the "Seasonal" window (Screen 1, following page) from the DSSAT v3 Shell main menu item ANALYSES, the driver program is activated, and after an introductory screen the user is presented with the following screen (Screen 2, following page). Screen 2 contains the contents of the file EXP.LST, the listing file in the current directory of selected FILEXs for seasonal analysis. This lists the file name, crop group code (generally "SN" for seasonal analysis, although it may be any valid crop code), and a file description. The description may be up to 60 characters long; if it is shorter, the description is padded with full stops. The file description is obtained from columns 26 through 85 of the first line of FILEX (see Table 2).

If the colors on the screen are difficult to see (such as when the program is being run on a monochrome laptop computer), you can force the program to display screens in monochrome by pressing the <ALT>-<F2> keys. Note that you cannot reverse the color scheme during a session with the program, nor is your preference stored from one session to another.

Use the mouse or cursor arrow keys to choose the Gainesville soybean irrigation experiment FILEX, UFGA7812.SNX (used in the example in Table 2). If the chosen FILEX cannot be found, an error message is printed on the screen, and the menu reappears for making another choice.



#### SCREEN 1.



SCREEN 2.

Once a valid FILEX name is selected, the driver checks to see if there is an existing output file with the same name in the current directory (this is controlled within FILEX, see above). If there is, then the user is warned that the output file will be overwritten. Press <Y> to continue regardless, or <N> to quit the program to allow you to rename or move the existing output file.

Once past Screen 2, the driver will issue appropriate commands and call up the crop model(s). The initial model-produced screen warns the user not to touch the keyboard. Once simulations are under way, each model run is summarized on the screen, so that the user can chart progress of the experiment (Screen 3, below, shows the first 20 simulations associated with model input file UFGA7812.SNX). Experiments with many treatments and/or many replicates may take a great deal of time to simulate, especially on older personal computers. No keyboard input should be made, unless an error occurs, until the simulations have finished.

To abort the simulation runs before they have finished, press the <ESC> key or <CTRL-BREAK>.

For each FILEX simulated, the driver updates or creates a listing file which stores the names of the summary results files (in similar fashion to EXP.LST, which stores the names of available FILEXs in the current directory). This file, SEASON-AL.LST, is of the same format (Table 3), and is used by the analysis program described in the next section. Two other messages may appear on the final screen:

RUN	TRT		TAM		SEEDW	TRAIN	TIRR	CET	PESW	TNUP	TNLC	TNLF	TSON	TSOC
					kg/ha	mm	mm	mm	mm	}	kg/ha-		kg/ha	t/ha
1	SB 1	47	116	5880	2905	849	0	446	141	18	21	27	3836	39
2	SB 1	46	118	7489	3565	834	0	509	84	18	1.9	27	3838	39
3	SB 1	46	116	6692	3166	904	0	489	117	18	21	27	3836	39
4	SB 1	46	121	5931	2939	502	0	452	138	34	3	28	3837	39
5	SB 1		117	7175	3602	718	0	491	135	26	14	28	3834	39
6	SB 1		119	5802	2942	833	0	479	111	17	19	28	3838	39
7	SB 1	47	119	6203	3415	611	0	466	141	27	8	30	3837	39
8	SB 1	47	118	6392	3210	513	0	455	90	30	6	29	3837	39
9	SB 1	46	119	6986	3280	872	0	486	92	17	23	26	3835	39
10	SB 1	46	116	6980	3214	557	0	487	71	23	. 9	31	3838	39
11	SB 1	47	118	6632	3329	445	0	449	115	34	1	29	3837	39
12	SB 1	46	118	5566	2808	462	0	446	92	29	4	29	3839	39
13	SB 1		117	6403	3253	819	0	501	125	19	1.7	29	3836	39
14	SB 1	46	116	6448	3140	527	0	432	80	24	8	31	3838	39
15	SB 1	47	117	7030	3457	803	0	481	101	24	18	26	3835	39
16	SB 1	46	117	6900	3388	534	0	473	89	28	7	31	3836	39
17	SB 1	46	117	4905	2287	493	0	423	157	29	3	31	3839	39
18	SB 1	46	117	7110	3521	828	0	517	144	23	17	29	3833	39
19	SB 1	46	117	6787	3479	684	0	478	86	20	15	29	3838	39
. 20	SB 1	46	113	4863	1798	689	0	412	98	16	17	27	3841	39

SCREEN 3.

- 1. If FNAME was set to "N," then the summary output file produced by the model(s), SUMMARY.OUT, was renamed to SUMMARY.SNS; the program tells you that this has been done;
- 2. If the summary output file of the appropriate name does not appear in SEA-SONAL.LST, then SEASONAL.LST is updated, and the program tells you that this has been done.

Press any key to continue. You will then be asked if you want to run another experiment. Respond by pressing the <N> or <ENTER> keys to exit the program, or the <Y> key to return to the opening screen showing file EXP.LST, where another experiment can be chosen and simulated (see Screen 2). You may simulate as many FILEXs as you like, one after the other, without exiting the driver program.

Simulation results are stored in the summary output file, in this example UFGA7812.SNS. The first 20 simulation records of this file are shown in Table 4.

#### INFORMATION AND ERROR MESSAGES

A number of information and error messages are produced by the driver program. In the list that follows, each message is preceded by a single-digit code and a three digit message/error number. If the single-digit code is "0," then this is a fatal error, and the program exits. If the code is "1," then the program will continue, as the error may not be fatal. Information messages have code "1" also.

0 001 Cannot find experiment file.

The FILEX experiment listing file could not be found in the current directory.

0 002 No entries found in file.

The FILEX experimental listing file was found, but it contains no valid entries.

1 003 Cannot find file:

The specified file cannot be found (non-fatal).

0 004 Error reading:

An undefined read error occurred when attempting to read the file. The problem is usually caused by incorrect format of the file.

0 005 No valid treatments found in file.

No valid treatments were found in the FILEX selected.

#### TABLE 4. SUMMARY OUTPUT FILE UFGA7812.SNS, FIRST 20 DATA RECORDS ONLY.

Columns 1-86

\*SUMMARY : UFGA7812SN GAINESVILLE, FLORIDA, SB IRRIGATION EXPERIMENT

!IDI	ENT:	IFIE	RS.			DATES.					DRY W	EIGHTS.
@RP	TN	ROC	CR	TNAM	FNAM	SDAT	PDAT	ADAT	MDAT	HDAT	DWAP	CWAM
1	1	100	SB	RAINFED	UFGA0001	78166	78166	78213	78282	78294	67	5880
2	1	100	SB	RAINFED	UFGA0001	79166	79166	79212	79284	79296	67	7489
3	1	100	SB	RAINFED	UFGA0001	80166	80166	80212	80282	80294	67	6692
4	1	100	SB	RAINFED	UFGA0001	81166	81166	81212	81287	81299	67	5931
5	1	100	SB	RAINFED	UFGA0001	82166	82166	82212	82283	82295	67	7175
6	1	100	SB	RAINFED	UFGA0001	83166	83166	83213	83285	83297	67	5802
7	1	100	SB	RAINFED	UFGA0001	84166	84166	84213	84285	84297	67	6203
8	1	100	SB	RAINFED	UFGA0001	85166	85166	85213	85284	85296	67	6392
9	1	100	SB	RAINFED	UFGA0001	86166	86166	86212	86285	86297	67	6986
10	1	100	SB	RAINFED	UFGA0001	87166	87166	87212	87282	87294	67	6980
11	1	100	SB	RAINFED	UFGA0001	88166	88166	88213	88284	88296	67	6632
12	1	100	SB	RAINFED	UFGA0001	89166	89166	89212	89284	89296	67	5566
13	1	100	SB	RAINFED	UFGA0001	90166	90166	90213	90283	90295	67	6403
14	1	100	SB	RAINFED	UFGA0001	91166	91166	91212	91282	91294	67	6448
15	1	100	SB	RAINFED	UFGA0001	92166	92166	92213	92283	92295	67	7030
16	1	100	SB	RAINFED	UFGA0001	93166	93166	93212	93283	93295	67	6900
17	1	100	SB	RAINFED	UFGA0001	94166	94166	94212	94283	94295	67	4905
18	1	100	SB	RAINFED	UFGA0001	95166	95166	95212	95283	95295	67	7110
19	1	100	SB	RAINFED	UFGA0001	96166	96166	96212	96283	96295	67	6787
20	1	100	SB	RAINFED	UFGA0001	97166	97166	97212	67279	97291	67	4863

Columns 87-176

						.WATER							.NITRO	GEN
HWAM	HWAH	BWAH	HWUM	H#AM	H#UM	IR#M	IRCM	PRCM	ETCM	ROCM	DRCM	SWXM	NI#M	NICM
3565	3565	3924	171	2083	2.05	0	0	834	509	35	365	84	0	0
3166	3166	3526	143	2218	2.05	0	0	904	489	38	419	117	0	0
2939	2939	2992	163	1806	2.05	0	0	502	452	1	70	138	0	0
3602	3602	3573	183	1972	2.05	0	0	718	491	8	243	135	0	0
2942	2942	2860	174	1695	2.05	0	0	833	479	11	390	111	0	0
3415	3415	2788	165	2070	2.05	0	0	611	466	13	150	141	0	0
3210	3210	3181	166	1934	2.05	0	0	513	455	9	117	90	0	0
3280	3280	3706	177	1849	2.05	0	0	872	486	22	431	92	0	0
3214	3214	3766	171	1878	2.05	0	0	557	487	5	153	71	0	0
3329	3329	3304	170	1953	2.05	0	0	445	449	1	39	115	0	0
2808	2808	2759	163	1719	2.05	0	0	462	446	1	81	92	0	0
3253	3253	3149	162	2013	2.05	0	0	819	501	43	309	125	0	0
3140	3140	3309	142	2213	2.05	0	0	527	432	27	145	80	0	0
3457	3457	3573	175	1973	2.05	0	0	803	481	13	365	101	0	0
3388	3388	3512	161	2104	2.05	0	0	534	473	3	128	89	0	0
2287	2287	2618	155	1474	2.05	0	0	493	423	4	68	157	0	0
3521	3521	3588	169	2081	2.05	0	0	828	517	20	305	144	0	0
3479	3479	3308	184	1894	2.05	0	0	684	478	27	252	86	0	0
1798	1798	3064	105	1705	2.05	0	0	689	412	29	309	98	0	0

Columns 177-252

						ORGANIC MATTER			PHOSPHORUS				
NFXM	NUCM	NLCM	NIAM	CNAM	GNAM	RECM	ONAM	OCAM	PO#M	POCM	CPAM	SPAM	
280	18	21	27	214	185	1000	3836	39	0	0	0	0	
337	18	19	27	265	227	1000	3838	39	0	0	0	0	
302	18	21	27	235	202	1000	3836	39	0	0	0	0	
288	34	3	28	220	187	1000	3837	39	0	0	0	0	
321	26	14	28	263	229	1000	3834	39	0	0	0	0	
292	17	19	28	219	187	1000	3838	39	0	0	0	0	
310	27	8	30	250	217	1000	3837	39	0	0	0	0	
301	30	6	29	241	204	1000	3837	39	0	0	0	0	
329	17	23	26	251	209	1000	3835	39	0	0	0	0	
313	23	9	31	243	205	1000	3838	39	0	0	0	0	
308	34	1	29	249	212	1000	3837	39	0	0	0	0	
282	29	4	29	207	179	1000	3839	39	0	0	0	0	
308	19	17	29	238	207	1000	3836	39	0	0	0	0	
303	24	8	31	240	200	1000	3838	39	0	0	0	0	
316	24	18	26	256	220	1000	3835	39	0	0	0	0	
311	28	7	31	251	216	1000	3836	39	0	0	0	0	
254	29	3	31	176	146	1000	3839	39	0	0	0	0	
324	23	17	29	262	224	1000	3833	39	0	0	0	0	
331	20	15	29	260	222	1000	3838	39	0	0	0	0	
240	16	17	27	150	115	1000	3841	39	0	0	0	0	

#### 0 006 Error in \*SIMULATION CONTROL factor levels.

The FILEX specified by the user is defective in one of the following ways: a) FNAME was not set or not found; b) NREPS was not set or not found; or c) the simulation control factor level with the lowest number specified by the user did not have a corresponding \*SIMULATION CONTROLS block in the file.

#### 0 007 Error in \*CULTIVAR factor levels in file:

A cultivar factor level was specified in the selected FILEX that did not have a corresponding cultivar description in the \*CULTIVARS section of the file.

- 1 008 Model runs completed!
- 1 009 SUMMARY.OUT renamed to SUMMARY.SNS.
- 1 010 SEASONAL.LST updated, added file.

Specified summary output file added to the listing file.

#### 0 011 A required file was not found .. aborting.

This usually refers to the absence of the file DSSATPRO.FLE, which could not be found.

#### 0 012 Excessive path length error.

You need to reduce the path length as specified in DSSATPRO.FLE for the crop model "cc" (e.g. MZ). Path lengths as specified in the DSSATPRO.FLE must be less than 36 characters in total length, including drive letter, colon, and leading and trailing slashes (\). If these paths are modified using the SETUP menu of the DSSAT v3 Shell (see Volume 1-3, Hunt et al. 1994, of this book for a description of the SETUP menu), then there is no problem, as the screens will not allow you to enter paths longer than this. If you modify DSSATPRO.FLE with a text editor, then you need to ensure that this total length is not exceeded.

#### 0 013 No code error.

The crop code specified (e.g. MZ) could not be found in the file DSSATPRO.FLE. This will occur if a cultivar is specified in FILEX that does not have a valid crop code.

#### 0 014 Read error in file:

An undefined read error occurred when reading the specified file; check the format of the file.

0 020 A problem was encountered executing another program. The driver was not able to execute another program. Check the free RAM that you have on your computer, and increase it if possible by unloading unnecessary resident programs (e.g., a network).

0 021 A problem was encountered erasing a file. The specified file could not be erased.

0 022 A problem was encountered copying a file. The specified file could not be copied successfully.

1 055 Problem in finding the appropriate help screen. The required help screen or the help screen file, SEADRV.HLP, could not be found.

1 100 Error! Undetermined error.

#### CHAPTER FOUR.

#### ANALYZING SEASONAL ANALYSIS EXPERIMENTS

#### OVERVIEW

Having produced a summary simulation output file from a seasonal experiment, the next step is to analyze this and compare treatments (these treatments may or may not be replicated, but in seasonal analysis there will usually be a number of replicates). A brief overview of the analysis program's capabilities follows, together with some general usage notes. It should be noted that the analysis program can handle a maximum size of 30 replicates or 20 treatments.

Figure 2 shows the major menu options available. The program does the following.

Biophysical Analysis. Calculates means, standard deviations, maxima and minima by treatment for any or all of the 35 summary output file variables. These can be plotted as box plots, cumulative function plots, or as mean-variance diagrams. All graphs can be screen dumped to a printer or output to a file for plotting.

Economic Analysis. Calculates means, standard deviations, maxima and minima by treatment of economic returns, and plots these as box plots, cumulative function plots, or mean-variance diagrams. Prices and costs can be changed within a session, and price-cost variability can be included in the analysis.




FIGURE 2. MENU OPTIONS FOR THE SEASONAL ANALYSIS PROGRAM.

Formal strategy evaluation of all treatments, if required, is carried out using mean-Gini stochastic dominance (see Appendix B herein).


Any number of summary output files can be analyzed during one session with the program. The user can also control the type and format of hardcopy outputs from the graphics produced.

While these analyses are being performed, results are written to a results file. At the completion of the session, the user can access this file and use the data contained within in any way required. For example, it could be edited for importing into a graphics, spreadsheet or statistics program.


#### AN EXAMPLE

The Seasonal Analysis program is called from the ANALYSES main menu of the DSSAT v3 Shell (Screen 4, below) and then from the "Seasonal"—"Analyze" submenus. After an introductory screen, the main menu appears on Screen 5 (on following page).

First you must select a cropping season file to analyze (i.e., a summary output file from a previously-run simulation). On selecting this item, the program searches SEASONAL.LST, the listing file that contains the available model summary output files in the current directory (see Table 3). These are presented to the user (see Screen 6, on following page). Note that the entries in SEASONAL.LST do not



SCREEN 4.



SCREEN 5.

have to match the entries in EXP.LST, either in number or in order; you may have run and analyzed the experiments in a different order, for example.

As for the driver program, if the colors on the screen are difficult to see (such as when the program is being run on a monochrome laptop comput-

	EXT ENAME -			
			ATED AND RAINFED . SB+MZ	
		-	RIGATION EXPERIMEN	
Exit				

SCREEN 6.

er), you can force the program to display screens in monochrome by pressing the <ALT>-<F2> keys. Again, note that you cannot reverse the color scheme during a session with the program, nor is your preference stored from one session to another.


Use the mouse or cursor keys to select the third file, UFGA7812.SNS, in Screen 6. After the file is selected, the program gives the user the opportunity to change the name of the analysis results file. By default, this file name will be the same as the summary output file, except the last letter of the extension will be "R" (for "results"). Note that file names are preserved across all three steps of the seasonal analysis procedure: if the model FILEX is UFGA7812.SNX, then simulation results from the model(s) are saved in UFGA7812.SNS, and analysis results in UFGA7812.SNR. If you want to change the results file name, enter a new name (8 characters maximum). Do not add the extension; this is added automatically, and cannot be changed, and will always be "ccR" where "cc" is the crop code (usually SN for seasonal analysis).

The next screen presented (Screen 7, on following page) summarizes the simulation runs found in the chosen summary output file. The experiment code, crop group and file title are displayed, with a treatment-by-treatment listing of treatment title, file ID, the number of replicates, and the appropriate crop pertaining to each treatment. If there are problems with the summary output file, for instance an unequal number of replicates because of model failure for some reason in some treatments, these problems will usually be apparent at this stage. Such errors are usually trapped by the analysis program and result in a warning message to the user and termination of the program.


Press any key to continue, and the main menu of the Analysis program appears again (Screen 5). The items in this menu are illustrated in turn.

# Analyze Biophysical Variables

On choosing the main menu option, "Analyze Biophysical Variables," in Screen 5, with the mouse or cursor keys, a list of the variables available for analysis appears (Screen 8, on following page). This is a listing of all the 35 output variables written to the summary output file. You can scroll up and down this list using the  $<\neq>$  and  $<\varnothing>$  keys on the keyboard. Choose variable number 9, "HAR YIELD kg/ha (i.e., harvest yield)," in Screen 8 by placing the cursor bar over the variable in the list and select it by pressing the space bar. A tick mark in the bracket to the right of the variable indicates that this is the variable selected. The space bar can be used to toggle the selection off and on.



SCREEN 7.



SCREEN 8.

	Varia	ble :	HAR YIEL	D kg/ha		
Treatment	Field	Crop	Mean	St.Dev.	Min	Max
1 RAINFED	UFGA0001	SB	3134.9	443.9	1798.0	3602.0
2 AUTOMATIC 90%	UFGA0001	SB	3529.2	144.1	3219.0	3761.0
3 AUTOMATIC 70%	UFGA0001	SB	3528.3			3761.0
4 AUTOMATIC 50%	UFGA0001	SB	3539.8	122.9	3249.0	3759.0
5 AUTOMATIC 30%	UFGA0001	SB	3506.1	109.9	3241.0	3725.0
6 AUTOMATIC 10%	UFGA0001	SB	3228.0	287.0	2530.0	3602.0
17 ET TOTAL mm	r 1					
17 ET TOTAL mm	[ ]					
17 ET TOTAL mm	[ ]					

SCREEN 9.


The program calculates various statistics and presents them on screen (see Screen 9, above). These values show, by treatment, the mean, standard deviation, minimum, and maximum harvest yield obtained from running the soybean simulation model. Screen 9 shows the results obtained from the simulation of the automatic irrigation experiment at Gainesville, Florida, UFGA7812.SNX, and referred to above. As might be expected for this simulation, mean soybean yield increased as the irrigation threshold increased (i.e., more water was applied to the crop).

Press any key to continue, and the Graphics main menu appears (Screen 10, on following page). Three types of graphs can be plotted, described as follows.

# GRAPHICS MAIN MENU

#### **OPTION 1. BOX PLOT**

If this option is selected in Screen 10, a list of all the treatments is presented (by default, all treatments are selected for plotting box plots when this option is selected). All of the treatments can be selected at once by pressing the <+> key, or they can be selected individually by using the space bar as described before under Screen 8. (To deselect all treatments, press the <-> key.) After treatment selection (use the default for this example), press the <ENTER> key and a box plot appears (see Screen 11, on second following page). This is a way of assessing visually the variability of the output variable under consideration. For the distri-



SCREEN 10.


bution of the variable for each treatment selected, the 0th (the lowest single short line), 25th (the lower of the short lines connected by the vertical bar), 50th (the star), 75th (the upper of the short lines connected by the vertical bar), and 100th (the upper single short line) percentiles are plotted. Visually, these box plots are sometimes clearer than cumulative probability curves if there are many treatments. The 50th percentile is the median of each output variable distribution, not the mean; but for symmetrical distributions, the median will often not differ greatly from the mean value. Note the effect of irrigation treatment on the distribution of soybean yield.

This graph may be plotted on your printer by pressing the <P> key while the graph is on the screen. If the graph does not plot, you may need to change hard-copy settings (refer to the section below, "Graphics Hardcopy Setup"). Depending on the printer and the resolution used, there may be a delay of a few seconds while this is done; wait for the graph to show on the screen again before continuing.

**NOTE**: To return to the Analysis program from any graph, press any key.

#### **OPTION 2. CUMULATIVE FUNCTION PLOT**


When this option is selected in Screen 10, output variables by treatment are plot-



## SCREEN 11.

ted as cumulative function plots. (Cumulative function plots are sometimes called cumulative probability function (CPF) plots or cumulative distribution function plots – these are the same.) Here, the output distribution for each treatment is ordered from smallest to largest, and plotted against equal increments of cumulative probability.

After selecting this option, the treatment selection screen appears, allowing the user to select which treatments are to be plotted in this way (see Screen 12, on fol-



SCREEN 12.


lowing page). A maximum of six cumulative function plots may be graphed at any time, and you can select or deselect all the treatments at once with the <+> or <-> key (as described before under Screen 8), or individual treatments with the space bar. If more than six treatments are selected, the program will plot the first six treatments selected, and the rest will be ignored.

For the example, keep all treatments selected (as illustrated in Screen 12) and press the <ENTER> key. The resulting plot is shown in Screen 13 (on following page). To print the graphs, press the <P> key; press the <ENTER> key to return to the Graphics main menu (Screen 10)

#### **OPTION 3. MEAN-VARIANCE PLOT**


When this option in Screen 10 is selected, output variables may be plotted in mean-variance space. The calculated mean is plotted against the variance for the output variable of interest, and the treatment numbers themselves are drawn on the graph. A maximum of 20 treatments may be plotted in this way. Such graphs are another way of giving an indication of the relative variability associated with each treatment, and are useful for visualizing the tradeoffs that must sometimes be made between striving for a higher mean value while increasing the variability (as described by the variance) for the output of interest.

Choose the mean-variance plot option to produce the plot (Screen 14, on second following page). Note the high variance and comparatively low mean for the



SCREEN 13.

rainfed treatment, Treatment Number 1. There is little to choose between Treatments 2, 3, and 4, in terms of their mean and variance. It seems fairly clear that if the irrigation threshold is at least 50 percent of field capacity, then soybean yields are not limited by water availability in this experiment.



#### SCREEN 14.

The y-axis for such a plot is always scaled automatically, and care will sometimes be needed in interpretation, as the difference between the means (i.e., the difference from the top to the bottom of the scale) may not be very much, and will sometimes be much less than appears from a cursory glance at the graph. To print the plot, press the <P> key, or press the <ENTER> key to return to the Graphics main menu (Screen 10).

**NOTE:** To calculate statistics for all variables in the summary output file, select all the variables from the variable menu (Screen 8) with the <+> key. This will result in means, standard deviations, maxima and minima being calculated for all 35 output variables. Results will be written to the results file, not the screen. If you want to see results and/or graphs on the screen, choose individual variables to analyze one by one. Before quitting the Analysis program, you are given the option to print the results file if you require.

# Analyze Economic Variables


Choosing the main menu option, "Analyze Economic Variables," in Screen 5, allows the analysis of the treatments in economic terms. When this option is selected, the Economic Evaluation main menu (Screen 15, on following page) is presented. There are three major options in Screen 15, described as follows:

## ECONOMIC EVALUATION MAIN MENU

#### **OPTION 1. ACCESS A PRICE FILE**


Before economic evaluation can be undertaken, the program must have access to a price-cost file that details the costs and prices to be used for the analysis. The program will try to read an appropriate price-cost file by itself without input from the user, but other options are also available. When "Access price file" is selected from Screen 15, Screen 16 (on following page) is presented; the price-file options available from this screen are described below.

- Tied Price-Cost Files. Use a price file, with extension PRI, that is tied to the experiment FILEX (in this example, file UFGA7812.PRI).
   This file option might be used when you have a complicated experiment and you wish to preserve the prices and costs that pertain to the experiment.
- Default Price-Cost File. A default price file, distributed with DSSAT v3, called DEFAULT.PRI, can be used. This default file may be as simple or as complicated as the user requires.
- User-Specified Price-Cost File. You can browse the directory structure of your hard disk and highlight the file you want to use. The directory can be browsed using the arrow keys and pressing the <ENTER> key for the highlighted selection. Alternatively, the mouse can be used to move the highlight bar and the right-hand mouse button will select the highlighted file.



SCREEN 15.

If no price-cost file can be found, or if no tied price-cost file exists, then the program will generate a tied price-cost file using default values. These values can be edited as required (see following section).



SCREEN 16.

Format and Content of Price-Cost Files. The format of the default price-cost file DEFAULT.PRI for seasonal analysis is shown in Table 5, together with a listing of the headers that appear in the file. The eleven prices and costs that are currently included are as follows.

Cost or Price	Units	Associated Model
		Output
1 Price of harvest product (e.g., grain	n) \$/t	yield, t/ha
2 Price of harvest byproduct	\$/t	byproduct yield, t/ha
3 Base production costs	\$/ha	-
4 Nitrogen fertilizer cost	\$/kg	N applied, kg/ha
5 Cost per N fertilizer application	\$	No. of N applications
6 Irrigation costs	\$/mm	irrigation applied, mm
7 Cost per irrigation application	\$	No. of irrigation applications
8 Seed cost	\$/kg	seed sown, kg/ha
9 Cost of organic amendments	\$/t	residue applied, t/ha
10 Phosphorus fertilizer cost	\$/kg	P applied, kg/ha
11 Cost per P fertilizer application	\$	No. of P applications

Note that costs and prices can be negative or positive; this might apply particularly to harvest byproduct, where a negative income is posited (i.e., it costs the farmer money to remove the byproduct – straw or stover, for example). Any monetary units can be used; so "\$" can be thought of as "money in general" rather than "dollars."

Economic evaluation of the treatments can take account of price and cost variability. Details on how this is done within the program are given in Appendix A.

Seasonal analysis price files, as shown in Table 5, contain 5 lines per section: a header line, a line containing the distribution type for each of the 11 prices and costs, and three lines of parameters describing the distributions (i.e., PAR1, PAR2, PAR3). Distribution types are described by the variable IDIS, and can have the following values:

- < 0 Ignored: the variable is not used in the analysis
- 0 Fixed: a deterministic or nonvariable price or cost is used
- 1 Uniform: U(a,b,), a=lower, b=upper bound, third parameter ignored
- 2 Triangular: T(a,b,c), a=lower, b=mode, c=upper bound
- Normal: N(x,s,), x=mean, s=standard deviation, third parameter ignored

is Analysis • Seasonal Ana

TABLE 5. PRICE-COST FILE DEFAULT.PRI.

```
* PRICE-COST_FILE : DEFAULT FOR SEASONAL ANALYSIS
```

- ! if IDIS=-1, cost/price component is ignored in analysis
- ! if IDIS= 0, fixed value in PAR1
- ! if IDIS= 1, uniform variate (PAR1=lower, PAR2=upper bound)
- ! if IDIS= 2, triangular variate (PAR1=lower, PAR2=mode, PAR3=upper bound)
- ! if IDIS= 3, normal variate (PAR1=mean, PAR2=st. dev.)
- ! File sectioned by crop. A crop's treatment sections must be contiguous.

_	ľ۷ΙΖ
*	TRF

*	TREAT	MENT	1
രൂ	M / CIC	CDAN	т

@PRAM	GRAN	BYPR	BASE	NFER	NCOS	IRRI	IRCO	SCOS	RESM	PCOS	PFER
IDIS	3	0	0	0	0	0	0	0	-1	-1	-1
PAR1	160.00	10.00	240.00	0.45	12.00	.50	12.50	.46	.00	.00	.00
PAR2	16.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
PAR3	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

#### \* SB

*	TREATMENT	1

11(11.	TATI-IIIIAT T										
@PRAM	GRAN	BYPR	BASE	NFER	NCOS	IRRI	IRCO	SCOS	RESM	PCOS	PFER
IDIS	3	0	0	0	0	0	0	0	-1	-1	-1
PAR1	320.00	0.00	390.00	0.45	12.00	.50	12.50	.46	.00	.00	.00
PAR2	32.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
PAR3	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

#### \* BN

#### \* TREATMENT 1

@PRAM	GRAN	BYPR	BASE	NFER	NCOS	IRRI	IRCO	SCOS	RESM	PCOS	PFER
IDIS	3	0	0	0	0	0	0	0	-1	-1	-1
PAR1	360.00	0.00	380.00	0.45	12.00	.50	12.50	.46	.00	.00	.00
PAR2	36.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
PAR3	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

#### Headers:

- PRAM Parameter
- IDIS Distribution type (see file header)
- PAR1 Distribution parameter 1
- PAR2 Distribution parameter 2
- PAR3 Distribution parameter 3
- GRAN Price of grain, \$/t
- BYPR Price of harvest byproduct, \$/t
- BASE Base production costs, \$/ha
- NFER Nitrogen fertilizer cost, \$/kg
- NCOS Cost per N fertilizer application, \$
- IRRI Irrigation cost, \$/mm
- IRCO Cost per irrigation application, \$/ha
- SCOS Seed cost, \$/kg
- RESM Cost of organic amendments, \$/t
- PCOS Phosphorus fertilizer cost, \$/kg
- PFER Cost per P fertilizer application, \$

Note that if IDIS equals 1, 2, or 3, then the prices and costs are stochastic.

Figure 3 shows the general shapes of the three stochastic price-cost distributions that may be used (uniform, triangular, and normal).

If you specify a large number (more than three) of stochastic prices and costs, and your computer is not of the fastest, the economic analysis program may take a long time to run. Usually it is best to use only a few stochastic prices and costs.

The price-cost file is sectioned by crop, then by treatment number within crop (see Table 5). You may have multiple treatment sections per crop; you may speci-




FIGURE 3. STOCHASTIC PRICE-COST DISTRIBUTIONS.

fy more than one treatment number, or you may specify the keyword ALL, in the \* TREATMENT line of a crop section. Thus, for example, "\* TREATMENT ALL" and "\* TREATMENT 1 2 3" are valid; the treatment numbers and keyword ALL should simply be space-delimited; the exact format does not matter. If you have \* TREATMENT ALL, this will ensure that those costs and prices will be used for all treatments pertaining to that crop. A fatal error occurs if there is no appropriate crop section in the price-cost file. Thus if you use the DEFAULT.PRI price-cost shown in Table 5 to analyze a wheat experiment, you will need to add a \*WH section to the file.

As noted above, if a section with ALL in the treatment header is found, then that section will be used for all the prices and costs for that crop. The program will match treatment numbers by section if it can. If treatment numbers in FILEX cannot be matched directly with the treatment sections in the price-cost file, then the program will use the next highest treatment number section that has been specified in the price-cost file. If you are unsure about the prices and costs used in any analysis, you can refer to the analysis results file, where the prices and costs used in each analysis are written out explicitly.


#### **OPTION 2. EDIT PRICE FILE FOR SENSITIVITY ANALYSIS**

The second option, "Edit price file for sensitivity analysis" in Screen 15 allows the user to make changes to a price-cost file. When this option is selected, you have the choice to edit each treatment separately or all of them together. Select all the treatments using the <+> key or select one at a time using the space bar. Press the <ENTER> key. The next screen presented (Screen 17, on following page) shows the current values of costs and prices. Press any key to continue. Screen 18 (on second following page) will be presented, from which you can select the cost-price variable to change. For example, to change the grain price, select this item. A submenu will give you the choice of distribution (or it may be fixed or ignored), and you will be prompted for the appropriate distribution parameters.

If you have made any changes, restore the original values of prices and costs so that the screen appears as in Screen 17. To do this, either reset any values changed using the menus, or exit this part of the program and then reenter it. Then select the "Done with changes" option or press the <ESC> key to return to the Economic Evaluation menu (Screen 15).


#### **OPTION 3. CALCULATE ECONOMIC RETURNS**

When this option is selected from Screen 15, the program will calculate the mean,



#### SCREEN 17.

standard deviation, maximum and minimum value of net return or gross margin per hectare for each treatment (see Screen 19, on following page), using the costs and prices specified. Note that for the example, returns per hectare are highly



SCREEN 18.

				ic Analys per Hecta			
Trea	tment	Field	Crop	Mean	St.Dev.	Min	Max
1 RAINFE	:D	UFGA000	1 SB	623.2	236.9	65.7	1045.0
2 AUTOMA	TIC 90%	UFGA000	1 SB	356.5	191.3	20.6	671.6
3 AUTOMA	TIC 70%	UFGA000	1 SB	534.0	187.1	210.6	811.8
4 AUTOMA	TIC 50%	UFGA000	1 SB	607.0	187.2	307.4	933.5
5 AUTOMA	TIC 30%	UFGA000	1 SB	668.8	189.4	345.0	982.1
6 AUTOMA	TIC 10%	UFGA000	1 SB	637.7	191.8	243.4	990.5


SCREEN 19.

variable; note also that returns per hectare decrease markedly as more irrigation is applied. Heavily irrigated treatments are clearly economically wasteful in this situation for the costs and prices used (which are fictitious and for illustrative purposes only).


From within Screens 17, 18 or 19, press any key to continue, and the economics Graphics/Strategy menu appears (Screen 20, on following page). The first three options in Screen 20 operate in exactly the same way as described for the biophysical variables in the section entitled, "Analyze Biophysical Variables." The fourth option in Screen 20, "Strategy Analysis," is described as follows.

# STRATEGY ANALYSIS - MEAN-GINI DOMINANCE

When the "Strategy Analysis" option is selected in Screen 20, the resulting screen (Screen 21, on following page) lists the mean-Gini dominant treatment of the experiment, in terms of the costs and prices used to analyze it. Appendix B discusses strategy analysis in some detail. Basically, however, a dominant treatment is one that would be preferred by a decision maker over the other ("dominated") treatments, if various things are assumed about the decision maker's attitudes and preferences. It is a form of decision analysis that takes account of the risk involved. Note that the dominant strategy (Treatment 5, displayed on Screen 21) produced the highest mean return per hectare (\$668.80/ha, as shown on Screen 19).



SCREEN 20.



SCREEN 21.

Results of the calculations carried out to establish this mean-Gini dominance can be viewed by pressing the <Y> or <ENTER> keys. Screen 22 displayed below, lists the mean return for each treatment, the mean return minus its gini coefficient, and whether the treatment is efficient (or dominant) or not. In the example shown, note that the extra cost of irrigating frequently is not justified in terms of the added benefit of more yield. This example is discussed in more detail in Appendix B.

**NOTE:** You should be careful in interpreting the output of Strategy Analysis, as the assumptions may not always be valid. It is, however, a useful tool for helping you to "prescreen" a wide variety of options and identifying those options or treatments that merit further investigation. Of course, there may be many reasons why a dominant treatment is not appropriate for a particular farmer; further analyses outside the confines of the DSSAT3 will always be required before much can be said about the feasibility of particular management options in any particular situation.

Another case where you should exercise great care in interpretation is when you are investigating the economic benefits of fertilizer use. You may have the situation where you are running a treatment with the nitrogen routines of the crop models turned off. If you analyze such a treatment economically, then you will often obtain abnormally large economic returns, apparently with no N inputs to the system!

			Strategy A	-		
		Mean-Gini Do	ominance: E(x			
			K) I	:) Gini ceo	fficient \$/ha	
		Treatment	Field	E(x)	E(x) - Γ(x)	Efficient
						(Yes/No)
1	SB	RAINFED	UFGA0001	623.2	486.9	N
2	SB	AUTOMATIC 90%	UFGA0001	356.5	244.2	
3	SB	AUTOMATIC 70%	UFGA0001	534.0	424.3	N
4	SB	AUTOMATIC 50%	UFGA0001	607.0	496.9	N N
5	SB	AUTOMATIC 30%	UFGA0001	668.8	558.1	Y
6	SB	AUTOMATIC 10%	UFGA0001	637.7	526.2	N

SCREEN 22.

You should also exercise caution when interpreting the economic benefits to fertilizer use in terms of a simulated N response curve, for example. The economic optimum N application rate will often be overestimated using the model, simply because the crop model and the economic analysis will usually assume that "all other things are equal". Of course, they are not; the inputs required to obtain a general yield level of 1 t of cereal per hectare and those required to obtain 7 t per hectare are likely to be very different (more labor for weed, pest, and disease control, etc). This highlights the general observation that running a simulation experiment is trivial; interpreting the output produced requires great care.

Press any key in Screen 22 to return to the Graphics/Strategy menu (Screen 20). Choose the "Quit" option in Screen 20 twice (or hit the <ESC> key twice) to return to the Seasonal Analysis main menu (Screen 5).

# MODIFY HARDCOPY OPTIONS

On choosing the main menu option, "Modify Hardcopy Options," in Screen 5, with the mouse or cursor keys, you can change the way in which hardcopies of the graphs are produced on your printer or plotter. The screen that appears (Screen 23, on following page) when this option is selected, lists the current graphics hardcopy options. These are stored in an ASCII file called GRAPH.INI (see Table 6). The various controller options can be changed from Screen 2, simply by selecting the option to change and choosing any of the valid options (thus your printer port might be LPT2 rather than LPT1). After making any changes to the controller options in this screen, you can select to abandon the changes you have made, or you can save the changes to the file GRAPH.INI.

Normally, configuration of the graphics program will be carried out through the configuration menu in the Seasonal and Sequence Analysis programs. You may wish to edit GRAPH.INI with a text editor, however. The section of GRAPH.INI that holds configuration data for the graphics program is under the [WMGraf] section of the INI file. Defaults for plotting are defined in this section, in the format "keyword=" followed by a string, integer, or real variable. Specifically, the keyword definitions and possible values are:

gcolor[0..7]: refers to the default color palette for plotting. Values are 0 to 15.

interval number of major divisions on the X and Y axis (-9 chooses


Autoscaling)

tics: number of tic marks between the major divisions (-9 chooses

Autoscaling)

driver: an integer value of 0 to 33 is specified. The printer/plotter options

are listed in Table 7.



SCREEN 23.

#### TABLE 6. SAMPLE SECTION OF GRAPH.INI.

```
[WMgraf]
color0=1
color1=15
color2=14
color3=12
color4=15
color5=10
color6=11
color7=13
interval=-9
tics=-9
driver=7
port=0
orientation=0
fontsize=6
xmult=1.00
ymult=1.00
usetics=Y
usekeyword=1
file=OUTPUT
```

port: 0 for LPT1:, 1 for LPT2:, 2 for COM1:, 3 for COM2:, or 4 for

redirection of output to a file

orientation: 0 for portrait or 1 for landscape fontsize: fontsize for labels (1 to 20)

xmult: X multiplier ymult: Y multiplier

file: name for file output if port=4

The printer types supported by the graphics program are shown in Table 7.

TABLE 7. PRINTER TYPES SUPPORTED BY THE GRAPHICS PROGRAM.

Driver Number	Driver Description
0	Epson 9 Pin 60 x 72 dpi
1	Epson 9 Pin 120 x 72 dpi
2	Epson 9 Pin 240 x 216 dpi
3	Epson 24 Pin 180 x 180 dpi
4	Epson 24 Pin 360 x 180 dpi
5	Epson 24 Pin 360 x 360 dpi
6	HP LaserJet/DeskJet B&W 100 dpi
7	HP LaserJet/DeskJet B&W 150 dpi
8	HP LaserJet/DeskJet B&W 300 dpi
9	HP DeskJet 500C 100 dpi 8 color
10	HP DeskJet 500C 150 dpi 8 color
11	HP DeskJet 500C 300 dpi 8 color
12	HP PaintJet 90 dpi B&W
13	HP PaintJet 180 dpi B&W
14	HP PaintJet 90 dpi 16 color
15	HP PaintJet 180 dpi 8 color
16	HP PaintJet 180 dpi 16 color (XL)
17	HP ThinkJet 192 dpi
18	HP 7475A Plotter A size paper
19	HP 7475A Plotter B size paper
20	HP 7475A Plotter A4 size paper
21	HP 7475A Plotter A3 size paper
22	HP 7550 Plotter A size paper
23	HP 7550 Plotter B size paper
24	HP 7550 Plotter A4 size paper
25	HP 7550 Plotter A3 size paper
26	HP 7440 Plotter A4 size paper
27	HP 7470 Plotter A3 size paper
28	HP LaserJet HPGL Mode A size paper
29	HP LaserJet HPGL Mode B size paper
30	PostScript Printer Courier
31	PostScript Printer Helvetica
32	PostScript Printer Times
33	PostScript Printer Symbol

Legends for the graphics program are taken from a DSSAT v3 file called DATA.CDE (see Table 8). (For a description of the DATA.CDE file, see the Appendix to Volume 1 of this book.) This file lists, among other things, the headers, abbreviations, and definitions of the 35 output variables in the summary model output file that can be analyzed using the seasonal analysis program, in the section headed by the \*SUMMARY keyword.

#### TABLE 8. EXPERIMENT DATA CODES FILE DATA.CDE — SUMMARY SECTION ONLY.

\*EXPERIMENTAL DATA CODES

```
*SUMMARY
SDAT START SIM day Simulation start date (YRDOY)
PDAT PLANTING day Planting date (YRDOY)
ADAT ANTHESIS day Anthesis date (YRDOY)
MDAT MATURITY day Physiol maturity date (YRDOY)
                    Harvest date (YRDOY)
HDAT HARVEST day
DWAP SOWING WT kg/ha Planting material wt (kg dm/ha)
CWAM TOPS WT. kg/ha Tops wt at maturity (kg dm/ha)
HWAM MAT YIELD kg/ha Yield at maturity (kg dm/ha)
HWAH HAR YIELD kg/ha Yield at harvest (kg dm/ha)
BWAH BYPRODUCT kg/ha By-product harvest (kg dm/ha)
HWUM WEIGHT mg/unit Wt at maturity (mg dm/unit)
H#AM NUMBER #/m2 Number at maturity (no/m2)
H#UM NUMBER #/unit Number at maturity (no/unit)
IR#M IRRIG APPS # Irrigation applications (no)
IRCM IRRIG mm Season irrigation (mm)
PRCM PRECIP mm Season precipitation (mm)
ETCM ET TOTAL mm Season evapotranspiration (mm)
                   Season surface runoff (mm)
ROCM RUNOFF mm
DRCM DRAINAGE mm Season water drainage (mm)
SWXM EXTR WATER cm Extr water at maturity (cm)
NI#M NITR APPL # Number of N applications (no)
NICM TOT N APP kg/ha Total inorganic N appl (kg/ha)
NFXM N FIX kg/ha N fixed during season (kg/ha)
NUCM N UPTAKE kg/ha N uptake during season (kg/ha)
NLCM N LEACH kg/ha N leached during season (kg/ha)
NIAM SOIL IN N kg/ha Soil inor-N at maturity (kg/ha)
CNAM CROP N kg/ha Tops N at maturity (kg/ha)
GNAM PRODUCT N kg/ha Product N at maturity (kg/ha)
RECM RESIDUE kg/ha Total residue applied (kg/ha)
ONAM ORGANIC N kg/ha Org soil N at maturity (kg/ha)
OCAM ORGANIC C t/ha Org soil C at maturity (t/ha)
PO#M P APPL #
               Number of P applications (no)
POCM TOT P APP kg/ha Total P applied (kg/ha)
CPAM CROP P kg/ha Tops P at maturity (kg/ha)
SPAM SOIL P kg/ha Soil P at maturity (kg/ha)
```

# SELECTING ANOTHER INPUT FILE FOR ANALYSIS

Having analyzed one simulation summary file, you can choose to analyze another file in Screen 5. Note that a new analysis results (SNR) file will be produced for each summary output file (SNS) you analyze. You can choose to print the results file at this stage in the program, if you require (see following paragraph).

When you have concluded all the analysis you require, quit the program from the main menu screen (Screen 5). A message will appear with a reminder of the path and name of the log file containing analysis results that has just been produced (an example of part of such a file is shown in Table 9). This file can be edited as required, and the data imported into any application capable of reading ASCII text files for whatever purpose you require. Before you exit the program, you are given the option of printing this file. You should be aware that the file may be very long, however, if you have carried out many analyses.

## Information and Error Messages

A number of information and error messages are produced by the Seasonal Analysis program. In the list that follows, each message is preceded by a single-digit code and a three digit message/error number. If the single-digit code is "0," then this is a fatal error, and the program exits. If the code is "1," then the program will continue, as the error may not be fatal. Information messages have code "1" also. Some of these messages are self-explanatory. Others are indications of serious problems and you should check your file formats.

## 0 001 Cannot find directory file:

The summary output listing file could not be found in the current directory.

#### 0 002 No entries found in file:

The summary output listing file could be found, but no valid entries were found in it.

#### 1 003 Cannot find file:

The specified file cannot be found in the appropriate directory.

## 0 004 Error reading:

An error occurred during file reading; this is usually due to incorrect format of the specified file.

## 0 007 Cannot access file:

The specified file cannot be found in the appropriate directory.

#### TABLE 9. PART OF SEASONAL ANALYSIS RESULTS FILE UFGA7812.SNR.

\*SN\_ANALYSIS\_LOG : UFGA7812SN GAINESVILLE, FLORIDA, SB IRRIGATION EXPERIMENT

is Analysis • Seasonal Ana

Date: 20 Apr, 1994 Time: 11:48:18

Input file : C:\DSSAT3\SEASONAL\UFGA7812.SNS —————

BIOLOGICAL VARIABLES

Calculated Values: Variable = HAR YIELD kg/ha

	treatment	field o	crop	mean	st.dev
1	RAINFED	UFGA0001	SB	3134.90	443.91
2	AUTOMATIC 90%	UFGA0001	SB	3529.20	144.06
3	AUTOMATIC 70%	UFGA0001	SB	3528.30	145.71
4	AUTOMATIC 50%	UFGA0001	SB	3539.75	122.89
5	AUTOMATIC 30%	UFGA0001	SB	3506.15	109.92
6	AUTOMATIC 10%	UFGA0001	SB	3228.00	286.99

percentiles							
treat	0th	10th	25th	50th	75th	90th	100th
1	1798.0	2755.9	2941.3	3233.5	3425.5	3525.4	3602.0
2	3219.0	3338.5	3468.0	3548.5	3632.5	3696.7	3761.0
3	3219.0	3336.9	3461.5	3543.0	3637.0	3695.9	3761.0
4	3249.0	3407.5	3482.8	3527.5	3629.5	3694.5	3759.0
5	3241.0	3431.2	3460.8	3481.0	3542.8	3679.2	3725.0
6	2530.0	2892.3	3047.8	3304.0	3430.5	3525.4	3602.0

BIOLOGICAL VARIABLES

Calculated Values: Variable = IRRIG APPS #

	treatment	field (	crop	mean	st.dev
1	RAINFED	. UFGA0001	SB	.00	.00
2	AUTOMATIC 90%	. UFGA0001	SB	22.25	3.99
3	AUTOMATIC 70%	. UFGA0001	SB	10.80	2.76
4	AUTOMATIC 50%	. UFGA0001	SB	6.65	2.11
5	AUTOMATIC 30%	. UFGA0001	SB	3.10	1.71
6	AUTOMATIC 10%	. UFGA0001	SB	.65	.81

			percentil	es			
treat	0th	10th	25th	50th	75th	90th	100th
1	.0	.0	.0	.0	.0	.0	.0
2	12.0	18.8	20.8	22.0	25.0	27.0	30.0
3	6.0	8.8	9.0	10.5	11.3	15.1	17.0
4	3.0	4.9	5.0	6.0	8.3	9.1	11.0
5	.0	1.9	2.0	3.0	4.0	6.0	7.0
6	.0	.0	.0	.0	1.0	2.0	2.0

1 008 Read error in subroutine GETCOD, file:

An error occurred in reading the specified file.

#### 0 009 Code could not be found:

The program attempted to find the specified code in the DSSATPRO.FLE, but could not find it. The pathname associated with the code specifies the location of the graphics program for the seasonal analysis graphics.

1 012 Treatments are not numbered consecutively from 1:

The treatments in the summary output file selected are not numbered consecutively starting with a treatment number of 1. Treatment numbers in the file can be edited to prevent this happening; a better solution is to edit treatment numbers in the relevant FILEX itself.

#### 1 013 Cannot find file:

The specified file cannot be found.

1 014 Must have at least 2 replicates for a CPF plot To plot cumulative probability functions, you must have a distribution with at least 2 values or replicates.

- 0 015 A problem was encountered generating a price file! Restart now.. An internally generated price file could not be completed.
- 1 020 A problem was encountered executing another program The program was not able to execute another program; check the free RAM that you have on your computer, and increase it if possible by unloading unnecessary resident programs (e.g. a network).
- 1 021 A problem was encountered copying a file The specified file could not be copied successfully.
- 1 022 A problem was encountered erasing a file The specified file could not be erased successfully.
- 1 023 Error in TUKEY.FOR

An error occurred when calculating percentiles of a distribution.

1 024 READ Error in file:

A read error occurred in the specified file; check the format of the file.

1 025 Unequal treatment reps in file:

Unequal treatment replicates were found in the selected summary output file; exit and fix the file to avoid this message.

#### 1 026 READ Error in DATA.CDE

An error occurred when reading the file DATA.CDE; check that it is complete and the format is correct.

1 027 All variances are zero

The variances for the selected treatments are zero.

1 028 Total number of runs exceeds 600 See message 031.

1 029 Number of treatments exceeds 20 See message 031.

1 030 Number of replicates exceeds 30 See message 031.

1 031 File is too big to analyze:

This error message arises in conjunction with one of three other messages, and refers to the fact that the selected summary output file is too large with respect to total number of runs (error message 028), number of treatments (error message 029), or number of replicates (error message 030).

1 032 Analysis results written to the file :

Analysis results have been written to the specified file.

1 033 Output written to:

Program output has been written to the specified file.

1 034 For graphics, choose variables one at a time! To produce graphs of model outputs, choose single variables.

1 035 Output already written to:

Output for this variable has already been written to the analysis results file.

1 036 For graphics, choose single variables As for message 034.

1 037 The program has no access to a price file. Access one!

0 038 Error in filename:

Error in filename specification.

1 039 Crop code not matched in price file :

There was no section in the price file corresponding to the specified crop code; you must edit the file so that this section exists.

1 040 Read error in price file:

Check the format of the price file; a read error occurred.

0 041 Cannot find file:

Specified file cannot be found.

0 042 Error in:

0 043 Read error in file:

Read error in the specified file.

0 044 Must have at least 2 replicates for a CPF plot!

See message 014.

1 045 Error in TUKEY.FOR; <Enter> to quit

See message 023.

0 046 ERIC2 size problem

Array overflow error.

1 047 A price file must be accessed using opt. 1 before using this option You must access a price file before attempting to carry out the economic calculations.

0 048 Error in CONVOL.FOR!

Error in combining distributions.

1 049 All variances are zero: <Enter> to continue

See message 027.

1 050 Cannot find a file .. choose again :

1 051 You must first select an analysis!

Select one of the analysis options before continuing.

1 052 All data are ZERO. Plotting causes unpredictable behavior!

1 055 Problem in finding the appropriate help screen

The appropriate help screen could not be found.

- 1 058 There were no matching files found!
- 1 060 The requested subdirectory to be searched doesn't exist!!!
- 1 100 Error!

Undetermined error.

- 1 131 You MUST turn on the printer now or the program will crash!
- 1 148 A problem was encountered in trying to print a file! The results file could not be printed successfully.

# REFERENCES

The following references contain more details on strategy analysis:

- Anderson, J. R., J.L. Dillon and J.B. Hardaker. 1977. Agricultural Decision Analysis. Iowa State University Press.
- Buccola, S. T. and A. Subaei. 1984. Mean-Gini analysis, stochastic efficiency and weak risk aversion. Australian Journal of Agricultural Economics 28, 77-86.
- Fawcett, R. H. and P.K. Thornton. 1990. Mean-Gini dominance in decision analysis. IMA Journal of Mathematics Applied in Business and Industry 6, 309-317.
- Halter, A. N. and G.W. Dean. 1971. Decisions under uncertainty with research applications. South-Western Publishing Company, Cincinnati, OH.
- Raiffa, H. 1968. Decision Analysis. Addison Wesley, Reading, MA.
- The Seasonal Analysis program is outlined in the following:
- Thornton, P. K. and G. Hoogenboom. 1994. A computer program to analyze single-season crop model outputs. Agronomy Journal (*in press*).
- Details on FILEX creation and editing may be found in:
- Imamura, D.T. 1994. Creating management files to run crop models & document experiments. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds). DSSAT v3. Vol. 1-4. University of Hawaii, Honolulu, HI.

#### Other References:

Geng, S., J.S. Auburn, E. Brandsetter and B. Li. 1988. A program to simulate meterological variables: Documentation for SIMMETEO. Agronomy Progress Report No. 204. Dept. of Agronomy and Range Sci., Univ. of California, Davis. CA.

- Hunt, L.A., J.W. Jones, P.K. Thornton, G. Hoogenboom, D.T. Imamura, G.Y. Tsuji and U. Singh. 1994. Accessing data, models and application programs. *In*: Tsuji, G.Y., G. Uehara and S. Balas (eds.). DSSAT v3. Vol. 1-3. University of Hawaii, Honolulu, HI.
- Jones, J.W., L.A. Hunt, G. Hoogenboom, D.C. Godwin, U. Singh, G.Y. Tsuji, N. Pickering, P.K. Thornton, W.T. Bowen, K.J. Boote and J.T. Ritchie. 1994. Input and output files. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds). DSSAT v3. Vol. 2-1. University of Hawaii, Honolulu, HI.
- Richardson, C.W. and D.A. Wright. 1984. WGEN: a model for generating daily weather variables. United States Department of Agriculture, Agricultural Research Sevice, ARS-8, Washington, DC.
- Thornton, P.K., P.W. Wilkens, G. Hoogenboom and J.W. Jones. 1994. Sequence analysis. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds). DSSAT v3. Vol. 3-2. University of Hawaii, Honolulu, HI.

# APPENDIX A. COMBINING YIELD AND PRICE DISTRIBUTIONS

If the user specifies price and cost variability, the Seasonal Analysis program proceeds by combining the simulated distributions of biophysical outputs with the user-specified distributions of costs and prices. The method used is illustrated below for a simulated yield distribution made up of seven replicates.

Gross margin or net return calculations involve simple algebra, in the simplest case no more than the following:

Return = Price \* Yield - Costs of production

The simulation models can produce a distribution of yields. If price is defined as a distribution also, then a way has to be found to estimate the new distribution for the quantity "price times yield." Similarly, distributions may have to be subtracted from each other to produce the "final" distribution of returns per hectare. The analysis program does this as follows.

The values of the relevant biophysical outputs (yield, residue, and so forth) for each replicate are combined algebraically with the inverse of the appropriate analytical cumulative probability function that is used to describe the particular cost or price, using five equi-distant percentiles of the CPF (the 0th, 25th, 50th, 75th, and 100th percentiles). The inverse of a cumulative probability distribution is an algebraic expression whereby the value of the random variable associated with any value of cumulative probability can be calculated. The distribution vector containing the values of gross margin or net return per hectare, which is then of length 5\*n, where n is the number of replicates, is sorted and collapsed to length n by linear interpolation.

Each algebraic operation on the distributions is done separately for each stochastic price or cost. The final distribution of returns per hectare will contain the same number of members as there were yields in the original yield distribution (i.e., number of replicates).

One point to bear in mind is that the method of combining distributions is not exact, but an approximation. You may find that the mean of the distribution of returns per hectare derived using one or more stochastic price or cost will be

somewhat different from the mean when all prices and costs are fixed. This is to be expected, but the differences should not be large, and ranking of treatments should not be greatly affected.

#### AN ILLUSTRATION

#### STEP 1

Order the 7-member simulated yield distribution from smallest to largest:

yield Y, t/ha: 0.90 1.60 1.90 2.10 2.40 2.50 3.10

#### STEP 2

Assume grain price is described by a triangular distribution with minimum value \$90/t, mode \$110/t, and maximum value \$120/t; calculate the following percentiles from the inverse of the triangular distribution:

percentile: 0.0 25.0 50.0 75.0 100.0

price P, \$/t: 90.0 102.2 107.3 111.3 120.0

#### STEP 3

Multiply each yield by each of the five price percentiles to form a vector of length 35; then order this from smallest to largest:

n: 1 2 3 4 .... 34 35

P\*Y: 81.00 91.98 96.57 100.17 .... 345.03 372.00

#### STEP 4

From the distribution of P\*Y, described by 35 values, calculate by linear interpolation the following percentiles of the distribution, so that for 7 values of yield, we obtain 7 values of P\*Y:

percentile: 0.0 16.7 33.3 50.0 66.7 83.3 100.0

P\*Y : 81.00 153.76 192.73 225.00 254.33 282.00 372.00

# APPENDIX B.

# THREE DECISION CRITERIA

The stochastic efficiency rules are an important class of decision criteria, and are particularly suited to the analysis of simulation model output. These have their basis in Bernoullian utility theory, and differ in the assumptions that are made about the decision maker's attitude to risk. (Refer to the "Reference" section in this Part for sources of information on the issues discussed in this appendix). These rules were developed to tackle the problem of portfolio selection in investment theory, but are now firmly- entrenched tools for risk analysis in all sorts of applications. All involve a pair-wise comparison of random variables, and strictly speaking, these should relate to financial gains and losses. The result of the analysis is an efficient set of treatments. The efficient set contains a subset of treatments that are superior (there may be one only, but sometimes there will be more than one efficient treatment). Three variations are described briefly below.

# MEAN-VARIANCE (EV) ANALYSIS

For two risky prospects, A and B, with means E(.) and variances V(.) respectively, then A dominates B if

$$E(A) = E(B)$$
 and  $V(A) < V(B)$  or if  $V(A) = V(B)$  and  $E(A) > E(B)$ .

A is then said to be EV-efficient. If prospects are plotted in EV space (V the ordinate, E the abscissa), then utility increases in a north-westerly direction. EV analysis assumes that the decision maker has a quadratic utility function for gains and losses, and/or that the risky prospects are distributed normally (or at least distributed symmetrically). These are often untenable assumptions, and the EV criterion has fairly weak discriminatory power (i.e., the efficient sets tend to be large).

# Stochastic Dominance (SD) Analysis

For two risky prospects, A and B, A dominates B by first-order stochastic dominance (FSD) if the Cumulative Distribution Function (CDF) of gains from A lies to the right of the CDF of B over the entire probability interval 0 to 1.

If the CDFs of A and B intersect, then no dominance by FSD can be established.

If, however, the area between the two CDFs below the point of intersection is greater than the area between the two CDFs above the point of intersection, then A dominates B by second-order stochastic dominance (SSD); otherwise, no dominance can be established, and both A and B are second-order efficient.

For FSD, no assumptions are made about the attitude of the decision maker to risk; for SSD, it is assumed the decision maker is averse to risk to some unknown degree. No assumptions need be made about the distributional properties of the random variables, either.

# MEAN-GINI DOMINANCE (MGD) ANALYSIS

For two risky prospects, A and B, A dominates B by MGD if:

$$E(A) >= E(B)$$
 and  $E(A) - G(A) >= E(B) - G(B)$ 

with strict inequality for one of these expressions, where E(.) is the mean, and G(.) is the Gini coefficient of distributions A and B (which is half the value of Gini's mean difference: the absolute expected difference of a pair of randomly selected values of the variable).


MGD, like SSD, assumes that the decision maker is averse to risk, but unlike SSD, the extremely risk-averse are excluded from the analysis. It is thus a more discriminating decision rule than SSD (since the MGD efficient set is usually smaller), and computationally, MGD is generally much easier to establish than SSD.

## AN EXAMPLE

In the seasonal analysis program, E-V analysis can be carried out visually from E-V plots of economic returns, and mean-Gini analysis may be carried out by choosing the appropriate menu options. (Notes on first- and second-degree stochastic dominance are included for interest's sake for those readers familiar with DSSAT Version 2.1).

To illustrate, consider again the example obtained by analyzing the file UFGA7812.SNS using the costs and prices as in the distribution version of UFGA7812.PRI.


The box plot in Screen 24 (on following page) shows the impact of large amounts of irrigation on monetary returns per hectare. If you look at the amount of irrigation water applied in the six treatments (Screen 25, on 2nd following page) and compare this with the yields obtained (see Screen 9), it is clear that much of the




#### SCREEN 24.

water applied in Treatments 2, 3, and 4 is wasted; only a small amount of supplemental irrigation is required to alleviate most of the water stress that may occur in most years.


The same can be seen in terms of the number of irrigation applications made in each treatment (Screen 26, on following page). We can conclude that the cost of irrigation water per mm, the cost of each irrigation application, and the limited yield response to heavy irrigation applications, combine in such a way that the most profitable option of the six considered is to apply irrigation at a threshold of 30 percent of field capacity.



SCREEN 25.



Screen 26.



#### SCREEN 27.

In terms of strategy analysis, the mean-Gini dominance calculations are shown in Screen 22 of the main text. As noted above, the dominant strategy also has the highest mean monetary return. In mean-Gini dominance, this will always be the case, but it will sometimes happen that the variability associated with this "highmean" treatment will be so great that it will be joined in the efficient set by another treatment with lower mean but lower variability. In such a case, no decision can be made with respect to which of the efficient treatments is better without knowing more about the preferences and attitudes of the particular decision maker. In any case, you should always remember that there is a variety of


sources of error in simulation experiments: errors in input data and errors in model specification, to name but two. Treatments with similar economic (or even biological performance) are likely to be "statistically indistinguishable" in terms of the model's inherent errors, in any case; there is then little point in applying increasingly sensitive analytical procedures in an attempt to distinguish what is probably indistinguishable.

Visual inspection of the six treatments for mean-variance dominance can be done for this experiment (see Screen 27, on previous page). Treatment 5 has the highest mean, but note from Screen 19 of the main text that the standard deviation (and hence the variance) of Treatments 4 and 5 are lower than that for Treatment 5. According to strict application of the E-V rules, Treatments 5, 4, and 3 are E-V efficient. The differences in simulated variances are very small between these three treatments, however. You should be careful not to be dogmatic in interpretation, and bear in mind the errors in the model and the model input data.

For purposes of comparison, inspection of the CPF plot of monetary returns for the six treatments (Screen 28, on following page) shows that none of the treatments is dominant by first-order stochastic dominance, since the CPF for Treatment 5 crosses the CPFs of Treatments 1 and 6. Further analysis (outside the DSSAT v3) shows that Treatment 5 is efficient or dominant according to second-order stochastic dominance.


As might be expected, the efficient sets of treatments according to the various stochastic efficiency rules are related (see Buccola and Subaei (1984) for more details). In essence, MG-efficient treatments and FSD/SSD efficient treatments are members of the EV-efficient set; further, MG efficient treatments are members of the FSD/SSD efficient set. To put it another way, EV-efficient sets tend to be larger than FSD/SSD efficient sets, which in turn tend to be larger than MG-efficient sets.

One more point to bear in mind is that for comparison purposes, calculations are made, and the analysis is carried out, on a per hectare basis. While making for simplicity, this implies even more about the particular nature of the decision maker's attitudes and preferences, but is often forgotten or ignored. Strictly speaking, these types of decision analysis relate to gains and losses of money in relation to total wealth. For further details, consult Raiffa (1968).



SCREEN 28.

# VOLUME 3-2



P.K. Thornton,
P.W. Wilkens,
G. Hoogenboom,
J.W. Jones

Sequence Analysis • Sequen

# CHAPTER ONE.

The Sequence Analysis program allows the user to carry out simulations of crop rotations or crop sequences (i.e., any combination of crops grown one after another) using the DSSAT v3 crop models, and then to analyze the results. A simulation experiment involving a crop rotation may be replicated through time using different weather sequences; the experiment is set up by the user, the appropriate models are run using a special program called the driver, and the user can then analyze the results using the sequence analysis program. The "sequence" aspect of the driver and analysis programs relates to the fact that what is being run are experiments of multiple cropping seasons; the carry-over of soil water and nutrient status is effected from one season or crop to the subsequent season or crop.

To clarify the terminology, a number of definitions are set out below:

Sequence: relates to the growing of particular crops, one after another over time, where the carry-over effects from one crop to the next, whatever they may be, are taken into account. A sequence may thus relate to the growing of maize planted every year for 10 years; a sequence may be a short rotation of maize planted every season followed by beans grown in the same wet season or calendar year; or a sequence may consist of a four-year crop rotation, for example.

*Treatment:* any particular sequence run over a number of years; treatment 1 might refer to maize grown every year for 10 years with low exogenous nitrogen fertilizer input; treatment 2 the same, with high nitrogen input; treatment 3, a maize-bean cropping system in alternate seasons with low nitrogen input; and so on.

Replicate: a repetition of the same sequence treatment run over the same conditions apart from weather. In a real field experiment, two sequence replicates might refer to neighboring plots run with the same weather conditions, or the sequences might be replicated with respect to time: replicate 1 grown over the period 1981-1985, and replicate 2 from 1986 to 1990. In the same way that computer experimentation can produce "pure" replication of single season performance by using multiple year weather sequences, so computer experimentation can produce pure replication of sequences, where starting conditions and management are identical, but variation arises out of different weather sequences over the years of interest and out of any intrinsic stochasticity that may be built into the model.

*Variation:* for a simulation model with no intrinsic stochasticity (such as the CERES or CROPGRO models), the sources of variation in a computer experiment arise from the following: (a) between treatments; (b) between replicates; (c) within sequences (i.e., between different years of the various sequence replicates). As for replicated computer experiments run over single seasons, the only sources of error that exist are model error and input data error, ultimately, as opposed to field experiments, where errors arise from measurement, micro-variations in soil and climate, and the rest. This "pure" replication can be difficult to analyze and interpret in the case of cropping sequences.

The driver program is capable of running up to 10 "treatments" or sequences. The analysis program, however, is capable of analyzing only one treatment at a time. Thus no direct treatment comparisons are possible using the analysis program. The major reason for this is to help foster "healthy skepticism" of sequence simulation results. At the current time, the sequence capabilities of the IBSNAT crop models have not been extensively tested. It is envisaged that most users of the sequence capability of the models will be interested in addressing "what if..." questions related to agricultural system performance. However, analysis results of multiple treatment sequence experiments are written to an ASCII file, and you can analyze these in any way you see fit outside the confines of DSSAT v3. You could, for example, compare and contrast different sequence strategies directly, although you should exercise care in interpreting the results you obtain.

There are three basic steps involved in Sequence Analysis:

- 1. The creation of an appropriate model input file;
- 2. Running the crop model(s) using the sequence driver;
- 3. Analyzing the results of the simulations using the analysis program.

The links between these steps are shown in Figure 1. Sequence analyses are run from the DSSAT v3 Shell (see Volume 1-3, Hunt et al. 1994, of this book for a description of the Shell) under the main menu item, ANALYSES. The three steps are explained in Chapter 2 herein.

#### System Requirements

The useable portion of your system's 640 Kb RAM should be at least 540 Kb in size for the models to run and for the analysis program and graphics to work.

If the driver or analysis program still does not work properly, one problem may be

associated with the number of BUFFERS and FILES defined in CONFIG.SYS. These will need to be set to at least 20 each.

Replicated sequence simulations on an 8086 or 80286 system may take a great deal of time. Sequence Analysis, like the rest of DSSAT v3, will operate without a math coprocessor, but this is not recommended.




FIGURE 1. STEPS IN SEQUENCE ANALYSIS.

Sequence Analysis • Sequen

# CHAPTER TWO. CREATING MODEL INPUT FILES FOR SEQUENCE ANALYSIS

The utility program XCreate that is provided with the DSSAT v3 software can be used to create model input files for running sequence analyses (see Volume 1-4, Imamura 1994, of this book for a description of the XCreate program). These model input files are referred to as FILEXs (see Volume 2-1, Jones et al. 1994, of this book for a description of this file). Alternatively, these files can be created using an ASCII text editor. The advantage of using the program XCreate is that the experiment listing file EXP.LST (see Volume 2-1, Jones et al. 1994, of this book for a description of this file) is updated automatically. If you create a sequence analysis FILEX yourself, you must either update EXP.LST or run the File Manager Utility program (accessed using the "Sequence — Inputs" menu items of the DSSAT v3 Shell; see Volume 1-3, Hunt et al. 1994, of this book for a description of the Shell) for the FILEX to be accessible to the system. The format of EXP.LST is shown in Table 1.

# FILEX FOR SEQUENCE ANALYSIS

Sequence analysis model input files created with XCreate have the extension SQX. An example of a sequence analysis FILEX is shown in Table 2. There are some important differences in the way in which a sequencing FILEX is set up, compared with experiment or seasonal FILEXs. In the \*TREATMENTS section of the file, instead of setting up a number of treatments, you specify a rotation "germ"; this is the sequence of crops that will be repeated over and over again. In Table 2, for instance, the "germ" consists of maize, followed by fallow (i.e., no crop is planted, but the models will simulate the soil water and nutrient processes on a daily basis until the next crop is planted). Note that the treatment number

TABLE 1. SEQUENCE EXPERIMENT LISTING FILE EXP.LST.

\*EXPERIMENT LIST

- @# FILENAME EXT ENAME
- 1 UFGA7803 SQX SEQUENCE ANALYSIS, SIMPLE MULTI-TREAT FILE, 5:5
- 2 UFGA7804 SQX BN-BN YR 1, SB YR 2 EXAMPLE, 10:5
- 3 EBAF1101 SQX MA-FA, 30 YRS, 15 REPS, NO N

(@N) is 1 for both rotation components. Each rotation component is assigned a number in ascending order, starting from 1 (the R column). Thus maize is the first component (R = "1"), and fallow is the second (R = "2"). The variables O and C in sequencing FILEXs should always be set to "1" and "0," respectively. These are options that have not yet been implemented.

The rotation germ will be repeated for as many seasons as are specified in the \*SIMULATION CONTROLS section of the FILEX, under NYERS (one of the GENERAL options found in this section). In Table 2, NYERS is "30," so the rotation will be continued for 30 years.

This example FILEX specifies that maize is to be planted on day 305 (from PDATE in the \*PLANTING DETAILS section of the file; note that PLANT under MANAGEMENT options in the \*SIMULATION CONTROLS block 1 (i.e., N = "1") is set to "R" for "recorded") in each year of simulation. Once the maize is mature, the fallow model will be run, until the maize model is called for planting in the next year.

This FILEX also specifies that there are to be 15 replicates of this sequence (refer to NREPS under GENERAL options in \*SIMULATION CONTROLS block 1). Weather for the site EBAF is to be simulated using WGEN (refer to WTHER under the METHOD options in \*SIMULATION CONTROLS block 1; this is set to "W").

You will notice that there are two simulation control blocks in this FILEX. In general, it is highly recommended that you specify as many simulation control blocks as there are rotation components. So if you specify 7 rotation components, it is safest to specify 7 simulation control blocks.

For sequence experiments, you should note that the values of NYERS, NREPS, START, YRDAY, RSEED, all the OPTIONS variables, WTHER, and all the OUT-PUTS variables are taken from the \*SIMULATION CONTROLS block with the lowest VALID number. The values of these variables in any other \*SIMULATION CONTROLS block are ignored. Thus in Table 2, the random number seed RSEED, for example, in block 1 equals 3517; in block 2, RSEED equals 2150. Since block 1 is a valid block number (i.e., in the \*TREATMENTS section SM is specified as "1" for the first component), then the values appearing here will be used. Block 2 is also valid, but the values of NYERS, etc., will be ignored. In general, you may specify simulation controls as you would for experiment or seasonal FILEXs; thus you may specify automatic planting, etc.

#### TABLE 2. A SAMPLE FILEX FOR CROP SEQUENCING: EBAF1101.SQX.

\*EXP.DETAILS: EBAF1101SQ MAIZE-FALLOW, 30 YEARS, 15 REPS, NO N

```
*TREATMENTS
                                     -----FACTOR LEVELS----
@N R O C TNAME...... CU FL SA IC MP MI MF MR MC MT ME MH SM

      1 1 1 0 Maize component
      1 1 0 1 1 0 0 1 0 0 0 0 1

      1 2 1 0 Fallow component
      2 2 0 0 0 0 0 0 0 0 0 1 2

*CULTIVARS
@C CR INGENO CNAME
1 MZ IB0058 NC+59
2 FA IB0001
*FIELDS
@L ID_FIELD WSTA.... FLSA FLOB FLDT FLDD FLDS FLST SLTX SLDP IB_SOIL
1 EBAF0001 EBAF -99 0 IB000 0 0 00000 -99 180 IBMZ910032
*INITIAL CONDITIONS
@C PCR ICDAT ICRT ICND ICRN ICRE
1
   MZ 11244
              100 -99 1.00 1.00
@C ICBL SH20 SNH4 SNO3
1
    5 0.265 0.6 1.5
1
     10 0.265 0.6 1.5
1
    20 0.265 0.6 1.5
 1
   30 0.248 0.6 1.5
 1 40 0.248 0.6 1.5
 1 50 0.248 0.6 1.5
 1
   60 0.248 0.6 1.5
    70 0.248 0.6 1.5
    80 0.248 0.6 1.5
 1 100 0.248 0.6 1.0
1 120 0.248 0.6 1.0
*PLANTING DETAILS
@P PDATE EDATE PPOP PPOE PLME PLDS PLRS PLRD PLDP PLWT PAGE PENV PLPH
1 11305 -99 6.2
                   6.2 S R 80 0 5.0 -99 -99.0 -99.0
*RESIDUES AND OTHER ORGANIC MATERIALS
@R RDATE RCOD RAMT RESN RESP RESK RINP RDEP
1 11300 IB001 5000
                   0.8
                         -9
                              -9
                                          15
*HARVEST DETAILS
@R HDATE HSTG HCOM HSIZ HPC
1 12304
                    100.0
*SIMULATION CONTROLS
@N GENERAL NYERS NREPS START YRDAY RSEED SNAME.....
1 GE
            30 15 S 11244 3517 MZ component
```

N N N

@N OPTIONS WATER NITRO SYMBI PHOSP POTAS DISES

Y Y

Y

1 OP

<sup>•</sup> DSSAT v3, Volume 3 • DSSAT v3, Volume 3

@NT	METHODS	מידעדים	TNCON	т.тсит	EVAPO	TNETI.	DHOTO					
	ME	W	M	E	R	S	C					
_	MANAGEMENT					~	Ū					
	MA	R	N	R	R	M						
@N	OUTPUTS	FNAME	OVVEW	SUMRY	FROPT	GROTH	CARBN	WATER	NITRO	MINER	DISES	LONG
1	OU	Y	N	A	7	N	N	N	N		N	N
@	AUTOMATIC N	MANAGEMI	ENT									
@N	PLANTING	PFIRST	PLAST	PH2OL	PH2OU	PH2OD	PSTMX	PSTMN				
1	PL	288	360	40	100	30	40	10				
@N	IRRIGATION	IMDEP	ITHRL	ITHRU	IROFF	IMETH	IRAMT	IREFF				
1	IR	30	50	100	IB001	IB001	10	0.75				
@N	NITROGEN	NMDEP	NMTHR	NAMNT	NCODE	NAOFF						
1	NI	30	50	25	IB001	IB001						
@N	RESIDUES	RIPCN	RTIME	RIDEP								
1	RE	100	1	20								
@N	HARVEST	HFIRST	HLAST	HPCNP	HPCNR							
1	HA	0	365	100	0							
@N	GENERAL	MVEDS	MDFDQ	מתאסת	ABUYA	PGEED	SNAME					
	GE	30	15		11244		FA cor				• •	
	OPTIONS				PHOSP							
	OP	Y	Y	Y	N	N	N					
	METHODS	WTHER			EVAPO	INFIL	PHOTO					
2	ME	W	М	E	R	S	С					
@N	MANAGEMENT	PLANT	IRRIG	FERTI	RESID	HARVS						
2	MA	R	N	R	R	R						
@N	OUTPUTS	FNAME	OVVEW	SUMRY	FROPT	GROTH	CARBN	WATER	NITRO	MINER	DISES	LONG
2	OU	Y	N	А	7	N	N	N	N	N	N	N
@	AUTOMATIC N	ANNIN CEMI	ידואיב									
_	PLANTING	PFIRST		DH3OI	חוארוו	מטטח	DCTMV	DCTMNT				
	PLANTING	155	200	40	100	30	40	10				
	IRRIGATION											
	IR	30	50		IB001			0.75				
	NITROGEN				NCODE		10	0.75				
	NI	30	50		IB001							
2												
	RESIDUES	RIPCN	RTIME	RIDEP								
@N	RESIDUES			RIDEP								
@N 2		RIPCN 100 HFIRST	1	20	HPCNR							

Refer to the \*TREATMENTS section in Table 2. Factor levels are specified as for experiment or seasonal FILEXs. Thus, we have to specify a cultivar level (CU) for each rotation component (even fallow, although this is a dummy value). The rotation is grown in the same plot of land (FL = "1" for both rotation components). Initial conditions (IC) are specified for the maize component (IC = "1;" note that these are the conditions that will pertain at the start of each sequence; in subsequent seasons, "initial conditions" in terms of soil water and ammonium and nitrate levels are output by the preceding fallow model). Planting of maize takes place according to the \*PLANTING DETAILS section 1 (MP = "1" for maize). Crop residue is applied at the start of the sequence according to the values specified in \*RESIDUES section 1 (MR = "1"). The maize crop is controlled by the simulation controls in SM="1."

For the fallow component, the cultivar and field is specified (CU = "2" and FL = "1"). Simulation control is specified (SM= "2," see above). One further factor level is needed: a \*HARVEST DETAILS section (MH = "1") is REQUIRED for any fallow component. This is necessary to tell the fallow model when to stop. In the HDATE slot (harvest date) found in the \*HARVEST DETAILS section, you must specify a year and date for the fallow model to halt. This must be specified so that it precedes the planting date, PDATE, of the next crop found in the \*PLANT-ING DETAILS section, if planting is done as recorded (i.e., if PLANT = "R," as it does in Table 2 in the \*SIMULATION CONTROLS section for the maize crop). If planting should be automatic (PLANT = "A"), then you should specify a value of HDATE such that it precedes or is equal to the first date of the planting window for the next crop; this would be specified in PFIRST in the AUTOMATIC MANAGEMENT section of the relevant \*SIMULATION CONTROLS block.

Note that in Table 2, HDATE is set to 12304. The year must be set to 12, since the maize is first planted in 1911 (i.e. we have to look ahead to the next maize crop), and day 304 precedes the planting date PDATE of 305.

Remember that this is a hypothetical sequence simulation; years have to be specified, and the FILEX in Table 2 assumes that the crop is planted in 1911. The actual year that the simulation starts is up to the user, since simulated weather is to be used.

Note that you could specify a year of fallow in the experiment simply by setting HDATE to 13304.

#### TIMING CONTROLS

One of the most difficult things to define is the control of timing by the driver and the crop models when run in sequence. Time is controlled internally in the models and the driver. All that is required from FILEX is that there is enough information to specify what happens exactly for the first germ of the rotation. In subsequent run-throughs of the germ, the years of planting, fertilizer additions, etc., will be automatically updated.

It is important that you understand how these operate for sequencing, because some users may want to set up sequence FILEXs manually. Some practice will probably be needed in this. The table below may help to make things clearer; it shows the first few iterations of the sequence specified in Table 2:

Run Number	Crop	Star	ted	Finis	shed	
		Year	Day	Year	Day	
1	MZ	1911	244	1912	059	} germ 1
2	FA	1912	060	1912	304	} "
3	MZ	1912	305	1913	057	} germ 2
4	FA	1913	058	1913	304	} "
5	MZ	1913	305	1914	049	} germ 3
etc.						
		- — — –	- — — -		- — — -	

"Started" refers to the date when the appropriate crop model was called; "finished" refers to when the appropriate crop model ended its run. The maize model "finished" its run once maturity had been reached; this is dependent on weather, to some extent, so that it may vary from one year to the next. The fallow model thus started at different dates, but it finished on the same day each year, as specified by HDATE. Note also that the starting date of simulation is day 244 of 1911, specified by YRDAY in \*SIMULATION CONTROLS block 1. Initial conditions relate to this date also (ICDAT = 11244 in the \*INITIAL CONDITIONS section), and residue is added to the system on day 300 of 1911 (RDATE = 11300 in the \*RESIDUES section). Planting of maize, however, first takes place on day 305 of 1911, and on day 305 of each year thereafter (PDATE = 11305 in the \*PLANTING DETAILS section).

### SIMULATION CONTROL OPTIONS

There are a number of simulation control options in FILEX that are generally important for sequence analyses (refer to the \*SIMULATION CONTROLS block number 1 (i.e., N = 1) in Table 2). These are described as follows.

#### **NYERS**

NYERS is the length of the sequence in years; it has a different meaning from NYERS in Seasonal Analysis (refer to Part 1 of this Volume, Volume 3-1, Thornton et al. 1994). NYERS may have a value between 1 and 50. Sequence experiments will normally be run using simulated weather (i.e., where the variable WTHER, one of the METHOD options, is set to "W" or "S"). If you have a real long-term experiment, this will presumably be unreplicated in terms of weather; you may then use WTHER set to "M" ("measured" weather). If for any reason you want to run a replicated sequence using historical weather, you would have to set up the FILEX to have multiple treatments with a different \*FIELDS block for each replicate; you would specify the germ for each treatment, and specify a different historical weather file to start the run with under the "WSTA...." header variable in each \*FIELDS control block. You would then need to check the availability of historical weather data files.

#### **NREPS**

NREPS specifies the number of replicates of the rotation or crop sequence. It may vary from 1 to 20. The impact of replication on the stability of simulation results is very important, and is addressed in the Appendix to this Part.

CAUTION: You are highly recommended to read the Appendix before using any of the sequence capabilities of DSSAT v3; it is easy to produce misleading results from analysis of simulated sequence experiments.

#### **RSEED**

RSEED is the random number seed for weather generation. With the same seed, you will obtain the same sequence of random numbers, and hence the same sequence of daily weather, if you start from the same starting date of simulation (SDATE). RSEED is used only if WTHER is set to "W" or "S." When sequences are replicated, the initial RSEED used is incremented to Rnew from the value in FILEX according to:

Rnew = RSEED + 5(i-1)

where *i* is the replicate number. If you run into problems, this will allow you to be able to calculate the value of the random number seed that gave rise to the problem, generate the offending weather sequence, and, hopefully, reproduce and isolate the problem.

#### **FNAME**

If this switch is set to "N," then the summary output file from the model runs will be named SUMMARY.SQS. If FNAME is set to "Y," then the summary output file name will be the same as the model FILEX name, except that the last letter of the extension will be changed from X to S. Thus for the experiment FILEX in Table 2, which has the name EBAF1101.SQX, the summary output file will be named EBAF1101.SQS, since the switch FNAME is set to "Y."

#### **SUMRY**

For sequence simulations, this controller should always be set to A (append), otherwise the summary output file will be successively overwritten by each treatment and earlier outputs lost. In Table 2, all the other OUTPUTS options are set to "N," to prevent output from the models. Since sequence simulations with many replicates can produce prodigious quantities of output data, it makes sense to turn these output files off, unless you need them specifically.

Although setting up sequence FILEXs may seem complicated, it is rather flexible. The distribution diskette of the Sequence Analysis program contains two other sequence FILEXs that illustrate some of this flexibility. UFGA7803.SQX contains a simple multiple treatment experiment. Treatment 1 involves soybean and fallow, and Treatment 2 bean and fallow. Pay special attention to the values of N and R in the \*TREATMENTS section of this file.

Another FILEX that is distributed with the DSSAT v3 software is UFGA7804.SQX. This is a more complicated rotation involving two bean crops in one season followed by soybean in the next. The rotation germ is thus specified as BN1 - FA1 - BN2 - FA2 - SB1 - FA3, spanning two seasons. Each fallow is distinct and must be so treated in the analysis (see Chapter 4 herein).

You may specify rotations with up to 9 distinct components. The sequence driver will operate even if no fallows are specified between each crop component. However, you are highly recommended to specify fallows between each crop component. It is also generally a good idea to make the sequence length exactly divisible by the germ length; thus, if your germ describes a four-year rotation, set NYERS to a multiple of four. This will avoid possible confusion when using the Sequence Analysis program.

# CHAPTER THREE. RUNNING SEQUENCE ANALYSIS EXPERIMENTS

#### OVERVIEW

The Sequence Analysis driver program takes the FILEX selected or created by the user, and runs through the rotation germ until NYERS have elapsed, calling the appropriate crop model.

The driver is a FORTRAN program that allows the user to pick an entry from EXP.LST (i.e., a particular FILEX; see Volume 2-1, Jones et al. 1994, of this book for a description of the EXP.LST file). The FILEX is then read and various controls are set. Each rotation component specified in the FILEX is then run in its order of appearance in the \*TREATMENTS block of the FILEX. The appropriate model is called for each component (the model is run under the command of the driver program), and it will be run for as many years as are specified by NYERS and for as many replicates as are specified by NREPS in the FILEX. When all runs have been completed, the results listing file SEQUENCE.LST (see the example in Table 3) is updated with the name and description of the summary output file produced. The user can then quit the program or choose another FILEX for running under the sequence driver.

The sequence driver can be run in a stand-alone mode or through the DSSAT v3 Shell (Volume 1-3, Hunt et al.1994, of this book). It is important to note that in which ever mode the driver is run, the program expects to find the model program(s) in the same directory. If model executable files are not found in that directory, then an error message is printed and the user must arrange the executable files so that this condition is met. The file DSSATPRO.FLE (see the Appendix to Volume 1 of this book for a description of this file) also expected to be in this same directory, with appropriate pointers to the relevant directories for the crop model executable files.

#### TABLE 3. SUMMARY MODEL OUTPUT LISTING FILE SEQUENCE.LST.

```
*SEQUENCING LIST

@# FILENAME EXT ENAME

1 UFGA7803 SQS SEQUENCE ANALYSIS, SIMPLE MULTI-TREAT FILE, 5:5
2 UFGA7804 SQS BN-BN YR 1, SB YR 2 EXAMPLE, 10:5
3 EBAF1101 SQS MZ-FA, 30 YRS, 15 REPS, NO N
```


From within DSSAT v3, the current directory for sequence runs will usually be C:\DSSAT3\SEQUENCE, where such files as EXP.LST, SEQUENCE.LST and appropriate FILEXs are stored.

The file EXP.LST may contain up to 99 experiments, a limit imposed by the file structure. It should be borne in mind that the sequence analysis program has a limit of being able to handle a maximum of 20 replicates and a total of 1000 separate model runs.


#### AN EXAMPLE

On activating the "Simulate" option under the "Sequence" window (Screen 1, below), the driver program is activated, and the user is presented with Screen 2 (on following page). Screen 2 contains the contents of the file EXP.LST, the listing file in the current directory of current or selected FILEXs for sequence analysis. This lists the file number, file name, crop group code ("SQ" for sequence analysis), and description. The description may be up to 60 characters long; if it is shorter, the description is padded with full stops. The file description is obtained from columns 26 through 85 of the first line of FILEX (see Table 2).

If the colors on the screen are difficult to see (such as when the program is being run on a monochrome laptop computer), you can force the program to display



SCREEN 1.



#### SCREEN 2.

screens in monochrome by pressing the <ALT>-<F2> keys. Note that you cannot reverse the color scheme during a session with the program, nor is your preference stored from one session to another.

If the chosen FILEX cannot be found, an error message is printed on the screen, and the menu reappears for making another choice.

Select the third FILEX, EBAF1101.SQX, in Screen 2, using the cursor keys or the mouse, and press the <ENTER> key. This is the same FILEX shown in Table 2.

Having chosen a valid FILEX name, the driver checks to see if there is an existing output file with the same name in the current directory (this is controlled within FILEX; see previous discussion). If there is, then the user is warned that the output file will be overwritten. Press the <ENTER> or <Y> key to continue regardless, or else press the <N> key to quit the program so you can rename or move the existing output file.

Once past Screen 2, the driver will issue appropriate commands and call up the crop model(s). The initial model-produced screen warns the user not to touch the

keyboard. Once simulations are under way, each model run is summarized on the screen, so that the user can chart progress of the experiment. Sequence experiments over many years and/or with many replicates may take a great deal of time to simulate, especially on older personal computers. No keyboard input should be made, unless an error occurs.

To abort the simulation runs before they have finished, press the <ESC> key or press <CTRL-BREAK>.

For each FILEX simulated, the driver updates or creates a listing file which stores the names of the summary results files (in similar fashion to EXP.LST, which stores the names of available FILEXs in the current directory). This file, SEQUENCE.LST, is of the same format (Table 3), and is used by the analysis program described in the next section. Two other messages may appear on the final screen:

- 1. If FNAME was set to "N," then the summary output file produced by the model(s), SUMMARY.OUT, was renamed to SUMMARY.SQS; the program tells you that this has been done;
- If the summary output file of the appropriate name does not appear in SEQUENCE.LST, then SEQUENCE.LST is updated, and the program tells you that this has been done.

Press the <ENTER> key to exit the program, or the <Y> key to return to Screen 2, showing file EXP.LST, where another experiment can be chosen and simulated. You may simulate as many FILEXs as you like, one after the other, without exiting the driver program.

Simulation results are stored in the summary output file, in this example EBAF1101.SQS (the first 20 data records of this file are shown in Table 4).

#### INFORMATION AND ERROR MESSAGES

A number of information and error messages are produced by the sequence driver program. In the list that follows, each message is preceded by a single-digit code and a three digit message/error number. If the single-digit code is "0," then this is a fatal error, and the program exits; if "1," then the program will continue, as the error may not be fatal. Information messages have code 1 also.

0 001 Cannot find experiment file:

The FILEX experiment listing file could not be found in the current directory.

# TABLE 4. SUMMARY OUTPUT FILE EBAF1101.SQS (FIRST 20 DATA RECORDS ONLY).

Columns 1-74

\*SUMMARY : EBAF1101SQ

!ID	IDENTIFIERS					DATES				
@RP	TN	ROC	CR	TNAM	FNAM	SDAT	PDAT	ADAT	MDAT	HDAT
1	1	110	MZ	Maize component	EBAF0001	11244	11305	12010	12059	12059
2	1	210	FA	Fallow component	EBAF0001	12060	-99	-99	-99	12304
3	1	110	MZ	Maize component	EBAF0001	12305	12305	13010	13057	13057
4	1	210	FA	Fallow component	EBAF0001	13058	-99	-99	-99	13304
5	1	110	MZ	Maize component	EBAF0001	13305	13305	14006	14049	14049
6				Fallow component	EBAF0001	14050	-99	-99	-99	14304
7	1	110	MZ	Maize component	EBAF0001	14305	14305	15008	15055	15055
8	1	210	FA	Fallow component	EBAF0001	15056	-99	-99	-99	15304
9	1	110	MZ	Maize component	EBAF0001	15305	15305	16007	16055	16055
10	1	210	FΑ	Fallow component	EBAF0001	16056	-99	-99	-99	16304
11	1	110	MZ	Maize component	EBAF0001	16305	16305	17009	17058	17058
12	1	210	FA	Fallow component	EBAF0001	17059	-99	-99	-99	17304
13	1	110	MZ	Maize component	EBAF0001	17305	17305	18010	18056	18056
14	1	210	FA	Fallow component	EBAF0001	18057	-99	-99	-99	18304
15	1	110	MZ	Maize component	EBAF0001	18305	18305	19008	19056	19056
16	1	210	FA	Fallow component	EBAF0001	19057	-99	-99	-99	19304
17	1	110	MZ	Maize component	EBAF0001	19305	19305	20006	20051	20051
18	1	210	FA	Fallow component	EBAF0001	20052	-99	-99	-99	20304
19	1	110	MZ	Maize component	EBAF0001	20305	21006	21006	21053	21053
20	1	210	FΑ	Fallow component	EBAF0001	21054	-99	-99	-99	21304

Columns 75-164

DRY W	EIGHTS							WATER.						
DWAP	CWAM	HWAM	HWAH	BWAH	H#WM	H#AM	H#UM	IR#M	IRCM	PRCM	ETCM	ROCM	DRCM	SWXM
27	5430	2006	2006	3734	348	487	78.6	0	0	1213	499	89	542	144
0	0	0	0	0	0	0	.00	0	0	615	221	45	352	141
29	2848	870	870	2112	369	200	32.2	0	0	1012	415	46	533	159
0	0	0	0	0	0	0	.00	0	0	559	194	54	325	144
27	4813	1748	1748	3336	342	432	69.7	0	0	632	382	26	225	143
0	0	0	0	0	0	0	.00	0	0	677	233	87	373	128
29	2537	824	824	1841	370	188	30.4	0	0	1070	384	86	565	162
0	0	0	0	0	0	0	.00	0	0	502	197	27	301	139
27	5061	1970	1970	3396	353	471	76.0	0	0	712	385	37	282	147
0	0	0	0	0	0	0	.00	0	0	454	198	28	236	139
34	1252	164	164	1114	434	32	11.2	0	0	1004	355	60	587	141
0	0	0	0	0	0	0	.00	0	0	641	226	41	376	139
28	2987	913	913	2215	356	217	35.0	0	0	940	404	50	469	157
0	0	0	0	0	0	0	.00	0	0	554	201	65	305	139
28	5498	2111	2111	3714	358	498	80.3	0	0	798	380	51	351	155
0	0	0	0	0	0	0	.00	0	0	493	217	19	276	136
26	3581	1292	1292	2490	335	326	52.5	0	0	807	369	64	349	161
0	0	0	0	0	0	0	.00	0	0	673.	229	79	386	141
29	4126	1450	1450	2901	368	333	53.7	0	0	851	400	42	398	152
0	0	0	0	0	0	0	.00	0	0	617	203	51	363	152

<sup>•</sup> DSSAT v3, Volume 3 • DSSAT v3, Volume 3

#### Columns 165-252

NITRO	GEN							ORGAN	IC MAT	TER	PHOSP	HORUS.		
NI#M	NICM	NFXM	NUCM	NLCM	NIAM	CNAM	GNAM	RECM	ONAM	OCAM	PO#M	POCM	CPAM	SPAM
0	0	0	26	22	24	26	12	5000	4260	43	0	0	0	0
0	0	0	0	14	40	0	0	3734	4221	42	0	0	0	0
0	0	0	13	29	24	13	6	0	4199	42	0	0	0	0
0	0	0	0	16	44	0	0	2112	4162	42	0	0	0	0
0	0	0	24	15	24	24	12	0	4139	42	0	0	0	0
0	0	0	0	13	42	0	0	3336	4098	41	0	0	0	0
0	0	0	12	31	23	12	5	0	4077	41	0	0	0	0
0	0	0	0	11	48	0	0	1841	4040	41	0	0	0	0
0	0	0	27	15	22	27	13	0	4017	40	0	0	0	0
0	0	0	0	11	36	0	0	3396	3980	40	0	0	0	0
0	0	0	5	30	23	5	1	0	3960	40	0	0	0	0
0	0	0	0	15	48	0	0	1114	3921	39	0	0	0	0
0	0	0	14	29	23	14	6	0	3898	39	0	0	0	0
0	0	0	0	10	42	0	0	2215	3863	39	0	0	0	0
0	0	0	26	13	22	26	13	0	3842	39	0	0	0	0
0	0	0	0	13	31	0	0	3714	3806	38	0	0	0	0
0	0	0	19	17	20	19	10	0	3788	38	0	0	0	0
0	0	0	0	13	43	0	0	2490	3752	38	0	0	0	0
0	0	0	20	19	22	20	9	0	3731	38	0	0	0	0
0	0	0	0	15	34	0	0	2901	3695	37	0	0	0	0

#### 0 002 No entries found in file:

The FILEX experimental listing file was found, but it contains no valid entries.

#### 1 003 Cannot find file:

The specified file cannot be found (non-fatal).

#### 0 004 Error reading:

An undefined read error occurred when attempting to read the file. The problem is usually caused by incorrect format of the file.

#### 0 005 No valid treatments found in file:

No valid treatments were found in the FILEX selected.

#### 0 006 Error in \*SIMULATION CONTROL factor levels:

The FILEX specified by the user is defective in one of the following ways: FNAME was not set or not found, NREPS was not set or not found, or the simulation control factor level with the lowest number specified by the user did not have a corresponding \*SIMULATION CONTROL block in the file.

#### 0 007 Error in \*CULTIVAR factor levels in file:

A cultivar factor level was specified in the selected FILEX that did not have a corresponding cultivar description in the \*CULTIVARS block of the file.

- 1 008 Model runs completed!
- 1 009 SUMMARY.OUT renamed to SUMMARY.SQS

#### 1 010 SEQUENCE.LST updated, added file:

Specified summary output file added to the listing file.

#### 0 011 A required file was not found .. aborting:

This usually refers to the absence of the file DSSATPRO.FLE, which could not be found.

#### 0 012 Excessive path length error:

You need to reduce the path length as specified in DSSATPRO.FLE for the crop model "cc" (e.g. MZ). Path lengths as specified in the DSSATPRO.FLE must be less than 36 characters in total length, including drive letter, colon, and leading and trailing slashes (\). If these paths are modified using the SETUP menu of the DSSAT3 shell, then there is no problem, as the screens will not allow you to enter paths longer than this. If you modify DSSATPRO.FLE with a text editor, then you need to ensure that this total length is not exceeded.

#### 0 013 No code error:

The crop code specified (e.g. MZ) could not be found in the file DSSATPRO.FLE. This will occur if a cultivar is specified in FILEX that does not have a valid crop code.

#### 0 014 Read error in file:

An undefined read error occurred when reading the specified file; check the format of the file.

0 015 Rotation Option feature not yet implemented; file:

The specified FILEX contained a value for the rotation option "O" other than 1; exit and fix the file.

0 016 SEQDRV: READ error, file:

A read error occurred while the sequence driver was reading the specified file.

#### 0 017 SEQDRV:

A sequence driver error occurred; check the format of FILEX.

0 018 Last model run could not be completed as specified Check the format and contents of FILEX; if this error occurs, then the simulation summary output file may not be analyzable.

- 0 019 This run mode is not yet implemented
- 0 020 A problem was encountered executing another program The driver was not able to execute another program; check the free RAM that you have on your computer, and increase it if possible by unloading unnecessary resident programs (e.g. a network).
- 0 021 A problem was encountered erasing a file The specified file could not be erased.
- 0 022 A problem was encountered copying a file The specified file could not be copied successfully.
- 1 055 Problem in finding the appropriate help screen The required help screen, or the help screen file SEQDRV.HLP, could not be found.

1 100 Error!

Undetermined error.

# CHAPTER FOUR.

# ANALYZING SEQUENCE ANALYSIS EXPERIMENTS

## OVERVIEW

Having produced a summary simulation output file from a sequence experiment, the next step is to analyze this (the experiment may or may not be replicated). A brief overview of the analysis program's capabilities follows, together with some general usage notes. It should be noted that the analysis program can handle a maximum of 1000 separate model runs.

Figure 2 shows the major menu options available. The program does the following.

Biophysical Analysis. Calculates means, standard deviations, maxima and minima by year and by rotation component for any of the 35 summary output file variables (a list of these is shown in Table 7). These can be plotted as box plots, cumulative function plots, mean-variance diagrams, coefficient of variation plots, or variance plots. All graphs can be screen dumped to a printer or output to a file for plotting.

Economic Analysis. Calculates means, standard deviations, maxima and minima by year and by rotation component of economic returns, and plots these as box plots, cumulative function plots, or mean-variance diagrams. Prices and costs can be changed within a session, and price-cost variability can be included in the analysis. Simple probability analysis can be carried out, where the user specifies a threshold level of economic returns per hectare; the probability of the specified sequence failing to meet this threshold in each sequence year is then calculated and can be plotted.

Any number of summary output files can be analyzed sequentially during one session with the program. The user can also control the way in which hardcopy outputs are produced from the graphics program.

While these analyses are being performed, results are written to a results file. The file can be printed from within the program, if required. At the completion of the session, the user can access this file and use the data contained within in any way required. For example, it could be edited for importing into a graphics, spreadsheet or statistics program.





FIGURE 2. MENU OPTIONS FOR THE SEQUENCE ANALYSIS PROGRAM.

#### AN EXAMPLE

The analysis program is called from the ANALYSES main menu item of the DSSAT v3 Shell and then the "Sequence-Analyze" submenus (Screen 3, on following page). After an introductory screen, the main menu screen (Screen 4, on following page) is presented.

First you must select a sequence output file to analyze (i.e., a summary output file from a previously-run simulation). On selecting this item, the program searches SEQUENCE.LST, the listing file that contains the available model summary output files in the current directory (Table 3). These are presented to the user (see Screen 5). Note that the entries in SEQUENCE.LST do not have to match the entries in EXP.LST, either in number or in order; you may have run and analyzed the experiments in a different order, for example.

Use the mouse or cursor keys to select the file EBAF1101.SQS in Screen 5. The program then gives the user the opportunity to change the name of the analysis results file. By default, this will be the same as the summary output file, except the last letter of the extension will be "R" (for "results"). Note that file names are preserved across all three steps of the sequence analysis procedure: if the model FILEX is



SCREEN 3.

EBAF1101.SQX, then simulation results from the model(s) are saved in EBAF1101.SQS, and analysis results in EBAF1101.SQR. If you want to change the results file name, enter a new name (8 characters maximum). Do not add the

DSSAT Version 3.0 Crop Sequencing Analysis	
Main Menu Select a cropping season file for analysis	
Analyse Biophysical variables Analyse Economic variables	
Modify hardopy options About SUSTAIN2	
Exit	
F1 (Help)	71440 Mem


SCREEN 4.

extension; this is added automatically, and cannot be changed, and will always be "ccR" where "cc" is the crop code (usually SQ for sequence analysis).


If the summary output file chosen contains more than 1 treatment, you will be asked to select which treatment to analyze. If there are more than 10 treatments in the file, then you may select only from amongst the first 10; the rest will be ignored.

The next screen presented (Screen 6, on following page) summarizes the simulation runs found in the chosen summary output file. The experiment code, number of runs and replicates, starting and ending year of the sequence, the number of model runs per replicate, the number of runs per rotation (i.e., the number of crop components as specified in FILEX), and the crop codes used, are shown to the user. If there are problems with the summary output file, for instance an unequal number of replicates because of model failure for some reason, these problems will usually be apparent at this stage. Such errors are usually trapped by the analysis program and result in a warning message to the user and termination of the program.

Note that in the "Crop Codes Used" portion of Screen 6, each crop code is followed by an integer. This is to allow analyses to be made on each separate crop component specified in the original FILEX that controlled the sequence experi-



Screen 5.



SCREEN 6.


ment. In some rotations, you may have 2 or more fallow components (one between maize and beans and another between beans and maize, for example). In both biological and economic terms, these fallows may be quite different, and need to be treated separately.

On pressing any key to continue, the main menu of the analysis program appears again (Screen 4). The items in this menu are illustrated in turn.


#### ANALYZE BIOPHYSICAL VARIABLES

On choosing the main menu option, "Analyze Biophysical Variables," in Screen 4, with the mouse or cursor keys, a list of the variables available for analysis appears (Screen 7, on following page). This is a listing of all the 35 output variables written to the summary output file. You can scroll up and down this list using the  $<\neq>$  and  $<\emptyset>$  arrow keys on the keyboard. Choose the variable, "HAR YIELD kg/ha," in Screen 7 by placing the cursor bar over the variable in the list and pressing the <ENTER> key.

The next screen presented (Screen 8, on following page) asks you to choose a crop code for analysis. Choose the MZ1 component (multiple crop codes are discussed below). Thus, we have now selected to look at maize yields.



SCREEN 7.




SCREEN 8.

	Tre	nds Over Time		
	Varia	able : HAR YIE	LD kg/ha	
	Crop Code	e(s) : MZ1		
Sequence Year	Mean	St.Dev.	Min	Max
1911.0	2223.9	406.0	1708.0	3041.0
1912.0	1087.5	394.2	517.0	1992.0
1913.0	1401.0	559.2	480.0	1987.0
1914.0	1242.3	674.8	183.0	2530.0
1915.0	1206.8	587.8	132.0	1970.0
1916.0	1323.1	614.0	164.0	2102.0
1917.0	971.6	621.6	80.0	1955.0
1918.0	913.9	500.1	114.0	2111.0
1919.0	1107.2	632.0	400.0	2467.0
1920.0	1291.9	539.4	129.0	2363.0
17 ET TOTAL mm	[ ]			
18 RUNOFF mm	r 1			

SCREEN 9.

The next screen (Screen 9, above ) shows the results of the calculations by the program. The screen is headed "Trends Over Time," as the trends in maize yields may well be what we are interested in. The output variable is shown (yield per hectare), together with the pertinent crop code (maize). For each appearance of the chosen crop component, the program displays the mean, standard deviation and minimum and maximum values of the selected variable. In the example, maize was grown each season, so an annual yield is displayed for the years 1911 to 1940 (remember, the year numbers are purely for convenience in this example). The experiment was replicated; if there were only one replicate, then the standard deviation would be zero, and the mean, the minimum and the maximum yield would be identical.

Press any key to continue, and repeat until the Graphics-Regression main menu screen appears (Screen 10, on following page). If at any time you forget which variable you are looking at or which crop components are being analyzed, move the cursor bar to the "About this plot" option to remind yourself. Five types of graphs can be plotted, described as follows.




SCREEN 10.

# GRAPHICS-REGRESSION MAIN MENU

#### **OPTION 1. BOX PLOT**

If this option is selected in Screen 10, a box plot appears (Screen 11, on following page). (by default, all years are selected for plotting box plots). The box plot is a way of assessing visually the variability over time of the output variable under consideration. For the distribution of the model output variable selected, the 0th (the lowest single short line), 25th (the lower of the short lines connected by the vertical bar), 50th (the star), 75th (the upper of the short lines connected by the vertical bar), and 100th (the upper single short line) percentiles are plotted. The 50th percentile is the median of each output variable distribution, not the mean; but for symmetrical distributions, the median will often not differ greatly from the mean value.

This graph may be plotted on your printer by pressing the <P> key while the graph is on the screen. If the graph does not plot, you may need to change hard-copy settings (refer to the section, "Graphics Hardcopy Setup"). Depending on the printer and the resolution used, there may be a delay of a few seconds while this is done; wait for the graph to show on the screen again before continuing.



SCREEN 11.

**NOTE:** To return to the analysis program from any graph, press any key.


### **OPTION 2. CUMULATIVE FUNCTION PLOT**

When this option is selected in Screen 10, output variables by year or season may also be plotted as cumulative function plots. (Cumulative function plots are sometimes called cumulative probability function (CPF) plots or cumulative distribution function plots – these are the same.) Here, the distribution for the cho-


sen output variable for each season or year is ordered from smallest to largest, and plotted against equal increments of cumulative probability.

After selecting this option, the year selection screen appears (Screen 12, below), allowing the user to select which years' values are to be plotted in this way. A maximum of six CPF plots may be graphed at any time, to reduce the confusion of the plot. You can select or deselect years all at once with the <+> or the <-> key, or individually with the space bar. If more than six years are selected, the program will plot the first six years selected; the rest will be ignored.

For the example, select the years 1911, 1913, 1915, 1917, 1919, and 1921 (as shown in Screen 12), and press the <ENTER> key. The resulting plot is shown in Screen 13 (on following page). To print, press the <P> key, or press the <ENTER> key to return the Graphics-Regression main menu (Screen 10).



SCREEN 12.




SCREEN 13.

### **OPTION 3. MEAN-VARIANCE PLOT**

When this option in Screen 10 is selected, output variables may be plotted in mean-variance space. The calculated mean is plotted against the variance for the output variable of interest, and the sequence year numbers themselves are drawn on the graph. All the seasons available may be plotted in this way, or you may choose a subset of seasons to avoid confusion on the graph. Such graphs are another way of giving an indication of the variability associated with each season in the sequence, and are useful for visualizing the tradeoffs that must sometimes

be made between striving for a higher mean value while increasing the variability (as described by the variance) for the output of interest.

Choose the mean-variance plot option to produce the plot (Screen 14, below). The y-axis for such a plot is always scaled automatically, and care will sometimes be needed in interpretation, as the difference between the means (i.e., the difference from the top to the bottom of the scale) may not be very much, and will sometimes be much less than appears from a cursory glance at the graph. To print the plot, press the <P> key, or press any key to return to the Graphics-Regression main menu (Screen 10).




SCREEN 14.

# **OPTION 4. VARIANCE PLOT**

If this option is selected in Screen 10, a time series is produced (Screen 15, below) of the variance of the output variable chosen over the length of the sequence. The variance will often be of use in determining whether variability in the system is increasing or decreasing over time. If it is increasing, then this may be an indication of long-term problems in the system leading to unsustainable performance, for example.

There will be some output variables where no change in variance is expected over




SCREEN 15.

time, such as in seasonal rainfall. If there is a clear trend in seasonal rainfall and you have used one of the weather generators, for example, this is clear indication of a serious problem (BUT refer to the Appendix). Return to the Graphic-Regression main menu (Screen 10) by pressing any key.

### **OPTION 5. COEFFICIENT OF VARIATION PLOT**

The fifth graphics option in Screen 10 allows you to plot the coefficient of variation of the selected output variable, calculated as (s/x) \* 100, where s is the standard deviation and x the mean, against time. This type of plot can give a useful



SCREEN 16.


indication of changes in relative variability through time. Screen 16 (on previous page) shows an example for maize yield. Note that although mean yield decreased through time, relative variability, as measured by the coefficient of variation, increased markedly.

Return to the Graphics-Regression main menu (Screen 10) by pressing any key.

### **OPTION 6. REGRESSION MENU**

Choose the "Regression Menu" option in Screen 10. The screen that appears (Screen 17, below) gives you the option of calculating a linear or exponential regression on the means of the seasonal output variable. The regression line with the original means can be plotted, as can the residuals from the regression.

If you have not yet read the nAppendix, then please do so now. It cannot be over-emphasized that the potential to produce spurious results is high at this stage in the analysis program. To reiterate a major conclusion of Appendix A, the chances of obtaining a meaningful regression of means with less than 10 replicates of the sequence are slim. You are urged to exercise caution in interpreting such analyses, and this is not something the program can do — your own common sense must prevail.



SCREEN 17.

#### REGRESSION MENU


From the regression menu, you must first choose to do a regression before plotting it or the residuals.

Linear Regression. To illustrate, choose the option, "Do a linear regression," in Screen 17. The resulting screen (Screen 18, below) gives the output, in terms of the calculated constant or intercept, the slope or gradient, the quantity  $r^2$ , the standard error of the gradient, and a t-test that tests the hypothesis that the gradient is significantly different from 0. The meaning of these outputs is as follows (from Snedecor and Cochran, 1980).

The program performs a simple least-squares regression and fits the following line to the data points:

$$y = mx + c$$

where y is the output variable under consideration (here, yield), m is the slope or gradient, x is the year number, and c is a constant (the y-axis intercept, or the value of y when x equals zero). The quantity  $r^2$  can be interpreted as the estimated proportion of the variance of y that can be attributed to its linear regression on x. The hypothesis that the gradient is significantly different from zero (i.e., a



Screen 18.

trend exists) can be tested by

$$t = m/s_m$$

where t is distributed as Student's t with n-2 degrees of freedom ( $s_m$  is the standard error of the gradient and n is the number of data points).

The model fitted,

$$y = a + i \Im x + e$$

where e is a random variable drawn from  $N(0,s_{x,y}^2)$ , makes a number of assumptions, including the following:

- 1. For each specific X there is a normal distribution of Y from which sample values of Y are drawn at random;
- 2. The normal distributions of Y for specific X are independent;
- 3. The normal distributions of Y for specific X all have the same variance  $s_{X,V}^2$ .

All these assumptions are often violated when looking at trends in sequences: the distribution of yields for any sequence year will often not be normal; the sequence distributions are not independent, since yields in one year will be dependent to some extent on yields in previous years; and the variances of output distributions often change markedly over the length of the sequence.

For these reasons, great care is needed in interpreting the regressions. A quick idea of the likely significance of the regression can be gained from inspection of the value of  $r^2$ ; for the 10 or 20 data points that will often be used in the program, any value less than 0.5 or so will indicate that the regression is not statistically significant.

In the example in Screen 18, the regression suggests that the slope or gradient is negative (i.e., on average, there is a trend for maize yields to decrease by 34 kg/ha each season). The standard error of the gradient is not large, compared with its value. The slope is significantly different from zero, according to the t-test. The regression explains a fair proportion of the variability in mean yield, since the value of  $r^2$  is moderate (0.6).

Exponential *Regression*. The exponential regression option operates in the same way, by fitting the linear transformation

$$ln(y) = ln(c) + mx$$


of the exponential function

$$y = c * exp(mx),$$

notation as above.

Plot the Regression Line. Having fitted a regression, the regression line can be plotted; choose this option from the Regression menu (Screen 17) to produce the plot (Screen 19, below). The fitted line is shown together with the seasonal means as small boxes. Note that the yield for 1911 is much higher than its regressed value. This is largely due to the 5 t/ha of crop residue added at the start of each sequence replicate (see Table 2).

Press any key to return to the Regression menu.



SCREEN 19.

Plot the Regression Residuals. Now choose to plot the residuals (Screen 20, on following page). These are the deviations of the points Y from the fitted line,

$$d_{v.x} = Y - Y = y - mx$$

where Y is the regressed value of output and Y is the simulated value from the crop model. No trends or patterns should be discernible in the residuals; such patterns are evidence of serious violations of the assumption of statistical independence in particular, and the resulting regression should be discarded or treated with caution.

To sum up, despite the patina of "objectivity" that may be given to your simulated results using regression to find trends, you should exercise great care in interpreting the outputs from the regression option. As noted above, there is no substitute for common sense.

# Analyzing More Than One Crop At A Time

The analysis program has the option for analyzing more than one crop at a time. To illustrate, return to the Analyses main menu (Screen 4), again select the option, "Analyze Biophysical Variables," and then choose the variable precipitation (PRECIP mm) from Screen 7, and pick both crop codes as shown in Screen 21 (on second following page.)


The resulting screen warns you that you have picked multiple crop codes. In the subsequent screen (Screen 22, on second following page), you have to make a choice as to how the program will analyze these multiple crops. There are three options, described as follows.

Option 1 - Additive. The values of the output variable for all selected crops will be simply added together to provide a grand total by year of the output of interest;

Option2 - Average. The values of the output variable for all selected crops will be averaged to provide a single "mean" value of the output of interest for the relevant calendar year;


Option 3 - Time Series. Each value of the output variable for all selected crop codes will be treated independently to provide a time series of the output of interest.

Which option you choose will depend on the output variable and what you are trying to achieve. It is important to understand the differences in these three options. For example, it may make sense to add total fertilizer applied across different crops; it may not make much sense to add bean yields and maize yields if grown in the same growing season in the same calendar year.




### SCREEN 20.

Choose the "Time series" option in Screen 22 for looking at precipitation for the maize-fallow experiment. The resulting screen (Screen 23, on second following page) lists the mean, standard deviation, minimum and maximum rainfall by sequence year. Note that the sequence years have non-zero decimal points. The time series is produced by treating maize and fallow separately; for the first replicate, maize was harvested on day 59 in 1912 (see Table 4, data record 1, under HDAT), with a cumulative rainfall mean of 1213 mm (Table 4, data record 1, under PRCM). For all 15 replicates, the mean harvest date was day 55.8 (you can check this by analyzing the maize harvest date). Thus the sequence year



SCREEN 21.



Screen 22.

number is calculated as 1912+(55.8/365), or 1912.2 to one decimal place (Screen 23).


The first fallow period of the first replicate stopped on day 304 in 1912, as it did for each year subsequently (Table 4): remember that planting of maize took place on day 305 each year. The mean sequence year number for the fallow rainfall total is thus calculated as 1912+(304/365), or 1912.8 to one decimal place. These are the year numbers that are used in all subsequent plots. Thus a box plot of precipitation shows a time series of these cumulative rainfall occurrences (see Screen 24, on following page).

You may notice that the rainfall amount for the maize crop in 1911 - 1912 appears higher than in other years. This is explained by the fact that in 1911, simulation with the maize model started on day 244 (Tables 2 and 4); in all other years, the maize model was run from day 305. Thus in 1911, the rainfall total covers a longer period than in any of the other years. This again illustrates the care that is needed in the interpretation of analysis results and the importance of understanding the nature of your crop sequence.

Now return to the Crop Code menu (Screen 21), choose MZ1 and FA1 as before,

	Tre	nds Over Time		
	Varia	able : PRECIP n	nm.	
	Crop Code	e(s) : MZ1 FA1		
Sequence Year	Mean	St.Dev.	Min	Max
1912.2	1050.9	137.3	763.0	1222.0
1912.8	638.1	100.1	519.0	898.0
1913.2	893.1	113.5	711.0	1174.0
1913.8	636.3	134.8	438.0	914.0
1914.1	846.6	99.2	632.0	1007.0
1914.8	631.2	124.8	380.0	850.0
1915.2	872.5	157.2	589.0	1131.0
1915.8	614.7	145.8	336.0	892.0
1916.2	880.7	141.4	712.0	1182.0
1916.8	557.8	163.2	392.0	981.0

SCREEN 23.



SCREEN 24.

but this time choose Analysis Option 1 (Additive) in Screen 22. Observe the differences in the tabular output and the plot; "maize" and "fallow" precipitations are added together by the calendar year in which they occurred (according to harvest dates in the summary output file).

Now do the same thing, but choose Analysis Option 2 (Average) in Screen 22; the average values will be produced by calendar year. Note that this analysis has little meaning here, but it is useful for understanding the differences in the analysis options.

The analysis program thus has the flexibility to analyze different combinations of rotation components. Again, you should be careful in interpreting the results, as they may not always be meaningful or useful.

# Analyze Economic Variables


Option 2, "Analyze Economic Variables," in the Sequence Analysis main menu (Screen 4) allows the analysis of the sequence in economic terms. On choosing this option, the Economic Evaluation main menu appears (Screen 25, on following page). There are four major options, described below.

# ECONOMIC EVALUATION MAIN MENU


# **OPTION 1. ACCESS A PRICE FILE**

Before economic evaluation can be undertaken, the program must have access to a price-cost file that details the costs and prices to be used for the analysis. The program will try to read an appropriate price-cost file by itself, but various options are open to the user. Select this option to get to the next menu, Screen 26 (on following page).

- \* Tied Price-Cost Files: Use a price file, extension PRQ, that is "tied" or directly related to the experiment FILEX (in the example, EBAF1101.PRQ). This option might be used when you have a complicated experiment and you wish to preserve the prices and costs that pertain to the experiment.
- \* Default Price-Cost File: A default price file, called DEFAULT.PRQ, can be used (this file is distributed with the DSSAT3). This default can be as simple or as complicated as the user requires (its format is shown in Table 5).
- \* User-Specified Price-Cost File: The user can browse the hard disk directory structure and find an appropriate PRQ file that will be used in the analysis.



SCREEN 25.



SCREEN 26.

Format and Content of Price-Cost Files. The format of the default price-cost file DEFAULT.PRQ for sequence analysis is shown in Table 5, together with a listing of the headers that appear in the file. The eleven prices and costs that are currently included are as follows.:

Cc	st or Price	Units	Associated Model Output
2 3 4 5 6 7 8	Price of harvest product (e.g., gra Price of harvest byproduct Base production costs Nitrogen fertilizer cost Cost per N fertilizer application Irrigation costs Cost per irrigation application Seed cost Cost of organic amendment	\$/t \$/ha \$/kg \$ \$/mm \$ \$/kg \$/t	\$/t yield, t/ha byproduct yield, t/ha  - N applied, kg/ha No. of N applications irrigation applied, mm No. of irrigation applications seed sown, kg/ha residue applied, t/ha
	Phosphorus fertilizer cost Cost per P fertilizer application	\$/kg \$	P applied, kg/ha No. of P applications

Note that costs and prices can be negative or positive; this might apply particularly to harvest byproduct, where a negative income is posited (i.e., it costs the farmer money to remove the byproduct — straw or stover, for example). Any monetary units can be used; so "\$" can be thought of as "money in general" rather than "dollars."

Economic evaluation of the sequence can take account of price and cost variability. Details on how this is done within the program are given in Appendix A to Part 1 (Seasonal Analysis) of this Volume.

Sequence analysis price files, as shown in Table 5, can contain many lines per section: a header line, a line containing a value that is used for generating stochastic values, and a time series of values. Stochastic generation of values is controlled as follows:

- 0 Fixed: a deterministic or non-variable price or cost is used
- >1 A normal variate is assumed, from the distribution N(x,s), where x is the mean value that appears in the time series, and s is the standard deviation. The value stored in the file is the standard deviation expressed as a percentage of the mean, i.e., the coefficient of variation.

## TABLE 5. PART OF THE DEFAULT SEQUENCE PRICE FILE, DEFAULT.PRQ.

\* PRICE-COST\_FILE : DEFAULT FOR SEQUENCE ANALYSIS

! Line for which YRDOY=# is %SD of price/cost

* MZ											
@YRDOY	GRAN	BYPR	BASE	NFER	NCOS	IRRI	IRCO	SCOS	RESM	PCOS	PFER
#	10.00	0.00	0.00	0.00	.00	0.00	.00	.00	.00	.00	.00
1978001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1979001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1980001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1981001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1982001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1983001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1985001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1986001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1987001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1988001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1989001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1990001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1991001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1992001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1993001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1994001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1995001	130.00	10.00	155.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
* SG											
@YRDOY	GRAN	BYPR	BASE	NFER	NCOS	IRRI	IRCO	SCOS	RESM	PCOS	PFER
#	10.00	0.00	0.00	0.00	.00	0.00	.00	.00	.00	.00	.00
1978001	330.00	10.00	395.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00
1979001	330.00	10.00	395.00	.50	12.00	.50	15.00	0.50	0.00	.00	.00

#### Headers

YRDOY Date of price or cost, year (YR) and day number (DOY)

GRAN Price of grain, \$/t

BYPR Price of harvest byproduct, \$/t

BASE Base production costs, \$/ha

NFER Nitrogen fertilizer cost, \$/kg

NCOS Cost per N fertilizer application, \$

IRRI Irrigation cost,  $\mbox{\$/mm}$ 

IRCO Cost per irrigation application, \$/ha

SCOS Seed cost, \$/kg

RESM Cost of organic amendments, \$/t

PCOS Phosphorus fertilizer cost, \$/kg

PFER Cost per P fertilizer application, \$

<sup>•</sup> DSSAT v3, Volume 3 • DSSAT v3, Volume 3

If you specify a large number (more than three) of stochastic prices and costs, and your computer is not one of the fastest, the economic analysis program may take a long time to run. Usually it is best to use only a few stochastic prices and costs.

The price-cost file is sectioned by crop as shown in Table 5. You may have different sections for different sequence components of the same crop; thus MZ1 and MZ2 might share the same set of prices and costs, or you could have two sections, one headed "\*MZ1" and one "\*MZ2." If no integer is specified with the crop code, it is assumed to be a general section, and will be used for all component numbers with that crop code.

**OPTION 2.** CHOOSE TO INCLUDE/EXCLUDE FALLOW PERIODS IN ANALYSIS The second option in the Economic Evaluation menu (Screen 25) allows the user to decide whether to include or exclude the effects of fallow periods in the analysis. Selecting this option toggles the text from "include" to "exclude" or viceversa. Fallow periods often have some economic cost, and you may want to incorporate these into the analysis. If you include them, then you must have a fallow section in the cost-price file you are using.

#### OPTION 3. EDIT PRICE FILE FOR SENSITIVITY ANALYSIS

When you choose this option in Screen 25, the program loads the default editor and the price file that has been selected. You may then make changes to the price file, save it, and exit to the analysis program. The editor that the program will load is the editor specified in the SETUP menu item of the DSSAT Shell (see Volume 1-3, Hunt et al. 1994, of this book for a description of the SETUP menu item). You should be careful when making edits in the price file that you preserve the format of the file, otherwise you may obtain error messages when the analysis program tries to read the modified file.


### **OPTION 4. DO ANALYSIS (CALCULATE ECONOMIC RETURNS)**

When this option is selected from Screen 25, the program will calculate the mean, standard deviation, maximum and minimum value of net return or gross margin per hectare for each sequence year using the costs and prices specified. The first set of results are for total returns (Screen 27, on following page), including all the crop components in the sequence (or excluding fallows, if you have selected this option). Once these results have been tabulated, you may want to view the returns arising from each separate crop component. If so, select <Yes> at this point to be presented with tables of returns by crop component.

		Mean	St.Dev.	Min	Max
Year 1		230.04	84.66	102.55	
Year 1		41.77	73.82	-62.64	228.98
Year 1		85.28	92.87		229.98
Year 1	.914	65.05	114.94	-95.57	320.76
Year 1	.915	56.40	95.37	-103.03	226.15
Year 1	.916	74.49	100.17	-99.50	246.28
Year 1	.917	24.89	101.02	-113.56	223.78
Year 1	.918	18.40	89.13	-105.71	251.42
Year 1	.919	47.88	109.34	-73.25	313.52
Year 1	.920	73.33	95.61	-103.87	293.66

SCREEN 27.


You then have the option to plot some results. The plot menu (Screen 28, below) allows you to do box plots of economic returns by crop component or total returns (all crop components included in the analysis). Select the option, "Box




SCREEN 28.

Plot of Total Returns," in Screen 28 and the resulting box plot for all years is shown in Screen 29 (below), in the same way as for the biophysical variable box plots described above.

Return to the plot menu (Screen 28). Select the "Probability Analysis" option; the resulting screen is shown as Screen 30 (on following page). Again, you may do a probability analysis by crop component or for total returns (all components




SCREEN 29.



SCREEN 30.

together). Select the "Total returns" option. You are then asked to enter a critical return, \$/ha, in Screen 31 (below). This might be a threshold value of returns that the sequence is required to generate. In some situations, the probability of



SCREEN 31.


failing to generate a certain level of returns from an enterprise is an important criterion of viability; if this probability of failure increases through time, then this raises serious questions concerning the long-term viability of the crop sequence or rotation. The probability analysis performed is one way of addressing this issue.

Having selected the critical return (Screen 31; enter a value of \$0/ha here), the program will calculate the probability each year of failing to meet this critical return. The resulting screen (Screen 32, below) shows the probability of the sequence failing to generate positive returns per hectare in each sequence year. Press any key to complete the display of the table. You are then asked if you want to plot these probabilities. Enter <Y> to produce the plot in Screen 33 (on following page).

The costs and prices used in the example are hypothetical (and are also constant throughout the sequence from 1911 to 1940; edit the file EBAF1101.PRQ to see this). As might be expected in such circumstances, reductions in mean yields result in increased probabilities of negative returns across the years of the sequence.

Pı	robability of	Obtaini	.ng <	.00 \$/Ha	
	Component	Year	Probabil	lity	
	ALL	1911	.000		
	ALL	1912	.297		
	ALL	1913	.207		
	ALL	1914			
	ALL	1915			
	ALL	1916			
	ALL	1917			
	ALL				
	ALL ALL	1919 1920			
	ALL	1920	.192		
	Do you want	to plo	ot this (Y	7/N)?	
		[NO]			

SCREEN 32.




SCREEN 33.

Press any key, then press <Escape> three times to return to the Analysis Main Menu (Screen 4).

# MODIFY HARDCOPY OPTIONS

Select this option in the Sequence Analysis main menu in Screen 4 to change the way in which hardcopies of graphs are produced on your printer or plotter. The screen that appears (Screen 34, on following page) lists the current graphics hardcopy options. These are stored in an ASCII file called GRAPH.INI (see Table 6).



SCREEN 34.

The various controller options can be changed from this screen, simply by selecting the option to change and choosing any of the valid options (thus your printer port might be LPT2 rather than LPT1). On finishing, you can abandon the changes you have made, or you can save the changes to the file GRAPH.INI.

Normally, configuration of the graphics program will be carried out through the configuration menu in the sequence and seasonal analysis programs. You may wish to edit GRAPH.INI with a text editor, however. The section of GRAPH.INI that holds configuration data for the graphics program is under the [WMGraf] section of the INI file. Defaults for plotting are defined in this section, in the format "keyword=" followed by a string, integer, or real variable. Specifically, the keyword definitions and possible values are as follows:

gcolor[0..7]: refers to the default color palette for plotting. Values are 0 to 15. interval: number of major divisions on the X and Y axis ("-9" chooses

Autoscaling)

tics: number of tic marks between the major divisions ("-9" chooses

Autoscaling)

driver: an integer value of 0 to 33 is specified. The printer/plotter options

are listed in Table 7.

0 for LPT1:, 1 for LPT2:, 2 for COM1:, 3 for COM2:, or 4 for redirecport:

tion of output to a file

orientation: 0 for portrait or 1 for landscape fontsize: fontsize for labels (1 to 20)

xmult: X multiplier ymult: Y multiplier

file: name for file output if port=4

The printer types supported by the graphics program are shown in Table 7.

You may also need to be aware that legends for the graphics program are taken from a DSSAT3 file called DATA.CDE (see Table 8 and Appendix C to Volume 2-1, Jones et al. 1994, of this book). This lists, among other things, the headers, abbreviations, and definitions of the 35 output variables in the summary model output file that can be analyzed using the seasonal analysis program, in the section headed by the \*SUMMARY keyword.

#### TABLE 6. SAMPLE SECTION OF GRAPH.INI.

[WMgraf] color0=1

color1=15

color2=14

color3=12

color4=15

color5=10

color6=11

color7=13

interval=-9

tics=-9 driver=7

port=0

orientation=0

fontsize=6

xmult=1.00

ymult=1.00

usetics=Y

usekeyword=1

file=OUTPUT

TABLE 7. PRINTER TYPES SUPPORTED BY THE GRAPHICS PROGRAM.

Driver Number	Driver Description
0	Epson 9 Pin 60 x 72 dpi
1	Epson 9 Pin 120 x 72 dpi
2	Epson 9 Pin 240 x 216 dpi
3	Epson 24 Pin 180 x 180 dpi
4	Epson 24 Pin 360 x 180 dpi
5	Epson 24 Pin 360 x 360 dpi
6	HP LaserJet/DeskJet B&W 100 dpi
7	HP LaserJet/DeskJet B&W 150 dpi
8	HP LaserJet/DeskJet B&W 300 dpi
9	HP DeskJet 500C 100 dpi 8 color
10	HP DeskJet 500C 150 dpi 8 color
11	HP DeskJet 500C 300 dpi 8 color
12	HP PaintJet 90 dpi B&W
13	HP PaintJet 180 dpi B&W
14	HP PaintJet 90 dpi 16 color
15	HP PaintJet 180 dpi 8 color
16	HP PaintJet 180 dpi 16 color (XL)
17	HP ThinkJet 192 dpi
18	HP 7475A Plotter A size paper
19	HP 7475A Plotter B size paper
20	HP 7475A Plotter A4 size paper
21	HP 7475A Plotter A3 size paper
22	HP 7550 Plotter A size paper
23	HP 7550 Plotter B size paper
24	HP 7550 Plotter A4 size paper
25	HP 7550 Plotter A3 size paper
26	HP 7440 Plotter A4 size paper
27	HP 7470 Plotter A3 size paper
28	HP LaserJet HPGL Mode A size paper
29	HP LaserJet HPGL Mode B size paper
30	PostScript Printer Courier
31	PostScript Printer Helvetica
32	PostScript Printer Times
33	PostScript Printer Symbol

# TABLE 8. EXPERIMENT DATA CODES FILE DATA.CDE - SUMMARY SECTION ONLY.

\*EXPERIMENTAL DATA CODES

```
*SUMMARY
SDAT START SIM day Simulation start date (YRDOY)
PDAT PLANTING day
                   Planting date (YRDOY)
ADAT ANTHESIS day
                   Anthesis date (YRDOY)
MDAT MATURITY day Physiol maturity date (YRDOY)
HDAT HARVEST day
                   Harvest date (YRDOY)
DWAP SOWING WT kg/ha Planting material wt (kg dm/ha)
CWAM TOPS WT. kg/ha Tops wt at maturity (kg dm/ha)
HWAM MAT YIELD kg/ha Yield at maturity (kg dm/ha)
HWAH HAR YIELD kg/ha Yield at harvest (kg dm/ha)
BWAH BYPRODUCT kg/ha By-product harvest (kg dm/ha)
HWUM WEIGHT mg/unit Wt at maturity (mg dm/unit)
H#AM NUMBER #/m2
                   Number at maturity (no/m2)
H#UM NUMBER #/unit Number at maturity (no/unit)
IR#M IRRIG APPS # Irrigation applications (no)
IRCM IRRIG mm
                   Season irrigation (mm)
PRCM PRECIP mm
                  Season precipitation (mm)
ETCM ET TOTAL mm Season evapotranspiration (mm)
ROCM RUNOFF mm
                  Season surface runoff (mm)
DRCM DRAINAGE mm
                   Season water drainage (mm)
SWXM EXTR WATER cm Extr water at maturity (cm)
NI#M NITR APPL #
                   Number of N applications (no)
NICM TOT N APP kg/ha Total inorganic N appl (kg/ha)
NFXM N FIX kg/ha N fixed during season (kg/ha)
NUCM N UPTAKE kg/ha N uptake during season (kg/ha)
NLCM N LEACH kg/ha N leached during season (kg/ha)
NIAM SOIL IN N kg/ha Soil inor-N at maturity (kg/ha)
CNAM CROP N kg/ha Tops N at maturity (kg/ha)
GNAM PRODUCT N kg/ha Product N at maturity (kg/ha)
RECM RESIDUE kg/ha Total residue applied (kg/ha)
ONAM ORGANIC N kg/ha Org soil N at maturity (kg/ha)
OCAM ORGANIC C t/ha Org soil C at maturity (t/ha)
PO#M P APPL #
              Number of P applications (no)
POCM TOT P APP kg/ha Total P applied (kg/ha)
CPAM CROP P kg/ha Tops P at maturity (kg/ha)
SPAM SOIL P kg/ha Soil P at maturity (kg/ha)
```

# SELECTING ANOTHER INPUT FILE FOR ANALYSIS

Having analyzed one simulation summary file, you can choose to analyze another file in Screen 5. If you choose to do so, you have the option to print the summary results file that you have generated during the session for the particular summary output file. Note that a new analysis results (SQR) file will be produced for each summary output file (SQS) you analyze. A sample of part of this file is reproduced in Table 9. This file can be edited as required, and the data imported into any application capable of reading ASCII text files for whatever purpose you require.

# Information and Error Messages

A number of information and error messages are produced by the sequence analysis program. In the list that follows, each message is preceded by a single-digit code and a three digit message/error number. If the single-digit code is "0," then this is a fatal error, and the program exits. If the code is "1," then the program will continue, as the error may not be fatal. Information messages have code "1" also. Some of these messages are self-explanatory. Others are indications of serious problems, and you should check your file formats.

# 0 001 Cannot find directory file:

The summary output listing file could not be found in the current directory.

### 0 002 No entries found in file:

The summary output listing file could be found, but no valid entries were found in it.

#### 1 003 Cannot find file:

The specified file cannot be found in the appropriate directory.

### 0 004 Error reading:

An error occurred during file reading; this is usually due to incorrect format of the specified file.

### 0 007 Cannot access file:

The specified file cannot be found in the appropriate directory.

# 1 008 Read error in subroutine GETCOD, file:

An error occurred in reading the specified file.

### 0 009 Code could not be found:

The program attempted to find the specified code in the DSSATPRO.FLE, but could not find it. The pathname associated with the code specifies the location of the graphics program for the sequence analysis graphics

#### TABLE 9. PART OF SEQUENCE ANALYSIS RESULTS FILE EPAF1101.SQR.

\*SQ\_ANALYSIS\_LOG : EBAF1101SQ

Date: 21 Apr, 1994 Time: 10:45:13

Analysis of Treatment Number 1

Input File Analysis

Experiment Code : EBAF 11 01

Number of runs : 900
Number of reps : 15
Starting year : 1911
Ending year : 1941
Runs per rep : 60
Runs per rotation: 2

Calculated Values: Variable = HAR YIELD kg/ha MZ1

Year	Mean	St.Dev
1911.0	2223.87	405.99
1912.0	1087.53	394.24
1913.0	1401.67	559.15
1914.0	1242.33	674.78
1915.0	1206.80	587.82
1916.0	1323.13	614.01
1917.0	971.60	621.63
1918.0	913.87	500.09
1919.0	1107.20	631.99
1920.0	1291.93	539.44
1921.0	595.13	360.27
1922.0	971.87	588.37
1923.0	916.47	566.53
1924.0	853.87	444.65
1925.0	935.80	363.33
1926.0	693.20	475.74
1927.0	1129.73	510.32
1928.0	304.27	338.10
1929.0	740.53	500.52
1930.0	650.47	402.82
1931.0	694.87	376.09
1932.0	911.07	485.26

1933				478.20	360.78		
1934				703.80	540.22		
1935				571.47	376.15		
1936				657.40	406.53		
1937				508.33	476.07		
1938				599.80	384.26		
1939				384.80	278.99		
1940	0.0			618.87	356.37		
	0.1	40.3	Percentil				4.00.1
Year	0th	10th	25th	50th	75th	90th	100th
1911.0	1708.0	1786.2	1903.0	2309.0	2403.0	2761.2	3041.0
1912.0	517.0	647.2	781.0	1167.0	1298.0	1446.8	1992.0
1913.0	480.0	606.2	999.0	1748.0	1869.5	1969.6	1987.0
1914.0	183.0	442.0	791.0	1142.0	1688.5	2082.2	2530.0
1915.0	132.0	418.0	794.0	1294.0	1594.0	1923.2	1970.0
1916.0	164.0	521.6	897.5	1346.0	1812.5	2026.6	2102.0
1917.0	80.0	239.8	531.5	829.0	1563.5	1812.6	1955.0
1918.0	114.0	432.6	573.5	882.0	1249.0	1296.2	2111.0
1919.0	400.0	499.0	590.0	911.0	1411.5	1969.2	2467.0
1920.0	129.0	719.0	965.0	1325.0	1640.5	1763.4	2363.0
1921.0	109.0	131.0	287.0	669.0	842.0	978.6	1261.0
1922.0	68.0	251.2	592.5	1098.0	1290.0	1418.8	2370.0
1923.0	84.0	133.4	588.0	930.0	1226.0	1571.6	2026.0
1924.0	83.0	247.8	579.0	912.0	1232.5	1393.6	1404.0
1925.0	129.0	545.0	736.5	1018.0	1130.0	1324.6	1541.0
1926.0	88.0	131.6	424.0	660.0	831.0	1368.6	1697.0
1927.0	115.0	581.0	456.5	1264.0	1509.5	1714.2	1917.0
1928.0	67.0	82.6	90.5	117.0	430.0	783.8	1123.0
1929.0	68.0	96.0	331.5	740.0	1012.5	1445.2	1552.0
1930.0	94.0	219.6	496.0	558.0	780.5	1068.6	1704.0
1931.0	90.0	217.6	417.0	677.0	934.5	1215.2	1280.0
1932.0	88.0	296.2	605.0	1019.0	1205.0	1476.4	1705.0
1933.0	36.0	74.2	101.5	527.0	712.0	939.8	1051.0
1934.0	43.0	96.4	396.0	701.0	911.5	1220.4	2116.0
1935.0	25.0	89.4	257.0	640.0	748.0	966.6	1338.0
1936.0	129.0	201.6	421.5	610.0	749.5	1106.0	1693.0
1937.0	54.0	74.2	100.5	390.0	749.5	1189.6	1488.0
1938.0	47.0	143.0	415.5	574.0	722.0	1102.8	1447.0
1939.0	46.0	67.4	89.0	449.0	601.0	694.4	827.0
1940.0	80.0	117.2	466.0	593.0	811.0	1126.2	1216.0

Regression of Means Output

Type = Exponential

Year	HAR YIELD kg/ha	Residual	Estimate
1911.	2223.8670	821.9390	1401.9280
1912.	1087.5330	-263.2627	1350.7960
1913.	1401.6670	100.1375	1301.5290
1914.	1242.3330	-11.7258	1254.0590
1915.	1206.8000	-1.5211	1208.3210
1916.	1323.1330	158.8826	1164.2510
1917.	971.6000	-150.1877	1121.7880
1918.	913.8666	-167.0073	1080.8740
1919.	1107.2000	65.7482	1041.4520
1920.	1291.9330	288.4659	1003.4670
1921.	595.1334	-371.7352	966.8685
1922.	971.8666	40.2621	931.6045
1923.	916.4667	18.8397	897.6270
1924.	853.8666	-11.0217	864.8884
1925.	935.8000	102.4562	833.3438
1926.	693.2000	-109.7501	802.9501
1927.	1129.7330	356.0688	773.6645
1928.	304.2667	-441.1804	745.4470
1929.	740.5333	22.2745	718.2588
1930. 1931.	650.4667 694.8666	-41.5955 28.0454	692.0621 666.8212
1932.	911.0667	268.5660	642.5006
1933.	478.2000	-140.8671	619.0671
1934.	703.8000	107.3115	596.4885
1935.	571.4667	-3.2664	574.7330
1936.	657.4000	103.6289	553.7711
1937.	508.3333	-25.2404	533.5737
1938.	599.8000	85.6870	514.1130
1939.	384.8000	-110.5623	495.3623
1940.	618.8666	141.5714	477.2952

#### 1 016 Bad crop code (record #, file):

Crop code found in the specified file that is not valid.

#### 1 017 More than 9 crop codes found in file

The summary output file contained more than 9 crop codes, its current limit.

#### 1 018 Sequence length exceeds 50 years

The summary output file is too long to analyze.

# Multiple Treatments Found in File:

Two or more sequence treatments were found in the summary output file. You must choose which one to analyze.

#### 1 020 A problem was encountered executing another program

The program was not able to execute another program; check the free RAM that you have on your computer, and increase it if possible by unloading unnecessary resident programs (e.g., a network).

#### Error in TUKEY.FOR 1 023

An error occurred when calculating percentiles of a distribution.

#### 1 024 READ Error in file :

A read error occurred in the specified file; check the format of the file.

# READ Error in DATA.CDE

An error occurred when reading the file DATA.CDE; check that it is complete and the format is correct.

#### 1 028 Total number of runs exceeds 1000

See message 031.

#### 1 029 Total number of years exceeds 50

See message 031.

# Number of replicates exceeds 20

See message 031.

1 030

#### 1 031 File is too big to analyze:

This error message arises in conjunction with one of three other messages, and refers to the fact that the selected summary output file is too large with respect to total number of runs (error message 028), number of years (error message 029), or number of replicates (error message 030).

#### 1 032 Analysis results written to the file:

Analysis results have been written to the specified file.

Program output has been written to the specified file.

0.038Error in filename:

Error in filename specification.

1 039 Crop code not matched in price file:

There was no section in the price file corresponding to the specified crop code; you must edit the file so that this section exists.

1 040 Read error in price file:

Check the format of the price file; a read error occurred.

0.041 Cannot find file:

Specified file cannot be found.

0.042Error in:

0.043 Read error in file:

Read error in the specified file.

0.044 Must have at least 2 replicates for a CPF plot!

0.046 ERIC2 size problem

Array overflow error.

- A price file must be accessed using opt. 1 before using this option 1 047 You must access a price file before attempting to carry out the economic calculations.
- 1 049 All variances are zero; <Enter> to continue
- 1 050 Cannot find a file .. choose again:
- 1 051 You must first select a model output file!

Select one of the analysis options before continuing.

- 1 052 More than 10 treatments found; rest ignored The simulation summary output file contains more than 10 treatments; you may choose one of the first 10 only.
- 1 053 You must choose a treatment .. or loop forever!!
- 1 055 Problem in finding the appropriate help screen The appropriate help screen could not be found.
- 1 058 There were no matching files found!
- 1 060 The requested subdirectory to be searched doesn't exist!!!

- 1 070 No valid data;
- For the crop code(s) and output variable selected, there are no valid data.
- 1 071 Error in regression routine (divide by zero or inputs out of range) Problem in regression calculations; check the summary output file.
- 1 072 Reported regression outputs will not be meaningful; Problem in regression.
- 1 073 Do a regression before plotting! You must do a regression before you can plot the results.
- 1 074 All residuals are zero
- 0 075 File DATA.CDE not found
- 0 076 Error in JNO

Problem in counter in summary output file; check its format.

- 1 077 You must choose at least ONE crop code from this list;
- 1 078 Multiple crop codes chosen .. Choose method of analysis
- 1 079 No data found as specified

No data could be found for the variable and crop code(s) chosen.

1 080 All data found are zero

No non-zero data could be found for the variable and crop code(s) chosen.

1 081 Problem in ECONO2

Problem in price-cost calculations.

- 1 082 You may select up to FOUR crop codes with this option
- 1 082 This is not implemented yet!
- 1 083 Box plot of total returns NOT available for only one crop!
- 1 100 Warning!

General warning message.

- 1 131 You MUST turn on the printer now or the program will crash!
- 1 148 A problem was encountered in trying to print a file! The results file could not be printed successfully.

# REFERENCES

The Sequence Analysis program is outlined in the following:

Thornton, P.K., G. Hoogenboom, P.W. Wilkens P W and W.T. Bowen. 1994. A computer program to analyze multi-season crop model outputs. Agronomy Journal (*in press*).

A good source of general information on regression is:

Snedecor, G.W. and W.G. Cochran. 1980. Statistical Methods. Iowa State University Press, Ames, IA.

#### Other References:

- Hunt, L.A., J.W. Jones, P.K. Thornton, G. Hoogenboom, D.T. Imamura, G.Y. Tsuji and U. Singh. 1994. Accessing data, models and application programs. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds.). DSSAT v3. Vol. 1-3. University of Hawaii, Honolulu, HI.
- Jones, J.W., L.A. Hunt, G. Hoogenboom, D.C. Godwin, U. Singh, G.Y. Tsuji, N. Pickering, P.K. Thornton, W.T. Bowen, K.J. Boote and J.T. Ritchie. 1994. Input and output files. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds). DSSAT v3. Vol. 2-1. University of Hawaii, Honolulu, HI.
- Thornton, P.K., G. Hoogenboom, P.W. Wilkens and J.W. Jones. 1994a. Seasonal analysis. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds.). DSSAT v3. Vol. 3-1. University of Hawaii, Honolulu, HI.

Sequence Analysis • Sequen

## APPENDIX A.

# THE STABILITY OF OUTPUT VARIABLES FROM REPLICATED SEQUENCE EXPERIMENTS

The main conclusion of this appendix can be stated simply: to obtain relatively stable estimates of output means and variances from replicated sequence experiments, you should use as many replications as possible. In practice, you should always use at least 10, and preferably nearer to 20 (the limit of the program).

Sequence outputs may be very unstable with fewer than 10 replicates. The major implication of this is that it will be possible for users to draw erroneous conclusions from insufficiently replicated sequence experiments. It is easy to show this with a computer program that "simulates" a crop model by drawing a random sample from a normal distribution (with mean 6 and standard deviation 1.5) to represent yield, does this for 12 "years" in sequence, and replicates this sequence as often as required, from 1 to 100. The null hypothesis of NO TREND OVER THE SEQUENCE is thus true.

Results are shown in Figure 3. In the first graph, with a sample size of 100 (100 replicates), there is no apparent trend (nor should there be, as there is none), and the maxima and minima of each distribution from one season to the next do not vary greatly. The other graphs show what happens to random samples with fewer and fewer replicates (20, 10, and 5, respectively). It can be seen that the plots become progressively more erratic; note the increasingly variable maxima and minima, and the highly variable spread of the median. With only 5 replicates we apparently have an upward trend of the median.

The sequence analysis program was written with two main hypotheses in mind:

- Cropping systems that have some sort of problem will eventually exhibit decreasing performance levels over time, be it in terms of yields or economic returns;
- 2. Some cropping systems will have problems over long periods of time that are exhibited in terms of increases in variability over the sequence.

The analyses included in the program are designed to allow the user to identify these types of problems. There may be situations where a simple graph of yields




FIGURE 3. "SIMULATED" SEQUENCE OUTPUTS SHOWING INCREASINGLY ERRATIC PLOTS AS REPLICATES FALL BELOW 100 (N = 20, 10 and 5, Respectively).

over time is sufficient to say with certainty, this is not a viable sequence. Other situations may not be so cut and dried.

As noted in the introduction to this document, the sequencing capabilities of the DSSAT v3 crop models have not been extensively tested, and this is another reason for exhibiting caution with regard to the conclusions you draw from any simulated sequence experiment.

# VOLUME 3-3



J.W. Hansen,
N.B. Pickering,
J.W. Jones,
C. Wells,
H. Chan,
D.C. Godwin

University of Florida

Massey University, University of Hawaii
International Fertilizer Development Center
International Benchmark Sites Network for Agrotechnology Transfer

# CHAPTER ONE.

Daily weather data are commonly used as input to mathematical models used in water related projects and agriculture. While the models expect the data to be complete and reliable, raw data from a weather station, or even a reliable secondary supplier of weather data, are often flawed. Common data problems include format errors, missing data, unreasonable values, data recorded in different units than needed, and data in an inconvenient format. Often there are no data available for a specific site, or a particular variable is not in the available weather record.

IBSNAT has focused on the development of crop models and software tools such as the DSSAT to aid research and development in agriculture. Available and reliable weather data are essential for good predictions using these crop models. The IBSNAT project has specified a minimum daily weather data set and format for use with the crop models. In DSSAT v2.1, (IBSNAT 1986), the required daily variables were solar radiation (MJ/ $m^2$ /d), maximum temperature ( $^{O}$ C) minimum temperature ( $^{O}$ C), and rainfall (mm). An extended DSSAT v2.1 data set included photosynthetically active radiation (PAR, mol/ $m^2$ /d). DSSAT v3 uses the same minimum weather data set and allows optional variables, such as PAR, dew point ( $^{O}$ C) and wind speed (m/s). (For a description of DSSAT v3 file formats, see Volume 2-1, Jones et al. 1994, of this book)

#### Program Description

The WeatherMan program is designed to simplify or automate many of the tasks associated with handling, analyzing, and preparing weather data for use with crop models or other simulation software. WeatherMan can be used either as a stand-alone package or called from within the DSSAT v3 Shell (for a description of the Shell, see Volume 1-3, Hunt et al. 1994, of this book). WeatherMan has the ability to translate both the format and units of daily weather data files, check for errors on import, and fill-in missing or suspicious values on export. WeatherMan can also generate complete sets of weather data comprising solar radiation, maximum and minimum temperature, rainfall, and photosynthetically active radiation. Summary statistics can be computed and reported in tables. The summary statistics or daily data can be viewed graphically.

WeatherMan is written in Borland Pascal v.7 (Borland, 1993). The user interface in WeatherMan was developed using the object-oriented Turbo Vision libraries

provided with Borland Pascal and includes standard pull-down menus; dialog boxes with push buttons, input lines, check boxes, radio buttons and scrolling dynamic lists; and context-sensitive, cross-referencing online help. The user interface functions with both keyboard and mouse.

### Overview of Functions

The WeatherMan's main menu items are: FILE, STATION, IMPORT/ EXPORT, GENERATE, ANALYZE, OUTPUT, AND QUIT. The FILE menu accesses a userselectable text editor for data entry and correction, accesses the operating system (DOS), and allows the current weather data directory to be changed. A new weather station is selected from the STATION menu. The IMPORT/EXPORT menu handles the conversion of file formats and units when importing and exporting weather into or from an archive data file. Importing data refers to reading a new weather data file and storing the data in an internal, archive data file. Exporting data refers to creating a new weather data file and writing data from the archive weather data file to a new data file in a prescribed format. WeatherMan checks for and flags format or range errors on import. On export, data flagged as missing or suspect can be replaced with estimates using several methods. The GENERATE menu permits generation of synthetic sequences of solar radiation, maximum and minimum temperature, rainfall, and photosynthetically active radiation for any duration. The ANALYZE menu includes the computation of summary statistics and the ability to display the results using tables or graphs. The OPTIONS menu allows the user to customize and save the current configuration. The user can terminate a WeatherMan session using QUIT from the main menu or selecting the option, "Exit," under the FILE menu.

#### System Requirements

WeatherMan is designed to run on an IBM compatible PC with DOS v3.1 or later and with at least 280 kB of available conventional RAM to work with 5 weather variables. Each additional variable requires about 12 kB of additional RAM. WeatherMan will store its overlay in expanded memory if it is available. It will be slower without expanded memory and require more conventional memory. We recommend at least 300 kB of available expanded memory when running WeatherMan. While a math co-processor is not required, it is recommended. A hard disk is recommended. Archive weather data occupies about 14 kB of disk space per year for five variables. Standard video drivers are detected automatically. Graphs can be output to several printers, plotters, and file formats.

# CHAPTER TWO. GETTING STARTED


## STARTING WEATHERMAN

WeatherMan can be run either from the DSSAT v3 Shell or as a stand-alone program. From the DSSAT v3 Shell, call the WeatherMan by using the cursor keys to select the DATA main menu item and then the submenu items, "Weather" and then "Utilities." Alternatively, WeatherMan can be called by typing WM from the DSSAT3 directory, or from any directory if \DSSAT3 is identified in the DOS PATH variable.

The opening screen of the WeatherMan has a main menu on the top line, a blank desktop in the center, and a status line on the bottom. An example of the startup screen appearance is given in Screen 1 (below).

## WEATHERMAN USER INTERFACE

The WeatherMan interface is written in Borland Pascal's Turbo Vision and generally follows the Microsoft Windows protocols. A mouse or a few standard keystrokes are used to access WeatherMan's features (Table 1).



#### SCREEN 1.

TABLE 1. USER INTERFACE ITEMS AND THEIR FUNCTIONS IN WEATHERMAN.

Item	Function
Main menu	Accessed with the <alt>-hotkey sequence, e.g., <alt>-<f>, accesses the FILE main menu item. Or press the <f10> key to select the menu and use the cursor keys.</f10></f></alt></alt>
Menu item	Press the hotkey letter or highlight the item using cursor keys, and use the <enter> key or left mouse button. Menu items (or sub-menus) do not require the <alt> sequence.</alt></enter>
Dialog box	A window that prompts for some user response. A dialog box may contain push buttons, input lines, input lists, radio buttons, or check boxes. In general, these items may be selected with a mouse, <tab>, <shift>-<tab), <alt="" an="" or="">-hotkey combination.</tab),></shift></tab>
Push button	A rectangular button that is activated by a mouse double- click or pressing the <enter> key. Most dialog boxes con- tain at-least OK and CANCEL buttons.</enter>
Input line	A highlighted bar that accepts string or numeric data. The cursor, <insert>, and <delete> keys are active in an input line.</delete></insert>
Input list	An input line followed by a down arrow icon opens a dialog box with a list of permissible entries. Activate by selecting the icon with a mouse or selecting the input line, and pressing the down cursor key.
Radio button	Radio buttons, $(ullet)$ , allow you to select one item from a set of options. Select with a mouse, up and down cursor keys and the <space> bar, or an <alt>-hotkey combination.</alt></space>
Check box	Check boxes, i.e., [X], allow you to select any combination from a set of options. Select the same way as radio buttons.
<f1></f1>	Context sensitive help.
CANCEL button	Ignores choice and returns to previous menu.
OK button	Accepts choice and exits the current dialog box or continues the process.
<esc></esc>	Equivalent to CANCEL.

Accepts highlighted choice and performs function. For most <ENTER> dialog boxes the default option is OK. For data entry dialog boxes, pressing the <ENTER> key is equivalent to pressing the <TAB> key. L mouse button Left button on the computer mouse. A single click highlights an item. Double click is equivalent to pressing the <ENTER> key. R mouse button Right button on the computer mouse. Equivalent to CANCEL. <TAB> Move to the next data entry cell. <SHIFT>-<TAB> Move to the previous data entry cell. <HOME> Move to first data entry cell. <END> Move to the last data entry cell. Down arrow Same as using <TAB> key in data entry dialog boxes. When an input line shows a down arrow icon, activates history or list dialog box with choices listed for selection. The history dialog box displays previous selections. Up arrow Same as using the <SHIFT>-<TAB> keys in data entry dialog boxes. <CTRL>-right arrow Move to next data column. <CTRL>-left arrow Move to previous data column.  $[ \blacksquare ]$ Click on [■] icon to close dialog box or window. An alternative to using the <ESC> key or CANCEL button. <ALT>-<X> Exit /Quit. <ALT>-<O> Exit /Quit.


<sup>•</sup> DSSAT v3, Volume 3 • DSSAT v3, Volume 3

Where the dialog box displays a Down Arrow (Ø) symbol, it is important to distinguish between the <TAB> and Down Arrow keys. The <TAB> and <SHIFT>-<TAB> keys are used for moving around the dialog box without the mouse, while the Down Arrow key activates a history list of previous choices or a list of available choices. An example of a history list is given in Screen 2 (below) for the choice of a weather input file name.

The previously selected file names are shown in the history list as UFGA7601.WTH, UFGA7801.WTH and UFGA7901.WTH. A file is selected by pressing the <ENTER> key with the name highlighted. Use of history lists helps speed up the selection process and avoid typing errors.

# COMMON DIALOG BOXES

A list dialog box is presented when you wish to select a weather station, select a file for import or export, select a file format, or select a file to edit or invert. An example of this type of dialog box, for selecting a weather station, is given in Screen 3 (on following page). The file mask on the first line may be restricted for particular operations. In selecting a weather station, a 4-letter name is expected and a .CLI extension is automatically appended. Selecting a file for import or export allows any legal DOS file name and extension. For a format file, any legal




Screen 2.

DOS name is accepted and the default extension of .FMT is appended. The "Format Name" dialog box has an additional Edit button that is explained in that section in Chapter 4. Files from other directories can also be listed by selecting a directory. An example of the "Weather Station" dialog box is given in Screen 3 (below).

Three kinds of archive files for a single station can exist: Raw (or observed), Filled, and Generated. The raw archive file is generally retained, while filled and generated archive files may be automatically deleted upon exiting the WeatherMan, depending on the options selected under the OPTIONS main menu item for "Temporary files" (see also the section entitled "Generate Menu" in Chapter 4). The archive file(s) are stored in the climate directory specified in DSSATPRO.FLE or in OPTION\"Directories" (see Chapter 4).

When an operation (e.g., "Export," "Statistics") can be performed on more than one type of data, an additional dialog box is used to clarify which archive file to use. An example of the "Archive File Type" dialog box is given in Screen 4 (on following page).

For several operations, a time period can be selected. The general form of the "Time Period" dialog box (see Screen 5, on following page) has both starting and ending



SCREEN 3.

Archive File Type —	
Archive types found:  (•) Observed data  ( ) Generated data  ( ) Filled data  OK	

SCREEN 4.

dates where the dates are in year and day-of-year format. In some cases the date may be year and month (see the "Graphics Menu" section in Chapter 4) or just the year (see the "Generate Menu" section in Chapter 4). The time period section may also be part of another larger dialog box. An example of the "Time Period" dialog box with year and day-of-year format is given in Screen 5 (below).

Time Pe		Day of
Starting date:	Year 1980	year 1
Inding date:	1987	365
OK		

SCREEN 5.

# Steps for Cleaning and Converting Weather Data

One of the main uses of WeatherMan is to develop complete daily weather data sets from raw data with missing data and incorrect values. Several steps are required to complete this process and obtain weather data files that are complete and in the desired format. The minimum requirements for cleaning and reformatting data are given in Table 2.

# Table 2. List of Essential Steps for Creating a Complete Daily Weather Data File with the Correct Format and Units from Raw Data in WeatherMan.

- 1. Define weather station name and enter site characteristics.
  - a. Select the menu item Station|Select Station and enter a 4-character code for the new station.
  - b. Enter the requested descriptive information for the new station in the form presented on the screen.
- 2. Import one or more raw data files.
  - a. Select the menu item Import/Export and Import Single File items.
  - b. Create a format definition for the data file that is being imported when prompted for selecting a file format. Select NEW format and EDIT buttons to create the format. Enter the requested information about the format (number of header lines, dates, variable and units and columns for variables). Then select the SAVE button and give the defined format a new 4-character name. Usually one would name the format so that it describes the source of raw data.
  - c. After saving the format, select OK on the screen and data from the raw data file will be read into an internal file named Station\_GEN.WTD, where Station\_GEN is the name of the weather station.
- 3. Compute weather generator parameters for the site.
  - a. Select Generate button, followed by Calculate Parameters.
  - b. Select the button for Both Sets of Parameters. This will calculate the necessary parameters for the weather generators so that missing data can be filled in the exported data file.
- 4. Export the weather data.
  - a. Select the Import/Export and Export Yearly Files buttons. Select the OBSERVED DATA button.
  - b. When prompted, enter starting and ending dates for the data to be exported.
  - c. For exporting daily weather data to be used in DSSAT v3, select the IBSNAT3 format file. Exported files will normally be located in the directory C:\DSSAT3\WEATHER and will be named according to the file naming conventions of DSSAT v3 (e.g., ????yy01.WTH, where ???? is the weather station code and yy is the year).

# CHAPTER THREE. INTRODUCTORY TUTORIAL

In this introductory tutorial, you are going to define a new weather station, import weather data and export data to a file of different format. You are also going to generate data, analyze both data sets and compare them using both tables and graphs.

In this tutorial, the nomenclature IMPORT/EXPORT | "Import single file" means go to the IMPORT/EXPORT menu item of the DSSAT v3 Shell, and then select the "Import single file" menu item from this menu. Selection is performed by highlighting the item and pressing the <ENTER> key, or double-clicking on the item with the left mouse button, or using the keyboard shortcut keys (i.e., <ALT>-<I> then <S>). Any of the three methods will work. Additional information is given in the section "WeatherMan User Interface" in Chapter 2.

# Browse the Menu and Online Help

Pressing the <F1> key provides context-sensitive, cross-referenced help. Look there first if questions arise while doing the exercise. Abbreviated help is displayed on the status line at the bottom of the screen. Pressing the <ESC> key or selecting the CANCEL button will allow you to back out of most processes. Go to the FILE main menu item and select "About" (i.e., FILE | "About"). Press the <F1> key to read an introductory screen describing WeatherMan. Highlight "User interface" and double-click or press the <ENTER> key to read about use of the keyboard and mouse. Help for cross-referenced topics can generally be accessed in the same way.

# SELECT A NEW STATION

Go to the STATION main menu item and open "Select station" (i.e., STATION | "Select station"). Enter "CCQU" for the station name. The "CC" is the ID for the institute, CIAT (Centro Internacional de Agricultura Tropical, Cali, Colombia), and the "QU" is the ID for the station location, Quilichao. When you select a new (i.e., nonexistent) station, a dialog box, similar to Screen 6 appears, but with default values in each field. The user should enter the values shown in Screen 6 for this example.

**NOTE:** When the information for a weather station has already been entered, the Screen 6 dialog box would not appear the next time that station is selected. "CCQU" must not be on the distribution disks.

Station Data		
Quilichao, NorthCauca, Co	olombi	a
grees): : ficient A: ficient B: ght (m): e height (m): emperature (°C): mplitude (°C): ing season (day):		3.080 -76.520 990.0 0.25 0.50 2.00 4.00 24.0 0.5 1
	Ca	ancel
		Quilichao, NorthCauca, Colombi  rees): grees): : ficient A: ficient B: ght (m): e height (m): emperature (°C): mplitude (°C): ing season (day): rowing season (days):


SCREEN 6.

# IMPORT DAILY WEATHER FILES

Select STATION | "Edit monthly means." The "-99" indicates a missing value. Select the CANCEL button or press the <ESC> key to return to the main menu.

Go to IMPORT/EXPORT | "Import single file." Import the file, CCQU1980.DAT by selecting it from the list. Since the format of CCQU1980.DAT does not match any of the format files distributed with WeatherMan, you will need to create a new format definition file. You will be asked for a format. Type or highlight NEW and select the EDIT button. Screen 7 (on following page), the "Edit File Format" dialog box, will be presented. Select the VIEW FILE button in Screen 7 to view the imported file. The "File Viewer" dialog box will be presented with the file CCQU1980.DAT in the viewer. Note the number of header lines in the file presented, and the starting position and width (in characters) of the data field for each variable. You can select variable names and units from lists by selecting the down arrow icon or by highlighting an input line and pressing the down cursor key. When you have entered the format information in the Viewer, the "Edit File Format" dialog box should look like Screen 7.

Select the SAVE FORMAT button and save the format as "CCQU." Then proceed with importing by selecting the OK button. If you have enabled the "Preview




SCREEN 7.

Formats" option under "Import Options," you will be presented with a "Format Preview" dialog box, similar to the one shown in Screen 20.

Now import the rest of the files as a group using the CCQU format that you just created.

Go to IMPORT/EXPORT | "Import multiple files" to import the rest of the files as a group, using the "CCQU" format that you just created. To do this, select "Add Group" in the dialog box presented. Enter the file mask, CCQU\*.DAT. You will then be asked to select a format for the group of files being imported. After selecting the format from the list presented when the SELECT FORMAT button is pressed, a listing of files, as shown in Screen 8 (on following page), which match the CCQU\*.DAT mask, will appear in Screen 8.

Select the OK button to import all of the files in the list. You will then be asked if you want to calculate monthly means. Select "No" since you will do that in the next step.



SCREEN 8.

## CALCULATE WEATHER GENERATOR PARAMETERS

Go to GENERATE | "Calculate parameters," to calculate parameters for both the WGEN and SIMMETEO weather generators. Use the <F1> key to see the differences between WGEN and SIMMETEO. For a more complete description of these two generators, see the section "Generate Menu" in this Chapter .

Go to STATION | "Edit monthly means" to view the monthly means which are used as parameters for SIMMETEO. The WGEN parameters cannot be viewed or edited directly from WeatherMan. They are, however, saved in a file (CCQU.CLI in the climate directory) and can be edited from the DSSAT v3 Shell (see Volume 1-3, Hunt et al. 1994, of this book for a description of the Shell).

### GENERATE WEATHER DATA

Go to GENERATE | "Generate data." Select SIMMETEO and simulate data for the same period of time as the data that you imported. This period of time becomes the defaults in the "Generate Weather Data" dialog box (Screen 30).

# CALCULATE STATISTICS


Go to ANALYZE | "Statistics." Select all statistics types and time groupings by checking all of the boxes, using a mouse or cursor keys and press the <SPACE> bar. Then, select the OK button to calculate statistics. Go to ANALYZE | "Report" to view the statistics files. Print only the monthly summary moments file. Highlight the appropriate items in the "Summary Statistics" or "View/Print Statistics" dialog box (see Screen 32 or Screen 33, respectively, in Chapter 4) and use the <F1> key if you need help understanding a statistic type or time grouping.

### CALCULATE STATISTICS FOR THE GENERATED DATA

Go again to ANALYZE | "Statistics." Select "Only moments" under Type of Statistic, and "Only Monthly Summary" under Grouping. When you are asked for the type of archive file, select "Generated data." View and print the results for the generated data. (NOTE: Check the file header to make sure it is statistics for generated, not observed data.)

## GRAPH OBSERVED DAILY TEMPERATURE

Go to ANALYZE | "Graph." Screen 9 (below) is presented. The initial default plots are always daily time series for observed data. Select the plot ranges with minimum and maximum temperature (TMIN and TMAX) by checking the check boxes at the left, using the <TAB> key and <SPACE> bar. Disable all other plot ranges in Screen 9.




SCREEN 9.

To view the graph, select the GRAPH button. If the graph is cluttered, you can plot a specified range of dates by selecting the RANGE button. Print the graph by pressing the <P> key while the graph is displayed. (Printing will take several minutes.) Pressing the <G> key toggles the grid lines on or off. Press any other key to return to Screen 9.


# Graph Statistics for Observed and Generated Data

As an example graph, we will compare monthly means for maximum daily temperature for observed and generated data, and for wet days and dry days. In the screen presented (Screen 9) when ANALYZE | "Graph" is selected, press the GROUPING button and then the "Monthly summary" time grouping. Highlight the station for the first plot range and use the down arrow icon to select statistics for generated data (CCQU GEN) from the list as shown in Screen 10 (below).

When Screen 11 (on following page) is presented, move to the field under "Variable" in Plot Num. 1 and select mean maximum temperature (TMAX Mean) from the list of available variables in the same way that you selected the station. Finally, move to the field under "Wet State" and select DRY. Repeat the process for the next 3 plot ranges. For Plot Num. 2, specify TMAX Mean on WET days



SCREEN 10.



SCREEN 11.

for generated data. For Plot Num. 3 and 4, specify TMAX Mean on DRY days and WET days for raw data. After you have specified the four plot ranges, the dialog box will look like Screen 11 (above).

Graph and print the results. Note the similarity between observed and generated maximum temperatures and the effect that rain (i.e. WET vs. DRY state) has on maximum temperature.

### EXPORT DAILY WEATHER FILES

Go to IMPORT/EXPORT | "Export yearly files." Select the predefined DSSAT v3 format file. Single-year files will be named automatically using a default naming convention. For this example, the first file exported will be called CCQU8001.WTH, containing data for 1980. Use FILE | "Edit" to access an external editor to view the newly created CCQU8001.WTH. Also view the original file that you imported (CCQU1980.DAT) and note the changes in format and units.

You are now familiar with the basic features of WeatherMan. Additional details on each menu in the WeatherMan main menu screen are described in Chapter 4.

# CHAPTER FOUR. WEATHERMAN REFERENCE GUIDE

# VARIABLES

WeatherMan works with a specific set of daily weather variables (Table 3). The set of variables, default range check values (minimum, maximum and maximum daily change), associated units, and unit conversion factors (multiplier and offset) are specified in a file, called WM.VAR. Variables are stored in their default units in the archive files. If you wish to add or change variables or units, please contact the authors for assistance.

### FILE MENU

The FILE menu item found on the WeatherMan main menu gives access to an editor, DOS functions, and additional help. The FILE pull-down menu is shown in Screen 12 (below) and its options are described as follows.

#### **E**DIT

The "Edit" option accesses a text editor so that data files can be viewed and edited. The user can use his/her own editor by changing the default under the OPTIONS | "Directories" menus.

<b>F</b> ile	<b>S</b> tation	Import/Export	<b>G</b> enerate	<b>A</b> nalyze	<b>O</b> ptions	Quit	14:55:44
<b>E</b> dit <b>I</b> nve							
	ge dir. <b>s</b> hell						
<b>A</b> bou	t						
Exit	Alt-X						

SCREEN 12.

TABLE 3. WEATHERMAN VARIABLES AND ASSOCIATED UNITS.


Variable	Description	Default unit	Other units
SRAD	Total daily solar radiation	$\mathrm{MJ/m}^2$	${\rm cal/cm^2}, W-{\rm h/m^2}$
TMAX	Maximum daily air temperature	°C	°F, °K
TMIN	Minimum daily air temperature	°C	°F, °K
RAIN	Total daily precipitation	mm	cm, inch
DEWP	Dew point temperature or vapor pressure	°C	°F, °K, Pa, kPa, MPa, mbar, bar
WIND	Total daily wind run	km	Miles, m/s, Knots
SUNH	Total daily sunshine hours	%Hrs	n/N, Hrs
PAR	Total daily photosynthetic radiation	$Mol/m^2$	
TDRY	Dry bulb air temperature at 9 am	°C	°F, °K
TWET	Wet bulb air temperature at 9 am	°C	°F, °K
EVAP	Total daily pan evaporation	mm	cm, inch

#### INVERT

The "Invert" option is a utility that reverses the order of lines in a text file (required for the output of some dataloggers which record in reverse chronological order).

#### CHANGE DIR.

The "Change dir." menu option will change the current directory to another weather data directory. The "Change Directory" dialog box is given in Screen 13 (below).



SCREEN 13.

The dialog box shown in Screen 13 applies to the data directory, where the daily weather data files are kept. The CHDIR button will change the directory tree to display the directories below the one that is highlighted. The REVERT button restores the tree to the one presented on entry into the dialog box. The OK button accepts the highlighted directory as the new data directory. The down arrow on the first line activates the history list of previously chosen data directories. The "Change dir." menu option is equivalent to changing the weather data directory under the OPTIONS | "Directories" menus.

#### DOS SHELL

Selecting the "Dos shell" menu option allows you to leave the WeatherMan program temporarily, without removing the program from the computer's RAM.

This function is useful for performing DOS functions like RENAME, DELETE or COPY files. When you have finished any of these functions and wish to return to the WeatherMan program, type EXIT at the DOS prompt.

#### Авоит

The "About" option displays additional information about the WeatherMan program. The opening screen gives the credits. Introductory information about the program can be accessed by pressing the <F1> key from the "About" dialog box presented when "About" is selected.

#### EXIT

The "Exit" option allows you to exit the Weatherman program. You may also exit by pressing the <ALT>-< X> keys.


#### STATION MENU

The STATION menu allows you to select a weather station and get general and climate information for the station. Most operations in WeatherMan require the selection of a weather station name. Two permanent files, located in the climate directory, are identified by the station name. A climate file (.CLI) contains descriptive information about the site, monthly weather generator coefficients, range check values and counts of valid and flagged data. The format of the climate files is given in Appendix B. The station name also identifies an archive file (.WTD) that has a standard format and set of units; this is required by most of the functions in WeatherMan (e.g., data checking, data-fill, weather generators, statistics, graphics). The archive file is also used for storage of imported data. If the user only wants to convert data file formats or change units of the variables using the "Convert" option under the IMPORT/EXPORT main menu item, then a permanent archive file is not retained. The STATION pull-down menu window is displayed in Screen 14 (on following page).

In Screen 14, after a weather station has been selected, the 4-letter station ID code is displayed on the first line of the menu window and also on the status line at the bottom of the screen. The example station ID code is "UFGA" in Screen 14. The menu options in the STATION menu are described as follows.

#### **SELECT STATION:**

The "Select station:" option shown in Screen 14 displays a list of all climate (CLI) files in the climate directory. This dialog box uses the "File List" dialog box but



SCREEN 14.

only allows a 4-letter station name. Selecting the OPTIONS main menu item and then the "Update" option after selecting the station from this menu, places the selected station name in the program's configuration file and automatically loads it the next time WeatherMan is started.

Whenever a new weather station is selected, the user is requested to input general information regarding the new station. These data items are listed in Table 4 along with an explanation of each item. Please note that the station's latitude is absolutely essential.

#### **EDIT STATION INFORMATION**

When the "Edit station information" option is selected in Screen 14, the "Station Data" dialog box (see Screen 15, on second following page) for entering additional data or editing existing data is presented.

#### **EDIT MONTHLY MEANS**

When a new station is selected, a user may select the "Edit monthly means" option in order to enter the monthly means of the weather variables for this station. An example of a "Monthly Means and Rainfall" data entry dialog box is given in Screen 16 (on second following page)

Although you do not need to enter the monthly means of the variables listed in Screen 16, many of the options for generating data filling in missing data during

TABLE 4. WEATHER STATION INFORMATION REQUIRED FOR A NEW STATION.

Latitude (degrees) Station latitude (+=N, -=S). Longitude (degrees) Station longitude (+=E, -=W). Elevation (m) Station elevation above mean sea level. Angstrom coefficient A Coefficient A in equation: SRAD = (A + B \* n/N) \*  $R_E$ , where  $R_E$  is extraterrestrial radiation and n is duration of bright sunshine, and N is daylength. Angstrom coefficient B Coefficient B in equation: SRAD = (A + B \* n/N) \*  $R_{\rm E}$ . Height of meteorological sensors above ground. Reference height (m) Wind reference height (m) Height of anemometer above ground. Mean annual average daily temperature. Mean annual temperature (°C) Temperature amplitude (°C) Half the range of monthly means for average daily temperature. Start of growing season (d) Mean day-of-year for last frost. Mean time from last frost to first frost. Duration growing season (d)

Export will be dis-abled until it has been completed. An alternative to manual data entry is to calculate the means from the daily data in the raw archive file. Monthly climate statistics are available from several secondary data sources (eg. Conway, et al., 1963; NOAA, 1974; Rudloff, 1981). The last two items in the dialog box shown in Screen 16 allow you to document the data source and the data collection period.

#### **CALCULATE MONTHLY MEANS**

The "Calculate monthly means" option in Screen 14 allows you to compute means from the data in the raw archive file. This is a reasonable option if there are sufficient reliable data in the archive file or if there are no available climate data. The user is given a warning message if there are less than five years of reliable data in the archive file. Calculating monthly means is equivalent to estimating the SIMMETEO parameters from the Generate menu (see the "Generate Menu" section in this Chapter). The "Calculate monthly means" option will overwrite manually-entered data.

Location: Gainesville, Florida	
Latitude (degrees): Longitute (degrees): Elevation (m): Angstrom coefficient A: Angstrom coefficient B: Reference height (m): Wind reference height (m): Mean annual temperature (°C): Temperature amplitude (°C): Start of growing season (day): Duration of growing season (days):	29.630 -82.370 10.0 0.25 0.50 1.00 3.00 20.9 7.5 1
OK	<b>C</b> ancel

SCREEN 15.

Monthly mean hours of bright sunshine and Angstrom coefficients (Prescott, 1940) are included to aid in the estimation of missing daily solar radiation data

	mean mon	thly va	lues	Total	Number	Mean	Angstro	m coef.
	SPRAD	TMAX			of wet			В
	(MJ/m2)	(°C)	(°C)	( mm )	days	(8)		
1					8.7		0.250	
2	13.4				8.3		0.250	
3	17.2				8.3		0.250	0.500
4					5.8		0.250	
5					7.9	-99.0		0.500
6	20.8				12.4		0.250	0.500
7	20.3	33.1	21.9	175.1	16.5	-99.0	0.250	0.500
8					16.2		0.250	0.500
9					11.3		0.250	0.500
10					6.5		0.250	0.500
11	12.0	24.5	11.5	59.3	6.0	-99.0	0.250	0.500
12	9.9	21.5	7.9	69.3	6.8	-99.0	0.250	0.500
<b>S</b> our	rce: Calcul	lated_fr	om_daily	y_data	1st year	: 1980	No. year	rs: <b>25</b>
		C	K			<b>C</b> ancel		
		7			7	1		

SCREEN 16.


where daily hours of bright sunshine (SUNH) are available. If SUNH data are not available in the archive file, "Calculate monthly means" will use the Angstrom coefficients entered in the "Station Data" dialog box as defaults (see Screen 15). If SUNH is available but daily radiation (SRAD) is not, then monthly Angstrom coefficients will be estimated by the relationship proposed by Rietveld (1978). If sufficient (>5yr) records with both SRAD and SUNH are found for a month, then Angstrom coefficients will be calculated for that month directly by linear regression.

#### IMPORT/EXPORT MENU

The IMPORT/EXPORT menu item found on the WeatherMan main menu allows you to perform all the necessary data manipulation for inserting data into an archive file and extracting it into other files. The IMPORT/EXPORT pull-down menu is shown in Screen 17 (below) and its options are described as follows.

#### FILE FORMATS

The "File format" option allows you to define the format of the target weather data file to be imported or the destination file to be exported. These formats are saved in files with .FMT extensions. For example, format definition files for DSSAT v2.1 (IBSNAT2.FMT) and DSSAT v3 (IBSNAT3.FMT) are distributed with the WeatherMan. A blank format, NEW.FMT, is provided as a template for constructing new format definition files. Format files specify columns of data, units




SCREEN 17.

for each data column, date formats (i.e., year/month/day or year/day of year), and file header options. Users can edit these formats and save the changes under new or existing names.

The "Format Name" dialog box that appears during Import, Export, and Convert operations is a variation of the "File List" dialog box (see Screen 10) with an additional EDIT button. The EDIT button allows the user to view, edit, and save format files. If a name is entered that doesn't match an existing format, the user will be prompted to edit a blank template format, NEW, and save it under the desired name. The "Edit File Format" dialog box presented when the EDIT button is pressed is shown in Screen 18 (below).

In Screen 18, the format name is displayed in the top right corner window. The "Header output option" in the top left region of the screen controls what header lines are added to a file during an Export operation. The header can match DSSAT v3 or v2.1 standards, consist of variable names right-justified in the columns in which the variables will be written, or can be read from a text file. Just below the "Header output option" is the "No. header lines:" which is the number of non-blank header lines to be skipped during Import.

The format for the date is entered in the upper right hand corner in Screen 18. For Import, the date of the first data point should be entered only if dates are not




SCREEN 18.

explicitly given in the import file. The date format can be year, month and day-of-month or year and day-of-year. The day-of-year format is inferred from a length of 0 for month and a length  $\geq$ 3 for the day.

Up to 12 variables can be imported in any order and with any units. The variables and their units are entered in the lower left-hand windows in Screen 18. The choice of variables and their units is made with lists that are activated by the down arrow or double clicking with the left mouse button on the appropriate cell in these windows. Moving from cell-to-cell is achieved with the <TAB> and <SHIFT>-<TAB> keys or single-clicking with the left mouse button. Based on the chosen variable, the list will reflect valid units. For example, for temperature variables only temperature units are listed (°C, °F, °K). The variables in the list and their associated units and conversion factors are contained in an external file (WM.VAR). Please contact the authors if you want to modify the list of variables.

The VIEW FILE button provides a file viewer to facilitate the choice of the position and length of the variables in the data file (see Screen 19, below).

The SAVE FORMAT button provides access to a "File List" dialog box so that a new or modified format can be saved to a file for subsequent use. The OK button will accept any format changes for the current IMPORT/EXPORT session but will not save them to a file, so when you quit the operation, any changes you have made to the format will be lost.




SCREEN 19.

The VIEW FILE button displays the file in conjunction with a ruler as shown in Screen 19.


If a format is being edited during an Import operation and the "Preview formats" option is enabled (with a tick mark) in the "Import Options" dialog box (see Screen 24), then a "Preview Format" dialog box (Screen 20, below) will be presented when either the OK or the SAVE button is pressed. The "Preview Format" dialog box displays a file viewer which shows the first 50 records of the weather file. The columns where the program, using the current format, will look for variables are labeled and highlighted.

#### **CONVERT FORMAT**

The "Convert format" option found in the IMPORT/EXPORT pull-down menu (see Screen 17) allows you to convert a weather data file from one format and set of units to another without defining a weather station. A permanent archive file for the raw data is not retained, and range checking and data fill are not performed. When converting a weather file format, the user will be prompted to: (1) select the target file to convert from, (2) select a format name for the target file, (3) select the destination file name to convert to, and (4) select a format for the destination file. The file names and format names are selected using the "File List" dialog box (see Screen 10 or Screen 21, on following page).



SCREEN 20.




SCREEN 21.

#### IMPORT...

The "Import..." option can be used to import a single file or a set of files into an archive file. The "Import single file" option uses the standard "File List" dialog box to select a import file name and format. These steps are identical to the first two steps discussed in the above "Convert format" section. The "Import multiple files" option builds a list of files and their corresponding formats. This feature is useful where the weather variables are stored in different files with different formats, or for a group of files with the same format. The "Files To Import" dialog box presented when this option is selected is shown in Screen 21.

In Screen 21, the ADD FILE button activates the IMPORT/EXPORT "File Name" dialog box and adds a file to the list displayed in the left-hand window of this screen. The REMOVE FILE button can be used to delete a highlighted file from the list. The first file chosen is inserted into the list with a format of "none." The SELECT FORMAT button activates the "Format Name" dialog box and the user can access the "Edit File Format" dialog box using the EDIT button in that dialog box. Adding subsequent files automatically assigns them the format name of the highlighted line. This feature facilitates adding several files with the same format to the list. The format of a highlighted file may also be modified from the SELECT FORMAT button. Files in the list are imported sequentially when the OK button is selected.



SCREEN 22.

A group of files with similar names can also be added using the ADD GROUP button in Screen 21. This feature is especially useful for importing many one-year file of the same format. Since a file mask is used to define the group, unwanted file names are occasionally inserted in the list, but these are easily removed by use of the REMOVE FILE button. The "Import Group File Mask" dialog box used to define the group is shown in Screen 22 (above).

If the "Preview formats option" is enabled under the "Import Options" dialog box (Screen 24), a "Preview Format" dialog box (Screen 20) will be presented before each file is imported.

On"Import," variables that have errors or are suspect are automatically flagged (see the section "Import Options" in this Chapter and Screen 23 to change this setting). The flags used are lower case letters. When an original value is filled-in, its flag is converted to upper case. The flags and their meaning are listed in Table 5.

At the end of the "Import" process, a summary report is given indicating the quantity and quality of data in the raw archive file. An example of this report is displayed in the "Import Statistics" dialog box as shown in Screen 23 (on following page).


## **IMPORT OPTIONS**

The options for import can be changed using the "Import options" menu item from Screen 17 which accesses the "Import Options" dialog box presented in Screen 24 and explained in Table 6.

TABLE 5. EXPLANATION OF ERROR CODES USED TO FLAG SUSPECT OR ERRONEOUS DATA.

Class	Description	Import code	Filled code
Range check	Above maximum	a	A
Range check	Below minimum	b	В
Range check	Greater than maximum		
	daily change	r	R
Conversion	Missing value	n	N
Conversion	Format error	е	E

When range checking is turned on, the variables are checked against a maximum value, a minimum value, and a maximum rate of change from one day to the next. The values inserted in the raw archive file are not changed but marked with an appropriate range check flag (see the "Import" section above). Default range values are provided for a new weather station and these can be edited using the "Edit range checks" option found in Screen 17 to access the "Edit Check Ranges" dialog box. An example of the "Edit Check Ranges" dialog box is shown in Screen 25 (on second following page).



SCREEN 23.


## TABLE 6. EXPLANATION OF IMPORT OPTIONS.

Option	Explanation
Format name:	The default action is to prompt for a format name. If the only file formats used are the DSSAT v2.1 or DSSAT v3 formats, the format name can be fixed as IBSNAT v2 or IBSNAT v3, respectively.
Check ranges:	The default is to perform range checking. The variables are checked for extreme values and the unaltered values are inserted in the raw data archive file and marked with a flag (see Edit Range Checks below). Import operations can speeded up without range checking and it can be performed later on the whole archive file using an option in the Analyze menu.
Overwrite existing data:	If this option is enabled, when the existing and new data both have valid values for the same dates, the new values will replace the existing values. Turning off this option causes the existing value to be retained under the same circumstances.
Prompt for non-numerics:	The default action is to prompt the user to give a numeric value to replace each new non-numeric string encountered (e.g., "TRACE" can be replaced with '0.0' for rainfall.) Turning off this option causes blanks to be treated as missing values and non-numeric characters to be treated as format errors.
Preview formats:	The default action is to present a "Preview Format" dialog box (Screen 20) every time a file is imported or a format is edited during Import. Turning-off this option prevents the "Preview Format" dialog box from being displayed.

[•] Import Options	
Format name: (•) Prompt for name. ( ) IBSNAT3 ( ) IBSNAT2	
Other options:  [X] Check ranges.  [X] Overwrite existing data.  [X] Prompt for non-numerics.  [X] Preview formats	
OK Cancel	

SCREEN 24.

All variables in Screen 25 are in the archive file units except for solar radiation (SRAD) and photosynthetically active radiation (PAR) which are in percent of extraterrestrial radiation. Updated ranges are saved to the weather station climate file. The DEFAULTS button restores the default values.



SCREEN 25.

#### EXPORT...

The "Export..." option in Screen 17 can be used to export a single file or a set of yearly files. The "Export single file" option uses the "Archive Type" dialog box (Screen 4) (if the raw archive file is not the only type), "Time Period" dialog box (Screen 5), and the "File List" dialog box (Screen 2) to select an export file name and format. The "Export yearly file" option uses the same dialog boxes, but the file export names are built automatically based on the DSSAT v2.1 or DSSAT v3 file naming conventions. The files can easily be renamed using the DOS RENAME command. Access to the "Edit Format" dialog box is from the "Format File" dialog box.

During "Import," errors or suspect values in the raw archive file are marked with a flag indicating the source of the error. On "Export," if a data item is filled in, the value's error flag is converted to an upper case letter. This reminds the user that the value was filled-in and the cause of the error. Error flag definitions are listed in Table 5.

#### **EXPORT OPTIONS**

The options for export can be changed using the "Export options" menu item which accesses the "Export Options" dialog box presented in Screen 26 (on following page) and discussed in Table 7.

When any of the data fill options are turned on in Screen 26 by placing an 'x' in the left-hand box in the "Other options:" menu list, there are a number of ways in which the data fill can be implemented. These options are accessed from the "Data fill" options menu item that invokes the" Data Fill Options" dialog box given in Screen 27 (on following page) and discussed in Table 8.

## GENERATE MENU

The GENERATE menu item found on the WeatherMan main menu allows estimation of the weather generator parameters and subsequent generation of daily weather data. The weather generators used are adaptations of WGEN (Richardson and Wright, 1984) and SIMMETEO (Geng et al. 1986; Geng and Auburn, 1988). The SIMMETEO generator is embodied in the WGEN generator but uses a different input section. The resulting WGEN/SIMMETEO is a translation of the FORTRAN version used internally in the DSSAT v3 crop models. In this version of WeatherMan, both generators are restricted to generating the DSSAT v2.1 extended weather data set of solar radiation, maximum temperature, minimum temperature, rainfall, and PAR.

Format name:  (*) Prompt for name.  ( ) IBSNAT3  ( ) IBSNAT2
Yearly file naming conventions:  (•) IBSNAT v.3  ( ) IBSNAT v.2
Other options:  [X] Fill missing data.  [X] Fill range errors.  [ ] Fill missing dates.  [ ] Export data flags.
OK Cancel
F1 Help Stn: UFGA   Prompt for a format name on export.

SCREEN 26.

File 9	Station Import/Export Generate Analyze Options Quit	14:19:23
	[*] Data Fill Options	
	Data fill method:  (*) Generate missing data with WGEN or SIMMETEO.  ( ) Monthly means and stochastic rainfall generations.	
	Solar radiation (SRAD and PAR): ( ) Use method selected above to estimate radiation. (•) Estimate radiation from sunshine hours.	
	Short (≤ 7 day) data gaps:  ( ) Use method selected above to fill data.  (•) Estimate missing data using 10-day running mean.	
	Model for weather generation: ( ) WGEN (•) SIMMETEO	
	Random seed for generator (1 to 32767): 3823	
	OK Cancel	
F1 Help	Stn: UFGA   Use a stochastic generator to fill missing data	ı.

SCREEN 27.

### TABLE 7. EXPLANATION OF EXPORT OPTIONS.

## Option Explanation Format name: The default action is to prompt for a format name. If the only file formats used are the DSSAT v2.1 or DSSAT v3 formats, the format name can be fixed as IBSNAT v2 or IBSNAT v3, respectively. Yearly file naming convention: The default is to use the DSSAT v3 file naming convention. The other option is to use the DSSAT v2 convention. The file naming conventions are (Station = 4 characters, yr = 2 characters): For DSSAT v2.1, use IBSNAT v2: Station + '0112.W' + yr (raw) Station + 'GEN.W' + yr (generated) For DSSAT v3, use IBSNAT v3: Station + yr + '01.WTH'(raw) Station + yr + '01.WTG' (generated) Fill missing data: The default is to fill missing data. If missing data are not filled, the value is written as -99.0 on output. The default is to replace data that are Fill range errors: flagged for range errors. This option is only in effect if Fill Missing Data is checked. If range errors are not filled, the original value is written on output. Fill missing dates: The default is to fill missing dates with sequential dates and fill variable values. If Fill Missing Dates is disabled, missing dates in the raw archive file will also exist in the output file. Export Data Flags: The default is to export the error flags as lower case if data are not filled and upper case if they were filled. If data are filled and error flags are not exported, there will be no indication that the data have been

#### TABLE 8. EXPLANATION OF DATA FILL OPTIONS.

#### Option

#### Explanation

Data fill method:

There are two generic data fill methods for all data. Solar radiation and short periods of missing data have additional methods. The first method is to generate all missing data with the WGEN or SIMMETEO weather generators (see Generator section). The second method uses monthly means from the climate file for all variables except rainfall; a simple stochastic generator is used for rainfall. Using monthly means for rainfall is not an option since it would cause severe problems with any water balance model if all days had some rainfall. Both methods only fill solar radiation, maximum and minimum temperature, rainfall, and PAR.

Solar radiation:

The default is to use the generic method selected above. An alternative is to estimate solar radiation using the Angstrom coefficients in the climate file. Sunshine hours data must be available in the raw archive file to use this method.

Short (≤ 7 Day) data gaps:

The default is to use the generic data fill method given above. An alternative is to use a 10-day running mean for gaps that are less than 7 days long. This may give a more realistic estimate of the actual average values for that period than using long-term means. For data gaps longer than 7 days, the above data fill methods will still be used.

Model for weather generation:

The default is to use the SIMMETEO model since it requires only the monthly means in the climate file. The WGEN model provides better estimates of variability if it has been parameterized from at least five years of good quality daily data. Model parameters must be in the climate file to use this option (see Generator section).


The DSSAT v3 modifications of WGEN/SIMMETEO use standard deviations rather than coefficients of variation which makes the generators more stable than the original versions. Monthly input parameters are now used for all variables, with linear interpolation computed internally. The modified SIMMETEO model uses monthly climate parameters and regression equations (Geng, et al. 1988; Geng and Auburn, 1986; Pickering et al. 1988) to compute the standard deviations.

The GENERATE menu provides the utilities necessary for estimating the generator parameters and generating daily data. The GENERATE menu is shown in Screen 28 (below) and its options are described as follows.

#### CALCULATE PARAMETERS

When the "Calculate parameters" option shown in Screen 28 is selected, the "Calculate Parameters" dialog box, shown in Screen 29 (on following page), is presented.

From Screen 29, the parameters for WGEN or SIMMETEO can be computed separately or together. A standard "Time Period" dialog box (i.e., "Starting" and "Ending" dates) is included in the dialog box shown in Screen 29, allowing you to choose a particular time period if desired. The default is to use all the data in the archive file, and the dates presented when Screen 29 appears should represent the range of dates available in the archive file. The computed monthly parameters are recorded in the climate file. Estimating the SIMMETEO parameters is equivalent to calculating monthly means from the STATION menu (see Screen 14) — both



SCREEN 28.

[ ] Calculate Parameters Model:
<pre>(•) WGEN generator parameter ( ) SIMMETEO monthly means ( ) Both sets of parameters</pre>
Day of Year year Starting date: 1980 1 Ending date: 1987 365
OK Cancel

SCREEN 29.

calculate the same statistics. If the monthly means in the climate file are from a longer and more reliable record than the daily data, the user should not estimate SIMMETEO's parameters since the monthly means in the climate file will be overwritten. Estimating generator parameters is a reasonable option if there are sufficient reliable data in the raw archive file or if there are no available climate data. The user is warned if there are less than five years of reliable data in the archive file.

## **GENERATE DATA**

The "Generate data" menu item accesses the "Generate Weather Data" dialog box which is shown in Screen 30 (on following page).

Generated data are output to an archive file called Station\_GEN.WTD. This file is usually treated as a temporary file for the duration of the WeatherMan session (see the following section entitled, "Options Menu" and the subsection "Temporary Files" for a description of how to change from a temporary file). Either the WGEN or SIMMETEO generator can be used to generate daily data. The standard "Time Period" dialog box is inserted to choose the years to be generated; only full years can be generated. The default action is to match the time period of the raw archive file, although any time period can be specified. For comparing yearly time series graphically, matching the dates is a good choice. Just because generated and raw data have the same time period does not mean that the generated data predict the raw daily data; only the means are predicted on average. A random number seed is generated and inserted in the dialog box shown in Screen 30. To generate an identical sequence of weather data, the same random number seed should be specified.

Model:  (•) WGEN  ( ) SIMMETEO	er Data —
Starting year: Ending year:	1980
Random seed (1 to 3919	32767):

SCREEN 30.


## Analyze Menu

The ANALYZE menu item found on the WeatherMan main menu allows you to calculate and present summary statistics in both tabular and graphical form. It also repeats the range check and data fill functions that are normally done automatically on IMPORT or EXPORT. Analysis is performed on raw, filled or generated data. The ANALYZE menu is shown in Screen 31 (on following page) and its options described as follows.

#### RANGE CHECK AND DATA FILL

The "Range check" and "Data fill" options listed in Screen 31 offer you another way to perform functions normally done on IMPORT or EXPORT.

Range check. The "Range check" option permits the range checking analysis to be done on the complete raw archive file. After the check is done, the results are given in an "Import Statistics" dialog box similar to the dialog box for IMPORT (see Screen 23). This re-checking process is useful when IMPORT has been done with incorrect range check values or if range checking had been turned off during IMPORT. It is also useful for identifying a reasonable set of range check values for a weather station by iteratively setting the range check values and viewing the results.



#### SCREEN 31.

Data fill. The "Data fill" option creates a filled archive file called Station\_FIL.WTD. This file is usually treated as a temporary file for the duration of the WeatherMan session (see the following section entitled, "Options Menu" and the subsection "Temporary Files" for a description of how to change from a temporary file). The filled archive file can be analyzed and compared with the raw data to check the data fill algorithms.

## **S**TATISTICS

The "Statistics" menu item listed in Screen 31 provides algorithms for summarizing the data in various ways. When this option is selected, the "Archive Type" dialog box is presented (Screen 32, on following page). This dialog box allows you to choose raw, filled, or generated archive files.

Statistics are output to summary files and are usually treated as temporary files for the duration of the WeatherMan session ( see the following section entitled, "Options Menu" and the subsection "Temporary Files" for a description of how to change from a temporary file). The SUM files are also used for the "Report" and "Graph" options under the ANALYZE menu. The "Time Period" dialog box allows the user to choose the time period to be analyzed. The default action is to analyze the whole archive file.

In Screen 32, there are four types of statistics to select from: "Moments," "Percentiles," "Distribution" and "Time structure." The default choice is to calculate moments only. "Moments" includes means, standard deviations, and

Type of Statistic: [X] Momments [] Percentiles [] Distibution [] Time structure		rouping: [X] Monthly summary [] Monthly time series [] Yearly time series
Starting date:	1980	
Ending date:	1987	365 Cancel

SCREEN 32.


skewness coefficient. "Percentiles" are the 0, 25, 50, 75, and 100 percentiles. "Distribution" includes both histograms and cumulative probabilities. "Time structure" includes autocorrelograms for all variables except rainfall, and has conditional probabilities for rainfall. All statistics are automatically computed for wet, dry and for all days, except "Time structure" which uses all days.

Also in Screen 32, three statistics groupings can be selected: "Monthly summary," "Monthly time series" and "Yearly time series." A fourth grouping comprised of all data combined, is automatically performed with the monthly summary. The time series analyses are relatively slow since they require considerable sorting prior to output. The default grouping is monthly summary. Table 9 describes these groupings in more detail.

## **R**EPORT

The "Report" option provides a way to view and print the summary (SUM) files created under "Statistics." When this option is selected, the "View/Print Statistics" dialog box shown in Screen 33 (on following page) is presented.

Screen 33 has the same Type and Grouping choices as the "Summary Statistics" dialog box shown in Screen 32. As a default, the same boxes are checked in Screen 33 as were checked in Screen 32 since those summary files already exist. If all the selected options have been previously analyzed, the files are viewed




SCREEN 33.

sequentially. Up to 12 summary files are possible for each type of archive file. When the OK button is pressed in Screen 33, the "Summary File" dialog box shown in Screen 34 (on following page) is presented.

The user can scroll both vertically and horizontally through the SUM file displayed in Screen 34. If the PRINT button in Screen 34 is pressed, the SUM file displayed in the window is printed to the parallel printer port. The OK button displays the next file while the CANCEL button aborts the viewing process.

TABLE 9. EXPLANATION OF STATISTICS TIME GROUPINGS.

Grouping	Explanation
All data combined	Pools all data together (computed automatically with monthly summary).
Monthly summary	Pools all the data from each month together (eg. all of January's, all of February's etc).
Monthly time series	Each month analyzed separately.
Yearly time series	Each year analyzed separately.




SCREEN 34.

Variable names that appear in summary files are given in Appendix A.

## **G**RAPH

The "Graph" option provides access to a graphics package to plot both the data in the archive files and in the statistics (SUM) files. The following six graph types are available: Time Plot, Box Plot, Histogram, Cumulative Distribution, Autocorrelation, and Rainfall Probability. Within each graph type, up to six plots can be defined (except for the Box Plot and Auto correlation which allow only a single plot), but only the checked plots will actually be plotted. A plot definition dialog box is used to create combinations of weather stations, variables, wet states, and time ranges. A default set of plots is automatically loaded into this dialog box. The down arrow or mouse can be used to access lists for the Station, Variable and Wet state columns. Only valid choices are displayed. For example, if statistics have not been calculated for a particular weather station, the statistics variables for that station will not be displayed. In addition, the Wet state column is not visible for a daily time grouping. The wet state refers to the occurrence of rainfall; choices are Wet, Dry, or All.


An example of a plot definition dialog box is given in Screen 35 (on following page) for a "Time Plot Range" where six plots are defined and two (TMAX and TMIN) are checked for plotting.




SCREEN 35.

The TYPE, GROUPING and RANGE buttons in Screen 35 control the graph choices, while the GRAPH button displays the graph, and the CANCEL button exits the dialog box. The TYPE button provides a choice of six graph types in the "Graph Type" dialog box that overlays the plot definition dialog box as shown in Screen 36 (below).

The GROUPING button accesses a "Select Grouping" dialog box similar to the right hand side of the "Summary Statistics" (Screen 32) or "View/Print Statistics"



SCREEN 36.




SCREEN 37.

(Screen 33) dialog boxes. Choices for Grouping are the same as in Screen 32 and 33, except there is an additional option: "Daily time series." In some of the graph types, the "Daily time series" option is replaced with an "All data" combined option, which pools all the available data together. An example of the "Select Grouping" dialog box is shown in Screen 37 (above) for a "Time plot."

The RANGE button in Screen 37 selects a global time period for the graph using the Time Period described in Chapter 2 in the section on "Common Dialog Boxes In WeatherMan." Extreme limits on the time period are given as defaults in year, day-of-year format (1800/001 to 2099/366) because it is impossible to determine all the possible time periods for combinations of plots. Only feasible ranges will be plotted. The GRAPH button calls the graphics program (WMGRAF.EXE) and plots the data.

An example of a graph generated by WeatherMan is shown in Screen 38 (on following page). Screen 38 shows a daily time series of mean solar radiation in MJ/m²/day on wetdays, SWMN, and on dry days, SDMN, over a 12-month period..

In Screen 38, the lower portion of the graphic screen contains a legend describing the data plotted. The legend contains a representation of the lines and symbols used for each plot, a multiplier for scaling the y-axis, and a brief text description of the variable. In general, the first 4 characters are the variable type. If a "W,"



SCREEN 38.

"D," or "A" appears in parentheses, it represents wet state (i.e., wet, dry, or all). The next four characters following the first comma are the station name, followed by "RAW" (observed data), "GEN" (generated data), or "FIL" (observed data with any missing or suspect data filled-in). The text following the final comma represents the time period (month, year, or "ALL"). Variable names that appear in graphs are defined in Appendix A.

## OPTIONS MENU

The OPTIONS menu item found on the WeatherMan main menu allows you to change and save options and defaults. The OPTIONS menu is shown in Screen 39 (on following page) and its options are described as follows.

**NOTE:** Unless the "Update options" option is selected first, the menu options listed in Screen 38 are only for the WeatherMan session you are currently working in.

m:lo	atation.	Trop cost / Exercise	Comomata	3maluma	<b>O</b> ptions	0	14.50.00
File	Station	Import/Export	Generate	Analyze			14:50:09
					Display Colors	<b>m</b> ode	
					Director Tempora		2
					1 Chipora	I y IIIC	
					Graph c Graph o		
					Graph 0	шерис	
					<b>U</b> pdate	options	

SCREEN 39.


## DISPLAY MODE

When the "Display mode" option is selected, the "Video Mode" dialog box shown in Screen 40 (below) is presented.

The "Video mode" window in Screen 40 is best left on "Autodetect" unless the program has difficulty selecting the correct mode and a manual choice of an alter-

Video mode:  ( • ) Autodetect mode  ( ) Color palette
( ) Color palette
<ul><li>( ) Black &amp; White palette</li><li>( ) Monochrome palette</li><li>( ) Custom palette</li></ul>
OK Cancel

SCREEN 40.



SCREEN 41.

native mode or color palette gives a better screen appearance. The LCD and plasma screens used on some portable computers often look better using a "Black and White palette" than with the automatically detected color mode. In addition, the "Colors" option in Screen 39 allows you to create a custom color palette. You may change the WeatherMan program default colors by doing the following: 1) select the "Colors" option, and choose your custom colors (see Screen 41, above, and the section "Colors" below); 2) select the "Display mode" option (Screen 39) and select "Custom palette" in Screen 40; 3) press the OK button; and 4) select the "Update" menu option from the OPTIONS menu. From that point on, whenever WeatherMan is started, your customized colors will be active.

### **COLORS**

The "Colors" option gives you access to the "Colors" dialog box which permits the default colors for the desktop (background), menus and dialog boxes to be changed. In order for these colors to remain in effect in subsequent WeatherMan sessions, following the description on how to do this in the above section, "Display mode." The "Colors" dialog box is shown in Screen 41 (above).

	Directories ————————————————————————————————————
[X] Obtain dir	ectories from DSSAIPRO.FLE.
Weather data:	C:\DSSAT3\WEATHER\
Climate files:	C:\DSSAT3\WEATHER\CLIMATE\
Graphics program:	C:\DSSAT3\
Graphic output:	C:\DSSAT3\WEATHER\
Editor path & file: Editor command line	C:DOS\EDIT.COM
OK	<b>C</b> ancel

SCREEN 42.

#### **DIRECTORIES**

When the "Directories" option in Screen 39 is selected, the "Directories" dialog box, shown in Screen 42 (above), is presented. This dialog box permits you to change the default directories and editor.


All the information listed in Screen 42 can also be obtained from the DSSAT v3 profile file called DSSATPRO.FLE (see Volume 1-3, Hunt et al. 1994, of this book for a description of this file). When the "Obtain directories from DSSATPRO.FLE" box in Screen 42 is checked, directories that conflict with those in DSSATPRO.FLE are disregarded. This box should generally be checked only when running WeatherMan under DSSAT v3.

The directory, name, and any command line options for the user's favorite editor can replace the default editor.

## TEMPORARY FILES

When the "Temporary files" option is selected, the "Temporary File Options" dialog box, shown in Screen 43 (on following page), is presented. From this dialog box, you can control the status of temporary files.

The files that are temporary are filled and generated archive (WTD) files and sta-



SCREEN 43.

tistics (SUM) files. These files should normally be deleted to avoid wasting disk space, but may be retained if desired. For example, generation and analysis of a very long weather record may justify keeping the generated and statistics files.


## GRAPH COLORS AND GRAPH OPTIONS

Both "Graph colors," and "Graph options" allows you to set graph options.

*Graph colors*. When the "Graph colors" option is selected, a "Graph Colors" dialog box dialog, as shown in Screen 44 (on following page), is presented, which allows you to set the colors of the background and graph (lines).

*Graph output.* When the "Graph output" option is selected, the "Graph Output Options" dialog box, shown in Screen 45 (on following page) is presented. In this dialog box, you can specify the device, port and orientation for hardcopy output.


In Screen 45, you can select an output device type/resolution/paper size combination from the scrolling list. If a "file" is selected as the output port (see the options under the "Port" window), the user is prompted for a file name using a standard "File List" dialog box prior to entering the graphics program from the ANALYZE | "Graph" menu item.



SCREEN 44.

## **UPDATE OPTIONS**

Selecting the "Update options" menu item allows you to save the options you have selected. All WeatherMan options are saved to the configuration file



SCREEN 45.

WM.CFG while Graphics program options are saved to DEVICE.FLE and GCON-FIG.FLE. These options are then used the next time WeatherMan is started.

## QUIT MENU

When the QUIT menu item is selected from the WeatherMan main menu, you can choose to exit the program. You may also use the <ALT>-<Q> key sequence as a shortcut key sequence to quit. The user may also use the shortcut-key options, <ALT>-<X> or <ALT>-<FX>, under the FILE menu to quit the WeatherMan program.

## REFERENCES

- Borland. 1993. Borland Pascal Version 7. Borland International, Scotts Valley, California.
- Conway, H.M. Jr, S.L. May Jr., and E. Armstrong, Jr. 1963. The Weather Handbook. Conway Publications, Atlanta, GA.
- Geng, S., J.S. Auburn, E. Brandsetter and B. Li. 1988. A program to simulate meterological variables: Documentation for SIMMETEO. Agronomy Progress report No. 204. Dept. of Agronomy and Range Sci., Univ. of California, Davis, CA.
- Geng, S. and J.S. Auburn. 1986. Weather simulation models based on summaries of long-term data. In Intl. Symp. on Impact of Weather Parameters on the Growth and Yield of Rice, April 7-10. International Rice Research Institute, Los Banos, Philippines.
- Hunt, L.A., J.W. Jones, P.K. Thornton, G. Hoogenboom, D.T. Imamura, G.Y. Tsuji and U. Singh. 1994. Accessing data, models and application programs. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds.). DSSAT v3. Vol. 1-3. University of Hawaii, Honolulu, HI.
- Jones, J.W., L.A. Hunt, G. Hoogenboom, D.C. Godwin, U. Singh, G.Y. Tsuji, N. Pickering, P.K. Thornton, W.T. Bowen, K.J. Boote and J.T. Ritchie. 1994. Input and output files. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds). DSSAT v3. Vol. 2-1. University of Hawaii, Honolulu, HI.
- NOAA. 1974. Climate of the States. Water Information Center, National Oceanographic and Atmospheric Administration, United States Department of Commerce, Asheville, NC.
- Pickering, N.B., J.W. Hansen, J.W. Jones, H. Chan, and D. Godwin. 1994. WeatherMan: A utility for managing and generating daily weather data. Agron. J. 86(2):332-337.
- Pickering, N.B., J.R. Stedinger, and D.A. Haith. 1988. Weather input for nonpoint-source pollution models. J. Irrig. Drain. Eng. 114(4):674-690.
- Prescott, J.A. 1940. Evaporation from a water surface in relation to solar radiation. Trans. R. Soc. S. Austr. 64: 114-118.

- Richardson, C.W. and D.A. Wright. 1984. WGEN: a model for generating daily weather variables. United States Department of Agriculture, Agricultural Research Service, ARS-8, Washington, DC.
- Rietveld, M.R. 1978. A new method for estimating the regression coefficients in the formula relating solar radiation to sunshine. Agricul. Meterol. 19:243-252.
- Rudloff, W. 1981. World-Climate. Wissenschaftliche Verlagsgesellschaft, mbH Stuttgart, Germany.

# APPENDIX A. ABBREVIATIONS USED IN WEATHERMAN

## Daily Weather Variables

**SRAD** Total daily solar radiation. TMAX Maximum daily air temperature. TMIN Minimum daily air temperature. RAIN Total daily precipitation. DEWP Dew point temperature or vapor pressure. WIND Total daily wind run. SUNH Total daily sunshine hours. PAR Total daily photosynthetic radiation. **TWET** Wet bulb air temperature at 9 a.m. **EVAP** Total daily pan evaporation.

## Summary Files

## TIME VARIABLES

DOC Number of days since January 1, 1801.

MTH Month (1 - January, 2 - February, etc.).

MNO Month number, counting from the first month in the data set.

YR Year of century (eg., 94 can represent 1994).

YRNO Year number, counting from the first year in the data set.

## **MOMENTS**

The first character in moment variables represents the weather variable type. The second represents wet state. The final two represent the type of statistic.

S	Total daily solar radiation.
X	Maximum daily air temperature.
N	Minimum daily air temperature.
R	Total daily precipitation.
P	Total daily photosynthetic radiation.
_D	Dry days (i.e., without precipitation).
W	Wet days (i.e., with precipitation).

_A	All days
_MN	Mean.
_SD	Standard deviation.
_SK	Skewness coefficient.

Kurtosis coefficient.

## **PERCENTILES**

\_\_KT

P0 Minimum.
P25 25th percentile.
P50 Median.

P75 75th percentile. P100 Maximum.

## **DISTRIBUTION**

BINi The relative frequency of observations falling within the ith interval.

## TIME STRUCTURE

SDEV Standard deviation.

LAGi Lag i (i=0..5) autocorrelation coefficients.

PW Probability of a wet day.

PWW Probability of a wet day following a wet day. PDW Probability of a wet day following a dry day.

PWWW Probability of a wet-wet sequence.
PDWW Probability of a dry-wet-wet sequence.
PWDW Probability of a wet-dry-wet sequence.
PDDW Probability of a dry-dry-wet sequence.

## APPENDIX B.

## CLIMATE FILE FORMAT

The climate file contains summary information on a site in five sections. The \*CLIMATE section contains characteristics of the location. The \*MONTHLY AVERAGES section contains monthly means and Angstrom coefficients used by the SIMMETEO weather generator. The \*WGEN PARAMETERS section contains the monthly distribution parameters used by the WGEN weather generator. The \*RANGE CHECK VALUES section contains the values used to check for outliers and suspect data during the Import process. The \*FLAGGED DATA COUNT section contains counts of total, erroneous, and suspect data in the archive file.

#### \*CLIMATE

LAT Latitude, degrees north. **LONG** Longitude, degrees east.

**ELEV** Elevation, m.

TAV Mean annual temperature, °C.

**AMP** Half of the mean temperature difference between the

warmest and coolest month.

SRAY Mean annual daily solar radiation,  $MJ/m^2/day$ . TMXY Mean annual daily maximum temperature, °C. **TMNY** Mean annual daily minimum temperature, °C.

**RAIY** Mean annual daily rainfall, mm.

**START** Mean day of year of the first frost-free day.

DURN Mean number of days between the last and the first frost. **ANGA** Intercept A in the Angstrom equation (Prescott, 1940). **ANGB** Multiplier B in the Angstrom equation (Prescott, 1940). **REFHT** 

Height of weather instruments above ground, m.

**WNDHT** Height of annemometer above ground, m.

First year of observed weather data. **GSST** 

**GSDU** Number of years of observed weather data.

## \*MONTHLY AVERAGES

MONTH Month (1 - January, 2 - February, etc.).

SAMN Mean daily solar radiation for month, MJ/m²/day. XAMN Mean daily maximum temperature for month, °C. NAMN Mean daily minimum temperature for month, °C.

RTOT Mean total rainfall for month, mm.

RNUM Mean number of days with rainfall for month.

SHMN Mean daily hours of bright sunshine for month, percent of

daylength.

AMTH Intercept A in the Angstrom equation for month.

BMTH Multiplier B in the Angstrom equation for month.

## \*WGEN PARAMETERS

MTH Month (1 - January, 2 - February, etc.).

SDMN Mean daily solar radiation on dry days, MJ/m²/day.
SDSD Standard deviation of solar radiation on dry days.
SWMN Mean daily solar radiation on wet days, MJ/m²/day.
SWSD Standard deviation of solar radiation on wet days.
XDMN Mean daily maximum temperature on dry days, °C.

XDSD Standard deviation of maximum temperature on dry days.

XWMN Mean daily maximum temperature on wet days, °C.

XWSD Standard deviation of maximum temperature on wet days.

NAMN Mean daily minimum temperature, °C.

NASD Standard deviation of minimum temperature.

ALPHA Alpha coefficient of gamma distribution for rainfall.

RTOT Total rainfall, mm.

PDW Probability of a wet day following a dry day.

RNUM Mean number of days with rainfall.

#### \*RANGE CHECK VALUES

MIN Minimum value for range check.
MAX Maximum value for range check.

RATE Maximum change between days for range check.

### \*FLAGGED DATA COUNT

BEGYR Year of first daily weather record.

BEGDY Day of year of first daily weather record.

ENDYR Year of last daily weather record.

ENDDY Day of year of last daily weather record.

TOTAL Total number of observations.

VALID Number of observations without error flags.


MISSING Number of missing values.

ERROR Number of values with non-numeric strings encountered.

ABOVE Number of values above the maximum. BELOW Number of values below the minimum.

RATE Number of values with greater than maximum change from

previous day.



L.A. Hunt, S. Pararajasingham

Genotype Coefficient Calculator •	• Genotype Coefficient Calculator	Genotype Coefficient Calculator	Genotype Coefficient Calculator	• Genotype Co

## CHAPTER ONE. INTRODUCTION

The Genotype Coefficient Calculator (or GenCalc) was developed to facilitate determination of the genotype coefficients that are made use of by the IBSNAT crop models (Hunt, 1988; Hunt et al., 1993). The first released version of the software was distributed earlier (Hunt et al., 1993; Hunt and Pararajasingham, 1993) with focus on the crop models distributed with Version 2.1 of the IBSNAT software package called DSSAT. DSSAT v3, however, has new crop models and new data standards and thus there was a need for GenCalc to be upgraded to facilitate use with the new models. The changes required are minor, but for consistency it was thought best to issue a users guide that relates specifically to the Version 3 series of models.

GenCalc V3.0 can be used with any model that is constructed to accord with certain basic requirements (Appendix 1). In particular, it requires genotype coefficient files that conform to the standard structures defined in Volume 2-1, Jones et al. 1994, of this book, and a crop model output file, OVERVIEW.OUT, that contains a list of simulated and measured values for 'key' variables. In use, it requires that a user respond to a number of prompts. Information to help with the choices is displayed on most screens.

## PROGRAM COMPONENTS

GenCalc encompasses a number of components, as depicted in flow chart form in Figure 1. The components are described as follows.

## **P**ROGRAMS

GENCALC.EXE. The shell program that sets up the various control files,

activates the overall control program, and runs the appro-

priate model (BASIC).

GENCON.EXE. A control program that reads simulated and measured data

from one of the model output files (OVERVIEW.OUT) and then, if needed, changes the appropriate genotype coefficient to bring simulated values closer to the measured data

(FORTRAN).

GENMEANS.EXE. An 'averaging' program that calculates means for coeffi-

cient values from individual experiments (BASIC).




FIGURE 1. GENCALC COMPONENTS.

The BASIC programs require a run-time module, BRUN45.EXE. It's path must be referenced in the path statement in the AUTOEXEC.BAT file.

## **F**ILES

DSSATPRO.FLE

A profile (configuration) file that indicates the name and location on disk of programs and files that are used by GenCalc. The file is detailed in Appendix B, along with

procedures for making changes to it. In DSSAT v3, GenCalc is located in directory C:\DSSAT3. For stand-alone use, the directory in which it is located could be chosen at the user's discretion. In all cases, however, the directory must be referenced by adding a 'SET' statement to the AUTOEXEC.BAT file. For a C:\DSSAT3 location, the required statement would be: SET DSSAT3 = C:\DSSAT3.

**GCRULES.FLE** 

A file containing the rules that govern the sequence of genotype coefficient calculations for different crops. This file can be located in any directory, but the directory must be referenced in the configuration file. Contents of the file are copied to a temporary file (GCRULES.CTR) that is used during computation.

??COEFF.TMP and ENDPOINT.TMP

Files generated internally at each new model run. The ?? indicates a crop code such as 'WH' for wheat. The calculated genotype coefficient values are stored in ??COEFF.TMP while end point information (simulated and measured values at completion) is stored in ENDPOINT.TMP for each coefficient. Information in these files is displayed for perusal at the completion of a genotype coefficient calculation session.

## REQUIREMENTS

In DSSAT v3, the file designated as FILEA required in addition to those which are necessary for running the DSSAT v3 models. The naming convention for these files and for FILEA is described in Volume 2-1, Jones et al. 1994, of this book. FILEA contains experimental data used to determine the goodness-of-fit of simulated results. The following data must be present in FILEA:

**Peanut:** Flowering date

Maturity date

Seed yield

Biomass at maturity

Seed number/m<sup>2</sup>

Seed number per pod

Seed dry weight

First pod date

Full pod date

Pod yield (dry)

*Maize:* Silking date

Maturity date
Grain yield (dry)
Biomass at maturity
Grain number/m<sup>2</sup>
Grain number per ear
Grain weight (dry)

Soybean: Flowering date

Maturity date Grain yield

Biomass at maturity (no leaves)

Grain number/m<sup>2</sup>
Grain number per pod
Grain dry weight

Wheat: Anthesis date

Maturity date
Grain yield (dry)
Biomass at maturity
Grain number/m<sup>2</sup>
Grain number per spi

Grain number per spike Grain weight (dry)

The files that contain the genotype coefficients for the models used with the calculator are named as ??XXXYY0.CUL, where "??" is the crop identification code, "XXX" is the model abbreviation and "YY" is the version number of the model. Genotype coefficient values calculated from model runs, at the user's discretion, may be entered into this cultivar file. As described under the GenCalc operation (see Step 5 in Chapter 4), the genotype coefficient values from the cultivar file are copied to the GCINIT.CTR file for display as initial values for the genotype in question. (The GCINIT.CTR file is explained in Figure 1). For the case where a genotype that is not present in the cultivar file is included in an experiment, the user must use an editor to enter into the cultivar file a unique number and name and an initial 'guess' at the genotype coefficients.

# System Requirements

GenCalc will run on any IBM or IBM-compatible computer with MS-DOS v3.0 and later. A hard disk drive with approximately 2 Mb free disk space is required. For stand-alone installation, GenCalc requires the creation (if not already present) of a directory C:\DSSAT3. The DSSATPRO.FLE described in the Components section of this guide and Appendix B must be placed in this directory. GenCalc also uses a number of subdirectories under C:\DSSAT3, namely GENOTYPE, PEANUT, SOYBEAN, and WHEAT. The GenCalc component programs together with the crop model executable programs are placed in the DSSAT3 subdirectory, while the crop model input files are placed in subdirectories named after the crop in question. Model and crop specific genotype coefficients files (??XXXYY0.CUL files) and the GCRULES.FLE are placed in the GENOTYPE subdirectory. All could be changed, as long as the location of the configuration file (DSSATPRO.FLE) remains the same as that of the program executables.

Genotype Coefficient Calculo	lator • Genotype Coefficient Calculator	Genotype Coefficient Calculator	Genotype Coefficient Calculator	• Genotype Co

# CHAPTER TWO. GETTING STARTED

GenCalc can be run from the DSSAT v3 Shell or as a stand-alone program. (See Volume 1-3, Hunt et al. 1994b, of this book for a description of the Shell.) From the DSSAT v3 Shell, open the DATA main menu, select "Genotype" from the menu (see Screen 1, below) and then select "Calculate" from the submenu presented. The first screen of the GenCalc program (Screen 3) will be presented.

To run GenCalc as a stand-alone program, refer to Hunt and Pararajasingham (1994).

Transfer experiment data sets with genotypes you wish to examine into the appropriate directory (e.g., wheat data into C:\DSSAT3\WHEAT), and use an editor to add the experiment(s) to the list in the EXP.LST file. (See Appendix A for an example of this file and Volume 2-1, Jones et al. 1994, for this book for a description of this file.) These data sets must be complete with weather and soils data and with data in the cultivar file.

DECISION	SUPPORT	SYSTEM	FOR	AGROTE	CHNOLOGY	TRANSFER
DATA	MODEL	AN	ALYS:	ES	TOOLS	SETUP/QUIT
B Background X Experiment G Genotype W Weather S Soil P Pest E Economic						
E ECOHOMIC						
Cultivar, ecoty	pe, and spe	ecies info	rmati	on.		
$ \uparrow \downarrow \rightarrow \leftarrow  \mathbf{n} $ ESC	noves thr	ough mer higher m	iu ch ienu	oices level		Version: 3.0


SCREEN 1.

# CHAPTER THREE. RUNNING GENCALC

When GenCalc is opened from the DSSAT v3 Shell DATA main menu, Screen 2 (below) is presented. Follow the procedure in the steps listed below to determine the coefficients for one genotype. This procedure is often followed in determining coefficients, but it is not the only one. It should thus be viewed as a starting point, not as a *fixed recipe*. Users may develop a different approach, as experience is gained, or they may miss some steps. Users should also be aware that some errors may cause the software to enter an endless loop. Should this appear to happen, turn off the computer or re-boot by pressing <CTR>-<ALT>-<DEL>.

# DETERMINE GENETIC COEFFICIENTS

- 1. In Screen 2, press the <I> key. This directs the genotype coefficient calculator to determine values for specific experiment/treatment combinations.
- 2. Select a crop in Screen 3 (on following page) for the genotype you wish to calculate



SCREEN 2.

```
G.C.CALCULATOR - INDIVIDUAL

PRESS:

B for BARLEY D for DRY BEAN A for AROIDS
I for MILLET Y for SOYBEAN C for CASSAVA
M for MAIZE P for PEANUT T for POTATO
R for RICE
S for SORGHUM
W for WHEAT

O for OTHER ESC for previous screen


NB. The model installed must meet Gencalc requirements. If you are unsure, exit and check Model and Gencalc documentation.

Determine genotype coefficients for one or more experiments; calculate average values after determining coefficients for several experiments.
```

### SCREEN 3.

- 3. Decide whether to delete the contents of individual values file (??COEFF.TMP) from previous GenCalc sessions. As the message on the screen indicates, the contents of this file must be deleted from time to keep the file size manageable.
- 4. When a crop is selected (e.g., M = Maize) in Screen 3, a list of genotypes available for that crop for analysis is presented in Screen 4 (on following page). Select one of the genotypes from the list.
- 5. After a genotype is selected in Screen 4, examine the list of genotype coefficients from the GCINIT.CTR file which will be displayed in a screen similar to Screen 5 (on following page). In example Screen 5, the coefficients shown are for maize. The coefficients displayed in this screen will be used as initial values for the first run of the calculator. Abbreviations are listed in the file GENCOEFF.ABV in the c:\DSSAT3\GENOTYPE directory (see Appendix C). If satisfied with the coefficients listed, press "Y" to accept the values. Or, press "N" to modify the values of one or more of the coefficient(s) for use in the first model run.

When "N" is selected in Screen 5, Screen 6 (on 2nd following page) is presented, in which you can alter the coefficient values. When values for all the coefficients listed are acceptable, press "Y" at the Screen 5 prompt.



#### SCREEN 4.

- 6. In the next dialog box presented, respond with an "N" to the prompt, 'Calculate ALL coefficients?'. And at the next prompt, respond with a "Y" to calculate only the DEVELOPMENT (those concerned with the duration of the life cycle) coefficients.
- 7. Screen 7 (on following page) will be presented which lists experiments which

```
G.C.CALCULATOR - INDIVIDUAL

CROP: Maize

MODEL: GECER930

Current coefficients are:
P1 P2 P5 G2 G3 PHINT
1 2 3 4 5 6
320. .520 940. 625. 6.00 75.0
Use these for first simulation of new run ?

Press: Y or N

Generally, the displayed coefficients should be used for the first run; changed for susequent runs. This helps in obtaining multi-site fits.
```

SCREEN 5.

```
G.C.CALCULATOR - INDIVIDUAL

CROP: Maize

MODEL: GECER940


Current coefficients are:
P1 P2 P5 G2 G4 PHINT
1 2 3 4 5 6
320. .520 940. 625. 6.00 75.0
Which coefficient to change ?
ENTER 1,2 etc. -->

Generally, the displayed coefficients should be used for the first run; changed for subsequent runs. This helps in obtaining multi-site fits.
```


## SCREEN 6.

include the selected genotype. Choose experiments to be used for genotype coefficient calculation by typing either "Y" or "N" to the prompt for each experiment.

8. The treatments for each experiment selected will be displayed in Screen 8 (on following page). Choose all or some treatment(s) in the chosen experiments for genotype coefficient calculation by responding appropriately ("Y" or "N") to the prompts on the screen.



SCREEN 7.



#### SCREEN 8.

9. In the dialog box next presented, type an "N" at the prompt, 'Selection of runs for this genotype complete?' because you want to set up another sequence of calculation for the genotype in question but with different initial coefficients.

Screen 5 will again be presented (see Step 5). Change one of the coefficient(s) by 20 to 30% as described under Step 5.

When the prompt 'Selection of runs for this genotype complete?' reappears, respond with "N" again to bring up the initial genotype coefficients list, but this time decrease the appropriate coefficient by 10 to 20%.

**NOTE:** Setting an array of initial values for particular coefficient(s) is necessary to develop data for examination of variation in the values fitted for the varying coefficient(s).

10. Now at the prompt, 'Selection of runs for this genotype complete?', type "Y" to proceed with the genotype coefficient calculation. The calculator will run the appropriate crop model, and data indicating the goodness-of-fit between predicted and actual data will be displayed on the screen as calculations proceed. For each set of calculations, final coefficient values and end point information are stored in files (??COEFF.TMP and ENDPOINT.TMP, respectively) so that these are available for subsequent viewing.

```
G.C.CALCULATOR - INDIVIDUAL

CROP: Maize MODEL: GECER930

All calculations completed ...

PRESS: C to view COEFFICIENTS
E to view END POINTS
O to view OUTPUTS
A to calculate AVERAGES

ENTER to proceed to the next menu

It is generally desirable to examine the endpoints. If the fit was not good, the process should be repeated with new initial values.
```

#### SCREEN 9.

11. When calculations are completed, press the <C> key in Screen 9 (above) to view the array of coefficients calculated for each set of calculations in the ??COEFF.TMP file (Screen 10, below). While viewing these final coefficient values, pay particular attention to the codes assigned by GenCalc, if at all, to each of the calculated genotype coefficients (see Appendix C for a description of these codes). Growth coefficients will have a "U" immediately following the numerical value. This indicates that the particular coefficient was not

```
*MAIZE COEFFICIENTS

@NGENO EXPMENT R RUN T ETYPE P1 P2 P5 G2 G3 PHINT IB0063 IBSI8001 2 1 1 IB0001 320.D.5200D 940.D 625.U6.000U75.00U IB0063 IBSI8001 2 1 2 IB0001 320.D.5200D 940.D 625.U6.000U75.00U IB0063 IBWA8301 2 1 1 IB0001 340. .5200M 940.M 625.U6.000U75.00U IB0063 IBWA8301 2 1 2 IB0001 340. .5200M 940.M 625.U6.000U75.00U IB0063 IBWA8301 2 1 3 IB0001 340. .5200M 940.M 625.U6.000U75.00U IB0063 IBWA8301 2 1 3 IB0001 340. .5200 940.M 625.U6 000U75.00U
```

SCREEN 10.

determined during the iterative calculations of the current session. The remaining coefficients should have no associated letter. If this is the case, press the exit key of your editor and proceed to Step 12. If, however, the development coefficients were associated with a letter, which may occur when the initial coefficients were either close to the maximum/minimum values, or were considerably different from the real values, proceed through the following steps:


- 11a. Screen 10 shows an an example ??COEFF.TMP file for maize. Make a note of the letter and the coefficient value for each coefficient listed which has a letter. The letter "M" indicates that the calculated coefficient reached the maximum or minimum value defined in the GCRULES.FLE file, while an "R" indicates that the maximum number of runs specified in the GCRULES.FLE file was reached before an acceptable end point was reached. Other codes that may appear are defined in Appendix C.
- 11b. Exit Screen 10 by pressing the <F7> key if using the editor (TVED.EXE) distributed with DSSAT v3. If you are using an editor of choice, use the required key to exit the screen. You will be returned to Screen 9.
- 11c. Now in Screen 9, press the <E> key to view the end-points in the END-POINT.TMP file (see Screen 11, below). For each coefficient with an associated letter noted in Screen 10, make a note as to whether the simulated value is greater or less than the measured value.

EXPERIMENT	TRTMT	COEFF	NAME		SIMULATED	MEASURED	REFERENCE TRAIT(S)
IBSI8001	1	3	DESP	(P2)	61.000	.000	SILKING DATE
IBSI8001	1	1	DUJU	(P1)	61.000	.000	SILKING DATE
IBSI8001	1	2	DUGF	(P5)	111.000	.000	MATURITY DATE
IBSI8001	2	3	DESP	(P2)	61.000	.000	SILKING DATE
IBSI8001	2	1	DUJU	(P1)	61.000	.000	SILKING DATE
IBSI8001	2	2	DUGF	(P5)	111.000	.000	MATURITY DATE
IBWA8301	1	3	DESP	(P2)	76.000	79.000	SILKING DATE
IBWA8301	1	1	DUJU	(P1)	78.000	79.000	SILKING DATE
IBWA8301	1	2	DUGF	(P5)	137.000	139.000	MATURITY DATE
IBWA8301	2	3	DESP	(P2)	76.000	79.000	SILKING DATE
IBWA8301	2	1	DUJU	(P1)	78.000	79.000	SILKING DATE
IBWA8301	2	2	DUGF	(P5)	137.000	135.000	MATURITY DATE
IBWA8301	3	3	DESP	(P2)	76.000	78.000	SILKING DATE
IBWA8301	3	1	DUJU	(P1)	78.000	78.000	SILKING DATE
IBWA8301	3	2	DUGF	(P5)	137.000	136.000	MATURITY DATE

SCREEN 11.

- 11d. Exit Screen 11 by pressing the <F7> key. You will again be returned to Screen 9.
- 11e. Press the <ENTER> key in Screen 9 to continue.
- 11f. Screen 12 (below) will be presented. Press the <G> key to return to the genotype selection screen (Screen 4).
- 11g. Choose the same genotype as selected before in Screen 4.
- 11h. If the letter from the??COEFF.TMP file (Screen 10) for a coefficient was an "R," respond with an "N" to the prompt, 'Use these for first simulation of new run?'. Then in the dialog box which appears, change the value for the appropriate coefficient. Increase the value by approximately 30% if the simulated value was less than the measured; decrease the value similarly if the inverse. Then proceed as from Step 6.

If the letter was an "M," proceed as from Step 5, but when the Coefficient Selection screen (Screen 6) is reached, press the <ENTER> key and edit the rules file. For the coefficient(s) in question, reduce the minimum (MNCEF) or increase the maximum (MXCEF) for rule set 2 of the crop in question, depending on whether the coefficient value noted in Step 11a was near the minimum or maximum. Then exit the rules file and proceed as indicated in Step 6.



SCREEN 12.

- 12. If the coefficient calculations proceeded to completion satisfactorily, press the <ENTER> key and you will be prompted in the next screen for selection of another genotype of the same crop, for the selection of another crop, or for return to the main menu. Press the <ENTER> key to return to the GenCalc main menu (Screen 2), and once within the main menu, press "A" for the calculation of average coefficients from previous determinations. Selecting "A" allows you to calculate the AVERAGES of coefficients calculated from various experiments using the Steps above. If desired, you may replace coefficient values in the cultivar file with these values (see Step 20).
- 13. The calculator will then prepare a list of coefficients calculated for the genotype in question in previous specific experiment/treatment runs (Screen 13, below). Each of these runs is assigned a sequence number in the listing (RUN column) as shown in Screen 10, along with a number denoting whether all (1), development (2) or growth (3) coefficients were determined (R column). A column headed with a "T" contains the number of the treatment used for the particular set of coefficient calculations.
- 14. In Screen 13, select a run number. Once a run number is chosen, mean coefficients are calculated from individual values obtained for different experiments and treatments but with the same initial coefficient values, along with their respective coefficients of variation. These values are displayed, together

```
G.C.CALCULATOR - AVERAGES
                                                                     VERSION: 3
          EXPMENT R RUN T ETYPE
    CODE
                                     P1
                                            P2
                                                  P5
                                                         G2
    IB0063 IBSI8001 2 1 1 IB0001
IB0063 IBSI8001 2 1 1 IB0001
                                    320.D.5200D 940.D 625.U6.000U75.00U
                                    320.D.5200D 940.D 625.U6.000U75.00U
    IB0063 IBSI8001 2 2
                          1 IB0001
                                    320.D.5200D 940.D 625.U6.000U75.00U
    IB0063 IBSI8001 2 2
                          2 IB0001
                                    320.D.5200D 940.D 625.U6.000U75.00U
    IB0063 IBWA8301 2 1
                          1 IB0001
                                    340. .5200M 940.M 625.U6.000U75.00U
    IB0063 IBWA8301 2 1
                          2 IB0001
                                    340. .5200M 940.M 625.U6.000U75.00U
    IB0063 IBWA8301 2
                          3 IB0001
                                    340. .5200M 940.M 625.U6.000U75.00U
    IB0063 IBWA8301 2 2
                         1 IB0001
                                    340. .5200M 940.M 625.U6.000U75.00U
    IB0063 IBWA8301 2 2
                          2 IB0001
                                    340. .5200M 940.M 625.U6.000U75.00U
    IB0063 IBWA8301 2 2
                         3 IB001
                                    340. .5200 940.M 625.U6.000U75.00U
    Which RUN to select ? [ Enter number from RUN column ] -->
     Main coefficients for different experiments and initial values.
     Initial values are referenced in the 'Run' column. T=treatments.
```

SCREEN 13.

```
G.C.CALCULATOR - AVERAGES

GENOTYPE: P10 X 304C

1 2 3 4 5 6

P1 P2 P5 G2 G3 PHINT

Old values: 320. .520 940. 625. 6.00 75.0

New vlues: 340. .520 .000 .000 .000

C.V.'s: 0 0 0 0 0 0

Treatments: 3 1 0 0 0 0

Number of experiments: 1

SELECT an additional run ? [ PRESS Y or N ]

Coefficient values determined for different experiments and one set of initial values. Coefficients of variation if more than 3 values.
```

## SCREEN 14.

with values currently in the cultivar file, in Screen 14 (above). Coefficients that were not estimated, or for which calculations were terminated before an acceptable end-point was reached, are displayed as zeros. These coefficients would have had a letter associated with them in the ??COEFF.TMP file (see Step 11).

- 15. In the dialog box at the bottom of Screen 14, press "Y" to select an additional run.
- 16. Press "Y" again when the second set of coefficients has been calculated. Press "Y" and "3" to select results from the third run.
- 17. This time press "N" at the prompt in Screen 14 to indicate that run selection is complete.
- 18. At this stage a list of standard deviations for coefficients in the different runs is presented. Select the one with the lowest standard deviation for the 'target' coefficient.
- 19. A list of 'new' and 'old' mean coefficient values is now displayed. In this list, coefficients that were not calculated will have been replaced by those in the cultivar file. Press "Y" at the prompt to accept all values.

- 20. Respond with a "Y" to the prompt asking whether or not to replace the 'old' values in the cultivar file.
- 21. Respond with an "N" to the prompt asking if you wish to edit the cultivar file, although including notes in the cultivar file may be useful for future reference.
- 22. At this stage, the process should be repeated from Step 1 to calculate the growth coefficients for the cultivar in question. Exit the averaging program and press the <ENTER> key to display the prompts to select another genotype or a different crop. Press the <G> key to select a genotype and repeat the process.
- 23. Respond with an "N" response to the prompt "Calculate DEVELOPMENT coefficients only." Follow this by a "Y" response to the prompt "Calculate GROWTH coefficients only" in Step 6. Continue with Step 7.

Repeat the process for the GROWTH coefficients. Upon completion, you should have both the DEVELOPMENT and GROWTH coefficients needed to run the appropriate crop model.

# DISCUSSION

The above step-by-step instructions cover the basics of GenCalc operation. The various options available in GenCalc, however, make it possible to determine genotype coefficients in a number of different ways. Users should be aware of this and should experiment with procedures that may be more appropriate for their own specific conditions. Users should also be aware that it may not be possible to 'fit' coefficients for some data sets. Should this appear to be the case, a user is encouraged to contact the authors and to provide them with a copy of the data set being used. Such communication will help both with development of the GenCalc software and with further enhancement of the crop models.

Genotype Coefficient Calculator •	Genotype Coefficient Calculator •	Genotype Coefficient Calculator	Genotype Coefficient Calculator	• Genotype Coefj

# REFERENCES

- Hunt, L.A. 1988. IBSNAT's genetic coefficients: coping with germplasm diversity. Agrotechnology Transfer No. 7 p. 1-5.
- Hunt, L.A. and S. Pararajasingham. 1993. GenCalc: Genotype coefficient calculator, user's guide, version 2.0. Crop Science Publication No. LAH-01-93, University of Guelph.
- Hunt, L.A., S. Pararajasingham, J.W. Jones, G. Hoogenboom, D.T. Imamura and R.M. Ogoshi. 1993. GENCALC Software to facilitate the use of crop models for analyzing field experiments. Agron. J. 85:1090-1094.
- Hunt, L.A., J.W. Jones, G. Hoogenboom, D.C. Godwin, U. Singh, N. Pickering, P.K. Thornton, K.J. Boote and J.T. Ritchie. 1994a. General input and output file structures for crop simulation models. *In:* Uhlir, P.F. and G.C. Carter (eds.) Crop Modeling and Related Environmental Data, A Focus on Applications for Arid and Semiarid REgions in Developing Countries. CODATA Monograph Series, Volume 1. CODATA, Paris, France, pp. 35-72.
- Hunt, L.A., J.W. Jones, P.K. Thornton, G. Hoogenboom, D.T. Imamura, G.Y. Tsuji and U. Singh. 1994b. Accessing data, models and application programs. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds.). DSSAT v3. Vol. 1-3. University of Hawaii, Honolulu, HI.
- IBSNAT. 1989. Decision support system for agrotechnology transfer V. 2.1: user's guide. Department of Agronomy and Soil Science, College of Tropical Agricultural and Human Resources. University of Hawaii, Honolulu, HI.
- IBSNAT. 1990. Documentation for IBSNAT crop model input and output files, V.
  2.1 for the decision support system for agrotechnology transfer (DSSAT V.
  2.1). Technical Report 5. Department of Agronomy and Soil Science, College of Tropical Agriculture and Human Resources, University of Hawaii, Honolulu, HI.
- Jones, J.W., L.A. Hunt, G. Hoogenboom, D.C. Godwin, U. Singh, G.Y. Tsuji, N. Pickering, P.K. Thornton, W.T. Bowen, K.J. Boote and J.T. Ritchie. 1994. Input and output files. *In:* Tsuji, G.Y., G. Uehara and S. Balas (eds). DSSAT v3. Vol. 2-1. University of Hawaii, Honolulu, HI.

# APPENDIX A. GENCALC MODEL REQUIREMENTS

For use with GenCalc, models must satisfy a number of basic requirements, as summarized below in Table 1. Details of these requirements are provided below:

- 1. The name of the EXE file should be built in accord with a convention in which the first two spaces are for a standard crop code (e.g., SB for soybeans; WH for wheat), and the next six are for an abbreviated model name and number (e.g., SBGRO941 for the soybean 'GRO' model, 94 version, modification 1).
- 2. Input and simulator components of the model should obtain basic run control information from the command line after the executable file name. For the simulator component, which may be the only component of some models, required information encompasses:(a) the name of the experiment details/simulator control file, (b) a symbol to indicate the nature of the experiment details file (e.g., 'X' for a standard experiment details file [see Volume 2-1, Jones et al. 1994, of this book for a description of this file]), (c) a symbol for the mode of model operation (a 'G', programmed in the model to turn off all prompts), (d) a run number and (e) a number indicating the treatment to be

# TABLE 1. REQUIREMENTS FOR CROP MODELS TO WORK UNDER GENCALC.

Aspect Requirement

Model name According to convention (e.g. GECER930 for the generic

CERES model)

Command line(s) With basic information for running the driver, input and/or

simulator components of the model.

Input files \*.CUL file with genotype coefficients. File name linked to

the Model EXE name according to convention

Output files OVERVIEW.OUT file with table of predicted and measured

data

Experiment details, soil

and weather files Standard (Jones et al., 1994).

Experiment data file Standard 'A' files with averages from one or more experi-

ments (Jones et al., 1994).

used. The latter two items may be omitted, in which case the run number will be assigned a value of one, and the first treatment encountered will be simulated. The information should be conveyed as in the example which follows:

# C:\CRGRO940.EXE XFILE.RUN X G 1 3

where CRGRO940.EXE is the name of the simulator; XFILE.RUN is the name of the file containing the experimental details; X is the experiment details file type; G is the simulator 'mode' switch (G indicates that all prompts should be switched off); 1 is the run number; and 3 is the number of the treatment to be used for simulation.

For the inputs component, where present, the required information encompasses the name of the file to be generated, its type, an inputs program 'mode' switch, and reference numbers for the experiment and treatment to be used. This required information should be conveyed as follows:

# C:\MINPT940.EXE XFILE.RUN X G 1 3

where MINPT940.EXE is the name of the inputs program; XFILE.RUN is the name of the file to be generated to transfer data to the simulator; X is the type of transfer file to be generated; G is the inputs 'mode' switch (G indicates that all prompts should be switched off); 1 is the experiment number (as in the EXP.LST file); and 3 is the treatment number.

For models which need to run with their own 'driver', the command line would need to be structured as in the example below:

# C:\MDRIVE940.EXE MINPT940.EXE CRGRO940.EXE X G 1 3 where MDRIV940.EXE is the name of the model 'driver'; MINPT940.EXE is the name of the inputs program (reader); CRGRO940.EXE is the name of the simulator; X is the type of transfer file; G is the 'mode' switch for input and simulator components; 1 is the experiment number (as in the EXP.LST file); and 3 is the treatment number.

3. The model should use a genotype coefficient file (or cultivar file) that is named in accord with the EXE file name, but that has a zero (0) in position 8 and an extension 'CUL'. The format of this file should accord with the standards laid down by Hunt et al. (1993) and in Volume 2-1 (Jones et al. 1994) of this book. In this standard, each line begins with 6 spaces for a cultivar identification code (the first two items should be the code for the Institute that assigned the num-

ber), a blank, 17 spaces for the cultivar name, a blank, 5 spaces for a type identifier (e.g., an identifier for highland or lowland bean ecotypes), and then data in a (1X, F5.?) format (i.e., 1 blank, followed by 5 spaces for a real variable with the required number of decimals). An example of a Cultivar file is shown in Table 2.

- 4. The model should produce an output file that is named OVERVIEW.OUT and that contains a list of simulated and measured values of 'key' variables. This file could contain additional information, but the structure and heading of this list, which could appear early or late in the file, should be as shown in Table 3.
- 5. The model should use standard files (Jones et al., 1994) to obtain required information on experimental conditions and experimental results. An example is shown in Table 4.

TABLE 2. EXAMPLE OF A CULTIVAR (GENOTYPE) COEFFICIENT FILE.

*WHEAT GE	NOTYPE COEFFICIENT	S							
!									
@NGENO	NAME	TYPE	DUGF	DESV	DESP	GNUM	GGRO	GNUS	BIOM
IB0002	WARED	WН6X	470.	.0030	.0054	30.00	1.00	.67	1.
IB0003	WALDRON	WН6X	470.	.0030	.0054	30.00	1.00	.67	1.
IB0004	ELLAR	WH6X	470.	.0030	.0054	28.50	1.00	.67	1.
IB0005	BUTTE	WН6X	470.	.0030	.0054	19.00	1.35	.67	1.
IB0006	WARD	WН6X	470.	.0030	.0030	23.00	1.00	.67	1.
IB0030	RONGOTEA	WH6X	470.	.0030	.0054	13.00	1.70	.60	1.
IB0031	KOPARA	WН6X	470.	.0030	.0054	13.00	1.70	.60	1.
IB0032	BOUNTY	WН6X	472.	.0330	.0074	21.00	1.35	.60	1.
IB0033	MOULIN	WН6X	472.	.0330	.0078	24.00	1.35	.63	1.

TABLE 3. EXAMPLE OF THE REQUIRED SECTION OF THE OVERVIEW.OUT FILE.

MAIN CROP VARIABLES :

@VARIABLES	PREDICTED	MEASURED
ANTHESIS DATE	91178	91179
MATURITY DATE	91207	91207
GRAIN YIELD (kg dm/ha)	7489	1234
GRAIN WEIGHT (mg dm)	27.0	20.5
GRAIN NUMBER (no/m2)	27771	-99
GRAINS PER SPIKE (no)	65.3	-99.0
MAX. LAI	3.0	-99.0
BIOMASS (kg dm/ha)	12879	099
STRAW (kg dm/ha)	5390	-99
GRAIN N (%)	2.07	2.86
BIOMASS N (kg/ha)	171.8	-99.0
STRAW N (kg/ha)	16.9	-99.0
GRAIN N (kg/ha)	154.9	-99.0

## TABLE 4. EXAMPLE OF AN EXPERIMENT DETAILS FILE.

```
*EXP.DETAILS: KSAS8101WH NITROGEN 3N*2I (GODWIN)
```

\*GENERAL

@PEOPLE

WAGGER, M.G. KISSEL, D

@ADDRESS

DEPT.AGRONOMY, KANSAS STATE UNIV, MANHATTAN, KANSAS

@SITE

ASHLAND, KS, USA 39.0; -97.0; 226; CFA

@NOTES

Documented in Wagger, M.G. 1983 Nitrogen cycling in the plan-soil system.

Ph.D. thesis, Kansas State Univ.

*	*TREATMENTS						-F	ACT(	OR I	LEVE	LS							
@	N	R	0	С	TNAME		CU	FL	SA	IC	MP	MI	MF	MR	MC	MT	ME	ME
	1	1	1	0	N1*I1	0-N; DRYLAND	1	1	0	1	1	1	1	1	0	0	0	0
	2	1	1	0	N2*I1	60-N;DRYLAND	1	1	0	1	1	1	2	1	0	0	0	0
	3	1	1	0	N3*I1	180-N;DRYLAND	1	1	0	1	1	1	3	1	0	0	0	0
	4	1	1	0	N1*I2	0-N; IRRIGATED	1	1	0	1	1	2	1	1	0	0	0	0
	5	1	1	0	N2*I2	60-N; IRRIGATED	1	1	0	1	1	2	2	1	0	0	0	0
	6	1	1	0	N3*I2	180-N; IRRIGATED	1	1	0	1	1	2	3	1	0	0	0	0

<sup>\*</sup>CULTIVARS

@C CR INGENO CNAME

1 WH IB0488 NEWTON

\*FIELDS

@L ID\_FIELD WSTA FLOS FLOT FLDD FLDS FLST SLTX SLDP ID\_SOIL 1 KSAS0001 KSAS 0 0 0 0 0 0 0 180 KSAS81IF01

# \*INITIAL CONDITIONS

@C PCR ICDAT ICRT

1 WH 81279 1200 @CICBL SH20 SNH4 SNO3

1 5 0.205 3.4 9.8

1 15 0.205 3.4 9.8 1 30 0.170 3.2 7.3

1 60 0.092 2.5 5.1

1 90 0.065 2.2 4.7

1 120 0.066 2.7 4.3

1 150 0.055 2.7 4.3

1 180 0.066 2.7 4.3

<sup>•</sup> DSSAT v3, Volume 3 • DSSAT v3, Volume 3

#### \*PLANTING DETAILS

@P PDATE EDATE PPOP PPOE PLME PLDS PLRS PLRD PLDP 1 81289 -99 162.0 162.0 0 R -99 -99 5.5

#### \*IRRIGATION AND WATER MANAGEMENT

@I IEFF

1 1.00

@I IDATE IROP RVAL
2 82096 1 65
2 82110 1 78
2 82117 1 70

#### \*FERTILIZERS (INORGANIC)

@F	FDATE	FMCD	FACD	FDEP	FAMN
2	81289	1	-99	15	60
3	81289	1	-99	15	90
3	82056	1	-99	1	90

### \*RESIDUES AND OTHER ORGANIC MATERIALS

@R RDATE RCOD RAMT RESN RESP RESK RINP RDEP 1 81279 1 6500 1.14 -99 -99 -99 15

# APPENDIX B. CONFIGURATION FILE (DSSATPRO.FLE)

The DSSATPRO.FLE file holds path statements to allow the shell program, GenCalc.EXE, to locate directories where necessary programs and/or files are stored, together with the names of programs required by GenCalc. The configuration file has three or four fields of information. The first field holds letter abbreviations or 'keys' that allow the shell program to identify the appropriate row of information. Abbreviations related to crop models in this field have an 'M' (Model) followed by the standard two letter abbreviation of the crop for which a simulation model is available in GenCalc. Abbreviations related to data (input files) for a particular crop model have the letter D (Data) preceded by the standard abbreviation for the crop concerned. In addition to the above, the paths for the rules file (GCRULES.FLE) and the text editor (TVED.EXE, shipped with DSSAT v3, or editor of choice) are also specified in the configuration file. The 3-letter 'key' for the rules file is CRD (CRop Data) while that for the editor is TOE (TOol for Editing).

The second field in the configuration file contains the drive in which the information is located (e.g. C:) while the third field consists of the complete path for the program or file required while running GenCalc. The paths shown in Table 5 are for the programs and files included on the distribution diskette; they could be changed if a user wishes to store the model programs and model input files in directories of his/her choice. In such a case, the user must change the appropriate path/s in the configuration file to match the 'new' location of the programs and/or input files. This may be accomplished simply by editing the configuration file with TVED.EXE or the editor installed in a user's computer. Care must be exercised while editing not to change the abbreviations in the linkage field. Edit the appropriate path/s and once done save the configuration file into the C:\DSSAT3 directory.

The fourth field contains program or file names; it is not present when the row contains directory information alone. The fourth field is the one that would have to be changed if a user wishes to install a replacement crop model. Naturally, such a model should conform in other respects to the requirements of GenCalc. To install, the names of the EXE files for the model in question should be entered in the fourth field of the appropriate row of information. Version 3.0 allows for the use of models that consist of separate 'driver', input and simulator components, so that the names of all three components must be entered into the appropriate row,

together with a symbol that is recognized by the inputs program and indicates the 'type' of file that should be produced to transfer information to the simulator module. Where a model does not have one of the components, a zero should be entered in place of the missing executable file name(s).

The configuration file also permits the loading of 'new' crop and appropriate data files. To do this, the appropriate abbreviations for the model and model input files must be inserted in the first field, and drive path and file name information in the subsequent fields of the configuration file. See Volume 2-1 (Jones et al. 1994) of this book for standard abbreviations of various crops.

# TABLE 5. EXAMPLE CONTENTS OF THE DSSATPRO.FLE FILE.

```
C: \DSSAT3 MDRIV940.EXE MINPT940.EXE GECER940.EXE I
MMZ
MPN
      C: \DSSAT3 MDRIV940.EXE MINPT940.EXE CRGRO940.EXE I
      C: \DSSAT3 MDRIV940.EXE MINPT940.EXE CRGRO940.EXE I
MSB
       C: \DSSAT3 MDRIV940.EXE MINPT940.EXE GECER940.EXE I
MWH
MZD
      C: \DSSAT3\MAIZE
PND
      C: \DSSAT3\PEANUT
      C: \DSSAT3\SOYBEAN
SBD
WHD
      C: \DSSAT3\WHEAT
TOE C: \DSSAT3 TVED.EXE
CRD C: \DSSAT3\GENOTYPE
```

# APPENDIX C. ABBREVIATIONS

Abbreviations used in GenCalc coefficient (??COEFF.TMP) files:

Abbreviation	Definition
D	No data available for comparison
M	Coefficient at maximum or minimum value
N	No response to changes in coefficient
R	Run number at a maximum
U	Coefficient not determined (not called for in rules file)

• DSSAT v3, Volume 3 • DSSAT v

• DSSAT v3, Volume 3 • DSSAT v

• DSSAT v3, Volume 3 • DSSAT v

• DSSAT v3, Volume 3 • DSSAT v

• DSSAT v3, Volume 3 • DSSAT v