SQL Server 2025 Vectors

Under the Hood and Into Production

Anthony Nocentino · Level 300 · Database Management



Agenda

Context first, then the demo that proves it.

1 Vectors 101: the math you need

2 Inside the VECTOR type

3 **Demo 1: vector internals**

4 Vector indexes: where they help and where they don't

5 **Demo 2: index performance at scale**

6 Into production: the lab and the app

7 **Demo 3: the RAG application**

8 Takeaways, then questions


Vectors 101

The math you need for the next hour, and nothing more



From text to a vector

Meaning in, a fixed-length list of numbers out



The model decides the dimension count. Similar meaning lands close together:

“git revert last commit…” distance 0.12 **“quattro formaggi pizza” distance 0.68**

The math in three ideas

Everything in this session is built from these

A vector is a list of numbers

VECTOR(3) '[1, 0, 0]'. Each number is a coordinate. Together they give a direction and a length.

- Our model: 768 numbers
- Same model, same count, always

Length is the norm

$|v| = \sqrt{(v_1^2 + v_2^2 + \ldots + v_n^2)}$

- [3, 4, 0] has length 5
- A unit vector has length 1


The dot product measures alignment

$v \cdot w = v_1w_1 + v_2w_2 + \ldots = |v|\ |w| \cos \theta$

- Same direction: largest
- At right angles: 0

Three vectors, three distances

VECTOR_DISTANCE: lower always means closer



Pair	cosine	euclidean	dot
v1 vs v1 (same)	0	0	−1
v1 vs v2 (30°)	0.134	0.518	−0.866
v1 vs v3 (90°)	1	1.414	0

cosine = 1 − cos θ: only the angle counts

euclidean = the straight-line gap between the tips

dot = −(v · w), negated so lower is closer

Unit vectors, so dot = cosine − 1, and euclidean = √(2 × cosine)

Cosine, Euclidean, or dot?

Normalize to unit length and all three rank results the same. They only disagree when length varies.

Cosine

Use when only meaning matters.

- The default for text embeddings
- Ignores vector length
- Short and long text on one topic score alike

Dot

Use when vectors are unit length, or length should win.

- Same order as cosine on unit vectors, and cheaper
- Recommenders, where length is popularity
- More people reviewed a pizza place

Euclidean

Use when absolute position matters.

- Images, sensors, clustering
- A length gap counts as distance
- A sensor is overheating (direction) by how much (magnitude)

Normalize when meaning lives in the direction: text, mixed sources. **Keep the magnitude** when length is the signal: counts, popularity, ratings.

Rule of thumb: use the metric your model's documentation recommends, and build the index with the same one.

Why normalize? At length 1, cosine, dot, and Euclidean all agree, so you can use the fastest one.

SIMILARITY SEARCH

Embed the question.
Measure it against the stored vectors.
Keep the closest K.

On this model, a strong match scores about 0.12 and an unrelated one about 0.68.

Inside the VECTOR type


Storage layout, precision, and exact search



Anatomy of a VECTOR

IEEE 754 floats behind an 8-byte header, stored in the row

One VECTOR(768) value: an 8-byte header, then the floats



One element, bit by bit (IEEE 754, little-endian on disk)



Dimensions set the size

VECTOR(n) stores n numbers behind the same 8-byte header

bytes = 8 + n × 4 float32 **bytes = 8 + n × 2** float16

Embedding model	Dimensions	VECTOR(n) float32	VECTOR(n, float16)
nomic-embed-text (our demos)	768	3,080 B	1,544 B
mxbai-embed-large	1,024	4,104 B	2,056 B
OpenAI text-embedding-3-small	1,536	6,152 B	3,080 B
OpenAI text-embedding-3-large	3,072	won't fit (Msg 2717)	6,152 B
The limit	1,998 / 3,996	8,000 B	8,000 B

The cap is 8,000 bytes, not a dimension count: 1,998 four-byte numbers or 3,996 two-byte ones. That's why float16 fits twice the dimensions.

Measured with DATALENGTH on SQL Server 2025 CU10. Size grows in a straight line with dimensions.

float32 or float16?

Use float16 when storage or dimensions are the limit and your vectors are unit length. Otherwise float32.

float32 (the default)

4 bytes per element, up to 1,998 dimensions.


- Generally available in SQL Server 2025
- Full precision for any workload
- Every client driver handles it

float16 (preview)

2 bytes per element, up to 3,996 dimensions.

- Half the storage and I/O; distances moved ~0.00001
- Fits 3,072-d models
- Needs PREVIEW_FEATURES; binary transport needs ODBC 18.7.1+ or JDBC 13.4+
- Can't mix with float32 in VECTOR_DISTANCE


768 dims on one 8 KB page



Same page, more vectors: 1,000 vectors at 768 dims took 500 pages as float32 and 200 as float16. An exact scan reads 60% fewer pages.

Where the bytes live

From database file, to filegroup, to an 8 KB page, to the row



~1.5 rows per page, so an exact scan of 10,000 vectors reads about 7,000 pages.
17 B row overhead: the row header plus an offset array for the two variable-length columns.
Some pages hold 1 row, some 2: rows were loaded out of key order, and page splits left pages half full.

Decode those 3,072 bytes by hand and all 768 floats match what SELECT prints.

How SQL Server runs a similarity search

Exact kNN (VECTOR_DISTANCE)




Data flows left to right here (SSMS draws it right to left). Every row is read and every distance computed before the sort keeps 10.

LIVE DEMO

Demo 1: Vector internals

Files and pages · decode a vector off the page · float16 · distance · the exact-search plan



Vector indexes

Where they help, and where they don't



Exact kNN vs approximate ANN


Exact visits every vector. ANN walks a graph and visits a few.

Exact kNN: measure every vector



Every row, every time. O(n). Perfect recall.

ANN (DiskANN): walk a graph



A few hops toward the query. Far fewer reads. Approximate.


kNN or ANN: which, when

Microsoft's guidance: exact search is fine up to about 50,000 vectors

Situation	Use	Why
Under ~50,000 vectors, or a filter cuts it that far	Exact kNN	Fast enough, perfect recall, nothing to maintain
A small table (about 1,000 rows)	Exact kNN	The index costs more reads than the scan
Hundreds of thousands to millions of vectors	ANN	535,731 vs 5,564 reads for one question at 1M rows
You need every true neighbor	Exact kNN	ANN found 84–89% of the true top 10 at 1M rows
A selective filter, on SQL Server 2025	kNN, or ANN with a large TOP_N	Filters run after the graph walk
The table changes all day	kNN, or ANN on Azure SQL	The 2025 index makes the table read-only

Exact search grows with every row

One exact kNN query on this laptop: average elapsed time by rows searched. Watch the shape, not the ms.



Times are from one laptop and move from run to run. Compare them to each other, not to your servers. Logical reads don't change.

Recall: the price of approximate

How many of the true top 10 the index found, at 1,000,000 rows

Search	Recall@10	Time per query	Logical reads
ANN, TOP_N = 10	0.84 – 0.89	8 – 10 ms	~6,400
ANN, TOP_N = 50, keep 10	0.96 – 0.98	24 – 28 ms	~20,800
Exact kNN	1.0	175 – 235 ms	535,731

One question, live in Demo 2: “How do I make an HTTP request in javascript” found 9 of the true top 10 with TOP_N = 10, and all 10 with TOP_N = 50. Recall falls as the table grows (0.96 at 10,000 rows). Ask for more candidates and keep the closest: that's oversampling, and the demo app does it 5×.

Times are from one laptop and move from run to run. Compare them to each other, not to your servers. Logical reads don't change.

Limits on SQL Server 2025, today

All three are fixed in the latest-version index on Azure SQL

Read-only tables

- INSERT, UPDATE, DELETE fail with Msg 42231
- Loading = drop the index, insert, rebuild
- Demo 3 runs that cycle live

Filters run after the walk

- TOP_N = 5 plus a selective filter returned 0 rows
- No error: silent
- Oversample TOP_N to compensate

An index version on its way out

- This earlier-version index will be retired
- TOP_N is deprecated
- Latest syntax: SELECT TOP (N) WITH APPROXIMATE

What an index build costs you

Building the index over 100,000 vectors on 12 cores. MAXDOP trades build time for room on the box.

Build	Elapsed	CPU	Memory grant	Exact kNN during the build
Default (all 12 cores)	140 s	~1,520 s	121 MB	~800 ms
WITH (MAXDOP = 4)	237 s	914 s	63 MB	~250 ms
WITH (MAXDOP = 1)	908 s	885 s	31 MB	~110 ms

Reads keep working

- SELECT and exact kNN run, starved for CPU
- Baseline kNN: about 40 ms

Writes and ANN don't

- INSERT, UPDATE fail with Msg 42231 at once
- VECTOR_SEARCH: Msg 42227 until done

Small footprint

- Used ~26 MB of memory at any MAXDOP
- tempdb under 10 MB; graph 26 MB

SQL Server 2025 CU10. Database-scoped MAXDOP = 1 was ignored (the build still ran at DOP 12); only the index option was honored. Times are from one laptop and move from run to run.

SQL Server 2025 vs Azure SQL

The type and functions are GA everywhere. The index is preview on-prem and GA on Azure.


	SQL Server 2025 (on-prem)	Azure SQL Database, Fabric, MI Always-up-to-date
VECTOR (float32), VECTOR_DISTANCE, AI_GENERATE_EMBEDDINGS	GA	GA
VECTOR(n, float16)	Preview: needs PREVIEW_FEATURES	GA
Vector index and VECTOR_SEARCH	Preview, earlier version (to be retired)	GA, latest version
Writes to an indexed table	Read-only: drop, load, rebuild	Full DML, maintained in the background
Filters	After the graph walk: oversample TOP_N	During the walk (iterative filtering)
Query syntax	TOP_N parameter (deprecated)	SELECT TOP (N) WITH APPROXIMATE
kNN or ANN?	You choose: VECTOR_DISTANCE or VECTOR_SEARCH	The optimizer chooses
Monitoring	No sys.dm_db_vector_indexes on CU10	sys.dm_db_vector_indexes

Azure SQL Managed Instance on the SQL Server 2025 update policy matches the on-prem column. Source: Microsoft Learn, CREATE VECTOR INDEX and VECTOR_SEARCH.

LIVE DEMO

Demo 2: Performance at scale

Build and inspect the index · kNN vs ANN · 1,000,000 rows · recall · the limits




Into production

Build a working application on all of it



The test lab

One laptop: SQL Server 2025 CU10 in Docker, Ollama on the host, no cloud



Adding vectors grew the database 3.7×

StackOverflowScale: 1,000,000 posts, each with a 768-dimension float32 embedding

	Size	Note
Posts (the source text)	1,244 MB	1.57M rows
QuestionEmbeddings	4,110 MB	3,080-byte vector + 481-byte chunk per row, 2 rows per page
Vector index graph	261 MB	Small next to the vectors
All tables, with vectors	5,982 MB	1,611 MB without the vectors and graph
Compressed backup (ZSTD)	4,246 MB	1.41:1. Vectors are floats and barely compress

Read I/O

- Exact kNN: ~535,000 pages, 4.1 GB
- ANN: ~6,000 pages

Write I/O


- ~3.6 KB of log per row
- 1M rows: ~3.6 GB of log per load

Plan for it

- Own filegroup, sized ahead
- Buffer pool, backups, restore time

RAG application architecture

The app sends text and gets rows back. It never sees a vector.



Patterns that make it production-ready

What Demo 3 builds, and why

Satellite table

Vectors in their own table and filegroup.

- Single INT key for the index
- Rebuild without touching Posts
- chunk = what was embedded

Procs as the contract

The app calls two procs.

- Exact fallback with no index
- Oversamples 5× for recall
- Swap models in one place

Least privilege

rag_app can EXECUTE, not SELECT.

- VIEW DEFINITION so the proc sees the index
- No access to the vectors
- Default database: StackOverflow

Operate it


Drop, load, rebuild on a schedule.

- The fallback isn't free at 1M rows
- Check for stale chunks
- Alert when the app reports kNN

LIVE DEMO

Demo 3: The RAG application

Schema · the search proc · least privilege · drop, load, rebuild · the app



Takeaways

Measure on your data, your model, your hardware

Storage

A VECTOR is a native float array in the row.

- float16 halves it for ~0.00001 of distance
- Embedding costs ~15 ms a row*

Indexes

Know where the line is.

- Exact search under ~50,000 vectors
- ANN at 1M rows: 5,564 reads, not 535,731
- Oversample to keep recall

Production

Put it behind procs.

- Least privilege by default
- Plan for read-only tables on 2025
- Watch the fallback path

** Environment specific: nomic-embed-text on Ollama, Apple M2 GPU, through a local NGINX TLS proxy. Your model, hardware, and network will differ, so measure it.*

Questions?

github.com/nocentino/vector-under-the-hood

Every demo, the lab, and the app, running on your laptop

- Vector data type: learn.microsoft.com/sql/t-sql/data-types/vector-data-type
- CREATE VECTOR INDEX: learn.microsoft.com/sql/t-sql/statements/create-vector-index-transact-sql
- VECTOR_SEARCH: learn.microsoft.com/sql/t-sql/functions/vector-search-transact-sql
- DiskANN: Subramanya et al., NeurIPS 2019