Message Tracing by Metric Log

Kunihiko Toumura

HITACHI
Inspire the Next

Current Status:
- done() emits a metric log (PR #2685, merged) [1]
- Once Messaging API support PRs are reviewed and merged (PR #2733, #2734, #2738, #2744,#2750, #2751), all core nodes emit metric log when message processing is completed.

```
14:21:51 - [metric] {"level":99,"nodeid":"D","event":"node.join.receive","msgid":"Y","timestamp":1579670511863}
14:21:53 - [metric] {"level":99,"nodeid":"D","event":"node.join.receive","msgid":"Z","timestamp":1579670513508}
14:21:56 - [metric] {"level":99,"nodeid":"D","event":"node.join.receive","msgid":"X","timestamp":1579670516424}
14:21:56 - [metric] {"level":99,"nodeid":"D","event":"node.join.correlate","msgid":"X", "value":{"join":["Y","Z"]},"...tamp":…}   [2]
14:21:56 - [metric] {"level":99,"nodeid":"D","event":"node.join.send","msgid":"X","timestamp":1579670516425}
14:21:56 - [metric] {"level":99,"nodeid":"D","event":"node.join.done","msgid":"X","...tamp":…}
14:21:56 - [metric] {"level":99,"nodeid":"D","event":"node.join.done","msgid":"Y","...tamp":…}   [1]
14:21:56 - [metric] {"level":99,"nodeid":"D","event":"node.join.done","msgid":"Z","...tamp":…}
```

Next Steps:
- Metric log for more precise tracing:
  - for the node which split a message or consolidate multiple messages (e.g. split/join, batch) [2]
- Graceful shutdown (as an experimental function):
  - waiting for process all messages in runtime.
  - PR already exists (#2296), but need to add test cases.