

SOC 통합 보안 대시보드 — 쿼리 정리

추출일: 2026-06-10 / 서버 매크로 + 대시보드 XML 기준

0. 핵심 매크로 soc_base

```
index=* sourcetype="modsec:audit:serial" | rex "----w+---A--\s+\[([^\]]+)\]\s+\$+\$+(?<src_ip>\d{1,3}(?:\.\d{1,3}){3})\s+(?<src_port>\d+)\s+(?<dest_ip>\d{1,3}(?:\.\d{1,3}){3})\s+(?<dest_port>\d+)" | rex "----w+---B--\s+(?<http_method>\$+)\s+(?<uri>\$+)" | rex "HTTP/[^\d.]+ (?<status>\d{3})" | rex max_match=200 "tag .attack-(?<atag>[a-z0-9-]+)" | rex max_match=200 "\[id \"(?<rid>\d+)\"]" | eval atk=mvfilter(match(atag,"^(sqli|xss|rce|lfi|injection-php)$")) | eval c_sqli=mvcount(mvfilter(atk=="sqli")), c_xss=mvcount(mvfilter(atk=="xss")), c_rce=mvcount(mvfilter(atk=="rce")), c_lfi=mvcount(mvfilter(atk=="lfi")), c_php=mvcount(mvfilter(atk=="injection-php")) | eval c_sqli=coalesce(c_sqli,0), c_xss=coalesce(c_xss,0), c_rce=coalesce(c_rce,0), c_lfi=coalesce(c_lfi,0), c_php=coalesce(c_php,0) | eval maxc=max(c_sqli,c_xss,c_rce,c_lfi,c_php) | eval signature=case(maxc==0,"WAF Anomaly",c_rce==maxc,"RCE",c_lfi==maxc,"Path Traversal/LFI",c_php==maxc,"PHP Injection",c_xss==maxc,"XSS",c_sqli==maxc,"SQL Injection",true(),"WAF Anomaly") | eval signature=if(match(_raw,"Brute force detected"),"Brute Force",signature) | eval all_attacks=mvjoin(mvdedup(atk),", ") | eval rule_ids=mvjoin(rid,", ") | eval cat_counts="xss:".c_xss.",sqli:".c_sqli.",rce:".c_rce.",lfi:".c_lfi.",php:".c_php | eval cat_variety=mvcount(mvdedup(atk)) | eval severity=case(signature=="SQL Injection",3,signature=="RCE",3,signature=="PHP Injection",3,signature=="Brute Force",3,signature=="XSS",2,signature=="Path Traversal/LFI",2,true(),1) | eval source_type="WAF Web" | append [search index=* sourcetype=syslog sguil_alert | rex field=_raw "Alert Received: \d+ (?<priority>\d+) (?<sclass>\$+) \$+ \[([^\]]+)\] \d+ \d+ \[(?<alert_msg>[^\]]+)\] (?<src_ip>[\d.]+) (?<dest_ip>[\d.]+)" | rex field=_raw "\[([^\]]+)\] [\d.]+ [\d.]+ \d+ (?<src_port>\d+) (?<dest_port>\d+)" | where isnull(sclass) OR sclass!="protocol-command-dec" | eval _rev=if(match(alert_msg,"(?:ATTACK_RESPONSE)",1,0) | eval _ti=src_ip, src_ip=if(_rev==1,dest_ip,src_ip), dest_ip=if(_rev==1,_ti,dest_ip) | eval _tp=src_port, src_port=if(_rev==1,dest_port,src_port), dest_port=if(_rev==1,_tp,dest_port) | fields - _rev _ti _tp | eval signature=case(match(alert_msg,"(?:sql.injection|select.*(from|user)|union.*select)","SQL Injection (IDS)",match(alert_msg,"(?:xss|cross.site.script)","XSS (IDS)",match(alert_msg,"(?:passwd|etc/|traversal|blfi|b|brfi|b|local.file|file.inclusion)","Path Traversal/LFI (IDS)",match(alert_msg,"(?:webshell|upload)","File Upload/Webshell (IDS)",match(alert_msg,"(?:brute.force|invalid.user|failed.password)","Brute Force (IDS)",match(alert_msg,"(?:port.scan|nmap|scan.detect|portscan)","Port Scan (IDS)",match(alert_msg,"(?:OSSEC)","OSSEC: "+replace(alert_msg,"^\[OSSEC\] ",""),true(),alert_msg) | eval ids_keep=if(match(alert_msg,"(?:nmap|webshell|passwd/etc/sql.injection|union.*select|select.*from|traversal|blfi|b|brfi|b|cross.site|xss|exploit|backdoor|upload)",1,0) | eval severity=case(priority=="1",3,priority=="2",3,priority=="3",2,priority=="4",2,true(),1) | eval source_type="IDS/OSSEC" | eval source="sguil" | append [search index=pfsense host=10.0.200.1 filterlog | rex "filterlog.?(?<action>block|pass),(?<in|out>).*?(?<proto>tcp|udp),\d+,(?<src_ip>\d{1,3}(?:\.\d{1,3}){3}),(?<dest_ip>\d{1,3}(?:\.\d{1,3}){3}),(?<src_port>\d+),(?<dest_port>\d+)" | where isnotnull(action) | bin _time span=1m | stats count as pkts, dc(dest_port) as ports, values(action) as fw_action by _time src_ip dest_ip | eval signature=case(ports>=10,"Port Scan",pkts>=500,"DDoS",true(),null()) | where isnotnull(signature) | eval severity=3 | eval source_type="pfSense" | append [search index=pfsense snort | regex _raw="snort \[ \d+ \]: " | rex "snort\[ \d+ \]: \s+ \[ (?<gid>\d+): (?<sid>\d+): (?<rev>\d+) \] \s+ (?<snort_msg>.*?) \s+ \[ Classification: \s+ (?<class>[^\]]+)\] \s+ \[ Priority: \s+ (?<prio>\d+) \] \s+ \[ (?<proto>w+)\] \s+ (?<src_ip>\d{1,3}(?:\.\d{1,3}){3}): (?<src_port>\d+) \s+ \s+ (?<dest_ip>\d{1,3}(?:\.\d{1,3}){3}): (?<dest_port>\d+)" | where isnotnull(src_ip) | eval _rev=if(match(snort_msg,"(?:ATTACK_RESPONSE)",1,0) | eval _ti=src_ip, src_ip=if(_rev==1,dest_ip,src_ip), dest_ip=if(_rev==1,_ti,dest_ip) | eval _tp=src_port, src_port=if(_rev==1,dest_port,src_port), dest_port=if(_rev==1,_tp,dest_port) | fields - _rev _ti _tp | eval signature=case(match(snort_msg,"(?:scan|nmap|sweep|recon)","Port Scan (Snort)",match(snort_msg,"(?:sqli|sql.injection|union|tautology|bsql|b)","SQL Injection (Snort)",match(snort_msg,"(?:xss|cross.?site|script|csrf)","XSS (Snort)",match(snort_msg,"(?:upload|webshell|executable|download)","File Upload/Webshell (Snort)",match(snort_msg,"(?:passwd/etc/|traversal|lfi|rfi|directory)","Path Traversal/LFI (Snort)",match(snort_msg,"(?:brce|b|remote.code|command.exec|os.command)","RCE (Snort)",match(snort_msg,"(?:ddos|flood|denial)","DDoS (Snort)",match(snort_msg,"(?:http.inspect|chunk|unesaped)","HTTP Anomaly (Snort)",true(),snort_msg) | eval severity=case(prio=="1",3,prio=="2",3,prio=="3",2,prio=="4",2,true(),1) | eval uri=snort_msg | eval source_type="pfSense" | eval source="snort" | eval _sw=src_ip | eval src_ip=if(match(signature,"(?:ET WEB_SERVER)",dest_ip,src_ip) | eval dest_ip=if(match(signature,"(?:ET WEB_SERVER)",_sw,dest_ip) | fields - _sw | where NOT cidrmatch("10.0.0/16",src_ip) AND NOT cidrmatch("192.168.0/16",src_ip) AND NOT cidrmatch("172.16.0/12",src_ip) AND NOT cidrmatch("127.0.0/8",src_ip) | eval severity=if(match(signature,"(?:sql|xss|cross.?site|script|csrf|upload|download|webshell|traversal|lfi|rfi|passwd/etc/ddos|flood|denial|scan|recon|nmap|sweep)",3,severity)
```

0-1. 공용 베이스 검색 (전체로그 탭, 30초 자동갱신)

`soc\_base`

0-2. 탭 토큰 필터

dev_filter (장비)

- `source_type="WAF Web"`
- `source_type="pfSense"`
- `source_type="IDS/OSSEC"`

atk_filter (공격유형)

- `match(signature,"(?i)sql")`
- `match(signature,"(?i)xss|cross.?site|script|csrf")`
- `match(signature,"(?i)ddos|flood|denial")`
- `match(signature,"(?i)upload|download|webshell|traversal|lfi|rfi|passwd|/etc/")`
- `match(signature,"(?i)scan|recon|nmap|sweep")`

1. 장비 상세 보기 (mode_dev — soc_base | search \$dev_filter\$ | where \$atk_filter\$)

1. \$dev_label\$ · \$atk_label\$ — 발생 건수

```
`soc_base` | search $dev_filter$ | where $atk_filter$ | stats count
```

2. 고유 출발지 IP

```
`soc_base` | search $dev_filter$ | where $atk_filter$ AND src_ip!="0.0.0.0" | stats dc(src_ip) as count
```

3. 고위험 (HIGH)

```
`soc_base` | search $dev_filter$ | where $atk_filter$ | where severity=3 | stats count
```

4. 마지막 발생

```
`soc_base` | search $dev_filter$ | where $atk_filter$ | stats latest(_time) as t | eval v=round((now()-t)/60,1) | table v
```

5. 시간대별 발생 추이 — \$dev_label\$ · \$atk_label\$

```
`soc_base` | search $dev_filter$ | where $atk_filter$ | timechart count as "건수"
```

6. 상위 출발지 IP (포트수 = 포트스캔 식별용)

```
`soc_base` | search $dev_filter$ | where $atk_filter$ | where src_ip!="0.0.0.0" | stats count as "건수", dc(dest_port) as "포트수", latest(_time) as lt, values(signature) as sig by src_ip | eval "최근 발생"=strftime(lt,"%m/%d %H:%M") | eval "시그니처"=mvjoin(sig," / ") | sort -"건수" | head 10 | table src_ip, "건수", "포트수", "최근 발생", "시그니처" | rename src_ip as "출발지 IP"
```

7. 공격 대상 IP

```
`soc_base` | search $dev_filter$ | where $atk_filter$ | where dest_ip!="0.0.0.0" | stats count as "건수", values(uri) as u by dest_ip | eval "주요 URI"=mvjoin(mvindex(u,0,4),", ") | sort -"건수" | head 10 | table dest_ip, "건수", "주요 URI" | rename dest_ip as "대상 IP"
```

8. \$dev_label\$ · \$atk_label\$ — 상세 로그 (최근 100건)

```
`soc_base` | search $dev_filter$ | where $atk_filter$ | eval Severity=case(severity=3,"HIGH",severity=2,"MEDIUM",true(),"LOW") | eval Time=strftime(_time,"%Y-%m-%d %H:%M:%S") | sort -_time | head 100 | table Time, source_type, signature, Severity, src_ip, src_port, dest_ip, dest_port, uri, status | rename source_type as "Source", signature as "Signature", src_ip as "Src IP", src_port as "Src Port", dest_ip as "Dest IP", dest_port as "Dest Port", uri as "URI", status as "Status"
```

2. 전체 로그 통합 뷰 (mode_all)

1. 장비별 탐지 비교 — \$atk_label\$ (전체 장비 기준)

```
`soc_base` | where $atk_filter$ | stats count by source_type | sort -count
```

2. ● WAF Web 마지막 수신

```
`soc_base` | where source_type="WAF Web" | stats latest(_time) as t | eval v=round((now()-t)/60,1) | table v
```

3. ● IDS/OSSEC 마지막 수신

```
`soc_base` | where source_type="IDS/OSSEC" | stats latest(_time) as t | eval v=round((now()-t)/60,1) | table v
```

4. ⚠ HIGH RISK (Last 5 min)

```
`soc_base` | where severity=3 | stats count
```

5. ▲ MEDIUM RISK (Last 5 min)

```
`soc_base` | where severity=2 | stats count
```

6. ● TOTAL EVENTS (Last 5 min)

```
`soc_base` | stats count
```

7. 전체 이벤트

```
(base=soc_all) | stats count
```

8. 고위험 이벤트 (Severity 3)

```
(base=soc_all) | where severity=3 | stats count
```

9. 고유 공격 출발지 IP

```
(base=soc_all) | where src_ip!="0.0.0.0" | stats dc(src_ip) as count
```

10. IDS / OSSEC 경보

```
(base=soc_all) | where source_type="IDS/OSSEC" | stats count
```

11. ⚠ HIGH 경보 — 즉시 대응 필요 (최근 20건, 분석 기간 내)

```
(base=soc_all) | where severity=3 | eval 경과_분=round((now()-_time)/60,0) | eval Time=strftime(_time,"%Y-%m-%d %H:%M:%S") | eval Severity=case(severity=3,"HIGH",severity=2,"MEDIUM",true(),"LOW") | sort -_time | head 20 | table Time, 경과_분, Severity, source_type, signature, src_ip, src_port, dest_ip, dest_port, uri, status | rename 경과_분 as "경과(분)", source_type as "Source", signature as "Signature", src_ip as "Src IP", src_port as "Src Port", dest_ip as "Dest IP", dest_port as "Dest Port", uri as "URI", status as "Status"
```

12. 반복 공격자 분석 (최초·최근 발생 시각)

```
(base=soc_all) | where src_ip!="0.0.0.0" | stats count as "이벤트 수", earliest(_time) as first_t, latest(_time) as last_t, values(signature) as sig_v, values(dest_ip) as ip_v by src_ip | eval "최초 발생"=strftime(first_t,"%m/%d %H:%M") | eval "최근 발생"=strftime(last_t,"%m/%d %H:%M") | eval 경과_분=round((now()-last_t)/60,0) | eval "공격 유형"=mvjoin(sig_v," / ") | eval "대상 IP"=mvjoin(ip_v," ") | sort -"이벤트 수" | head 10 | table src_ip, "이벤트 수", "최초 발생", "최근 발생", 경과_분, "공격 유형", "대상 IP" | rename src_ip as "공격자 IP", 경과_분 as "경과(분)"
```

13. 공격 유형 Top 10 — 위험도 MEDIUM 이상 (각 로그 이벤트의 severity 기준 · 상단 '위험도 필터'와 무관)

```
(base=soc_all) | where severity>=2 | stats count by signature | sort -count | head 10
```

14. 시간대별 이벤트 추이 (소스별)

```
(base=soc_all) | timechart count by source_type
```

15. 위험도별 분포

```
(base=soc_all) | eval sev_label=case(severity=3,"HIGH",severity=2,"MEDIUM",true(),"LOW") | stats count by sev_label | sort -count
```

16. 탐지 소스별 이벤트 분포

```
(base=soc_all) | chart count over source_type by signature
```

17. 공격 대상 서버 (dest_ip)

```
(base=soc_all) | where dest_ip!="0.0.0.0" AND isnotnull(dest_ip) | stats count as "이벤트 수", values(signature) as sig_v by dest_ip | eval "주요 시그니처"=mvjoin(sig_v," / ") | sort -"이벤트 수" | head 10 | table dest_ip, "이벤트 수", "주요 시그니처" | rename dest_ip as "목적지 IP"
```

18. 보안 이벤트 목록 (최대 50건)

```
(base=soc_all) $sev_filter$ | eval Severity=case(severity=3,"HIGH",severity=2,"MEDIUM",true(),"LOW") | eval Time=strftime(_time,"%Y-%m-%d %H:%M:%S") | sort -_time | head 50 | table Time, source_type, signature, Severity, src_ip, src_port, dest_ip, dest_port, uri, status | rename source_type as "Source", signature as "Signature", src_ip as "Src IP", src_port as "Src Port", dest_ip as "Dest IP", dest_port as "Dest Port", uri as "URI", status as "Status"
```

3. 웹로그 원본 뷰 (mode_weblog — index=web sourcetype=waf_web)

1. 전체 요청 수

```
index=web sourcetype=waf_web | stats count
```

2. 고유 클라이언트 IP

```
index=web sourcetype=waf_web | rex "^(?<cip>\S+)" | stats dc(cip) as c
```

3. 오류 응답 (4xx/5xx)

```
index=web sourcetype=waf_web | rex "\" (?<st>\d{3}) \" | where st>=400 | stats count
```

4. 마지막 수신

```
index=web sourcetype=waf_web | stats latest(_time) as t | eval v=round((now()-t)/60,1) | table v
```

5. 시간대별 요청 추이 (상태코드 계열)

```
index=web sourcetype=waf_web | rex "\" (?<st>\d{3}) \" | eval cls=case(st>=500,"5xx",st>=400,"4xx",st>=300,"3xx",true(),"2xx") | timechart count by cls
```

6. HTTP 메서드 분포

```
index=web sourcetype=waf_web | rex "\" (?<method>[A-Z]+) \" | stats count by method | sort -count
```

7. 상위 요청 URI (Top 15)

```
index=web sourcetype=waf_web | rex "\" [A-Z]+ (?<uri>[^\?]+) \" | stats count as cnt by uri | sort -cnt | head 15 | rename uri as "URI", cnt as "요청 수"
```

8. 상위 클라이언트 IP (Top 15)

```
index=web sourcetype=waf_web | rex "^(?<cip>\S+)" | stats count as cnt by cip | sort -cnt | head 15 | rename cip as "클라이언트 IP", cnt as "요청 수"
```

9. 전체 웹 요청 로그 (최근 200건) — 위험분류 없이 모든 요청

```
index=web sourcetype=waf_web | rex "^(?<cip>\S+) \S+ \S+ \[[^\]]+\] \" (?<method>\S+) (?<uri>\S+) [^\"]*\" (?<status>\d{3}) (?<bytes>\d+) \" (?<referer>[^\"]*)\" \" (?<ua>[^\"]*)\" \" | eval Time=strftime(_time,"%Y-%m-%d %H:%M:%S") | sort -_time | head 200 | table Time, cip, method, status, bytes, uri, ua | rename cip as "Client IP", method as "Method", status as "Status", bytes as "Bytes", uri as "URI", ua as "User-Agent"
```