

A 10x10 grid with a complex pattern of black and white squares. The pattern is composed of several distinct regions: a 2x2 block of black squares in the top-left corner, a 2x2 block of black squares in the top-right corner, a 2x2 block of black squares in the bottom-left corner, and a 2x2 block of black squares in the bottom-right corner. The remaining squares are white. A green zigzag line is drawn across the grid, starting from the top-left corner and ending at the bottom-right corner. A black square is located at the bottom-right corner of the grid.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).

--