

A 10x10 grid with a grayscale pattern. The pattern consists of dark gray and light gray squares. A series of green zigzag lines are drawn across the grid, starting from the top left and moving towards the bottom right. The lines are drawn in a way that they follow the diagonal of the grid, creating a series of peaks and valleys. The grid is divided into four quadrants by a vertical line at column 5 and a horizontal line at row 5. The top-left and bottom-right quadrants are mostly light gray, while the top-right and bottom-left quadrants are mostly dark gray. The green zigzag lines are drawn in a way that they follow the diagonal of the grid, creating a series of peaks and valleys. The lines are drawn in a way that they follow the diagonal of the grid, creating a series of peaks and valleys.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).