

A 20x20 grid with a complex pattern of black, white, and gray squares. The grid is divided into four quadrants by a vertical line at column 10 and a horizontal line at row 10. The top-left and bottom-right quadrants contain a checkerboard pattern of black and white squares. The top-right and bottom-left quadrants contain a pattern of gray squares. A green zigzag line starts at the top-left corner and moves horizontally across the top row, then vertically down the left column, then horizontally across the bottom row, and finally vertically up the right column. A black square is located at the intersection of the 10th column and 10th row.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).

--