

A 10x10 grid with a grayscale pattern. The pattern consists of dark gray, light gray, and white squares. A green zigzag line is drawn across the grid, starting from the bottom-left corner and ending at the top-right corner. The zigzag line is composed of small, repeating 'V' shapes. The grid is divided into four quadrants by a vertical line at column 5 and a horizontal line at row 5. The top-left and bottom-right quadrants contain a grayscale pattern, while the top-right and bottom-left quadrants are white. The green zigzag line is drawn across the entire grid, starting from the bottom-left corner and ending at the top-right corner.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 :	0000	8 :	1000
1 :	0001	9 :	1001
2 :	0010	A :	1010
3 :	0011	B :	1011
4 :	0100	C :	1100
5 :	0101	D :	1101
6 :	0110	E :	1110
7 :	0111	F :	1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).

--