

The diagram is a 10x10 grid with a complex pattern. The grid is divided into four quadrants. The top-left and bottom-right quadrants contain a checkerboard pattern of black and white squares. The top-right and bottom-left quadrants contain a pattern of black and white squares with diagonal lines. The center of the grid is filled with a dense pattern of green zigzag lines. The grid is labeled with numbers 1 through 9 along the right edge.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).