

A 10x10 grid with various patterns and a green zigzag line. The grid is divided into four quadrants by a vertical line at column 5 and a horizontal line at row 5. The top-left quadrant (columns 1-5, rows 1-5) contains a pattern of black and white squares. The top-right quadrant (columns 6-10, rows 1-5) contains a pattern of black and white squares. The bottom-left quadrant (columns 1-5, rows 6-10) contains a pattern of black and white squares. The bottom-right quadrant (columns 6-10, rows 6-10) contains a pattern of black and white squares. A green zigzag line starts at the top-left corner (row 1, column 1) and ends at the bottom-right corner (row 10, column 10), zigzagging between the two main vertical lines of the grid.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).

--