

The grid is a 10x10 square. The top-left and bottom-right quadrants (columns 1-5, rows 1-5 and columns 6-10, rows 6-10) have a checkerboard pattern of gray and white squares. The top-right and bottom-left quadrants (columns 6-10, rows 1-5 and columns 1-5, rows 6-10) have a pattern of gray squares along the main diagonal and its reflection. The bottom-right corner contains a green zigzag line and a small table of numbers.

7	7	6	6
7	7	6	6
8	8	5	5
8	8	5	5
9	9	4	4
9	9	4	4
		3	3
		3	3
		2	2
		2	2
		1	1
		1	1

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the **green** line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).