

The image displays a 10x10 grid with a complex pattern of gray and white squares. A green zigzag line is drawn across the grid, starting from the bottom-left corner and moving towards the top-right. The grid is also overlaid with a grid of diagonal lines, creating a series of small triangles. The pattern of gray and white squares is irregular, with some areas showing a checkerboard-like arrangement and others showing solid gray or white blocks. The green zigzag line is composed of many small, sharp turns, creating a jagged path through the grid.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).

--