

The diagram is a 10x10 grid. The left half (columns 1-5) features a checkerboard pattern of gray and white squares, with diagonal lines running from the top-left to the bottom-right. The right half (columns 6-10) also features a checkerboard pattern, but with green zigzag paths overlaid. The bottom row is labeled with numbers 1 through 10, corresponding to the columns.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the **green** line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

|          |          |
|----------|----------|
| 0 : 0000 | 8 : 1000 |
| 1 : 0001 | 9 : 1001 |
| 2 : 0010 | A : 1010 |
| 3 : 0011 | B : 1011 |
| 4 : 0100 | C : 1100 |
| 5 : 0101 | D : 1101 |
| 6 : 0110 | E : 1110 |
| 7 : 0111 | F : 1111 |

[illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).