

A 10x10 grid with a grayscale pattern. The pattern is composed of black, white, and gray squares. A green zigzag line is drawn across the grid, starting from the top-left corner and ending at the bottom-right corner. The line follows a path that moves horizontally across the top row, then vertically down the first column, then horizontally across the second row, and so on, creating a series of 'V' and inverted 'V' shapes. The grid is divided into four quadrants by a vertical line between columns 5 and 6 and a horizontal line between rows 5 and 6. The top-left and bottom-right quadrants are white, the top-right and bottom-left quadrants are gray, and the central area is a mix of black and white squares.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).